

HSCの開発ステータス、 フィルターの開発方針

宮崎 聰

国立天文台

Subru User's Meeting
2009/01/16



Hyper Suprime-Cam

- FOV: 1.5 deg in diameter
 - ~ 10 times faster Survey speed than Sprime-Cam
- Image quality: Instrument PSF < 0.3 (FWHM)
 - Equivalent with SC in r, i, z, Y band:



HyperSuprime Feasibility Studyの現状

宮崎聰 小宮山裕

国立天文台ハワイ観測所

2005.8.25



HSC Collaboration

1. Camera Mechanics
 - Dewar, Shutter, Filter Exchanger
2. PFU Mechanics
 - Telescope I/F, Attitude Control, InR
3. Optics
 - Wide Field Corrector
 - Filter
4. Sensor
 - CCD
 - Readout electronics
5. Data Management
6. Project Management
 - Schedule, Budget



HSC Collaboration

1. Camera Mechanics

- Dewar, Shutter, Filter Exchanger

NAOJ/IAA

2. PFU Mechanics

- Telescope I/F, Attitude Control, InR

Mitsubishi

3. Optics

- Wide Field Corrector
- Filter

Canon
NAOJ

4. Sensor

- CCD
- Readout electronics

Hamamatsu
N/UT/KEK

5. Data Management

N/UT/KEK/P


6. Project Management


NAOJ

- Schedule, Budget




HSC Overview






(C) Uraguchi

SC and HSC



SC


SC is already very
large.



HSC




HSC System Design



Error budget Distribution

Frame FEM Analysis



Flexure is allowed but tuned by design and additional manufacturing


図 2-2 解析モデル断面斜視図

Alignment between Dewar and Lens is crucial.



PFU Mechanics Design


- Defining Specifications of
 - Frame
 - Hexapod Actuators (steward platform)
 - Instrument rotator





PFU Mechanics Design

- Defining Specifications of
 - Frame
 - Hexapod Actuators (steward platform)
 - Instrument rotator



Mitsubishi has almost
finished this design study
just recently



Camera Mechanics

(a) CCD Dewar

Scale up of Suprime-Cam's
48 W(173K) Pulse Tube Cooler X 2

(b) Shutter

Prototype built


(c) Filter Exchanger

ASIAA Contribution, under design

Wang's talk




HSC Dewar




Mechanical and thermal design completed
Prototype being built this spring



CCD Mosaic



116 CCDs
Height variation
 $< 25 \text{ micron(p-v)}$




SiC monolithic
cold plate




Shutter Prototype

- Goal 10 second exposure with 1 % precision



Optics (WFC)

Designed Image quality : FWHM << 0.2 arcsec



General Lens Data

| | |
|--------------|-------------------|
| Focal length | 18416[mm] |
| image scale | 0.0893[mm/arcsec] |
| image size | φ 498[mm] |

0.17 arcsec/pix (15 um pix)

Convex Aspheric lens
is feasible only at few
optics firms including
Canon



Designed Image quality

| | 0 | 0.125 | 0.25 | 0.5 | 0.75 | [deg] |
|--------|-----|-------|------|-----|------|-------|
| g | 1.0 | 2.7 | 3.6 | | | |
| (0.49) | 5.8 | 5.5 | 6.3 | 9.2 | 5.2 | |
| r | 1.9 | 3.0 | 4.2 | | | |
| (0.63) | 1.3 | 1.5 | 3.4 | 4.0 | 4.5 | |
| i | 3.1 | 3.8 | 5.7 | | | |
| (0.77) | 2.8 | 3.8 | 5.1 | 5.3 | 4.4 | |
| z | 3.8 | 4.3 | 6.7 | | | |
| (0.90) | 2.8 | 4.1 | 5.0 | 6.3 | 4.6 | |

RMS spot radius (micron)

upper:SC, lower:HSC



Designed Image quality

| | 0 | 0.125 | 0.25 | 0.5 | 0.75 | [deg] |
|-------------|-----|-------|------|-----|------|---------------|
| g (0.49) | 1.0 | 2.7 | 3.6 | 9.2 | 5.2 | 0.12'' (FWHM) |
| r (0.63) | 1.9 | 3.0 | 4.2 | | | |
| i (0.77) | 1.3 | 1.5 | 3.4 | 4.0 | 4.5 | |
| z (0.90) | 3.1 | 3.8 | 5.7 | | | |
| | 2.8 | 3.8 | 5.1 | 5.3 | 4.4 | |
| | 3.8 | 4.3 | 6.7 | | | |
| | 2.8 | 4.1 | 5.0 | 6.3 | 4.6 | |

RMS spot radius (micron)

upper:SC, lower:HSC



4. Sensor CCD


Hamamatsu (HPK) Fully Depleted CCD

Product of long term (10 years) NAOJ-
HPK Collaboration

HSC is a primary motivation of the
development (upgrade of Suprime-Cam)





HPK FDCCD








HPK FDCCD





HPK FDCCD






FDCCD Characterization


| | |
|------------------------|---|
| Parallel CTE | 0.999995 |
| Serial CTE | 0.999995 |
| Quantumn Efficeincy | 40 % (400 nm) 90 % (650 nm) 40 % (10000 nm) |
| Thickness | 200 μ m |
| Dark Current | 1.4 [e/hour/pixel] |
| Full Well | 180,000 [e] |
| Amplifier Responsivity | 5.8 [μ V/e] |
| Read Noise | 4.4 e at 150 kHz reaout |

$$T_{\text{CCD}} = -100^{\circ}\text{C}$$



QE Comparison







Super Suprime-Cam


- Prototype of Hyper Suprime-Cam
- Offered to general observers (shared risk basis) since August, 2008
- 40 % QE increase in z' confirmed



Super Suprime-Cam

- Prototype of Hyper Suprime-Cam
- Offered to general observers (shared risk basis) since August, 2008
- 40 % QE increase in z' confirmed


No observer's complaint so far.

A detailed astronomical image of the Omega Nebula (M17). The central feature is a dense cluster of young stars, appearing as a bright, reddish-orange core surrounded by a complex network of glowing gas clouds. The gas is primarily composed of hydrogen and helium, emitting light at various wavelengths. The nebula is set against a dark, star-filled background, with numerous smaller stars of varying colors visible throughout the field.

M17 B R_c z'

Filter



Designing Interference Filter





Filter Prototype


- Standard Evaporation method
- 60 cm phi



All specs are met
including the uniformity

Filter Structure

- 6 glass surface is required because the film built by the standard evaporation is porous





Sputtering deposition

- A way to obtain dense film
- We need to explore this option to make things simpler
- Possible vendors
 - Asahi Spectra
 - Barr Associate






Narrow band Filter

- Prototyping at Barr Associates through Hayashino-san
- Spec. for prototype filter
 - Dimension : $D=600\text{mm}$, $t=15\text{mm}$
 - Substrate : Schott B270
 - Central Wavelength (CW) : 6000\AA
 - ΔCW : 17\AA ($r < 200\text{mm}$), 30\AA ($200\text{mm} < r < 250\text{mm}$)
 - Pass-band width (BW) : 80\AA
 - ΔBW : 15\AA ($r < 200\text{mm}$), 20\AA ($200\text{mm} < r < 250\text{mm}$)
 - No blocking layer

Narrow band Filter

- Result
 - BW and CW meet the spec.
 - Δ BW and Δ CW meet the spec.
 - Unexpected CW gradient in a few cm scale is detected
 - Overall, the prototype filter is a promising one.





Narrow Band Filter

- Asahi Spectra's effort
 - Building new sputtering facility
 - Goal of cut off wavelength uniformity
 - $< 10 \text{ \AA}$

Both Asahi and Barr are possible options.



Project Milestones

Constraint

- Dark Energy Survey (2011/01 Survey start)
- Grant-in-Aid ends (2012/03)

2009/03 Design Review

2010/12 Assembly Completed at Mitaka

2011/1 Ship to Hawaii

2011/6 Engineering First Light

2011/9 Science Observations starts



フィルター持ち込みポリシー

- 必要性
 - Suprime-Camでは、ポリシーが不明確だったため、運用現場が混乱してしまった。
 - HSCはよりフィルターはより高価になる(SCの最低10倍)



ポリシーの決め方

T副観測所長の提案

1. 観測所、HSC製作組でたたき台を作成
2. 科学的、運用面を含め多角的に検討
(SAC + 観測所で検討WG?)
3. 観測所長が決定
4. 予算申請等を開始



ポリシーたたき台

- 現場レベルで検討中
- 基本的な考え方
 - フィルターを観測所に引き渡した時点で、制作者にはその所有権を放棄してもらう
- 観測所は受け入れ後、一般公開を行う



ポリシーたたき台

- 現場レベルで検討中
- 基本的な考え方
 - フィルターを観測所に引き渡した時点で、
制作者にはその所有権を放棄してもらう

破損等における責任
を観測所は負わない

- 観測所は受け入れ後、一般公開を行う



ポリシーたたき台

- 現場レベルで検討中
- 基本的な考え方
 - フィルターを観測所に引き渡した時点で、
制作者にはその所有権を放棄してもらう

破損等における責任
を観測所は負わない

- 観測所は受け入れ後、一般公開を行う

フィルター製作はコミュニティーへの貢献



HSC Project Status

Design completed
by 2009/1



Risk

| | | |
|------------------------|------|----------------|
| 1. Camera Mechanics | 80 % | Green |
| 2. PFU Mechanics | 70 % | Yellow → Green |
| 3. Optics | | |
| - Wide field Corrector | 95 % | Green |
| - Filter | 60 % | Green |
| 4. Sensor | | |
| - CCD | 95 % | Green |
| - Readout electronics | 60 % | Green |
| 5. Data Management | 40 % | Green |
| 6. Project Management | | |
| - Schedule | | Yellow |
| - Budget | | Orange |



Summary

HSC design and prototyping is underway almost on schedule.

Design Review is scheduled on
March 2, 2009