

6 すばる FITS ヘッダ統一案 (観測装置開発者に向けて)

「すばる」共同利用が始まろうとしている現在、「すばる」観測装置の FITS データの共通ヘッダー規約、観測装置固有ヘッダー規約の検討が進められている。それらの規約の最新の案をサンプルヘッダーとともにここに紹介する。(この項目は改訂が頻繁に行なわれているので最新情報は Web 上を参照のこと (7.4.4 節参照。ただしアクセス制限あり)。)

(この節は「すばる FITS 検討会 (SFITS)」(小杉、市川、濱部、水本、矢動丸、金光、高田、洞口、泉浦、渡邊、青木 (賢)、青木 (和)、宮田)、および、すばる各観測装置開発グループの検討に基づくものである。)

6.1 すばる FITS ヘッダルール (Ver.1.2.0(Mar 10, 2000))

すばるの観測装置で取得されたデータは、全て観測装置から FITS 形式で出力される。これらの FITS データはハワイ島ヒロの山麓施設 (ハワイ観測所) でアーカイブされ、将来公開される予定である。アーカイブの検索項目は、基本的に全て FITS ヘッダーに含まれていなければならない。また、いくつもの観測装置のデータを一括して検索できるようにするためにも、FITS キーワードは可能な限り観測装置間で共通化すべきである。データ解析に関しては、解析に必要なパラメータは FITS ヘッダーから抽出される場合が多い。解析処理ソフトウェアの共通化による開発作業の省力化を図るためにも FITS キーワードの共通化が望まれる。そこで、すばるでは以下の FITS ヘッダルールを定める。

- 基本的に FITS のルール (NOST Standard、この手引き第 3 章参照) に従う。
- ヘッダー辞書 (次節参照) で定義されたのキーワードを、定義した意味以外では使用しない。また、ヘッダー辞書内で Common と分類されたキーワードは必ず使用しなければならない。(なぜこれらのキーワードがすばる FITS データで重要なのか、は下の注を参照。)
- 観測装置固有ヘッダー一覧は共通ヘッダーキーワードと同様に観測装置グループが辞書を作成し、公開しなければならない (装置固有ヘッダー辞書参照)。装置固有辞書は装置グループ内の決定により改訂を行なうが、辞書の改訂、および、改訂履歴を Web で公表すること。公表は、アスキーテキストファイルを <ftp://www2.naoj.org> にアップロード (最新のもので上書き) することとする。
- 当該観測装置からデータが生産されはじめて以降は、過去に使用したキーワードは別の意味で使用しないこと。また、単位も変更しないこと。
- 当該観測装置からデータが生産されはじめて以降は、辞書の改訂を行なったら、ヘッダーキーワード INS-VER の記述に何らかの変更を加えること。
- 観測装置固有キーワードは、以下に例示するような 'COMMENT' で始まる行を挿入することによりブロック化する。
COMMENT Subaru Device Dependent Header Block for FOCAS
- 観測装置固有のヘッダーは、頭 2 文字を装置 ID として与え、残り 6 文字を装置開発者が自由に使用する。その際可能な限り略号表に従った記述を行う。装置 ID は 'A_:', 'B_:', 'C_:' のような形式とし、重複は許されない。現在、'C_': CIAO、'F_': FOCAS、'H_': HDS、'M_': MIRTOS、'O_': OHS、'S_': Suprime-Cam、'Q_': COMICS、'V_': VTOS、'I_': IRCS が予約されている。(CAC には今のところ装置固有のヘッダーはない。)

- キーワード作成時の略号の組み合わせ順序は、キーワードのカテゴリーを参照して Image, Instrument, Telescope / Time / Environment / Statistics, Unit / Action とする (略号表 (6.4 節) 参照、各略号はさらに短縮可能)。例えば、露出開始時のスリットポジションアングルは、スリット: SLT、ポジションアングル: P/PA、露出開始時: STR を組み合わせて作成するが、その順序は、SLT (Category = Instrument)、P/PA (Statistics / Unit)、STR (Action) となり、キーワードは SLT_PSTR となる。
- 撮像観測の場合は WCS を記述する。
- Extension については ASCII Table Extension のみが可能である。
- 天体名は可能な限り IAU 表記に従う。
- 値の単位は辞書の記述に従うが、基本的に SI 単位系とする。
- インラインコメントにはキーワードの意味、及び、値の単位が明示される。
- ピクセルの座標値はピクセル中央を基準とし、ピクセル番号は 1 から始まる。
- キーワード OBS-MOD について 当該データがどのようなタイプのデータかが一目でわかるように統一する。最初の 4 文字は以下のどれかを使用することとする。なお、文字は全て大文字とする。

撮像関連: IMAG
 分光関連: SPEC
 偏光撮像: IPOL
 偏光分光: SPOL

'_' (アンダーバー) を 1 文字つけて、それ以降は何を書いても良いこととするが、その文字列についても、同じものを時期によって違う意味で使ってはならない。観測制御と解析の連携をとるために、OBS-MOD は山頂観測制御システムからステータスとして取得することを推奨する (抽象化コマンドを用いた観測時)。

- キーワード DATA-TYP について 現在は以下のキーワードが指定可能である。これ以外のものを使用する必要がある場合、登録をおこなってから使用することとする。

OBJECT
 FLAT
 DOMEFLAT
 DOMEFLAT_ON
 DOMEFLAT_OFF
 SKYFLAT
 DARK
 COMPARISON
 BIAS
 STANDARD
 STANDARD_STAR
 TEST

- フィルターやグリズムについて フィルターやグリズムを複数持っている観測装置の場合、それぞれの一意性を保証できるように名前付け、あるいは、番号付けすること。新しいものに置き換わった場合は、名前を必ず変更すること。

(注: なぜ *COMMON* キーワードがずばる *FITS* データで重要なのか)

Keyword Name	Reason
AIRMASS	Roughly estimated one is convenient in archival search
BIN-FACT1	The basic keyword for image features
BIN-FACT2	The basic keyword for image features
BITPIX	The basic keyword for image features
BLANK	The basic keyword for image features
BSCALE	The basic keyword for image features
BUNIT	The basic keyword for image features
BZERO	The basic keyword for image features
CDELT1	The basic keyword for image features
CDELT2	The basic keyword for image features
CRPIX1	The basic keyword for image features
CRPIX2	The basic keyword for image features
CRVAR1	The basic keyword for image features
CRVAR2	The basic keyword for image features
CTYPE1	The basic keyword for image features
CTYPE2	The basic keyword for image features
CUNIT1	The basic keyword for image features
CUNIT2	The basic keyword for image features
DATASET(*)	Only needed to OBJECT type data. Needed by DASH.
DATA-TYP	Used as an key for archival search and essential for data analysis.(DASH etc)
DATE-OBS	The basic keyword for image features
DEC	The basic keyword for image features (origin of RA2000 & DEC2000)
DEC2000	DEC may not be written in J2000.0. The key for archival search by coordinate.
DETECTOR	The basic keyword for image features
DET-TMP	The basic keyword for image features
DISPAXIS(S)	Convenient in spectrum plotting of raw data.
DISPERSR(S)	The basic keyword for image features
END	Essential for FITS data
EQUINOX	Essential for knowing RA and DEC epoch, and calculating RA2000 & DEC2000
EXP-ID	For the grouping of data by simultaneous exposure.
EXPTIME	The basic keyword for image features
EXTEND	Essential for FITS data with ASCII Table Extensions.
FOC-POS	The basic keyword for observation description
FOC-VAL	Needed by QDAS in focusing task.
FRAMEID	This is the unique key for archival system.
GAIN	The basic keyword for image features
HST	The basic keyword for observation description
INSTRUME	This is used in online data registration at Hilo.
LONGPOLE(I)	The basic keyword for image features
LST	The basic keyword for observation description
MJD	This is used in data search as a unique key for time.
NAXIS	Essential for FITS data
NAXIS1	Essential for FITS data with 2-d image
NAXIS2	Essential for FITS data with 2-d image
NAXIS3	Essential for FITS data with 3-d image as those from MIRTOS
OBJECT	The basic keyword for observation description
OBS-ALOC	Can identify the control mode and where the instrument was.
OBSERVAT	The basic keyword for observation description
OBSERVER	The basic keyword for observation description
OBS-MOD	The key for selecting data in data search in archival system
PCnnmmmm(I)	Essential for setting control command to telescope (moving object onto the slit etc)
POLARIZn(P)	The basic keyword for observation description
PROP-ID	Essential for setting view parameter in archival system
RA	The basic keyword for observation description (origin of RA2000 & DEC2000)
RA2000	RA may not be written in J2000.0. Key for archival search by coordinate.
RADECSYS	RA and DEC may not be written in FK5.
RET-ANGn(P)	Essential in data analysis of polarimetric data.
RETPLATn	The basic keyword for observation description
SIMPLE	Essential for FITS data
SLIT(S)	The basic keyword for observation description
SLTCPIX1(S)	Convenient in making plot of raw data spectrum
SLTCPIX2(S)	Convenient in making plot of raw data spectrum
SLT-LEN(S)	The basic keyword for observation description
SLT-PA(S)	The basic keyword for observation description
SLT-WID(S)	The basic keyword for observation description
TELESCOP	Essential for knowing the origin of data
TELCOCUS	Can be one of the key for identifying the causality of empty image.
TIMESYS	Essential for knowing time system used in the data
UT	The basic keyword for observation description
WAVELEN(S)	Convenient in making plot of raw data spectrum.
WAV-MAX(S)	Convenient in making plot of raw data spectrum.
WAV-MIN(S)	Convenient in making plot of raw data spectrum.
WCS-ORIG(I)	Used for identifying WCS is written by toolkit or not.

6.2 基本ヘッダー辞書

6.2.1 基本ヘッダー辞書各項目の説明

観測装置間で共通化できるキーワードは、基本ヘッダー辞書に記述される。基本ヘッダー辞書内の各項目の意味は以下の通りである。

Header Key Word：FITS ヘッダーキーワード

Revised：最終更新日付

Category：分類。

Importance：重要度。以下の値をもつ

Common：必須キーワード

Imaging：撮像データに必須なキーワード

Spectroscopy：分光観測データに必須なキーワード

Polarimetry：偏光観測データに必須なキーワード

Object：天体フレームに必須なキーワード

Optional：キーワードの定義のみで、必須ではない。ただし、装置固有キーワードの中で基本ヘッダー (Optional) と同じ意味のものがある場合には、基本ヘッダーを優先する。

Alias：ツールキットの Status Distribution Service を利用して OBS からステータスを取得する場合の指定キーワード。ここに Toolkit と書かれていれば、(FITS 化)Toolkit により入力が可能である。また、Next Toolkit となっていれば、次バージョンのツールキットで計算ツールを提供予定。全観測装置に共通なものは、"FITS.SBR.???" の形式をとり、観測装置ごとに参照ステータスが変化するものは、"FITS.#Inst.???" の形式をとる。ただし、'#Inst' は観測装置の 3 文字略称で、以下の通り。

- IRCS → IRC
- AO → AOS
- CIAO → CIA
- OHS → OHS
- FOCAS → FCS
- HDS → HDS
- COMICS → COM
- Suprime-Cam → SUP
- MIRTOS → MIR
- CAC → CAC
- VTOS → VTO

FormatC：キーワード値の記述形式 (C 言語形式)。

FormatF：キーワード値の記述形式 (Fortran 形式)。

Unit：キーワード値の単位。キーワード値の単位は基本的にこの単位で記述するものとする。ただし、どうしても問題が生ずる場合には、別途すばる側担当者と相談のこと。

Recommend：すばるが推奨する規定値。矛盾が生じない限りこの値を使用する。SIMPLE, OBSERVAT については必ずこの値を使用する。

Sample：値の例。

Obsoluted：すでに使われなくなったキーワードを表す。

Comment : FITS ヘッダー内に記述されるインラインコメントの内容。値に単位が必要な場合は、単位の記述もおこなう。

DescriptionE : キーワードの意味や定義 (英語)

DescriptionJ : キーワードの意味や定義 (日本語)

6.2.2 基本ヘッダー辞書 (1999/03/05)

紙面の都合により、上記項目の内 HeaderKeyWord, Category, Importance, FormatF, Unit, Recommended, Alias(DistributionService) の 7 個の項目を ABC 順の辞書に収録し、HeaderKeyWord, Category, Importance, FormatF, Unit, Recommended, Sample, Comment, DescriptionE, DescriptionJ の 10 個の項目を Category 順の辞書に収録した。

● Key Word の ABC 順基本辞書

[Dictionary = Basic] (Key Word の ABC 順、その 1(1/4): A ~ CRPIX2)

Header KeyWord	Category	Importance	FormatF	Unit	Recommend	RevisedDate	Alias (DistributionService)
ADC	Telescope	Optional	F20.3	degree	-	1998/12/10	FITS.SBR.ADC
ADC-END	Telescope	Optional	F20.3	degree	-	1998/12/10	FITS.SBR.ADC
ADC-STR	Telescope	Optional	F20.3	degree	-	1998/12/10	FITS.SBR.ADC
ADC-TYPE	Telescope	Optional	A20	-	-	1998/12/10	FITS.SBR.ADC-TYPE
AG-PRB1	Telescope	Optional	F20.3	mm	-	1998/12/10	-
AG-PRB2	Telescope	Optional	F20.3	degree	-	1998/12/10	-
AIRM-END	Time	Optional	F20.3	-	-	1999/03/01	FITS.SBR.AIRMASS
AIRM-STR	Time	Optional	F20.3	-	-	1998/11/25	FITS.SBR.AIRMASS
AIRMASS	Time	Common	F20.3	-	-	1998/11/25	FITS.SBR.AIRMASS
ALT-END	Telescope	Optional	F20.5	degree	-	1998/11/24	FITS.SBR.ALTITUDE
ALT-STR	Telescope	Optional	F20.5	degree	-	1998/11/24	FITS.SBR.ALTITUDE
ALTITUDE	Telescope	Optional	F20.5	degree	-	1998/11/24	FITS.SBR.ALTITUDE
AO-FREQ	Telescope	Optional	I20	Hz	-	1998/12/10	-
AO-TIP	Telescope	Optional	A8	-	-	1999/03/01	-
AO-WFS	Telescope	Optional	F20.5	-	-	1998/12/14	-
APERTURE	Spectroscopy	Optional	A30	-	-	1998/12/14	-
APT-SIZE	Spectroscopy	Optional	F20.3	arcsec	-	1998/12/14	-
APTC-DEC	Spectroscopy	Optional	F20.8	degree	-	1999/03/01	-
APTC-RA	Spectroscopy	Optional	F20.8	degree	-	1999/03/01	-
APTCPIX1	Spectroscopy	Optional	F20.1	pixel	-	1998/12/10	-
APTCPIX2	Spectroscopy	Optional	F20.1	pixel	-	1998/12/10	-
AUTOGUID	Instrument	Optional	A8	-	-	1998/12/10	-
AZ-END	Telescope	Optional	F20.5	degree	-	1998/11/24	FITS.SBR.AZIMUTH
AZ-STR	Telescope	Optional	F20.5	degree	-	1998/11/24	FITS.SBR.AZIMUTH
AZIMUTH	Telescope	Optional	F20.5	degree	-	1998/11/24	FITS.SBR.AZIMUTH
BIN-FCT1	Instrument	Common	I20	pixel	-	1998/11/24	-
BIN-FCT2	Instrument	Common	I20	pixel	-	1998/11/24	-
BITPIX	FITS	Common	I20	-	-	1998/12/14	-
BLANK	File	Common	I20	-	-	1999/03/01	-
BSCALE	File	Common	F20.8	-	-	1998/12/14	-
BUNIT	File	Common	A10	-	-	1998/11/25	-
BZERO	File	Common	F20.8	-	-	1998/12/14	-
C2ELT1	WCS	Optional	F20.8	degree	-	1998/11/24	Toolkit
C2ELT2	WCS	Optional	F20.8	degree	-	1998/11/24	Toolkit
C2NIT1	WCS	Optional	A8	-	degree	1998/11/25	Toolkit
C2NIT2	WCS	Optional	A8	-	degree	1998/11/25	Toolkit
C2PIX1	WCS	Optional	F20.1	pixel	-	1999/03/01	Toolkit
C2PIX2	WCS	Optional	F20.1	pixel	-	1999/03/01	Toolkit
C2VAL1	WCS	Optional	F20.8	degree	-	1998/11/24	Toolkit
C2VAL2	WCS	Optional	F20.8	degree	-	1998/11/24	Toolkit
C2YPE1	WCS	Optional	A8	-	RA---TAN	1998/11/25	Toolkit
C2YPE2	WCS	Optional	A8	-	DEC--TAN	1998/11/25	Toolkit
CDEL1	File	Common	F20.8	-	-	1998/12/14	Toolkit
CDEL2	File	Common	F20.8	-	-	1998/11/24	Toolkit
CDj_i	WCS	Optional	F20.8	-	-	1999/09/28	Toolkit
COADD	Instrument	Optional	I20	-	-	1998/12/10	-
COMMENT	Comment	Optional	A79	-	-	1998/12/14	-
CRPIX1	File	Common	F20.1	pixel	-	1999/03/01	Toolkit
CRPIX2	File	Common	F20.1	pixel	-	1999/03/01	Toolkit

[Dictionary = Basic] (Key Word の ABC 順、その 2(2/4): CRVAL1 ~ INSVER)

Header KeyWord	Category	Importance	Format	F Unit	Recommend	RevisedDate	Alias (DistributionService)
CRVAL1	File	Common	F20.8	-	-	1998/11/24	Toolkit
CRVAL2	File	Common	F20.8	-	-	1998/11/24	Toolkit
CTYPE1	File	Common	A10	-	RA---TAN	1998/11/25	Toolkit
CTYPE2	File	Common	A10	-	DEC--TAN	1998/11/25	Toolkit
CUNIT1	File	Common	A10	-	degree	1998/11/25	Toolkit
CUNIT2	File	Common	A10	-	degree	1998/11/25	Toolkit
DATA-TYP	Object	Common	A30	-	-	1998/11/25	-
DATASET	Object	Object	A20	-	-	1998/12/14	FITS.#Inst.DATASET
DATE-OBS	Time	Common	A10	UTC	-	1998/11/25	Toolkit
DEC	Object	Common	A12	-	-	1998/12/14	FITS.SBR.DEC
DEC2000	Object	Common	A12	-	-	1998/11/25	Toolkit
DET-Ann	Instrument	Optional	F20.3	degree	-	1998/12/14	-
DET-ID	Instrument	Optional	I20	-	-	1998/12/10	-
DET-NSMP	Instrument	Optional	I20	-	-	1998/12/10	-
DET-P1nn	Instrument	Optional	F20.3	arcsec	-	1999/03/01	-
DET-P2nn	Instrument	Optional	F20.3	arcsec	-	1999/03/01	-
DET-RST	Instrument	Optional	I20	-	-	1998/12/14	-
DET-SMPL	Instrument	Optional	A20	-	-	1998/12/14	-
DET-TAVE	Instrument	Optional	F20.2	K	-	1998/12/14	-
DET-TMAX	Instrument	Optional	F20.2	K	-	1999/03/01	-
DET-TMED	Instrument	Optional	F20.2	K	-	1999/03/01	-
DET-TMIN	Instrument	Optional	F20.2	K	-	1999/03/01	-
DET-TMP	Instrument	Common	F20.2	K	-	1999/03/01	-
DET-TSD	Instrument	Optional	F20.2	K	-	1999/03/01	-
DET-Tnn	Instrument	Optional	F20.2	K	-	1999/03/01	-
DET-VER	Instrument	Optional	A30	-	-	1998/12/14	-
DETECTOR	Instrument	Common	A20	-	-	1998/12/10	-
DETPXSZ1	Instrument	Optional	F20.4	mm	-	1998/12/14	-
DETPXSZ2	Instrument	Optional	F20.4	mm	-	1998/12/14	-
DISPAXIS	Spectroscopy	Spectroscopy	I20	-	-	1998/12/10	-
DISPERSR	Spectroscopy	Spectroscopy	A20	-	-	1998/12/10	-
DOM-HEND	Environment	Optional	F20.1	%	-	1999/03/01	FITS.SBR.DOM-HUM
DOM-HSTR	Environment	Optional	F20.1	%	-	1999/03/01	FITS.SBR.DOM-HUM
DOM-HUM	Environment	Optional	F20.1	%	-	1999/03/01	FITS.SBR.DOM-HUM
DOM-PEND	Environment	Optional	F20.2	hpa	-	1998/12/14	FITS.SBR.DOM-PRS
DOM-PRS	Environment	Optional	F20.2	hpa	-	1998/12/14	FITS.SBR.DOM-PRS
DOM-PSTR	Environment	Optional	F20.2	hpa	-	1998/12/14	FITS.SBR.DOM-PRS
DOM-TEND	Environment	Optional	F20.2	K	-	1999/03/01	FITS.SBR.DOM-TMP
DOM-TMP	Environment	Optional	F20.2	K	-	1998/12/14	FITS.SBR.DOM-TMP
DOM-TSTR	Environment	Optional	F20.2	K	-	1999/03/01	FITS.SBR.DOM-TMP
DOM-WEND	Environment	Optional	F20.2	m/s	-	1999/03/01	FITS.SBR.DOM-WND
DOM-WMAX	Environment	Optional	F20.2	m/s	-	1999/03/01	-
DOM-WMIN	Environment	Optional	F20.2	m/s	-	1999/03/01	-
DOM-WND	Environment	Optional	F20.2	m/s	-	1999/03/01	FITS.SBR.DOM-WND
DOM-WSTR	Environment	Optional	F20.2	m/s	-	1999/03/01	FITS.SBR.DOM-WND
EFP-MIN1	Instrument	Optional	I20	pixel	-	1999/03/01	-
EFP-MIN2	Instrument	Optional	I20	pixel	-	1999/03/01	-
EFP-RNG1	Instrument	Optional	I20	pixel	-	1998/12/14	-
EFP-RNG2	Instrument	Optional	I20	pixel	-	1998/12/14	-
END	FITS	Common	-	-	-	1998/11/24	Toolkit
EQUINOX	Object	Common	F20.1	year	-	1998/12/14	FITS.SBR.EQUINOX
EXP-ID	Instrument	Common	A12	-	-	1998/12/14	-
EXP1TIME	Time	Optional	F20.3	sec	-	1998/12/14	-
EXPTIME	Time	Common	F20.2	sec	-	1998/12/14	-
EXTEND	FITS	Common	BOOLEAN	-	-	1998/11/24	-
F-RATIO	Origin	Optional	F20.2	-	-	1998/12/14	-
FILTERnn	Instrument	Optional	A30	-	-	1998/12/14	-
FLT-Ann	Instrument	Optional	F20.2	degree	-	1998/12/14	-
FOC-LEN	Origin	Optional	F20.3	mm	-	1998/11/24	-
FOC-POS	Origin	Common	A12	-	-	1998/12/14	FITS.#Inst.FOC-POS
FOC-VAL	Origin	Common	F20.3	mm	-	1999/03/01	FITS.SBR.FOC-VAL
FRAMEID	Instrument	Common	A12	-	-	1998/12/14	-
GAIN	Instrument	Common	F20.3	e/ADU	-	1998/12/14	-
HISTORY	Comment	Optional	A60	-	-	1998/12/14	-
HST	Time	Common	A12	HST	-	1998/12/14	-
HST-END	Time	Optional	%12s	HST	-	1998/11/25	-
HST-STR	Time	Optional	%12s	HST	-	1998/11/25	-
IMGROT	Telescope	Optional	F20.3	degree	-	1999/03/01	FITS.SBR.IMGROT
IMR-END	Telescope	Optional	F20.3	degree	-	1999/03/01	FITS.SBR.IMGROT
IMR-STR	Telescope	Optional	F20.3	degree	-	1999/03/01	FITS.SBR.IMGROT
IMR-TYPE	Telescope	Optional	A20	-	-	1999/03/01	FITS.SBR.IMR-TYPE
INR-END	Telescope	Optional	F20.3	degree	-	1999/03/01	FITS.SBR.INSROT
INR-STR	Telescope	Optional	F20.3	degree	-	1999/03/01	FITS.SBR.INSROT
INS-VER	Instrument	Optional	A30	-	-	1999/03/01	-

[Dictionary = Basic] (Key Word の ABC 順、その 3(3/4): INSROT ~ SLT-PA)

Header KeyWord	Category	Importance	Format	F Unit	Recommend	RevisedDate	Alias (DistributionService)
INSROT	Telescope	Optional	F20.3	degree	-	1999/03/01	FITS.SBR.INSROT
INST-PA	Instrument	Optional	F20.3	degree	-	1999/03/01	FITS.SBR.INST-PA
INSTRUME	Instrument	Common	A20	-	-	1999/03/01	-
LONGPOLE	WCS	Imaging	F20.1	degree	180.0	1999/03/01	Toolkit
LST	Time	Common	A12	LST	-	1999/03/01	Toolkit
LST-END	Time	Optional	A12	LST	-	1999/03/01	Toolkit
LST-STR	Time	Optional	A12	LST	-	1999/03/01	Toolkit
M2-ANG1	Telescope	Optional	F20.3	arcsec	-	1998/12/10	-
M2-ANG2	Telescope	Optional	F20.3	arcsec	-	1998/12/14	-
M2-POS1	Telescope	Optional	F20.3	mm	-	1998/12/14	-
M2-POS2	Telescope	Optional	F20.3	mm	-	1998/12/14	-
M2-TIP	Telescope	Optional	A8	-	-	1998/12/10	FITS.SBR.M2-TIP
M2-TYPE	Telescope	Optional	A8	-	-	1998/12/10	FITS.SBR.M2-TYPE
MJD	Time	Common	F20.8	day	-	1998/12/10	Toolkit
MJD-END	Time	Optional	F20.8	days	-	1999/03/01	Toolkit
MJD-STR	Time	Optional	F20.8	days	-	1999/03/01	Toolkit
N2XIS	WCS	Optional	I20	-	2	1999/03/01	Toolkit
N2XIS1	WCS	Optional	I20	pixel	-	1998/12/10	Toolkit
N2XIS2	WCS	Optional	I20	-	-	1999/03/01	Toolkit
NAS-TAVE	Environment	Optional	F20.2	K	-	1999/03/01	-
NAS-TMAX	Environment	Optional	F20.2	K	-	1999/03/01	-
NAS-TMIN	Environment	Optional	F20.2	K	-	1999/03/01	-
NAS-TSD	Environment	Optional	F20.1	K	-	1999/03/01	-
NAXIS	FITS	Common	I20	-	-	1999/03/01	Toolkit
NAXIS1	FITS	Common	I20	pixel	-	1999/03/01	Toolkit
NAXIS2	FITS	Common	I20	-	-	1999/03/01	Toolkit
NAXIS3	FITS	Optional	I20	-	-	1999/03/01	-
OBJECT	Object	Common	A30	-	-	1998/11/25	FITS.#Inst.OBJECT
OBS-ALOC	Telescope	Common	A12	-	-	1999/03/01	FITS.#Inst.OBS-ALOC
OBS-MOD	Instrument	Common	A30	-	-	1999/03/01	-
OBSERVAT	Origin	Common	A20	-	NAOJ	1999/03/01	Toolkit
OBSERVER	Origin	Common	A50	-	-	1999/03/01	FITS.#Inst.OBSERVER
OUT-HEND	Environment	Optional	F20.1	%	-	1999/03/01	FITS.SBR.OUT-HUM
OUT-HSTR	Environment	Optional	F20.1	%	-	1999/03/01	FITS.SBR.OUT-HUM
OUT-HUM	Environment	Optional	F20.1	%	-	1999/03/01	FITS.SBR.OUT-HUM
OUT-PEND	Environment	Optional	F20.2	hpa	-	1999/03/01	FITS.SBR.OUT-PRS
OUT-PRS	Environment	Optional	F20.2	hpa	-	1999/03/01	FITS.SBR.OUT-PRS
OUT-PSTR	Environment	Optional	F20.2	hpa	-	1999/03/01	FITS.SBR.OUT-PRS
OUT-TEND	Environment	Optional	F20.2	K	-	1999/03/01	FITS.SBR.OUT-TMP
OUT-TMP	Environment	Optional	F20.2	K	-	1999/03/01	FITS.SBR.OUT-TMP
OUT-TSTR	Environment	Optional	F20.2	K	-	1999/03/01	FITS.SBR.OUT-TMP
OUT-WEND	Environment	Optional	F20.2	m/s	-	1999/03/01	FITS.SBR.OUT-WND
OUT-WMAX	Environment	Optional	F20.2	m/s	-	1999/03/01	-
OUT-WMIN	Environment	Optional	F20.2	m/s	-	1999/03/01	-
OUT-WND	Environment	Optional	F20.2	m/s	-	1999/03/01	FITS.SBR.OUT-WND
OUT-WSTR	Environment	Optional	F20.2	m/s	-	1999/03/01	FITS.SBR.OUT-WND
P20JP1	WCS	Optional	F20.1	-	0.0	1998/12/10	-
P20JP2	WCS	Optional	F20.1	-	0.0	1998/12/10	-
P2iijjj	WCS	Optional	F20.8	-	-	1998/12/10	Toolkit
PCiijjj	WCS	Imaging	F20.8	-	-	1998/12/10	Toolkit
POL-ANGn	Polarimetry	Optional	F20.2	degree	-	1999/03/01	-
POLARIZn	Polarimetry	Polarimetry	A30	-	-	1999/03/01	-
PRD-MIN1	Instrument	Optional	I20	pixel	-	1999/03/01	-
PRD-MIN2	Instrument	Optional	I20	pixel	-	1999/03/01	-
PRD-RNG1	Instrument	Optional	I20	pixel	-	1999/03/01	-
PRD-RNG2	Instrument	Optional	I20	pixel	-	1999/03/01	-
PROJP1	WCS	Optional	F20.1	-	0.0	1998/12/10	-
PROJP2	WCS	Optional	F20.1	-	0.0	1998/12/10	-
PROP-ID	Origin	Common	A8	-	-	1998/11/25	FITS.#Inst.PROP-ID
RA	Object	Common	A12	-	-	1998/12/14	FITS.SBR.RA
RA2000	Object	Common	A12	-	-	1998/12/14	Toolkit
RADECSYS	Object	Common	A8	-	FK5	1998/11/25	Toolkit
RET-ANGn	Polarimetry	Polarimetry	F20.2	degree	-	1998/12/14	-
RETPLATn	Polarimetry	Polarimetry	A30	-	-	1998/11/25	-
SECZ	Time	Optional	F20.3	-	-	1998/12/14	FITS.SBR.SECZ
SECZ-END	Time	Optional	F20.3	-	-	1998/11/24	FITS.SBR.SECZ
SECZ-STR	Time	Optional	F20.3	-	-	1998/11/24	FITS.SBR.SECZ
SEEING	Environment	Optional	F20.2	arcsec	-	1998/12/14	FITS.SBR.SEEING
SIMPLE	FITS	Common	BOOLEAN	-	T	1998/11/25	Toolkit
SLIT	Spectroscopy	Spectroscopy	A20	-	-	1998/12/10	-
SLT-LEN	Spectroscopy	Spectroscopy	F20.3	arcsec	-	1998/12/14	-
SLT-OBJP	Spectroscopy	Optional	F20.3	arcsec	-	1998/12/14	-
SLT-PA	Spectroscopy	Spectroscopy	F20.1	degree	-	1998/12/14	-

[Dictionary = Basic] (Key Word の ABC 順、その 4(4/4): SLT-PEND ~ Z)

Header KeyWord	Category	Importance	FormatF	Unit	Recommend	RevisedDate	Alias (DistributionService)
SLT-PEND	Spectroscopy	Optional	F20.1	degree	-	1998/12/14	-
SLT-PSTR	Spectroscopy	Optional	F20.1	degree	-	1998/12/14	-
SLT-WID	Spectroscopy	Spectroscopy	F20.3	arcsec	-	1998/12/14	-
SLTC-DEC	Spectroscopy	Optional	F20.5	degree	-	1998/12/10	-
SLTC-RA	Spectroscopy	Optional	F20.5	degree	-	1998/12/10	-
SLTCPIX1	Spectroscopy	Spectroscopy	F20.1	pixel	-	1998/12/14	-
SLTCPIX2	Spectroscopy	Spectroscopy	F20.1	pixel	-	1998/12/14	-
SV-PRB	Telescope	Optional	F20.3	mm	-	1998/12/14	-
TELESCOP	Origin	Common	A30	-	-	1998/12/14	FITS.SBR.TELESCOP
TELFOCUS	Telescope	Common	A30	-	-	1998/12/14	FITS.SBR.TELFOCUS
TIMESYS	Time	Common	A8	-	UTC	1998/12/14	Toolkit
TRAN-END	Environment	Optional	F20.3	-	-	1998/12/14	FITS.SBR.TRANSP
TRAN-STR	Environment	Optional	F20.3	-	-	1998/12/14	FITS.SBR.TRANSP
TRANSP	Environment	Optional	F20.3	-	-	1998/12/14	FITS.SBR.TRANSP
UT	Time	Common	A12	UTC	-	1998/12/10	Toolkit
UT-END	Time	Optional	A12	UTC	-	1998/12/10	Toolkit
UT-STR	Time	Optional	A12	UTC	-	1998/12/10	Toolkit
UT1-UTC	Time	Optional	F20.5	sec	-	1998/12/14	FITS.SBR.UT1-UTC
WAV-MAX	Spectroscopy	Spectroscopy	F20.4	nm	-	1998/12/14	-
WAV-MIN	Spectroscopy	Spectroscopy	F20.4	nm	-	1998/12/14	-
WAVELEN	Spectroscopy	Spectroscopy	F20.4	nm	-	1998/12/10	-
WCS-ORIG	WCS	Imaging	A20	-	-	1998/12/10	Toolkit
WEATHER	Environment	Optional	A30	-	-	1998/12/14	FITS.SBR.WEATHER
ZD	Time	Optional	F20.5	degree	-	1998/11/24	FITS.SBR.ZD
ZD-END	Time	Optional	F20.5	degree	-	1998/11/25	FITS.SBR.ZD
ZD-STR	Time	Optional	F20.5	degree	-	1999/03/01	FITS.SBR.ZD

● Category 順基本辞書 (詳細説明付)

[Dictionary = Basic] (Category 順、その 1-1: Comment)

```

-----
HeaderKeyWord: COMMENT
Category      : Comment
Importance    : Optional
FormatF       : A79
Unit          : -
Recommend     : -
Sample        : 'Comment '
Comment       : Comment
DescriptionE   : Used for describing the comments about what can not be described by Keyword and
                  parameters.
DescriptionJ   : ヘッダー中にキーワードとパラメータで表現しきれないようなコメントを記述したい場合に用いる。
-----
HeaderKeyWord: HISTORY
Category      : Comment
Importance    : Optional
FormatF       : A60
Unit          : -
Recommend     : -
Sample        : 'QDAS ok'
Comment       : History
DescriptionE   : Used for describing the history of data analysis and so on performed to the data.
DescriptionJ   : 当該データに対してなされた処理履歴。
-----

```

[Dictionary = Basic] (Category 順、その 2-1: Environment)

```

-----
HeaderKeyWord: DOM-HEND
Category      : Environment
Importance    : Optional
FormatF       : F20.1
Unit          : %
Recommend     : -
Sample        : 5.4
Comment       : Humidity in the dome at exp. end (%)
DescriptionE   : Humidity measured in the dome at the exposure end. Unit is %.
DescriptionJ   : 露出終了時のドーム内湿度。単位はパーセント (%)。
-----

```

[Dictionary = Basic] (Category 順、その 2-2: Environment(続))

HeaderKeyWord:	DOM-HSTR
Category	: Environment
Importance	: Optional
FormatF	: F20.1
Unit	: %
Recommend	: -
Sample	: 5.3
Comment	: Humidity in the dome at exp. start (%)
DescriptionE	: Humidity measured in the dome at the exposure start. Unit is %.
DescriptionJ	: 露出開始時のドーム内湿度。単位はパーセント (%)。

HeaderKeyWord:	DOM-HUM
Category	: Environment
Importance	: Optional
FormatF	: F20.1
Unit	: %
Recommend	: -
Sample	: 23.1
Comment	: Humidity measured in the dome
DescriptionE	: Humidity measured in the dome. Unit is %.
DescriptionJ	: ドーム内で測定した湿度。単位はパーセント (%)。

HeaderKeyWord:	DOM-PEND
Category	: Environment
Importance	: Optional
FormatF	: F20.2
Unit	: hpa
Recommend	: -
Sample	: 645.83
Comment	: Dome atm. pressure at exposure end (hpa)
DescriptionE	: Atmospheric pressure in the dome at the end of the exposure. Unit is hpa.
DescriptionJ	: 露出終了時のドーム内気圧。単位は hpa。

HeaderKeyWord:	DOM-PRS
Category	: Environment
Importance	: Optional
FormatF	: F20.2
Unit	: hpa
Recommend	: -
Sample	: 648.21
Comment	: Atmospheric pressure in the Dome (hpa)
DescriptionE	: Atmospheric pressure in the Dome. Unit is hpa.
DescriptionJ	: 露出中の典型的な時刻に測定されたドーム内での気圧。単位は hpa。

HeaderKeyWord:	DOM-PSTR
Category	: Environment
Importance	: Optional
FormatF	: F20.2
Unit	: hpa
Recommend	: -
Sample	: 645.14
Comment	: Dome Atm. pressure at exp.start (hpa)
DescriptionE	: Atmospheric pressure in the dome at the start of the exposure. Unit is hpa.
DescriptionJ	: 露出開始時のドーム内気圧。単位は hpa。

HeaderKeyWord:	DOM-TEND
Category	: Environment
Importance	: Optional
FormatF	: F20.2
Unit	: K
Recommend	: -
Sample	: 273.16
Comment	: Temp. in the dome at exp. end (K)
DescriptionE	: Temperature measured in the dome/enclosure at the exposure end. Unit is Kelvin (K).
DescriptionJ	: 露出終了時にドーム内で測定された気温。単位はケルビン (K)。

HeaderKeyWord:	DOM-TMP
Category	: Environment
Importance	: Optional
FormatF	: F20.2
Unit	: K
Recommend	: -
Sample	: 273.39
Comment	: Temperature measured in the dome (K)
DescriptionE	: Temperature measured in the dome/enclosure. Unit is Kelvin (K).
DescriptionJ	: 露出中の典型的な時刻にドーム内で測定された気温。単位はケルビン (K)。

[Dictionary = Basic] (Category 順、その 2-3: Environment(続))

```

-----
HeaderKeyWord: DOM-TSTR
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 273.14
Comment       : Temp. in the dome at exp. start (K)
DescriptionE   : Temperature measured in the dome/enclosure at the exposure start. Unit is Kelvin
                  (K).
DescriptionJ   : 露出開始時にドーム内で測定された気温。単位はケルビン (K)。
-----
HeaderKeyWord: DOM-WEND
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 10.88
Comment       : Wind vel. in dome at exp. end (m/s)
DescriptionE   : Wind velocity measured in the dome/enclosure at the exposure end (m/s).
DescriptionJ   : 露出終了時に測定したドーム内風速 (m/s)。
-----
HeaderKeyWord: DOM-WMAX
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 8.34
Comment       : Max wind vel. in dome during exp. (m/s)
DescriptionE   : Maximum wind velocity (m/s) measured inside of the dome/enclosure during the
                  exposure.
DescriptionJ   : 露出中にドーム内部で測定された最大風速。単位は m/s。
-----
HeaderKeyWord: DOM-WMIN
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 5.22
Comment       : Min wind vel. in dome during exp. (m/s)
DescriptionE   : Minimum wind velocity (m/s) measured inside of the dome/enclosure during the
                  exposure.
DescriptionJ   : 露出中にドーム内部で測定された最小風速。単位は m/s。
-----
HeaderKeyWord: DOM-WND
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 9.12
Comment       : Wind velocity in the dome (m/s)
DescriptionE   : Wind velocity measured in the dome/enclosure (m/s).
DescriptionJ   : ドーム内で測定した風速 (m/s)。
-----
HeaderKeyWord: DOM-WSTR
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 10.99
Comment       : Wind vel. in dome at exp. end (m/s)
DescriptionE   : Wind velocity measured in the dome/enclosure at the exposure start (m/s).
DescriptionJ   : 露出開始時に測定したドーム内風速 (m/s)。
-----
HeaderKeyWord: NAS-TAVE
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 274.01
Comment       : Averaged Temperature in Nas.enclosure(K)
DescriptionE   : The average of the temperature (Kelvin) in the Nasmyth enclosure.
DescriptionJ   : 露出中のナスミス室内の平均温度。単位はケルビン (K)。
-----

```

[Dictionary = Basic] (Category 順、その 2-4: Environment(続))

```

-----
HeaderKeyWord: NAS-TMAX
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 274.13
Comment       : Max temperature in Nasmyth enclosure (K)
DescriptionE   : Maximum temperature (Kelvin) in the Nasmyth enclosure.
DescriptionJ   : 露出中のナスミス室内の最高温度。単位はケルビン (K)。
-----
HeaderKeyWord: NAS-TMIN
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 273.66
Comment       : Min temperature in Nasmyth enclosure (K)
DescriptionE   : Minimum temperature (Kelvin) in the Nasmyth enclosure.
DescriptionJ   : 露出中のナスミス室内の最低温度。単位はケルビン (K)。
-----
HeaderKeyWord: NAS-TSD
Category      : Environment
Importance    : Optional
FormatF       : F20.1
Unit          : K
Recommend     : -
Sample        : 0.3
Comment       : Standard Dev. of the Nas. room Temp. (K)
DescriptionE   : Standard Deviation of the temperature (Kelvin) in the Nasmyth enclosure.
DescriptionJ   : 露出中のナスミス室内における温度変化の標準偏差。単位はケルビン (K)。
-----
HeaderKeyWord: OUT-HEND
Category      : Environment
Importance    : Optional
FormatF       : F20.1
Unit          : %
Recommend     : -
Sample        : 5.7
Comment       : Outside humidity at exp. end (%)
DescriptionE   : Humidity (%) measured outside of the dome/enclosure at the exposure end.
DescriptionJ   : 露出終了時にドーム外部で測定された湿度。単位はパーセント (%)。
-----
HeaderKeyWord: OUT-HSTR
Category      : Environment
Importance    : Optional
FormatF       : F20.1
Unit          : %
Recommend     : -
Sample        : 5.5
Comment       : Outside humidity at exp. start (%)
DescriptionE   : Humidity (%) measured outside of the dome/enclosure at the exposure start.
DescriptionJ   : 露出開始時にドーム外部で測定された湿度。単位はパーセント (%)。
-----
HeaderKeyWord: OUT-HUM
Category      : Environment
Importance    : Optional
FormatF       : F20.1
Unit          : %
Recommend     : -
Sample        : 15.3
Comment       : Humidity measured outside of dome (%)
DescriptionE   : Humidity (%) measured outside of the dome/enclosure.
DescriptionJ   : ドーム外部で測定された湿度。単位はパーセント (%)。
-----
HeaderKeyWord: OUT-PEND
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : hpa
Recommend     : -
Sample        : 623.12
Comment       : Outside Atmos.press. at exp. end (hpa)
DescriptionE   : Atmospheric pressure (hpa) outside of the dome/enclosure at the exposure end.
DescriptionJ   : 露出終了時にドーム外部で測定された気圧。単位は hpa。
-----

```

[Dictionary = Basic] (Category 順、その 2-5: Environment(続))

```

-----
HeaderKeyWord: OUT-PRS
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : hpa
Recommend     : -
Sample        : 621.45
Comment       : Atmospheric pressure outside dome (hpa)
DescriptionE   : Atmospheric pressure (hpa) outside of the dome/enclosure.
DescriptionJ   : ドーム外部で測定された気圧。単位は hpa。
-----
HeaderKeyWord: OUT-PSTR
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : hpa
Recommend     : -
Sample        : 621.32
Comment       : Outside Atmos.press. at exp. start (hpa)
DescriptionE   : Atmospheric pressure (hpa) outside of the dome/enclosure at the exposure start.
DescriptionJ   : 露出開始時にドーム外部で測定された気圧。単位は hpa。
-----
HeaderKeyWord: OUT-TEND
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 274.01
Comment       : Outside temperature at exp. end (K)
DescriptionE   : Temperature (Kelvin) measured outside of the dome/enclosure at the exposure end.
DescriptionJ   : 露出終了時にドーム外部で測定された気温。単位はケルビン (K)。
-----
HeaderKeyWord: OUT-TMP
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 277.39
Comment       : Temperature measured outside of dome (K)
DescriptionE   : Temperature (Kelvin) measured outside of the dome/enclosure.
DescriptionJ   : ドーム外部で測定された気温。単位はケルビン (K)。
-----
HeaderKeyWord: OUT-TSTR
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 273.44
Comment       : Outside temperature at exp. start (K)
DescriptionE   : Temperature (Kelvin) measured outside of the dome/enclosure at the exposure start.
DescriptionJ   : 露出開始時にドーム外部で測定された気温。単位はケルビン (K)。
-----
HeaderKeyWord: OUT-WEND
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 11.24
Comment       : Outside wind velocity at exp. end (m/s)
DescriptionE   : Wind velocity (m/s) measured outside of the dome/enclosure at the exposure end.
DescriptionJ   : 露出終了時にドーム外部で測定された風速。単位は m/s。
-----
HeaderKeyWord: OUT-WMAX
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 13.19
Comment       : Max Outside wind vel. during exp. (m/s)
DescriptionE   : Maximum wind velocity (m/s) measured outside of the dome/enclosure during the
                  exposure.
DescriptionJ   : 露出中にドーム外部で測定された最大風速。単位は m/s。
-----

```

[Dictionary = Basic] (Category 順、その 2-6: Environment(続))

```

-----
HeaderKeyWord: OUT-WMIN
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 9.59
Comment       : Min Outside wind vel. during exp. (m/s)
DescriptionE  : Minimum wind velocity (m/s) measured outside of the dome/enclosure during the
                exposure.
DescriptionJ  : 露出中にドーム外部で測定された最小風速。単位は m/s。
-----
HeaderKeyWord: OUT-WND
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 6.49
Comment       : Wind velocity outside of dome (m/s)
DescriptionE  : Wind velocity (m/s) measured outside of the dome/enclosure.
DescriptionJ  : ドーム外部で測定された風速。単位は m/s。
-----
HeaderKeyWord: OUT-WSTR
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : m/s
Recommend     : -
Sample        : 9.43
Comment       : Outside wind velocity at exp. start(m/s)
DescriptionE  : Wind velocity (m/s) measured outside of the dome/enclosure at the exposure start.
DescriptionJ  : 露出開始時にドーム外部で測定された風速。単位は m/s。
-----
HeaderKeyWord: SEEING
Category      : Environment
Importance    : Optional
FormatF       : F20.2
Unit          : arcsec
Recommend     : -
Sample        : 0.34
Comment       : StarSize FWHM at telescope focus(arcsec)
DescriptionE  : FWHM of the star size at telescope focus. It'll be measured with autoguider.
                Unit is arcsec.
DescriptionJ  : 望遠鏡焦点部における星像の FWHM。オートガイダーを用いて測定される。単位は arcsec。
-----
HeaderKeyWord: TRAN-END
Category      : Environment
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 0.875
Comment       : Sky transparency at the end of exposure
DescriptionE  : Sky transparency at the end of exposure
DescriptionJ  : 露出終了時の大気透過率。
-----
HeaderKeyWord: TRAN-STR
Category      : Environment
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 0.875
Comment       : Sky transparency at beginning of exp.
DescriptionE  : Sky transparency at the beginning of the exposure.
DescriptionJ  : 露出開始時の大気透過率。
-----
HeaderKeyWord: TRANSP
Category      : Environment
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 0.875
Comment       : Sky transparency
DescriptionE  : Sky transparency
DescriptionJ  : 露出中の典型的な時刻における大気透過率。
-----

```

[Dictionary = Basic] (Category 順、その 2-7: Environment(続))

```
-----
HeaderKeyWord: WEATHER
Category      : Environment
Importance    : Optional
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'CLEAR  '
Comment       : Weather condition
DescriptionE   : Weather condition. CLEAR/FINE/nn%CLOUD...?
DescriptionJ   : 天候情報。CLEAR/FINE/nn%CLOUD... などがある。
-----
```

[Dictionary = Basic] (Category 順、その 3-1: File)

```
-----
HeaderKeyWord: BLANK
Category      : File
Importance    : Common
FormatF       : I20
Unit          : -
Recommend     : -
Sample        : -32768
Comment       : Value used for NULL pixels
DescriptionE   : Value used to specify the absence of pixel values. BLANK is normally used to fill
out regions of the frame that have not been exposed e.g. because of windowing.
DescriptionJ   : ピクセル値がこの BLANK 値と等しい場合、このピクセル値は意味のない値であると解釈される。
-----
HeaderKeyWord: BSCALE
Category      : File
Importance    : Common
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 1.12345678
Comment       : Real=fits-value*BSCALE+BZERO
DescriptionE   : This keyword shall be used, along with the BZERO keyword, when the array pixel
values are not the true physical values. Equation:
physical_value = BZERO + BSCALE x array_value
DescriptionJ   : データのピクセル値が実際の物理値を表していない時に、そのピクセル値を実際の物理値へ変換するた
めに用いる。その値は、キーワード BZERO と共に書き下される以下の変換式により求められる。
物理値 = BZERO + BSCALE x ピクセル値
-----
HeaderKeyWord: BUNIT
Category      : File
Importance    : Common
FormatF       : A10
Unit          : -
Recommend     : -
Sample        : 'ADU  '
Comment       : Unit of original pixel values
DescriptionE   : The value field shall contain a character string, describing the physical units in
which the quantities in the array, after applicatin of BSCALE and BZERO, are
expressed.
DescriptionJ   : データが表す実際の物理値（キーワード BSCALE とキーワード BZERO による変換式を使ってピクセル値
から計算される）の単位であり、文字列で与えられる。
-----
HeaderKeyWord: BZERO
Category      : File
Importance    : Common
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 0.00000001
Comment       : Real=fits-value*BSCALE+BZERO
DescriptionE   : This keyword shall be used, along with the BSCALE keyword, when the array pixel
values are not the true physical values, to transform the primary data array values
to the true values. Equation: physical_value = BZERO + BSCALE x array_value.
DescriptionJ   : データのピクセル値が実際の物理値を表していない時に、そのピクセル値を実際の物理値へ変換するた
めに用いられる。この変換式以下の通りである。物理値 = BZERO + BSCALE x ピクセル値
-----
```

[Dictionary = Basic] (Category 順、その 3-2: File(続))

```

-----
HeaderKeyWord: CDELT1
Category      : File
Importance    : Common
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 0.00001212
Comment       : X Scale projected on detector (#/pix)
DescriptionE  : The value is a floating point number giving the partial derivative of the
                coordinate specified by the CTYPE1 keywords with respect to the pixel index,
                evaluated at the reference point CRPIX1, in units of the coordinate specified by
                the CTYPE1 keyword.
DescriptionJ  : キーワード CRPIX1 で表される基準ピクセルの位置において+1 ピクセル移動した時の、キーワード CTYPE1
                で表される座標値の増分を表す。
-----
HeaderKeyWord: CDELT2
Category      : File
Importance    : Common
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 0.00001155
Comment       : Y scale projected on detector (#/pix)
DescriptionE  : The value is a floating point number giving the partial derivative of the
                coordinate specified by the CTYPE2 keywords with respect to the pixel index,
                evaluated at the reference point CRPIX2, in units of the coordinate specified by
                the CTYPE2 keyword.
DescriptionJ  : キーワード CRPIX2 で表される基準ピクセルの位置において+1 ピクセル移動した時の、キーワード CTYPE2
                で表される座標値の増分を表す。
-----
HeaderKeyWord: CRPIX1
Category      : File
Importance    : Common
FormatF       : F20.1
Unit          : pixel
Recommend     : -
Sample        : 512.5
Comment       : Reference pixel in X (pixel)
DescriptionE  : Pixel position of the reference point along #1 axis. By convention the center of
                the pixel is pix.0, pix.5 gives the right edge of the pixel and (pix-1).5 its left
                edge. Origin is (1,1).
DescriptionJ  : 第1軸方向での参照基準点の位置を、その軸上での目盛であるインデックスで表した浮動小数点数であ
                る。ピクセル中央が xxx.0、右端が xxx.5、左端が (xxx-1).5 となる。原点は (1,1)。
-----
HeaderKeyWord: CRPIX2
Category      : File
Importance    : Common
FormatF       : F20.1
Unit          : pixel
Recommend     : -
Sample        : 512.5
Comment       : Reference pixel in Y (pixel)
DescriptionE  : Pixel position of the reference point along #2 axis. By convention the center of
                the pixel is pix.0,pix.5 gives the bottom edge of pixel and (pix-1).5 its top edge.
                Origin is (1,1).
DescriptionJ  : 第2軸方向での参照基準点の位置を、その軸上での目盛であるインデックスで表した浮動小数点数であ
                る。ピクセル中央が xxx.0、右端が xxx.5、左端が (xxx-1).5 となる。原点は (1,1)。
-----
HeaderKeyWord: CRVAL1
Category      : File
Importance    : Common
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 29.33333333
Comment       : Physical value of the reference pixel X
DescriptionE  : The value field shall contain a floating point number giving the value of the
                partial coordinate specified by the CTYPE1 keyword at the reference point CRPIX1.
DescriptionJ  : 参照基準点 CRPIX1 での CTYPE1 の座標における値であり、浮動小数点数で表される。
-----
HeaderKeyWord: CRVAL2
Category      : File
Importance    : Common
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 2.09777777
Comment       : Physical value of the reference pixel Y
DescriptionE  : The value field shall contain a floating point number giving the value of the
                partial coordinate specified by the CTYPE2 keyword at the reference point CRPIX2.
DescriptionJ  : 参照基準点 CRPIX2 での CTYPE2 の座標における値であり、浮動小数点数で表される。
-----

```

[Dictionary = Basic] (Category 順、その 3-3: File(続))

```

-----
HeaderKeyWord: CTYPE1
Category      : File
Importance    : Common
FormatF       : A10
Unit          : -
Recommend     : RA---TAN
Sample        : 'RA---TAN'
Comment       : Pixel coordinate system
DescriptionE   : Type of projection used for X axis. RA---TAN or DEC--TAN for imaging mode, and
                  WAVELENGTH for dispersion axis of spectroscopy mode.
DescriptionJ   : 座標名を表す文字列。撮像観測の場合は 'RA---TAN' 或いは、'DEC--TAN' となり、分光観測の場合は
                  'WAVELENGTH' が推奨される。
-----
HeaderKeyWord: CTYPE2
Category      : File
Importance    : Common
FormatF       : A10
Unit          : -
Recommend     : DEC--TAN
Sample        : 'DEC--TAN'
Comment       : Pixel coordinate system
DescriptionE   : Type of projection used for Y axis. RA---TAN or DEC--TAN for Imaging mode, and
                  WAVELENGTH for dispersion axis of spectroscopy mode.
DescriptionJ   : 座標名を表す文字列。撮像観測の場合は 'RA---TAN' 或いは、'DEC--TAN' となり、分光観測の場合は
                  'WAVELENGTH' が推奨される。
-----
HeaderKeyWord: CUNIT1
Category      : File
Importance    : Common
FormatF       : A10
Unit          : -
Recommend     : degree
Sample        : 'degree '
Comment       : Units used in both CRVAL1 and CDELTA1
DescriptionE   : Physical unit used in both CRVAL1 and CDELTA1. 'nm' is recommended for spectroscopy
                  mode.
DescriptionJ   : 第1軸が表す実際の座標値の単位であり、文字列で与えられる。空間情報の場合は 'degree'、波長情
                  報の場合は 'nm' が推奨される。
-----
HeaderKeyWord: CUNIT2
Category      : File
Importance    : Common
FormatF       : A10
Unit          : -
Recommend     : degree
Sample        : 'degree '
Comment       : Units used in both CRVAL2 and CDELTA2
DescriptionE   : Physical unit used in both CRVAL2 and CDELTA2. 'nm' is recommended for spectroscopy
                  mode.
DescriptionJ   : 第2軸が表す実際の座標値の単位であり、文字列で与えられる。空間情報の場合は 'degree'、波長情
                  報の場合は 'nm' が推奨される。
-----

```

[Dictionary = Basic] (Category 順、その 4-1: FITS)

```

-----
HeaderKeyWord: BITPIX
Category      : FITS
Importance    : Common
FormatF       : I20
Unit          : -
Recommend     : -
Sample        : 32
Comment       : # of bits storing pix values
DescriptionE   : The absolute value specify the number of bits that represent a data value. The only
                  valid values are: 8, 16 (16-bit integer), 32 (32-bit integer), -32 (IEEE single
                  precision floating point), -64 (IEEE double precision floating point).
DescriptionJ   : キーワードの値は整数であり、その絶対値はデータ構造のサイズを求める際に用いられ、一つのデー
                  値を表現するために使われるビット数を表す。有効な値は次の5つである: 8、16 (16ビット整数)、32
                  (32ビット整数)、-32 (単精度浮動小数点数)、-64 (倍精度浮動小数点数)
-----
HeaderKeyWord: END
Category      : FITS
Importance    : Common
FormatF       : -
Unit          : -
Recommend     : -
Sample        : -
Comment       : -
DescriptionE   : This keyword has no associated value. Columns 9-80 shall be filled with ASCII
                  blanks.
DescriptionJ   : このキーワードは値を持たない。9-80 列は ASCII 空白となる。
-----

```

[Dictionary = Basic] (Category 順、その 4-2: FITS(続))

HeaderKeyWord:	EXTEND
Category	: FITS
Importance	: Common
FormatF	: BOOLEAN
Unit	: -
Recommend	: -
Sample	: F
Comment	: Presence of FITS Extention
DescriptionE	: If FITS file contains extensions, the keyword EXTEND and the value T must appear in the primary header just after the last NAXISn card image. The presence of this keyword with the value T in the primary header does not require that extensions be present.
DescriptionJ	: FITS ファイルが extension を持つ場合は、Primary ヘッダー内にこのキーワードを記述し、値を 'T' とする。記述位置は最後に記述されている NAXISn の直後である。このキーワードの記述があり、その値が 'T' であっても、実際には extension を持たない、ということも許される。
HeaderKeyWord:	NAXIS
Category	: FITS
Importance	: Common
FormatF	: I20
Unit	: -
Recommend	: -
Sample	: 2
Comment	: # of axes in frame
DescriptionE	: The value field shall contain a non-negative integer no greater than 999, representing the number of axes in an ordinary data array. A value of zero signifies that no data follow the header in the HDU (Header and Data Unit).
DescriptionJ	: このキーワードの値は 999 を越えない非負の整数であり、データ配列中の軸の数を表す。この値が 0 の場合は、その FITS 要素の中にデータが存在しないことを示す。
HeaderKeyWord:	NAXIS1
Category	: FITS
Importance	: Common
FormatF	: I20
Unit	: pixel
Recommend	: -
Sample	: 1024
Comment	: # of pixels/row
DescriptionE	: Number of pixels along the X axis (rows). If NAXIS is equal to 0, there should not be any NAXISn keywords.
DescriptionJ	: データ配列の第 1 軸方向のデータ要素数を表す。NAXIS が 0 の場合、NAXISn には一切記述してはならない。
HeaderKeyWord:	NAXIS2
Category	: FITS
Importance	: Common
FormatF	: I20
Unit	: -
Recommend	: -
Sample	: 1024
Comment	: # of rows (also # of scan lines)
DescriptionE	: Number of pixels along the Y axis (lines). If NAXIS is equal to 0, there should not be any NAXISn keywords.
DescriptionJ	: データ配列の第 2 軸方向のデータ要素数を表す。NAXIS が 0 の場合、NAXISn には一切記述してはならない。
HeaderKeyWord:	NAXIS3
Category	: FITS
Importance	: Optional
FormatF	: I20
Unit	: -
Recommend	: -
Sample	: 36
Comment	: # of the 3rd axis
DescriptionE	: Number of pixels along the Z (3rd) axis. If NAXIS is equal to 0, there should not be any NAXISn keywords.
DescriptionJ	: データ配列の第 3 軸方向のデータ要素数を表す。NAXIS が 0 の場合、NAXISn には一切記述してはならない。
HeaderKeyWord:	SIMPLE
Category	: FITS
Importance	: Common
FormatF	: BOOLEAN
Unit	: -
Recommend	: T
Sample	: T
Comment	: Standard FITS format
DescriptionE	: SIMPLE must be equal to T to conform to FITS. This keyword should be appeared at the top of the HDU.
DescriptionJ	: ファイルが FITS の規約に準拠していれば値を T とする。すばるでは必ず T としなければならない。プライマリヘッダー部の先頭になければならない。

[Dictionary = Basic] (Category 順、その 5-1: Instrument)

```

-----
HeaderKeyWord: AUTOGUID
Category      : Instrument
Importance    : Optional
FormatF       : A8
Unit          : -
Recommend     : -
Sample        : 'OFF'
Comment       : Auto Guide ON/OFF
DescriptionE   : This keyword shows whether the Auto Guider (AG) was ON or OFF. If the value is ON,
                  it means that the telescope is tracking by using the AG system.
DescriptionJ   : Auto Guider(AG) が積分中に ON か OFF かを記述する。AG が ON とは、AG による tracking が行われ
                  ている事を意味する
-----
HeaderKeyWord: BIN-FCT1
Category      : Instrument
Importance    : Common
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 1
Comment       : Binning factor of X axis (pixel)
DescriptionE   : Binning factor of X axis (pixel) when reading the data. X means a direction of
                  NAXIS1.
DescriptionJ   : データ読みだし時の X 方向のビンニング数。X 方向とは CCD の NAXIS1 に沿った方向。
-----
HeaderKeyWord: BIN-FCT2
Category      : Instrument
Importance    : Common
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 1
Comment       : Binning factor of Y axis (pixel)
DescriptionE   : Binning factor of Y axis (pixel) when reading the data. Y means a direction of
                  NAXIS2.
DescriptionJ   : データ読みだし時の Y 方向のビンニング数。Y 方向とは CCD の NAXIS2 に沿った方向。
-----
HeaderKeyWord: COADD
Category      : Instrument
Importance    : Optional
FormatF       : I20
Unit          : -
Recommend     : -
Sample        : 10
Comment       : Frame is created by # of sub-exposures
DescriptionE   : 'COADD' shows how many sub-exposures were co-added into a frame. Integration time
                  of each sub-exposure is shown in 'EXPTIME'. Total integration time of a frame
                  corresponds to the product of 'EXPTIME' and this 'COADD'.
                  (EXPTIME = EXPTIME * COADD)
DescriptionJ   : 1 frame が何枚の sub-exposure を足しあわせた物かを記述する。sub-exposure の積分時間は
                  EXPTIME で記述され、EXPTIME と COADD を掛け合わせた物が最終的な 1 frame の積分時間に対応す
                  る。(EXPTIME = EXPTIME * COADD)
-----
HeaderKeyWord: DET-Ann
Category      : Instrument
Importance    : Optional
FormatF       : F20.3
Unit          : degree
Recommend     : -
Sample        : 0.045
Comment       : Relative angle of nn-th detector (deg)
DescriptionE   : Angle between nn-th detector and instrument's standard line (degree)
DescriptionJ   : nn 番目の検出器の基準線に対する相対的な取付角 (degree)
-----
HeaderKeyWord: DET-ID
Category      : Instrument
Importance    : Optional
FormatF       : I20
Unit          : -
Recommend     : -
Sample        : 2
Comment       : ID of the detector used for this data
DescriptionE   : ID of the detector used for this fits data. The detector can be identified by the
                  number when the instrument equips multi detectors.
DescriptionJ   : 複数の検出器からなる観測装置の場合、当該データを生成させた検出器 (CCD) 等の識別子
-----

```

[Dictionary = Basic] (Category 順、その 5-2: Instrument(続))

HeaderKeyWord:	DET-NSMP
Category	: Instrument
Importance	: Optional
FormatF	: I20
Unit	: -
Recommend	: -
Sample	: 1
Comment	: # of multi-sampling in an exposure
DescriptionE	: number of multi-sampling in an exposure
DescriptionJ	: 1 回の露出中に複数回の読み出しを行う場合にその回数

HeaderKeyWord:	DET-P1nn
Category	: Instrument
Importance	: Optional
FormatF	: F20.3
Unit	: arcsec
Recommend	: -
Sample	: 61.875
Comment	: Relative X pos of nn-th detector(arcsec)
DescriptionE	: X Position of the nn-th detector center relative from the field center or instrument standard position
DescriptionJ	: 複数個の検出器を持つ装置の場合に、装置基準位置、或いは、フィールドセンターから nn 番目の検出器の中心位置までの X 軸 (第 1 軸) 方向の相対位置

HeaderKeyWord:	DET-P2nn
Category	: Instrument
Importance	: Optional
FormatF	: F20.3
Unit	: arcsec
Recommend	: -
Sample	: 120.125
Comment	: Relative Y pos of nn-th detector(arcsec)
DescriptionE	: Y Position of the nn-th detector center relative from the field center or instrument standard position
DescriptionJ	: 複数個の検出器を持つ装置の場合に、装置基準位置、或いは、フィールドセンターから nn 番目の検出器の中心位置までの Y 軸 (第 2 軸) 方向の相対位置

HeaderKeyWord:	DET-RST
Category	: Instrument
Importance	: Optional
FormatF	: I20
Unit	: -
Recommend	: -
Sample	: 2
Comment	: reset number before exposure
DescriptionE	: Number of detector reset performed before exposure.
DescriptionJ	: 露出前に検出器をリセットした回数。

HeaderKeyWord:	DET-SMPL
Category	: Instrument
Importance	: Optional
FormatF	: A20
Unit	: -
Recommend	: -
Sample	: 'destructive'
Comment	: sampling method
DescriptionE	: Sampling method of produced image.
DescriptionJ	: どのようなパターンでデータをサンプリングしたかを示す文字列。

HeaderKeyWord:	DET-TAVE
Category	: Instrument
Importance	: Optional
FormatF	: F20.2
Unit	: K
Recommend	: -
Sample	: 121.87
Comment	: Average of the detector temperature (K)
DescriptionE	: Average of the detector temperature during exposure. Unit is Kelvin (K).
DescriptionJ	: 検出器の平均の温度。基本的には時間平均を意味している。単位はケルビン (K)。

HeaderKeyWord:	DET-TMAX
Category	: Instrument
Importance	: Optional
FormatF	: F20.2
Unit	: K
Recommend	: -
Sample	: 121.99
Comment	: Max detector temperature during exp. (K)
DescriptionE	: Maximum detector temperature during the exposure. Unit is Kelvin (K).
DescriptionJ	: 露出中の検出器の最高温度。単位はケルビン (K)。

[Dictionary = Basic] (Category 順、その 5-3: Instrument(続))

```

-----
HeaderKeyWord: DET-TMED
Category      : Instrument
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 121.54
Comment       : Median of the detector temperature (K)
DescriptionE   : Median of the detector temperature during the exposure. Unit is Kelvin (K).
DescriptionJ   : 露出中の検出器温度のメディアン値。単位はケルビン (K)。
-----
HeaderKeyWord: DET-TMIN
Category      : Instrument
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 125.88
Comment       : Min detector temperature during exp. (K)
DescriptionE   : Minimum detector temperature during the exposure. Unit is Kelvin (K).
DescriptionJ   : 露出中の検出器の最低温度。単位はケルビン (K)。
-----
HeaderKeyWord: DET-TMP
Category      : Instrument
Importance    : Common
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 165.12
Comment       : Detector temperature (K)
DescriptionE   : Detectors' typical (representative) temperature. Unit is Kelvin (K).
DescriptionJ   : 検出器の温度の典型的な値 (代表値)。単位はケルビン (K)。
-----
HeaderKeyWord: DET-Tnn
Category      : Instrument
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 165.13
Comment       : nn-th Detector temperature (K)
DescriptionE   : nn-th Detectors' typical (representative) temperature. Unit is Kelvin (K).
DescriptionJ   : n n 番目の検出器温度の典型的な値 (代表値)。単位はケルビン (K)。
-----
HeaderKeyWord: DET-TSD
Category      : Instrument
Importance    : Optional
FormatF       : F20.2
Unit          : K
Recommend     : -
Sample        : 0.21
Comment       : Standard Dev. of the detector temp (K)
DescriptionE   : Standard deviation of the detector temperature during the exposure. Unit is Kelvin (K).
DescriptionJ   : 露出中の検出器温度の標準偏差。単位はケルビン (K)。
-----
HeaderKeyWord: DET-VER
Category      : Instrument
Importance    : Optional
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'Ver.1-c-2'
Comment       : Detector control command script name
DescriptionE   : Detector control command script name
DescriptionJ   : 検出器制御コマンドスクリプトの名前。
-----
HeaderKeyWord: DETECTOR
Category      : Instrument
Importance    : Common
FormatF       : A20
Unit          : -
Recommend     : -
Sample        : 'CCD0001 '
Comment       : Name of the detector/CCD
DescriptionE   : Name/Identification of the detector/CCD.
DescriptionJ   : CCD 等の検出器の名称
-----

```

[Dictionary = Basic] (Category 順、その 5-4: Instrument(続))

```

-----
HeaderKeyWord: DETPXSZ1
Category      : Instrument
Importance    : Optional
FormatF       : F20.4
Unit          : mm
Recommend     : -
Sample        : 0.0401
Comment       : Detector pixel size in axis1 (mm)
DescriptionE   : Detector pixel size in first axis (NAXIS1). Unit is mm.
DescriptionJ   : 検出器の第1軸 (NAXIS1) 方向のピクセルサイズ。単位は mm。
-----
HeaderKeyWord: DETPXSZ2
Category      : Instrument
Importance    : Optional
FormatF       : F20.4
Unit          : mm
Recommend     : -
Sample        : 0.0399
Comment       : Detector pixel size in axis2 (mm)
DescriptionE   : Detector pixel size in second axis (NAXIS2). Unit is mm.
DescriptionJ   : 検出器の第2軸 (NAXIS2) 方向のピクセルサイズ。単位は mm。
-----
HeaderKeyWord: EFP-MIN1
Category      : Instrument
Importance    : Optional
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 5
Comment       : Start X pos. of effective area (pix)
DescriptionE   : Start pixel position of effective data region in first axis(NAXIS1).
                  Effective data region means the region excluding overscan region and includes the
                  information from the sky.
DescriptionJ   : 第1軸 (NAXIS1) 方向の有効領域の開始ピクセル位置。有効領域とはオーバースキャン領域を含まない、
                  天体の情報を含む領域を指す。
-----
HeaderKeyWord: EFP-MIN2
Category      : Instrument
Importance    : Optional
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 10
Comment       : Start Y pos. of effective area (pix)
DescriptionE   : Start pixel position of effective data region in second axis(NAXIS2).
                  Effective data region means the region excluding overscan region and includes the
                  information from the sky.
DescriptionJ   : 第2軸 (NAXIS2) 方向の有効領域の開始ピクセル位置。有効領域とはオーバースキャン領域を含まない、
                  天体の情報を含む領域を指す。
-----
HeaderKeyWord: EFP-RNG1
Category      : Instrument
Importance    : Optional
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 1024
Comment       : X Range of overscan area (pix)
DescriptionE   : Range of effective data region in first axis(NAXIS1). Unit is pixel.
                  Effective data region means the region excluding overscan region and includes the
                  information from the sky.
DescriptionJ   : 第1軸 (NAXIS1) 方向の有効領域のピクセル単位での大きさ。有効領域とはオーバースキャン領域を含ま
                  ない、天体の情報を含む領域を指す。
-----
HeaderKeyWord: EFP-RNG2
Category      : Instrument
Importance    : Optional
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 1024
Comment       : Y Range of overscan area (pix)
DescriptionE   : Range of effective data region in second axis(NAXIS2). Unit is pixel.
                  Effective data region means the region excluding overscan region and includes the
                  information from the sky.
DescriptionJ   : 第2軸 (NAXIS2) 方向の有効領域のピクセル単位での大きさ。有効領域とはオーバースキャン領域を含ま
                  ない、天体の情報を含む領域を指す。
-----

```

[Dictionary = Basic] (Category 順、その 5-5: Instrument(続))

HeaderKeyWord:	EXP-ID
Category	: Instrument
Importance	: Common
FormatF	: A12
Unit	: -
Recommend	: -
Sample	: CACE00000231
Comment	: ID of the exposure this data was taken
DescriptionE	: ID of an exposure this data was taken. Effective for multi detectors. First 3 characters represent instrument. The 4th character is 'E'. Remaining 8 digits are sequential number. The representation of first 3 characters are the same with for FRAMEID.
DescriptionJ	: このデータの撮られた露出を表す ID 番号。複数の検出器に対してこの ID 番号が使われる。最初の 3 文字は観測装置を表す。4 文字目は常に'E'。残りの 8 桁の数字が通し番号を表す。最初の 3 文字の表記方法は FRAMEID と同じ。
HeaderKeyWord:	FLT-Ann
Category	: Instrument
Importance	: Optional
FormatF	: F20.2
Unit	: degree
Recommend	: -
Sample	: 6.12
Comment	: Inclination of nn-th Filter (degree)
DescriptionE	: Inclination of the nn-th filter reference to optical axis. Unit is degree. When filter surface is normal to optical axis, this value is 0.0.
DescriptionJ	: nn 番目のフィルターの光軸に対する角度。単位は度 (degree)。0 度の時に光軸とフィルター面が直交する。
HeaderKeyWord:	FILTERnn
Category	: Instrument
Importance	: Optional
FormatF	: A30
Unit	: -
Recommend	: -
Sample	: 'FILTER:R'
Comment	: Filter name/ID
DescriptionE	: Filter/Grism name/ID in nn-th filter wheel which is used in the exposure.
DescriptionJ	: nn 番目のフィルターホイールに入っている、観測に使用されたフィルターまたはグリズムの識別子。nn は 2 桁の整数。
HeaderKeyWord:	FRAMEID
Category	: Instrument
Importance	: Common
FormatF	: A12
Unit	: -
Recommend	: -
Sample	: CACA00000478
Comment	: Image sequential number
DescriptionE	: Sequential number identifying the frame. First 3 characters represent instrument. The 4th character is 'A' for raw data or 'Q' for reduced data. The following 8 digit is for a sequential number.
DescriptionJ	: フレームを識別するための通し番号。最初の 3 文字は観測装置を表す。4 文字目は生データは'A'、処理済みには 'Q' がつく。残りの 8 桁の数字が通し番号を表す。
HeaderKeyWord:	GAIN
Category	: Instrument
Importance	: Common
FormatF	: F20.3
Unit	: e/ADU
Recommend	: -
Sample	: 1.456
Comment	: AD conversion factor (electron/ADU)
DescriptionE	: AD conversion factor of the detector. Unit is electron/ADU.
DescriptionJ	: 検出器の A/D 変換の係数。単位は electron/ADU。
HeaderKeyWord:	INS-VER
Category	: Instrument
Importance	: Optional
FormatF	: A30
Unit	: -
Recommend	: -
Sample	: 'FOCAS-H01C01M01F01'
Comment	: Version of the instrument /control-soft
DescriptionE	: INS-VER describes a version of both the instrument hardware and control-software, including the detector control-software (Messia) and version of FITS keyword dictionary.
DescriptionJ	: 観測装置のハード及び制御ソフトのバージョンが記述される。また、CCD 制御ソフト (Messia) のバージョンや FITS 辞書のバージョンも含まれる。

[Dictionary = Basic] (Category 順、その 5-6: Instrument(続))

HeaderKeyWord:	INST-PA
Category	: Instrument
Importance	: Optional
FormatF	: F20.3
Unit	: degree
Recommend	: -
Sample	: 89.999
Comment	: P.A. of Instrument flange (degree)
DescriptionE	: Position Angle of the instrument flange (degree). This value will be used for calculating the Slit P.A. and CCD P.A. The angle is 0 in north direction and 90 degree in east.
DescriptionJ	: 観測装置フランジの方位角 (Position Angle:P.A.). スリットと CCD の方位角を計算するのに使われる。単位は度 (degree) で、北を0度とし、東を90度とする。
HeaderKeyWord:	INSTRUME
Category	: Instrument
Importance	: Common
FormatF	: A20
Unit	: -
Recommend	: -
Sample	: 'OHS'
Comment	: Name of instrument
DescriptionE	: Character string representing the name of the instrument.
DescriptionJ	: 観測装置の名称を表す文字列。
HeaderKeyWord:	OBS-MOD
Category	: Instrument
Importance	: Common
FormatF	: A30
Unit	: -
Recommend	: -
Sample	: 'Imaging'
Comment	: Observation Mode
DescriptionE	: Observation Mode of the data taken (Spectroscopy, Imaging, Imaging-Polarimetry, Spectro-Polarimetry, etc.). The value is defined by Instrument Developers.
DescriptionJ	: データ取得時の観測モードが記述される (Spectroscopy, Imaging, Imaging-Polarimetry, Spectro-Polarimetry, etc.). 値は装置開発者が定義する。
HeaderKeyWord:	PRD-MIN1
Category	: Instrument
Importance	: Optional
FormatF	: I20
Unit	: pixel
Recommend	: -
Sample	: 1
Comment	: Start X pos. of partial readout (pix)
DescriptionE	: If the CCD data is taken by partial readout, this keyword shows a start X-position of partial readout. The value presents a physical CCD pixel where a partial readout is started (greater than 0).
DescriptionJ	: 部分読み出しデータにおいて CCD 上の読み出し開始 X 位置を示す。ここで X とは NAXIS1 軸に沿った方向。部分読み出しをしない時は、開始が1となる。もしビニングをした場合でも、この項目の値は読み出しを開始する CCD 上の物理的ピクセル位置を表す。
HeaderKeyWord:	PRD-MIN2
Category	: Instrument
Importance	: Optional
FormatF	: I20
Unit	: pixel
Recommend	: -
Sample	: 1
Comment	: Start pos Y of partial readout (pix)
DescriptionE	: If the CCD data is taken by partial readout, this keyword shows a start Y-position of partial readout. The value presents a physical CCD pixel where a partial readout is started (greater than 0).
DescriptionJ	: 部分読み出しデータにおいて CCD 上の読み出し開始 Y 位置を示す。ここで Y とは NAXIS2 軸に沿った方向。部分読み出しをしない時は、開始が1となる。もしビニングをした場合でも、この項目の値は読み出しを開始する CCD 上の物理的ピクセル位置を表す。
HeaderKeyWord:	PRD-RNG1
Category	: Instrument
Importance	: Optional
FormatF	: I20
Unit	: pixel
Recommend	: -
Sample	: 2048
Comment	: X Range of the partial readout (pix)
DescriptionE	: If the data is taken by partial readout, this keyword shows a range of partial readout along a X-direction. The value is a actually CCD range being used for data. $PRD-RNG1 = BIN-FCT1 * EFP-RNG1$.
DescriptionJ	: 部分読み出しデータにおいて PRD-MIN1 (CCD 上の部分読み出し開始 X 位置) からの NAXIS1 方向の読みだしの幅を示す。ビニングをした場合でも、この項目の値は読み出しをする CCD 上の物理的ピクセル幅を表している。 $PRD-RNG1 = BIN-FCT1 * EFP-RNG1$

[Dictionary = Basic] (Category 順、その 5-7: Instrument(続))

```
-----
HeaderKeyWord: PRD-RNG2
Category      : Instrument
Importance    : Optional
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 1024
Comment       : Y range of the partial readout (pix)
DescriptionE  : If the data is taken by partial readout, this keyword shows a range of partial
                readout along a Y-direction. The value is a actually CCD range being used for
                data. PRD-RNG2 = BIN-FCT2 * EFP-RNG2.
DescriptionJ  : 部分読み出しデータにおいて PRD-MIN2 (CCD 上の部分読み出し開始 Y 位置) からの NAXIS2 方向の
                読みだしの幅を示す。ビニングをした場合でも、この項目の値は読み出しをする CCD 上の物理的
                ピクセル幅を表している。PRD-RNG2 = BIN-FCT2 * EFP-RNG2
-----
```

[Dictionary = Basic] (Category 順、その 6-1: Object)

```
-----
HeaderKeyWord: DATA-TYP
Category      : Object
Importance    : Common
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'BIAS'
Comment       : Type / Characteristics of this data
DescriptionE  : This keyword describe a data type/characteristics.
                /OBJECT/BIAS/DARK/DOMEFLAT/SKYFLAT/INSTFLAT/COMPARISON/STANDARD_STAR/...
DescriptionJ  : 取得データの種別を記述する。/OBJECT/BIAS/DARK/DOMEFLAT/SKYFLAT/INSTFLAT/COMPARISON
                /STANDARD_STAR/...
-----
HeaderKeyWord: DATASET
Category      : Object
Importance    : Object
FormatF       : A20
Unit          : -
Recommend     : -
Sample        : 'o98003d1021'
Comment       : ID of an observation dataset
DescriptionE  : ID of an observation dataset
DescriptionJ  : 観測データセットの I D。この値は必要に応じて制御系から撮像、あるいはフレーム生成コマンドのパ
                ラメータとして投入される。
-----
HeaderKeyWord: DEC
Category      : Object
Importance    : Common
FormatF       : A12
Unit          : -
Recommend     : -
Sample        : '-01:23:45.67'
Comment       : DEC of pointing (+/-DD:MM:SS.SS)
DescriptionE  : Declination of telescope pointing. This value is based on an EQUINOX of observer's
                target table. Notice that this value dose NOT show accurate field center of the
                instrument.
DescriptionJ  : 望遠鏡指向位置の赤緯で、分点は項目 EQUINOX に記述されている。必ずしも観測装置の視野中心と一致
                する必要はない。
-----
HeaderKeyWord: DEC2000
Category      : Object
Importance    : Common
FormatF       : A12
Unit          : -
Recommend     : -
Sample        : '+20:00:12.34'
Comment       : DEC(J2000) of pointing (+/-DD:MM:SS.SS)
DescriptionE  : Declination of pointing based on J2000 equinox. If telescope control system is
                based on the J2000, this value is equals to the value of keyword DEC. Notice that
                this value dose NOT show accurate field center of the instrument.
DescriptionJ  : 分点 J 2 0 0 0 に準拠した赤緯。もし項目 EQUINOX に J2000 が用いられていれば、DEC と同じ値と
                なる。必ずしも観測装置の視野中心と一致する必要はない。
-----
```

[Dictionary = Basic] (Category 順、その 6-2: Object)

```

-----
HeaderKeyWord: EQUINOX
Category      : Object
Importance    : Common
FormatF       : F20.1
Unit          : year
Recommend     : -
Sample        : 1999.01
Comment       : Standard FK5 (years)
DescriptionE   : Epoch of the mean equator and equinox of the coordinate system used to express the
                  WCS mapping. (FK5).
DescriptionJ   : 望遠鏡指向の基準となる分点。この分点を基準として、RA、DEC をヘッダー中に記述する。
-----
HeaderKeyWord: OBJECT
Category      : Object
Importance    : Common
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : '3C120'
Comment       : Target Description
DescriptionE   : Identification of object observed.
DescriptionJ   : 観測対象天体の名称、或いは、識別子
-----
HeaderKeyWord: RA
Category      : Object
Importance    : Common
FormatF       : A12
Unit          : -
Recommend     : -
Sample        : '01:01:02.003'
Comment       : RA of telescope pointing (HH:MM:SS.SSS)
DescriptionE   : Right Ascension of telescope pointing. This value is based on an EQUINOX. Notice
                  that this value dose NOT show accurate field center of an instrument.
DescriptionJ   : 望遠鏡指向位置の赤経で、分点は項目 EQUINOX に記述されている。必ずしも観測装置の視野中心と一致
                  する必要はない。
-----
HeaderKeyWord: RA2000
Category      : Object
Importance    : Common
FormatF       : A12
Unit          : -
Recommend     : -
Sample        : '21:54:32.123'
Comment       : RA(J2000) pointing (HH:MM:SS.SSS)
DescriptionE   : Right Ascension of pointing based on J2000 equinox. If telescope control system is
                  based on the J2000, this value is equals to the value of keyword RA. Notice that
                  this value dose NOT show accurate field center of the instrument.
DescriptionJ   : 分点 J 2 0 0 0 に準拠した望遠鏡指向位置の赤経。必ずしも観測装置の視野中心と一致する必要はない。
-----
HeaderKeyWord: RADECSYS
Category      : Object
Importance    : Common
FormatF       : A8
Unit          : -
Recommend     : FK5
Sample        : 'FK5'
Comment       : The equatorial coordinate system
DescriptionE   : The equatorial coordinate system used at observatory. FK5 is the default system at
                  SUBARU.
DescriptionJ   : すばるで用いている空間座標系の基準。推奨値、FK5。
-----

```

[Dictionary = Basic] (Category 順、その 7-1: Origin)

```

-----
HeaderKeyWord: F-RATIO
Category      : Origin
Importance    : Optional
FormatF       : F20.2
Unit          : -
Recommend     : -
Sample        : 6.12
Comment       : Monochromatic F-Ratio of the camera
DescriptionE   : Monochromatic F-Ratio of the instrument camera.
DescriptionJ   : 装置の F 値。
-----

```

[Dictionary = Basic] (Category 順、その 7-2: Origin(続))

```

-----
HeaderKeyWord: FOC-LEN
Category      : Origin
Importance    : Optional
FormatF       : F20.3
Unit          : mm
Recommend     : -
Sample        : 100000.111
Comment       : Focal length of the telescope (mm)
DescriptionE   : Focal length of the telescope.
DescriptionJ   : 望遠鏡の焦点距離。
-----
HeaderKeyWord: FOC-POS
Category      : Origin
Importance    : Common
FormatF       : A12
Unit          : -
Recommend     : -
Sample        : 'CASSEGRAIN'
Comment       : Focus where the instrument is attached
DescriptionE   : Focus name where the instrument is attached. /PRIME/CASSEGRAIN/NASMYTH-IR
                /NASMYTH-OPT/COUDE/
DescriptionJ   : 観測装置が装着されている焦点名。
-----
HeaderKeyWord: FOC-VAL
Category      : Origin
Importance    : Common
FormatF       : F20.3
Unit          : mm
Recommend     : -
Sample        : 100000.254
Comment       : Encoder value of the focus unit (mm)
DescriptionE   : Position of the telescope focus unit (secondary mirror, prime focus unit).
DescriptionJ   : 望遠鏡の合焦に使用されるユニットの位置。
-----
HeaderKeyWord: OBSERVAT
Category      : Origin
Importance    : Common
FormatF       : A20
Unit          : -
Recommend     : NAOJ
Sample        : 'NAOJ'
Comment       : Observatory
DescriptionE   : Observatory where the data was taken. Recommended values are 'NAOJ' or
                'Nat1.Astr.Obs.Japan'.
DescriptionJ   : データの取得された観測所名。'NAOJ' 或いは、'Nat1.Astr.Obs.Japan' を使用すること。
-----
HeaderKeyWord: OBSERVER
Category      : Origin
Importance    : Common
FormatF       : A50
Unit          : -
Recommend     : -
Sample        : 'G.KOSUGI, et al.'
Comment       : Name(s) of observer(s)
DescriptionE   : This keyword shows the name(s) of observer(s) who took the data.
DescriptionJ   : 当該データを取得した観測者 (グループ)。
-----
HeaderKeyWord: PROP-ID
Category      : Origin
Importance    : Common
FormatF       : A8
Unit          : -
Recommend     : -
Sample        : 'o98003'
Comment       : Proposal ID
DescriptionE   : Proposal ID of the observation.
DescriptionJ   : 観測プロポーザル ID。
-----
HeaderKeyWord: TELESCOP
Category      : Origin
Importance    : Common
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'Subaru'
Comment       : Telescope/System which Inst. is attached
DescriptionE   : Subaru / Hilo Software Simulator / Hilo Optical Simulator
                / Mitaka Software Simulator / Mitaka Optical Simulator
DescriptionJ   : データ取得に使用された望遠鏡・システム名。Subaru / Hilo Software Simulator
                / Hilo Optical Simulator / Mitaka Software Simulator / Mitaka Optical Simulator.
-----

```

[Dictionary = Basic] (Category 順、その 8-1: Polarimetry)

```

-----
HeaderKeyWord: POL-ANGn
Category      : Polarimetry
Importance    : Optional
FormatF       : F20.2
Unit          : degree
Recommend     : -
Sample        : 45.01
Comment       : P.A. of n-th Polarizer (degree)
DescriptionE   : Position Angle (degree) of the n-th Polarizer. The angle for the north is 0 degree,
                  and increases for eastward rotation.
DescriptionJ   : 偏光素子のセットされた位置角。北方向を0度とし、東回りに増加する。単位は degree。
-----
HeaderKeyWord: POLARIZn
Category      : Polarimetry
Importance    : Polarimetry
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'Polarizer01'
Comment       : Identifier of n-th Polarizer
DescriptionE   : Name or identifier of n-th Polarizer.
DescriptionJ   : n 番目の偏光素子の名前あるいは I D。
-----
HeaderKeyWord: RET-ANGn
Category      : Polarimetry
Importance    : Polarimetry
FormatF       : F20.2
Unit          : degree
Recommend     : -
Sample        : 30.12
Comment       : P.A. of n-th Retarder Plate (degree)
DescriptionE   : Position angle of n-th Retarder Plate
DescriptionJ   : n 番目の波長板の回転角。単位は degree。
-----
HeaderKeyWord: RETPLATn
Category      : Polarimetry
Importance    : Polarimetry
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'Retarder01'
Comment       : Identifier of n-th Retarder Plate
DescriptionE   : Name or identifier of n-th Retarder Plate for Polarimetry
DescriptionJ   : n 番目の波長板の名前あるいは I D。
-----

```

[Dictionary = Basic] (Category 順、その 9-1: Spectroscopy)

```

-----
HeaderKeyWord: APERTURE
Category      : Spectroscopy
Importance    : Optional
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'Aperture01'
Comment       : Identifier of the entrance aperture
DescriptionE   : This keyword shows an ID of the aperture mask. Detailed parameters of the aperture
                  mask can be seen in an aperture list which is provided by the instrument group.
DescriptionJ   : 用いられた Aperture mask の ID を記述する。各 Aperture の詳細なパラメータについては各観測装置
                  グループが用意する Aperture List を参照の事。
-----
HeaderKeyWord: APT-SIZE
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.3
Unit          : arcsec
Recommend     : -
Sample        : 0.805
Comment       : Diameter of the aperture (arcsec)
DescriptionE   : This keyword shows a diameter of the aperture mask (arcsec). Detailed parameters of
                  the aperture mask (e.g. shape and size) can be seen in an Aperture list which will
                  be provided by the instrument group. (See also 'APERTURE'.)
DescriptionJ   : Aperture の直径の大きさを記述する。単位は arcsec。詳しい Aperture の形状等は装置ごとに用意さ
                  れる Aperture list を参照の事。(APERTURE の項も参照の事)
-----

```

[Dictionary = Basic] (Category 順、その 9-2: Spectroscopy(続))

```

-----
HeaderKeyWord: APTC-DEC
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.8
Unit          : degree
Recommend     : -
Sample        : 138.28976543
Comment       : DEC of the aperture center (degree)
DescriptionE   : This keyword shows a declination of the aperture center (degree). A position
                  described by 'APTC-RA' and this 'APTC-DEC' corresponds to that on the detector
                  described by 'APTCPIX1' and 'APTCPIX2'. (See 'APTCPIX1' and 'APTCPIX2')
DescriptionJ   : Aperture 中心の Dec. を記述する。単位は degree。これと APTC-RA で記述される位置が、検出器上で
                  は APTCPIX1, APTCPIX2 に対応する。(APTCPIX1, APTCPIX2 も参照の事)
-----
HeaderKeyWord: APTC-RA
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.8
Unit          : degree
Recommend     : -
Sample        : 23.45678901
Comment       : RA of the aperture center (degree)
DescriptionE   : 'APTC-RA' shows a right ascension of the aperture center (degree). A position
                  described by 'APTC-DEC' and this 'APTC-RA' corresponds to a position on the
                  detector described by 'APTCPIX1' and 'APTCPIX2'. (See 'APTCPIX1' and 'APTCPIX2')
DescriptionJ   : Aperture 中心の R.A. を記述する。単位は degree。これと APTC-DEC で記述される位置が、検出器上
                  では APTCPIX1, APTCPIX2 に対応する。(APTCPIX1, APTCPIX2 も参照の事)
-----
HeaderKeyWord: APTCPIX1
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.1
Unit          : pixel
Recommend     : -
Sample        : 511.5
Comment       : Aperture center projected on det.(pix)
DescriptionE   : This keyword shows a position on the detector where a ray of 'WAVELEN' come from
                  the aperture center was dropped. This is written in a unit of pixel along the first
                  axis described by NAXIS1 keyword.
DescriptionJ   : Aperture 中心から来た波長 WAVELEN の光が落ちる検出器上の位置を記述する。NAXIS1 で記述される
                  軸に沿った値で、単位は pixel。
-----
HeaderKeyWord: APTCPIX2
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.1
Unit          : pixel
Recommend     : -
Sample        : 511.5
Comment       : Aperture center projected on det.(pix)
DescriptionE   : This keyword shows a position on the detector where a ray of 'WAVELEN' come from
                  the aperture center was dropped. This is written in a unit of pixel along the
                  second axis described by NAXIS2 keyword.
DescriptionJ   : Aperture 中心から来た波長 WAVELEN の光が落ちる検出器上の位置を記述する。NAXIS2 で記述される
                  軸に沿った値で、単位は pixel。
-----
HeaderKeyWord: DISPAXIS
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : I20
Unit          : -
Recommend     : -
Sample        : 1
Comment       : Dispersion axis in frame
DescriptionE   : The number of axis (n of NAXISn) along to dispersion.
DescriptionJ   : スペクトルの分散方向の軸番号 (NAXISn の n に対応)
-----
HeaderKeyWord: DISPERSR
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : A20
Unit          : -
Recommend     : -
Sample        : 'Grizm500-6400'
Comment       : Identifier of the disperser used
DescriptionE   : Identifier (Name, grooves, etc.) of the disperser used.
DescriptionJ   : 使用している分散素子の名前など
-----

```

[Dictionary = Basic] (Category 順、その 9-3: Spectroscopy(続))

```

-----
HeaderKeyWord: SLIT
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : A20
Unit          : -
Recommend     : -
Sample        : 'Longslit03'
Comment       : Identifier of the entrance slit used
DescriptionE   : Identifier (Name, etc.) of the entrance slit used.
DescriptionJ   : 使用しているスリットの名前
-----
HeaderKeyWord: SLT-LEN
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.3
Unit          : arcsec
Recommend     : -
Sample        : 65.255
Comment       : Length of the slit used (arcsec)
DescriptionE   : Length of the slit used. (arcsec)
DescriptionJ   : スリットを天球面に投影したときの空間的な長さ (arcsec)
-----
HeaderKeyWord: SLT-OBJP
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.3
Unit          : arcsec
Recommend     : -
Sample        : 30.254
Comment       : Object position on the slit (arcsec)
DescriptionE   : Object's position on the slit (arcsec). The zero point is defined for each
                  instrument.
DescriptionJ   : スリット上の天体の位置 (スリットに沿った方向)。原点は観測装置ごとに定める。
-----
HeaderKeyWord: SLT-PA
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.1
Unit          : degree
Recommend     : -
Sample        : 33.3
Comment       : Slit Position Angle (degree)
DescriptionE   : Typical position angle of the slit during exposure (degree). 0 degree for the
                  north, and increased for the east direction.
DescriptionJ   : 露出中のスリットの典型的な位置角。北を0度とし、東回りに取った角度で表される。
-----
HeaderKeyWord: SLT-PEND
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.1
Unit          : degree
Recommend     : -
Sample        : 32.2
Comment       : Slit PA at exposure end (degree)
DescriptionE   : Position angle of the slit at the end of exposure (degree). The method of defining
                  the angle is the same with 'SLT-PA'.
DescriptionJ   : 露出終了時のスリットの位置角。角度の定義は'SLT-PA'に同じ。
-----
HeaderKeyWord: SLT-PSTR
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.1
Unit          : degree
Recommend     : -
Sample        : 34.4
Comment       : Slit PA at exposure start (degree)
DescriptionE   : Position angle of the slit at the start of exposure (degree). The method of
                  defining the angle is the same with 'SLT-PA'.
DescriptionJ   : 露出開始時のスリットの位置角。角度の定義は'SLT-PA'に同じ。
-----
HeaderKeyWord: SLT-WID
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.3
Unit          : arcsec
Recommend     : -
Sample        : 0.155
Comment       : Width of the slit used (arcsec)
DescriptionE   : Width of the slit used. (arcsec)
DescriptionJ   : 天球面に投影した時のスリット幅 (arcsec)
-----

```

[Dictionary = Basic] (Category 順、その 9-4: Spectroscopy(続))

```

-----
HeaderKeyWord: SLTC-DEC
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 188.73662
Comment       : slit center DEC at the EQUINOX (degree)
DescriptionE   : DEC corresponding to slit center described by the EQUINOX (degree)
DescriptionJ   : EQUINOX で示される分点でのスリット中心の赤緯
-----
HeaderKeyWord: SLTC-RA
Category      : Spectroscopy
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : -12.58243
Comment       : slit center RA at the EQUINOX (degree)
DescriptionE   : RA corresponding to slit center described by the EQUINOX (degree).
DescriptionJ   : EQUINOX で示される分点でのスリット中心の赤経
-----
HeaderKeyWord: SLTCPIX1
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.1
Unit          : pixel
Recommend     : -
Sample        : 512.5
Comment       : Slit center projected on detector(pixel)
DescriptionE   : Slit center projected on detector at WAVELENGTH for the axis 1 (pixel)
DescriptionJ   : 検出器上での WAVELEN にあたる波長とスリット中心に相当する位置。第1軸について。
-----
HeaderKeyWord: SLTCPIX2
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.1
Unit          : pixel
Recommend     : -
Sample        : 512.5
Comment       : Slit center projected on detector(pixel)
DescriptionE   : Slit center projected on detector at WAVELENGTH for the axis 2 (pixel)
DescriptionJ   : 検出器上での WAVELEN にあたる波長とスリット中心に相当する位置。第2軸について。
-----
HeaderKeyWord: WAV-MAX
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.4
Unit          : nm
Recommend     : -
Sample        : 6522.1234
Comment       : Longest wavelen. focused on detector(nm)
DescriptionE   : Longest wavelength focused on the detecrtor (nm).
DescriptionJ   : 検出器に写っている波長の最大値。
-----
HeaderKeyWord: WAV-MIN
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.4
Unit          : nm
Recommend     : -
Sample        : 6585.5432
Comment       : Shortest wavelen.focused on detector(nm)
DescriptionE   : Shortest wavelength focused on the detecrtor (nm).
DescriptionJ   : 検出器に写っている波長の最小値。
-----
HeaderKeyWord: WAVELEN
Category      : Spectroscopy
Importance    : Spectroscopy
FormatF       : F20.4
Unit          : nm
Recommend     : -
Sample        : 655.3278
Comment       : Wavelength at detector center (nm)
DescriptionE   : Central wavelength of focused on the detector (nm).
DescriptionJ   : 観測されたデータの中心波長
-----

```

[Dictionary = Basic] (Category 順、その 10-1: Telescope)

```

-----
HeaderKeyWord: ADC
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : degree
Recommend     : -
Sample        : 11.244
Comment       : ADC PA during exposure (degree)
DescriptionE  : Typical position angle of atmospheric dispersion compensator during exposure
                (degree).
DescriptionJ  : 露出中の大気分散補償器の位置角の典型的な値。(degree)
-----
HeaderKeyWord: ADC-END
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : degree
Recommend     : -
Sample        : 12.929
Comment       : ADC PA at exposure end (degree)
DescriptionE  : Position angle of atmospheric dispersion compensator at the end of exposure
                (degree).
DescriptionJ  : 露出終了時の大気分散補償器の位置角。(degree)
-----
HeaderKeyWord: ADC-STR
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : degree
Recommend     : -
Sample        : 12.989
Comment       : ADC PA at exposure start (degree)
DescriptionE  : Position angle of atmospheric dispersion compensator at the start of exposure
                (degree).
DescriptionJ  : 露出開始時の大気分散補償器の位置角。
-----
HeaderKeyWord: ADC-TYPE
Category      : Telescope
Importance    : Optional
FormatF       : A20
Unit          : -
Recommend     : -
Sample        : 'BLUE'
Comment       : ADC name/type if used
DescriptionE  : Identifier of atmospheric dispersion compensator used (BLUE, NONE).
DescriptionJ  : 用いられた大気分散補償器の種類。(BLUE, NONE)
-----
HeaderKeyWord: AG-PRB1
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : mm
Recommend     : -
Sample        : 25.234
Comment       : AG Probe position (r:mm,x:mm)
DescriptionE  : First axis component of auto guider's probe position(mm). (CASS/NAS:r:mm, PF:x:mm).
DescriptionJ  : オートガイダーの位置の第1軸成分 (mm)。主焦点ではX方向、その他の焦点では動径方向を意味する。
-----
HeaderKeyWord: AG-PRB2
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : degree
Recommend     : -
Sample        : 25.234
Comment       : AG Probe position (Theta:degree, y:mm)
DescriptionE  : Second axis component of auto guider probe position(CASS/NAS:Theta:degree,PF:y:mm).
DescriptionJ  : オートガイダーの位置の第2軸成分。主焦点ではY方向、その他の焦点では回転方向を意味する。
-----
HeaderKeyWord: ALT-END
Category      : Telescope
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 78.12345
Comment       : Altitude at exposure end (degree)
DescriptionE  : Altitude of telescope pointing at exposure end (degree).
DescriptionJ  : 露出終了時の仰角。単位は degree。多重露出フレームの場合は、最終露出終了時の仰角。
-----

```

[Dictionary = Basic] (Category 順、その 10-2: Telescope(続))

```

-----
HeaderKeyWord: ALT-STR
Category      : Telescope
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 78.15678
Comment       : Altitude at start exposure (degree)
DescriptionE   : Altitude of telescope pointing at exposure start (degree).
DescriptionJ   : 露出終了時の仰角。単位は degree。多重露出フレームの場合は、最初の露出開始の仰角。
-----
HeaderKeyWord: ALTITUDE
Category      : Telescope
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 78.23456
Comment       : Altitude of telescope pointing (degree)
DescriptionE   : Typical altitude of telescope pointing (degree). Altitude changes during the
                  exposure.
DescriptionJ   : 観測中の典型的な仰角。露出の中間時刻における仰角が望ましい。
-----
HeaderKeyWord: AO-FREQ
Category      : Telescope
Importance    : Optional
FormatF       : I20
Unit          : Hz
Recommend     : -
Sample        : 10
Comment       : frequency of AO loop (Hz)
DescriptionE   : Frequency of AO control (Hz). Times per second the deformable mirror was
                  transformed.
DescriptionJ   : A O の制御 (波面補正) 周波数 (Hz)。可変形鏡を 1 秒間に変形させた (=波面補正) 回数。
-----
HeaderKeyWord: AO-TIP
Category      : Telescope
Importance    : Optional
FormatF       : A8
Unit          : -
Recommend     : -
Sample        : 'ON'
Comment       : Action of AO tip-tilt Mirror (ON/OFF)
DescriptionE   : Action of AO tip-tilt Mirror (ON/OFF)
DescriptionJ   : A O の tip-tilt 鏡を作動させたか否か (有/無)。値: 'ON' , または 'OFF' ,
-----
HeaderKeyWord: AO-WFS
Category      : Telescope
Importance    : Optional
FormatF       : F20.5
Unit          : -
Recommend     : -
Sample        : 1.21111??
Comment       : sigma of residual wave front??
DescriptionE   : sigma of residual wave front??
DescriptionJ   : ウェーブフロントセンサーでの補正後の残差??
-----
HeaderKeyWord: AZ-END
Category      : Telescope
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : -23.45678
Comment       : Azimuth angle at exposure end (degree)
DescriptionE   : Azimuth angle of telescope when an exposure ends (degree). North is 0, East is 90
                  degree.
DescriptionJ   : 露出終了時の方位角。多重露出フレームの場合は、最終露出の終了時の方位角。北が 0 度、東が 90 度。
-----
HeaderKeyWord: AZ-STR
Category      : Telescope
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 23.56789
Comment       : Azimuth angle at exposure start (degree)
DescriptionE   : Azimuth angle of telescope when an exposure begins (degree). North is 0, East is 90
                  degree.
DescriptionJ   : 露出開始時の方位角。多重露出フレームの場合は、最初の露出の開始時の方位角。北が 0 度、東が 90
                  度。
-----

```

[Dictionary = Basic] (Category 順、その 10-3: Telescope(続))

HeaderKeyWord:	AZIMUTH
Category	: Telescope
Importance	: Optional
FormatF	: F20.5
Unit	: degree
Recommend	: -
Sample	: 23.51111
Comment	: Azimuth of telescope pointing (degree)
DescriptionE	: Typical azimuth angle of the telescope during the exposure (degree). North is 0, and East is 90.
DescriptionJ	: 露出中の典型的な方位角。北が0度、東が90度。露出の中間時刻における方位角が望ましい。

HeaderKeyWord:	IMGROT
Category	: Telescope
Importance	: Optional
FormatF	: F20.3
Unit	: degree
Recommend	: -
Sample	: 45.998
Comment	: Angle of the Image Rotator (degree)
DescriptionE	: This keyword shows a typical angle of the Image Rotator during the exposure (degree). (See 'IMR-END' and 'IMR-STR'.) The angle for the north is 0, and increases for eastward rotation. The range of the angle is from 0 to 360 degree.
DescriptionJ	: Image Rotator の露出中の典型的な角度を記述する。単位は degree。(IMR-END、IMR-STR も参照の事)。北の方角が0度、東回りで増加する。値の範囲は0度から360度である。

HeaderKeyWord:	IMR-TYPE
Category	: Telescope
Importance	: Optional
FormatF	: A20
Unit	: -
Recommend	: -
Sample	: 'RED' ,
Comment	: Identifire of the image rotator
DescriptionE	: This keyword shows a kind of the Image Rotator used for the observation. 'RED', 'BLUE', 'IR' indicate the Image Rotators for opt-red wavelength, opt-blue wavelength, and IR wavelength, respectively. If the Image Rotator is not used, the value is 'NONE'.
DescriptionJ	: 使用されている Image rotator の種類を記述する。種類としては RED(可視赤用)、BLUE(可視青用)、IR (赤外用) および NONE(rotator なし) がある。

HeaderKeyWord:	IMR-END
Category	: Telescope
Importance	: Optional
FormatF	: F20.3
Unit	: degree
Recommend	: -
Sample	: 45.954
Comment	: Image rotator angle at end (degree)
DescriptionE	: This keyword shows an angle of the Image Rotator (degree) at the end of the exposure. (See also 'IMGROT')
DescriptionJ	: 露出終了時点での、Image Rotator の原点位置からの角度を記述する。単位は degree。角度の定義については IMGROT を参照のこと。

HeaderKeyWord:	IMR-STR
Category	: Telescope
Importance	: Optional
FormatF	: F20.3
Unit	: degree
Recommend	: -
Sample	: 46.229
Comment	: Image rotator angle at start (degree)
DescriptionE	: This keyword shows an angle of the Image Rotator (degree) at the beginning of the exposure. (See also 'IMGROT')
DescriptionJ	: 露出開始時点での、Image Rotator の原点位置からの角度を記述する。単位は degree。角度の定義については IMGROT を参照のこと。

HeaderKeyWord:	INR-END
Category	: Telescope
Importance	: Optional
FormatF	: F20.3
Unit	: degree
Recommend	: -
Sample	: -23.456
Comment	: Instrument Rotator angle at end (degree)
DescriptionE	: Angle of instrument rotator at the end of the exposure (degree).
DescriptionJ	: 露出終了時の instrument rotator 回転角。多重露出フレームの場合は、最終露出の終了時の回転角。

[Dictionary = Basic] (Category 順、その 10-4: Telescope(続))

```

-----
HeaderKeyword: INR-STR
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : degree
Recommend     : -
Sample        : 14.567
Comment       : Instrument Rotator angle at Start (deg)
DescriptionE   : Angle of instrument rotator at the start of the exposure (degree).
DescriptionJ   : 露出開始時の instrument rotator 回転角。多重露出フレームの場合は、最初の露出開始時の回転角。
-----
HeaderKeyword: INSR0T
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : degree
Recommend     : -
Sample        : -23.444
Comment       : Typical inst. rot. angle at exp.(degree)
DescriptionE   : Typical angle of instrument rotator during the exposure (degree).
DescriptionJ   : 露出時の典型的 instrument rotator 回転角。露出開始時と終了時の中間時刻における回転角が望ましい。
-----
HeaderKeyword: M2-ANG1
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : arcsec
Recommend     : -
Sample        : 0.015
Comment       : Theta X of the M2 (arcsec)
DescriptionE   : X-direction Angle of the secondary mirror (arcsec).
DescriptionJ   : 第2鏡のX方向の角度 (arcsec)。
-----
HeaderKeyword: M2-ANG2
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : arcsec
Recommend     : -
Sample        : 0.026
Comment       : Theta Y of the M2 (arcsec)
DescriptionE   : Y-direction Angle of the secondary mirror (arcsec).
DescriptionJ   : 第2鏡のY方向の角度 (arcsec)
-----
HeaderKeyword: M2-POS1
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : mm
Recommend     : -
Sample        : 5.123
Comment       : X-Position of the M2 (mm)
DescriptionE   : X-direction Position of the secondary mirror (mm).
DescriptionJ   : 第2鏡のX方向の位置 (mm)
-----
HeaderKeyword: M2-POS2
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : mm
Recommend     : -
Sample        : 0.023
Comment       : Y-Position of the M2 (mm)
DescriptionE   : Y-direction Position of the secondary mirror (mm).
DescriptionJ   : 第2鏡のY方向の位置 (mm)
-----
HeaderKeyword: M2-TIP
Category      : Telescope
Importance    : Optional
FormatF       : A8
Unit          : -
Recommend     : -
Sample        : 'OFF'
Comment       : Tip/Tilt of the Secondary Mirror(ON/OFF)
DescriptionE   : Tip-Tilt of the secondary mirror (ON/OFF).
DescriptionJ   : 第2鏡の Tip-Tilt の有無 (ON/OFF)
-----

```

[Dictionary = Basic] (Category 順、その 10-5: Telescope(続))

```

-----
HeaderKeyWord: M2-TYPE
Category      : Telescope
Importance    : Optional
FormatF       : A8
Unit          : -
Recommend     : -
Sample        : 'Opt'
Comment       : Type of the Secondary Mirror (Opt/IR)
DescriptionE   : Type of the Secondary Mirror (Opt/IR)
DescriptionJ   : 第2鏡の種類 (Opt/IR)
-----
HeaderKeyWord: OBS-ALOC
Category      : Telescope
Importance    : Common
FormatF       : A12
Unit          : -
Recommend     : -
Sample        : 'OBSERVATION'
Comment       : Allocation mode for Instrument
DescriptionE   : The status of the allocation mode for Instrument. This keyword describes whether
                  the instrument is in Observing or Stand-by mode.
DescriptionJ   : 観測装置の取り付け状態 (観測状態で望遠鏡に付いているか待機状態で待機室内にあるかの区別) を示
                  す項目。観測装置が待機室内にあってもデータの取得が可能なので、装置の状況を区別する必要がある。
                  取り得る値は、STAND-BY と OBSERVATION。
-----
HeaderKeyWord: SV-PRB
Category      : Telescope
Importance    : Optional
FormatF       : F20.3
Unit          : mm
Recommend     : -
Sample        : 10.598
Comment       : SV Probe position (mm)
DescriptionE   : This keyword shows the (radius) position of slit viewer's probe. The value of 0
                  corresponds to center of optical axis and unit is in mm.
DescriptionJ   : Slit Viewer Probe の位置 (動径方向成分) を記述する。原点は光軸中心であり単位は mm。Slit Viewer
                  の probe の位置は 1 次元で表される。
-----
HeaderKeyWord: TELFOCUS
Category      : Telescope
Importance    : Common
FormatF       : A30
Unit          : -
Recommend     : -
Sample        : 'CASSEGRAIN'
Comment       : Focus where a beam is reachable
DescriptionE   : Focus where a beam is reachable. /PRIME/CASSEGRAIN/NASMYTH-IR/NASMYTH-OPT/COUDE/
DescriptionJ   : 天体からの光がどの焦点に到達するかを記述。取り得る値は PRIME, CASSEGRAIN, NASMYTH-IR,
                  NASMYTH-OPT, COUDE。FOC-POS と比較することで、装置に光が届いているかをチェックできる。
-----

```

[Dictionary = Basic] (Category 順、その 11-1: Time)

```

-----
HeaderKeyWord: AIRM-END
Category      : Time
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 1.221
Comment       : Air mass at exposure end
DescriptionE   : Air mass when an exposure ends.
DescriptionJ   : 露出終了時の大気量。多重露出の場合は、最終露出の終了時刻の大気量。
-----
HeaderKeyWord: AIRM-STR
Category      : Time
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 1.224
Comment       : Air mass at exposure start
DescriptionE   : Air mass when an exposure begins.
DescriptionJ   : 露出開始時の大気量。多重露出の場合は、最初の露出の開始時刻の大気量。
-----

```

[Dictionary = Basic] (Category 順、その 11-2: Time(続))

```

-----
HeaderKeyWord: AIRMASS
Category      : Time
Importance    : Common
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 1.223
Comment       : Typical air mass during exposure
DescriptionE   : Typical air mass during the exposure.
DescriptionJ   : 露出中の典型的な大気量。露出中の平均大気量、或いは、露出中間時刻の大気量が望ましい。
-----
HeaderKeyWord: DATE-OBS
Category      : Time
Importance    : Common
FormatF       : A10
Unit          : UTC
Recommend     : -
Sample        : '1998-09-14'
Comment       : Observation start date (yyyy-mm-dd)
DescriptionE   : UTC date at the beginning of the exposure. Format : yyyy-mm-dd
DescriptionJ   : 露出開始の時点の日時。単位は UTC で、yyyy-mm-dd の形式とする。
-----
HeaderKeyWord: EXP1TIME
Category      : Time
Importance    : Optional
FormatF       : F20.3
Unit          : sec
Recommend     : -
Sample        : 0.015
Comment       : Exposure time of a frame(sec)
DescriptionE   : 'EXP1TIME' shows an integration time (sec) of each sub-exposure. Total integration
                : time of a frame is accumulated by this 'EXP1TIME' and 'COADD' which shows how many
                : sub-exposures were coadded. ('COADD' and 'EXPTIME'). (EXPTIME = EXP1TIME * COADD)
DescriptionJ   : 各々の sub-exposure の積分時間を記述する。単位は sec。1 frame あたりの積分時間はこの EXP1TIME
                : と枚数 COADD の積となる。(COADD,EXPTIME も参照)(EXPTIME = EXP1TIME * COADD)
-----
HeaderKeyWord: EXPTIME
Category      : Time
Importance    : Common
FormatF       : F20.2
Unit          : sec
Recommend     : -
Sample        : 1234.56
Comment       : Total integration time of the frame(sec)
DescriptionE   : 'EXPTIME' shows an integration time [sec] of a frame. If a frame was made from
                : some sub-exposures, the 'EXPTIME' corresponds to the product of 'EXP1TIME' and
                : 'COADD'. (EXPTIME = EXP1TIME * COADD)
DescriptionJ   : このデータの、1 frame あたりの積分時間を記述する。単位は sec。1 frame が sub-exposure の足
                : し合わせである場合 EXPTIME は EXP1TIME と COADD の積と等しくなる。(EXPTIME= EXP1TIME * COADD)
-----
HeaderKeyWord: HST
Category      : Time
Importance    : Common
FormatF       : A12
Unit          : HST
Recommend     : -
Sample        : '14:25:00.012'
Comment       : Typical HST at exposure (HH:MM:SS.SSS)
DescriptionE   : Typical Hawaii Standard Time of exposure (HH:MM:SS.SSS). A middle time of the
                : exposure is recommended.
DescriptionJ   : 露出中の典型的 Hawaii Standard Time (ハワイ標準時)。露出開始と終了の間でのハワイ標準時を、
                : 多重露出の場合には、最初の露出開始と最終の露出終了の間におけるハワイ標準時が望ましい。
-----
HeaderKeyWord: HST-END
Category      : Time
Importance    : Optional
FormatF       : %12s
Unit          : HST
Recommend     : -
Sample        : '14:27:00.012'
Comment       : HST at exposure end (HH:MM:SS.SSS)
DescriptionE   : Hawaii Standard Time when an exposure ends (HH:MM:SS.SSS).
DescriptionJ   : 露出終了時の Hawaii Standard Time (ハワイ標準時)。多重露出の場合には、最終露出終了の時刻。
-----

```

[Dictionary = Basic] (Category 順、その 11-3: Time(続))

```

-----
HeaderKeyWord: HST-STR
Category      : Time
Importance    : Optional
FormatF       : %12s
Unit          : HST
Recommend     : -
Sample        : '14:23:00.012'
Comment       : HST at exposure start (HH:MM:SS.SSS)
DescriptionE  : Hawaii Standard Time when an exposure begins (HH:MM:SS.SSS).
DescriptionJ  : 露出開始時の Hawaii Standard Time (ハワイ標準時)。多重露出の場合は、最初の露出開始時の時刻。
-----
HeaderKeyWord: LST
Category      : Time
Importance    : Common
FormatF       : A12
Unit          : LST
Recommend     : -
Sample        : '00:25:00.012'
Comment       : Typical LST during exp. (HH:MM:SS.SSS)
DescriptionE  : Typical Local Sidereal Time during the exposure (HH:MM:SS.SSS). A middle time of
                the exposure is recommended.
DescriptionJ  : 露出中の典型的 Local Sidereal Time (地方恒星時)。単一露出の場合には露出開始と終了の中間に
                おける地方恒星時を、多重露出の場合には、最初の露出開始と最終の露出終了の中間における地方恒星
                時が望ましい。
-----
HeaderKeyWord: LST-END
Category      : Time
Importance    : Optional
FormatF       : A12
Unit          : LST
Recommend     : -
Sample        : '00:27:00.012'
Comment       : LST at end of exposure (HH:MM:SS.SSS)
DescriptionE  : Local Sidereal Time at the end of the exposure (HH:MM:SS.SSS).
DescriptionJ  : 露出終了時の Local Sidereal Time (地方恒星時)。多重露出の場合は、最終露出終了時の恒星時。
-----
HeaderKeyWord: LST-STR
Category      : Time
Importance    : Optional
FormatF       : A12
Unit          : LST
Recommend     : -
Sample        : '00:23:00.012'
Comment       : LST at start of exposure (HH:MM:SS.SSS)
DescriptionE  : Local Sidereal Time at start of the exposure (HH:MM:SS.SSS).
DescriptionJ  : 露出開始時の Local Sidereal Time (地方恒星時)。多重露出の場合は、最初の露出が開始された時
                の恒星時。
-----
HeaderKeyWord: MJD
Category      : Time
Importance    : Common
FormatF       : F20.8
Unit          : day
Recommend     : -
Sample        : 51137.01789537
Comment       : Modified Julian Date at typical time
DescriptionE  : Modified Julian Date at typical time during the exposure. MJD=JD-2400000.5
                (JD:Julian Date)
DescriptionJ  : 露出中の典型的な時刻における修正ユリウス日。MJD は MJD = ユリウス日-2400000.5 と定義されて
                いる。「典型的な」をどのように解釈定義するかは観測機器によって任意。
-----
HeaderKeyWord: MJD-END
Category      : Time
Importance    : Optional
FormatF       : F20.8
Unit          : days
Recommend     : -
Sample        : 51137.01789537
Comment       : Modified Julian Date at the end of exp.
DescriptionE  : Modified Julian Date at the end of the exposure. MJD=JD-2400000.5 (JD:Julian Date)
DescriptionJ  : 露出終了時点における修正ユリウス日
-----
HeaderKeyWord: MJD-STR
Category      : Time
Importance    : Optional
FormatF       : F20.8
Unit          : days
Recommend     : -
Sample        : 51137.01789537
Comment       : Modified Julian Date of the start exp.
DescriptionE  : Modified Julian Date at the start of the exposure. MJD=JD-2400000.5 (JD:Julian
                Date)
DescriptionJ  : 露出開始時点における修正ユリウス日
-----

```

[Dictionary = Basic] (Category 順、その 11-4: Time(続))

```

-----
HeaderKeyWord: SECZ
Category      : Time
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 1.026
Comment       : SEC(Zenith Distance) at typical time
DescriptionE   : A secant of zenith distance at typical time of exposure. A middle time of the
                  exposure is recommended.
DescriptionJ   : 露出中の典型的 sec Z (天頂距離のセカント)。露出開始と終了の中間時刻における値を、多重露出フ
                  レームの場合には、最初の露出開始と最終の露出終了の中間時刻における値が望ましい。
-----
HeaderKeyWord: SECZ-END
Category      : Time
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 1.027
Comment       : SEC(Zenith Distance) at exposure end
DescriptionE   : A secant of zenith distance at exposure end time.
DescriptionJ   : 露出終了時の sec Z (天頂距離のセカント)。多重露出フレームの場合は、最終露出終了時の sec Z。
-----
HeaderKeyWord: SECZ-STR
Category      : Time
Importance    : Optional
FormatF       : F20.3
Unit          : -
Recommend     : -
Sample        : 1.025
Comment       : SEC(Zenith Distance) at exposure start
DescriptionE   : A secant of zenith distance at exposure start time.
DescriptionJ   : 露出開始時の sec Z (天頂距離のセカント)。多重露出フレームの場合は、最初の露出開始時の sec Z。
-----
HeaderKeyWord: TIMESYS
Category      : Time
Importance    : Common
FormatF       : A8
Unit          : -
Recommend     : UTC
Sample        : 'UTC'
Comment       : Time System used in the header
DescriptionE   : Explicit time scale specification of the Telescope. UTC is default/defined time
                  system for SUBARU.
DescriptionJ   : 時刻系の基準。すばるでは既定値、'UTC'。
-----
HeaderKeyWord: UT
Category      : Time
Importance    : Common
FormatF       : A12
Unit          : UTC
Recommend     : -
Sample        : '00:25:36.160'
Comment       : HH:MM:SS.SSS typical UTC at exposure
DescriptionE   : UTC at typical time (for example, middle) of exposure (format HH:MM:SS.SSS).
DescriptionJ   : 積分を代表する (例えば中間) 時刻の U T C。形式は HH:MM:SS.SSS
-----
HeaderKeyWord: UT-END
Category      : Time
Importance    : Optional
FormatF       : A12
Unit          : UTC
Recommend     : -
Sample        : '00:25:37.660'
Comment       : HH:MM:SS.SSS UT at end of the exposure
DescriptionE   : Coordinated Universal Time at the end of the exposure (HH:MM:SS.SSS).
DescriptionJ   : 露出終了時における UTC
-----
HeaderKeyWord: UT-STR
Category      : Time
Importance    : Optional
FormatF       : A12
Unit          : UTC
Recommend     : -
Sample        : '00:25:34.660'
Comment       : HH:MM:SS.SSS UTC at start exposure time
DescriptionE   : Coordinated Universal Time at start of the exposure (HH:MM:SS.SSS).
DescriptionJ   : 露出開始時刻における UTC
-----

```

[Dictionary = Basic] (Category 順、その 11-5: Time(続))

```

-----
HeaderKeyWord: UT1-UTC
Category      : Time
Importance    : Optional
FormatF       : F20.5
Unit          : sec
Recommend     : -
Sample        : 0.43893
Comment       : difference between UT1 and UTC
DescriptionE   : Difference between UT1 and UTC. This value is used for calculating LST.
DescriptionJ   : UT1 と UTC の差。LST の計算に用いられる。
-----
HeaderKeyWord: ZD
Category      : Time
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 12.34567
Comment       : Zenith Distance at typical time (degree)
DescriptionE   : Zenith Distance at typical time in exposure (degree). A middle time of the exposure
                  is recommended.
DescriptionJ   : 露出中の典型的な天頂距離。露出開始と終了の中間時刻における天頂距離を、多重露出フレームの場合
                  には、最初の露出開始と最終の露出終了の中間時刻における天頂距離が望ましい。
-----
HeaderKeyWord: ZD-END
Category      : Time
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 12.34577
Comment       : Zenith Distance at exposure end (degree)
DescriptionE   : Zenith Distance at the exposure end time (degree).
DescriptionJ   : 露出終了時の天頂距離。多重露出フレームの場合は、最終の露出終了時の天頂距離。
-----
HeaderKeyWord: ZD-STR
Category      : Time
Importance    : Optional
FormatF       : F20.5
Unit          : degree
Recommend     : -
Sample        : 12.34557
Comment       : Zenith Distance at exp. start (degree)
DescriptionE   : Zenith Distance at the exposure start time (degree).
DescriptionJ   : 露出開始時の天頂距離。多重露出フレームの場合は、最初の露出が開始された時の天頂距離。
-----

```

[Dictionary = Basic] (Category 順、その 12-1: WCS)

```

-----
HeaderKeyWord: C2ELT1
Category      : WCS
Importance    : Optional
FormatF       : F20.8
Unit          : degree
Recommend     : -
Sample        : 0.00001233
Comment       : Size projected to detector pix.X(degree)
DescriptionE   : The value is a floating point number giving the partial derivative of the
                  coordinate specified by the C2YPE1 keywords with respect to the pixel index,
                  evaluated at the reference point C2PIX1, in units of the coordinate specified by
                  the C2YPE1 keyword.
DescriptionJ   : キーワード C2PIX1 で表される基準ピクセルの位置において+1 ピクセル移動した時の、キーワード C2YPE1
                  で表される座標値の増分を表す。
-----
HeaderKeyWord: C2ELT2
Category      : WCS
Importance    : Optional
FormatF       : F20.8
Unit          : degree
Recommend     : -
Sample        : 0.00001234
Comment       : Size projected on detector Y-axis (deg)
DescriptionE   : The value is a floating point number giving the partial derivative of the
                  coordinate specified by the C2YPE2 keywords with respect to the pixel index,
                  evaluated at the reference point C2PIX2, in units of the coordinate specified by
                  the C2YPE2 keyword.
DescriptionJ   : キーワード C2PIX2 で表される基準ピクセルの位置において+1 ピクセル移動した時の、キーワード C2YPE2
                  で表される座標値の増分を表す。
-----

```

[Dictionary = Basic] (Category 順、その 12-2: WCS(続))

HeaderKeyWord:	C2NIT1
Category	: WCS
Importance	: Optional
FormatF	: A8
Unit	: -
Recommend	: degree
Sample	: 'degree '
Comment	: Units used in both C2VAL1 and C2ELT1
DescriptionE	: Physical unit used in both C2VAL1 and C2ELT1. 'degree ' is recommended for the 2nd WCS for spectroscopy/polarimetry.
DescriptionJ	: 第2 WCS の第1 軸方向が表す実際の座標値の単位であり、文字列で与えられる。分光・偏光観測の場合、第2 WCS としては 'degree ' が推奨される。
HeaderKeyWord:	C2NIT2
Category	: WCS
Importance	: Optional
FormatF	: A8
Unit	: -
Recommend	: degree
Sample	: 'degree '
Comment	: Units used in both C2VAL2 and C2ELT2
DescriptionE	: Physical unit used in both C2VAL2 and C2ELT2. 'degree ' is recommended for the 2nd WCS for spectroscopy/polarimetry.
DescriptionJ	: 第2 WCS の第2 軸方向が表す実際の座標値の単位であり、文字列で与えられる。分光・偏光観測の場合、第2 WCS としては 'degree ' が推奨される。
HeaderKeyWord:	C2PIX1
Category	: WCS
Importance	: Optional
FormatF	: F20.1
Unit	: pixel
Recommend	: -
Sample	: 512.5
Comment	: Reference pixel X on detector (pixel)
DescriptionE	: Slit projected pixel position of the reference point along #1 axis in the spectroscopy/polarimetry mode. By convention the center of the pixel is pix.0, pix.5 gives the right edge of the pixel and (pix-1).5 its left edge. Origin is (1,1).
DescriptionJ	: 第2 WCS 系列の参照点の検出器座標系第1 軸方向での値。この WCS 系列は、分光・偏光観測でスリットやダイアフラムの CCD 上への投影位置を正確に示すために用いられる。簡便のためピクセル中心を pix.0、ピクセル右端が pix.5、左端が (pix-1).6 とする。原点 (1,1)。
HeaderKeyWord:	C2PIX2
Category	: WCS
Importance	: Optional
FormatF	: F20.1
Unit	: pixel
Recommend	: -
Sample	: 512.5
Comment	: Reference pixel Y on detector (pixel)
DescriptionE	: Slit projected pixel position of the reference point along #2 axis in the spectroscopy/polarimetry mode. By convention the center of the pixel is pix.0, pix.5 gives the right edge of the pixel and (pix-1).5 its left edge. Origin is (1,1).
DescriptionJ	: 第2 WCS 系列の参照点の検出器座標系第2 軸方向での値。この WCS 系列は、分光・偏光観測でスリットやダイアフラムの CCD 上への投影位置を正確に示すために用いられる。簡便のためピクセル中心を pix.0、ピクセル右端が pix.5、左端が (pix-1).5 とする。原点 (1,1)。
HeaderKeyWord:	C2VAL1
Category	: WCS
Importance	: Optional
FormatF	: F20.8
Unit	: degree
Recommend	: -
Sample	: 188.73662083
Comment	: Physical value of ref. pixel X (degree)
DescriptionE	: The value field shall contain a floating point number giving the value of the partial coordinate specified by the C2YPE1 keyword at the reference point C2PIX1.
DescriptionJ	: 第2 WCS 系列で参照基準点 C2PIX1 の C2YPE1 の座標系における値。この WCS 系列は、分光・偏光観測でスリットやダイアフラムの CCD 上への投影位置を正確に示すために用いられる。
HeaderKeyWord:	C2VAL2
Category	: WCS
Importance	: Optional
FormatF	: F20.8
Unit	: degree
Recommend	: -
Sample	: 12.48544329
Comment	: Physical value of ref. pixel Y (degree)
DescriptionE	: The value field shall contain a floating point number giving the value of the partial coordinate specified by the C2YPE2 keyword at the reference point C2PIX2.
DescriptionJ	: 第2 WCS 系列で参照基準点 C2PIX2 の C2YPE2 の座標系における値。この WCS 系列は、分光・偏光観測でスリットやダイアフラムの CCD 上への投影位置を正確に示すために用いられる。

[Dictionary = Basic] (Category 順、その 12-3: WCS(続))

```

-----
HeaderKeyWord: C2YPE1
Category      : WCS
Importance    : Optional
FormatF       : A8
Unit          : -
Recommend     : RA---TAN
Sample        : 'RA---TAN'
Comment       : Pixel coordinate system
DescriptionE   : Type of projection used for #1 axis in 2nd WCS. 'RA---TAN' or 'DEC--TAN' is
                  recommended for spectroscopy/polarimetry mode.
DescriptionJ   : 第2 WCS 第1座標軸の座標名を表す文字列。分光データの第2 WCS の場合は 'RA---TAN' 或いは、
                  'DEC--TAN' が推奨される。
-----
HeaderKeyWord: C2YPE2
Category      : WCS
Importance    : Optional
FormatF       : A8
Unit          : -
Recommend     : DEC--TAN
Sample        : 'DEC--TAN'
Comment       : Pixel coordinate system
DescriptionE   : Type of projection used for #2 axis in 2nd WCS. 'RA---TAN' or 'DEC--TAN' is
                  recommended for spectroscopy/polarimetry mode.
DescriptionJ   : 第2 WCS 第2座標軸の座標名を表す文字列。分光データの第2 WCS の場合は 'RA---TAN' 或いは、
                  'DEC--TAN' が推奨される。
-----
HeaderKeyWord: LONGPOLE
Category      : WCS
Importance    : Imaging
FormatF       : F20.1
Unit          : degree
Recommend     : 180.0
Sample        : 180.0
Comment       : The North Pole of standard system (deg)
DescriptionE   : The north pole of the standard system in the native system (degree).
DescriptionJ   : 局所球面座標系における天球座標の北極の方向 (degree)。撮像観測に対応する TAN 変換の場合は 180.0
                  度として良い。
-----
HeaderKeyWord: N2XIS
Category      : WCS
Importance    : Optional
FormatF       : I20
Unit          : -
Recommend     : 2
Sample        : 2
Comment       : Dimension of axes in 2nd WCS
DescriptionE   : Dimension of the 2nd WCS
DescriptionJ   : スリットの投影をWCSで記述するときの軸の数。通常 2。主に分光モードで用いられる。
-----
HeaderKeyWord: N2XIS1
Category      : WCS
Importance    : Optional
FormatF       : I20
Unit          : pixel
Recommend     : -
Sample        : 1024
Comment       : # of pixels/row for slit projection
DescriptionE   : Number of pixels along the X axis of the slit projection.
DescriptionJ   : スリットの投影をWCSで記述するときの X 軸 (第1軸) 方向の画素数。主に分光モードで用いられる。
-----
HeaderKeyWord: N2XIS2
Category      : WCS
Importance    : Optional
FormatF       : I20
Unit          : -
Recommend     : -
Sample        : 1024
Comment       : # of scan lines for slit projection
DescriptionE   : Number of pixels along the Y axis of the slit projection.
DescriptionJ   : スリットの投影をWCSで記述するときの Y 軸 (第2軸) 方向の画素数。主に分光モードで用いられる。
-----
HeaderKeyWord: P2iiijjj
Category      : WCS
Importance    : Optional
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 1.00000000
Comment       : Pixel Coordinate translation matrix
DescriptionE   : Pixel Coordinate translation matrix for spectroscopy: iii and jjj are the axis
                  numbers, 001 or 002.
DescriptionJ   : データの画素値座標系から歪みや回転を取り除くのに用いられる変換行列。主に分光モードで使用され
                  る。
-----

```

[Dictionary = Basic] (Category 順、その 12-4: WCS(続))

```

-----
HeaderKeyWord: P20JP1
Category      : WCS
Importance    : Optional
FormatF       : F20.1
Unit          : -
Recommend     : 0.0
Sample        : 0.0
Comment       : Projection type of the first axis
DescriptionE   : Projection type of the X (1-st) axis for slit projection: fixed to 0.0
DescriptionJ   : スリットの投影について、いくつかの投影法で必要となるパラメータの X(第 1) 軸方向の値。主に分光
                  モードで使用される。
-----
HeaderKeyWord: P20JP2
Category      : WCS
Importance    : Optional
FormatF       : F20.1
Unit          : -
Recommend     : 0.0
Sample        : 0.0
Comment       : Projection type of the second axis
DescriptionE   : Projection type of the Y (2-nd) axis for slit projection: fixed to 0.0
DescriptionJ   : スリットの投影について、いくつかの投影法で必要となるパラメータの Y(第 2) 軸方向の値。主に分光
                  モードで使用される。
-----
HeaderKeyWord: PCiii jjj
Category      : WCS
Importance    : Imaging
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 1.00000000
Comment       : Pixel Coordinate translation matrix
DescriptionE   : Pixel Coordinate translation matrix: iii and jjj are the axis numbers, 001 or 002.
DescriptionJ   : データの画素値座標系から歪みや回転を取り除くのに用いられる変換行列
-----
HeaderKeyWord: PROJ1
Category      : WCS
Importance    : Optional
FormatF       : F20.1
Unit          : -
Recommend     : 0.0
Sample        : 0.0
Comment       : Projection type of the first axis
DescriptionE   : Projection type of the X (1-st) axis: fixed to 0.0
DescriptionJ   : 局所球面座標から平面座標へのいくつかの投影法で必要となる。パラメータの X(第 1) 軸方向の値。
                  撮像観測に対応する TAN 変換では 0.0
-----
HeaderKeyWord: PROJ2
Category      : WCS
Importance    : Optional
FormatF       : F20.1
Unit          : -
Recommend     : 0.0
Sample        : 0.0
Comment       : Projection type of the second axis
DescriptionE   : Projection type of the Y (2-nd) axis: fixed to 0.0
DescriptionJ   : 局所球面座標から平面座標へのいくつかの投影法で必要となる。パラメータの Y(第 2) 軸方向の値。
                  撮像観測に対応する TAN 変換では 0.0
-----
HeaderKeyWord: WCS-ORIG
Category      : WCS
Importance    : Imaging
FormatF       : A20
Unit          : -
Recommend     : -
Sample        : 'SUBARU Toolkit'
Comment       : Origin of the WCS value
DescriptionE   : Origin of the World coordinate values. Specify 'SUBARU Toolkit' if it's
                  calculated using toolkit.
DescriptionJ   : WCS パラメータの出处。すばるツールキットを使用した場合、'SUBARU Toolkit' という値が入る。
-----
HeaderKeyWord: CDj_i
Category      : WCS
Importance    : Optional
FormatF       : F20.8
Unit          : -
Recommend     : -
Sample        : 0.0445
Comment       : Pixel coordinate transformation matrix
DescriptionE   : Pixel Coordinate transformation matrix which will be a default for world coordinate
                  discription in FITS format.
DescriptionJ   : データの画素値空間座標系から歪みや回転を取り除くのに用いられる変換行列。
-----

```

6.3 装置固有ヘッダー辞書

観測装置固有のキーワードは、頭2文字を定められた装置IDとし、残り6文字を装置開発グループが定義して利用する。共通ヘッダーキーワードと同様な辞書が観測装置グループによって作成され、公開されることになっている。

6.3.1 CIAO 固有ヘッダー辞書

Header Key Word	Value Format	Type	Unit	Comment
C_OMASK	%15s	string		Identifier of the Occulting Mask
C_LYOTST	%15s	string		Identifier of the Lyot Stop
C_LYOANG	%5.1f	double	degree	Lyot stop position angle
C_CAMERA	%15s	string		Camera mode
C_BNCTMP	%6.2f	double	K	Optical bench temperature
C_COLX	%6.2f	double	um	Collimator lens x position
C_COLY	%6.2f	double	um	Collimator lens y position
C_VACUUM	%8.3f	double	torr	Vacuum inside dewar
C_SHUTTR	%3s	string		Shutter above CIAO on/off
C_DETPOS	%5d	integer	um	Detector stage position
C_WATER1	%5.2f	double	1/min	Water flow to rack1
C_WATER2	%5.2f	double	1/min	Water flow to rack2
C_AO	%15s	string		On or off of adaptive optics
C_AO-WFS	%7.5f	double		Sigma of deformable mirror
C_AO-TIP	%15s	string		AO tip-tilt on/off
C_AO-FRE	%5d	integer	Hz	Frequency of AO loop

6.3.2 COMICS 固有ヘッダー辞書

[COMICS Dictionary 1/2]

Header Key Word	Value Format	Type	Unit	Comment
Q_DTYPE	%10s	string		type of this file spec/img/slitview
Q_OBSID	%8d	integer		Observation ID of COMICS
Q_WINDOW	%10s	string		Entrance Window
Q_M1MOTA	%8d	integer		Pulse count of 1st mir. para to bench
Q_M1MOTB	%8d	integer		Pulse count of 1st mir. vert to bench
Q_SLTVEW	%8s	string		Slit Viewer on/off
Q_SPFILE	%20s	string		File name of spectroscopy
Q_SVWMIN	%10.4f	double	nm	Observed Wavelength of S Viewer min
Q_SVWMAX	%10.4f	double	nm	Observed Wavelength of S Viewer max
Q_DETP1	%10.5f	double	K	Temperature of the detector spec-1
Q_DETP2	%10.5f	double	K	Temperature of the detector spec-2
Q_DETP3	%10.5f	double	K	Temperature of the detector spec-3
Q_DETP4	%10.5f	double	K	Temperature of the detector spec-4
Q_DETP5	%10.5f	double	K	Temperature of the detector spec-5
Q_DETP6	%10.5f	double	K	Temperature of the detector spec-6
Q_CFTP1	%6.2f	double	K	Temp. of the cooled finger spec
Q_CFTP2	%6.2f	double	K	Temp. of the cooled finger img
Q_OPTP1	%6.2f	double	K	Temp. of the optics spec-A
Q_OPTP2	%6.2f	double	K	Temp. of the optics spec-B
Q_OPTP3	%6.2f	double	K	Temp. of the optics spec-C
Q_OPTP4	%6.2f	double	K	Temp. of the optics img-A
Q_OPTP5	%6.2f	double	K	Temp. of the optics img-B
Q_OPTP6	%6.2f	double	K	Temp. of the optics img-C
Q_COHTP1	%6.2f	double	K	Temp. of the cooler head spec
Q_COHTP2	%6.2f	double	K	Temp. of the cooler head img
Q_SHDTP1	%6.2f	double	K	Temp. of the shield A
Q_SHDTP2	%6.2f	double	K	Temp. of the shield B
Q_ABTP1	%6.2f	double	K	Temperature of Ambient thermometer
Q_ABTP2	%6.2f	double	K	Temperature of Ambient thermometer
Q_ABTP3	%6.2f	double	K	Temperature of Ambient thermometer
Q_CLKVER	%30s	string		Clock version
Q_CLKFL	%30s	string		Clock macro file name
Q_CLKMCC	%30s	string		Comment on clock pattern macro
Q_CLKNM	%30s	string		Clock pattern name
Q_CLKCLC	%30s	string		Comment on each clock pattern
Q_PIXTIM	%6.2f	double	microsec	Clock duration for a pixel
Q_FRRATE	%8.4f	double	Hz	Detector Framerate
Q_READTM	%12.8f	double	sec	Time for reading out 1 exp

Header Key Word	Value Format	Type	Unit	Comment
Q_NDRATE	%3d	integer	1/243	N.D. rate of the detector
Q_NDEFF	%10.8f	double		efficiency of the integ by using N.D.
Q_CHOP	%8s	string		Chopping on/off
Q_CPWTP	%8s	string		Tip-tilt with chopping on/off
Q_CPBMS	%16s	string		Chopping beam at the 1st exp.
Q_CPFREQ	%8.4f	double	Hz	Chopping Frequency
Q_CPTIME	%10.6f	double	sec	Chopping period per 1 beam
Q_CPEXP	%d	integer		Number of exp of 1 chopping beam
Q_CPEXAD	%d	integer		Number of coadded exp.
Q_CPFRA	%d	integer		Number of frame of 1 chopping beam
Q_CPNUM	%d	integer		Number of chopping in this file
Q_INT1BM	%6f	double	sec	Integration time per 1 position
Q_CPTHRW	%10.4f	double	arcsec	Chopping throw
Q_CPPA	%8.4f	double	deg	Chopping P.A.
Q_NDTIME	%2f	double	sec	Nodding period
Q_NDOFRA	%10.4f	double	arcsec	Nodding offset R.A.
Q_NDOFDE	%8.4f	double	arcsec	Nodding offset Dec
Q_NDBEM	%12s	string		Nodding Beam main/offset
Q_NDCOM	%30s	string		Comment about Nodding
Q_GRTMOT	%d	integer		Pulse count of grating motor
Q_GRTANG	%10.6f	double	deg	Grating Tilt Angle
Q_WVMIN1	%10.4f	double	nm	Observed Wavelen on Spec Det-1 min
Q_WVMAX1	%10.4f	double	nm	Observed Wavelen on Spec Det-1 max
Q_WVMIN2	%10.4f	double	nm	Observed Wavelen on Spec Det-2 min
Q_WVMAX2	%10.4f	double	nm	Observed Wavelen on Spec Det-2 max
Q_WVMIN3	%10.4f	double	nm	Observed Wavelen on Spec Det-3 min
Q_WVMAX3	%10.4f	double	nm	Observed Wavelen on Spec Det-3 max
Q_WVMIN4	%10.4f	double	nm	Observed Wavelen on Spec Det-4 min
Q_WVMAX4	%10.4f	double	nm	Observed Wavelen on Spec Det-4 max
Q_WVMIN5	%10.4f	double	nm	Observed Wavelen on Spec Det-5 min
Q_WVMAX5	%10.4f	double	nm	Observed Wavelen on Spec Det-5 max

6.3.3 FOCAS 固有ヘッダー辞書

(注: ASCII TABLE EXTENSION あり。)

Header Key Word	Value Format	Type	Unit	Comment
F_TMP-A	F6.2	double	K	Temperature of MOS unit(K)
F_TMP-B	F6.2	double	K	Temperature of lens unit (K)
F_TMP-C1	F6.2	double	K	Temperature of collimator beam unit-1 (K)
F_TMP-C2	F6.2	double	K	Temperature of collimator beam unit-2 (K)
F_TMP-C3	F6.2	double	K	Temperature of collimator beam unit-3 (K)
F_TMP-D	F6.2	double	K	Temperature of Camera lens unit (K)
F_TMP-E1	F6.2	double	K	Temperature of VME-1 (K)
F_TMP-E2	F6.2	double	K	Temperature of VME-2 (K)
F_TMP-F1	F6.2	double	K	Temperature of driver-unit A-1 (K)
F_TMP-F2	F6.2	double	K	Temperature of driver-unit A-2 (K)
F_TMP-G1	F6.2	double	K	Temperature of driver-unit B-1 (K)
F_TMP-G2	F6.2	double	K	Temperature of driver-unit B-2 (K)
F_TMP-H1	F6.2	double	K	Temperature of driver-unit C-1 (K)
F_TMP-H2	F6.2	double	K	Temperature of driver-unit C-2 (K)
F_TMP-I1	F6.2	double	K	Temperature of driver-unit D-1 (K)
F_TMP-I2	F6.2	double	K	Temperature of driver-unit D-2 (K)
F_TMP-J1	F6.2	double	K	Temperature of driver-unit E-1 (K)
F_TMP-J2	F6.2	double	K	Temperature of driver-unit E-2 (K)
F_DEWERX	SP,F8.2	double	um	X-position of dewer stage (micron meter)
F_DEWERY	SP,F8.2	double	um	Y-position of dewer stage (micron meter)
F_DEWERZ	SP,F8.2	double	um	Z-position of dewer stage (micron meter)
F_HOLANG	F3.1	double	degree	angle of mask holder (degree)
F_MSK-ID	A9	string		ID of mask (for all mode)
F_CAD-ID	A9	string		ID of CAD data for mask cutting
F_CADREF	A50	string		ID/name of image/catalog data for mask design
F_DISPER	F5.3	double	nm/pixel	dispersion of grism (nm / pixel)
F_SLT-NO	I3	integer		total # of slit on mask
F_POSANG	F6.2	double	degree	PA of cross-dispersion axis (degree)

6.3.4 HDS 固有ヘッダー辞書

(注: ASCII TABLE EXTENSION 有。)

Header KeyWord	Value Format	Type	Unit	Comment
H_INPOWR	f6.2	double	Volt	Input power for the flat lamp
H_IMSLCR	a8	string		Image slicer (ON, OFF)
H_ISTYPE	a10	string		Type of the image slicer
H_S-MSK1	f6.3	double	mm	Upper mask position from the center
H_S-MSK2	f6.3	double	mm	Lower mask position from the center
H_S-INCL	f7.2	double		Slit inclination angle at the horizontal plane
H_D-UNIT	i1	integer		ID number of the detector unit
H_D-OTHR	a10	string		Use of the other CCD in this mosaic
H_SHUTTR	a10	string		Entrance shutter (OPEN, CLOSE)
H_HARTMN	a10	string		Hartmann shutter (U-OPEN,L-OPEN,ALL-OPEN,ALL-CLOSE)
H_COLLIM	a10	string		Collimator (BLUE, RED)
H_CLPSTN	f6.2	double	mm	Collimator position (mm)
H_CLFOCL	f10.5	double	mm	Collimator focal length (mm)
H_CLOFFA	f10.5	double	degree	Collimator offset angle (degree)
H_ECHELL	a10	string		Echelle (BLUE, RED, NIR)
H_ECONST	f7.3	double	grooves/mm	Ruling pitch (grooves/mm)
H_EBLAZE	f7.3	double	degree	Blaze Angle (degree)
H_EEPSRN	f7.3	double	degree	Offset Angle of the Incident Beam (degree)
H_EGAMMA	f7.3	double	degree	Echelle Gamma Angle (constant)
H_EROTAN	f10.5	double	degree	Echelle Rotation Angle (degree)
H_CROSSD	a10	string		Cross Disperser (BLUE, RED, MIRROR, NIR)
H_CCONST	f7.3	double	grooves/mm	Ruling pitch (grooves/mm)
H_CBLAZE	f7.3	double	degree	Blaze Angle (degree)
H_CEPSRN	f7.3	double	degree	Offset Angle at Blaze Wavelength (degree)
H_CGAMMA	f7.3	double	degree	Cross Disperser Gamma Angle (constant)
H_CTABAN	f10.5	double	degree	Rotation angle of the turn table (degree)
H_CROTAN	f10.5	double	degree	Cross Disperser Rotation Angle (degree)
H_CMRFL	f10.5	double	mm	Camera focal length (mm)
H_FOCUS	f10.5	double	mm	Focusing unit position (mm)
H_PITCH	f9.5	double	degree	Focusing unit pitching angle (degree)
H_YAWING	f9.5	double	degree	Focusing unit yawing angle (degree)
H_F-DRV1	f9.5	double	mm	Focusing driver1 position (mm)
H_F-DRV2	f9.5	double	mm	Focusing driver2 position (mm)
H_F-DRV3	f9.5	double	mm	Focusing driver3 position (mm)
H_DETROT	f9.5	double	degree	Rotation angle of the detector unit (degree)
H_ET1AVE	f6.2	double	K	Average (Kelvin)
H_ET1MIN	f6.2	double	K	Minimum (Kelvin)
H_ET1MAX	f6.2	double	K	Maximum (Kelvin)
H_ET1DEV	f6.2	double	K	Standard Deviation (Kelvin)
H_AO-TYP	a20	string		Type of correction (Tip-Tilt)
H_AO-ORD	i3	integer		Maximum order included
H_AO-OBJ	a20	string		star used for wavefront correction
H_AO-RA	a20	string		RA of star used for wavefront correction
H_AO-DEC	a20	string		Dec of star used for wavefront correction
H_ZAXIS1	a20	string		Axis1 of zero'th order light monitor of Echelle (Along slit/Cross slit/None)
H_ZAXIS2	a20	string		Axis2 of zero'th order light monitor of Echelle (Along slit/Cross slit/None)
H_ZA1POS	f7.2	double	pixel	peak position in axis1
H_ZA2POS	f7.2	double	pixel	peak position in axis2
H_ZWID1	f7.2	double	pixel	Width in axis1 of the stellar image (pixel)
H_ZWID2	f7.2	double	pixel	Width in axis2 of the stellar image (pixel)
H_ZDELT	f6.4	double	mm	Pixel size (mm)
H_ZSCALE	f8.5	double	mm/pixel	Physical length on the slit plane projected into one pixel
H_ZTMP	f5.1	double	K	Detector temperature (Kelvin)
H_SUPER	a10	string		Super Resolution Mode (POS1, POS2, NONE)
H_AG-OBJ	a20	string		Guide object name
H_AG-ORA	a20	string		RA of the guide object
H_AG-ODE	a20	string		Dec of the guide object
H_AG-RA	a20	string		RA of the tracked pos. on the slit guide pos.
H_AG-DEC	a20	string		Dec of the tracked pos. on the slit guide pos.
H_AG-EQN	f6.1	double		Equinox of H_AG-RA and H_AG_DEC

6.3.5 CISCO/OHS 固有ヘッダー辞書

Header Key Word	Value Format	Type	Unit	Comment
O_MSK	%30s	string		MASK name of OH Suppression
O_SLT	%30s	string		OHS slit
O_SLTLEN	%7.3f	double	arcsec	OHS slit length (arcsec)
O_SLTWID	%7.3f	double	arcsec	OHS slit width (arcsec)
O_FOCVAL	%7.3f	double		OHS FOCUS Value

6.3.6 SuprimeCam 固有ヘッダー辞書

Header Key Word	Value Format	Type	Unit	Comment
S_UFNAME	A40	CHARACTER		User assigned file name
S_FRMPOS	A4	CHARACTER		Frame position (IIJJ)
S_BCTAVE	F9.3	REAL	ADU	Average count outside effective data
S_BCTSD	F9.3	REAL	ADU	S.D. of the count outside the eff. data
S_AG-OBJ	A40	CHARACTER		Name of the guide-star
S_AG-RA	A12	CHARACTER		R.A. of the guide-star
S_AG-DEC	A12	CHARACTER		Dec. of the guide-star
S_AG-EQN	F6.1	REAL	y	Equinox of the guide-star position
S_AG-X	F7.2	REAL	mm	Position of the guiding probe (X)
S_AG-Y	F7.2	REAL	mm	Position of the guiding probe (Y)
S_AG-R	F7.2	REAL	mm	Position of the guiding probe (R)
S_AG-TH	F7.2	REAL	degree	Position of the guiding probe (theta)
S_ETMED	F6.2	REAL	K	Averaged temp. in Camera enclosure (Kelvin)
S_ETMAX	F6.2	REAL	K	Maximum temp. in Camera enclosure (Kelvin)
S_ETMIN	F6.2	REAL	K	Minimum temp. in Camera enclosure (Kelvin)

6.3.7 MIRTOS 固有ヘッダー辞書

[MIRTOS Dictionary 1/2]

Header Key Word	Value Format	Type	Unit	Comment
M_WINDOW	%-8s			MIRTOS dewar entrance window
M_M1MOT1	%6d			Beam Stearing Mirror Direction (count)
M_M1MOT2	%6d			Beam Stearing Mirror Direction (count)
M_M2MOT1	%6d			Beam Splitter Direction (count)
M_M2MOT2	%6d			Beam Splitter Direction (count)
M_BEAM	%d			Number of Beam Description M_BEAMn
M_BEAM1	%-8.68s			
M_BEAM2	%-8.68s			
M_BEAM3	%-8.68s			
M_BEAM4	%-8.68s			
M_CHID	%-8.16s			ID of camera channel of MIRTOS
M_OBSID	%-8.16s			ID of set of chop/nod observation
M_TWID	%-8.16s			ID of two-wavelength simultaneous file
M_FLATID	%-8.16s			ID of the most recent flat field file
M_DARKID	%-8.16s			ID of the most recent dark exposure file
M_DET01	%8.5f			Rel X pos of NIR from MIR on sky (pixel)
M_DET02	%8.5f			Rel Y pos of NIR from MIR on sky (pixel)
M_CHOPTM	%8.2f			Chopping period (sec)
M_CHOPTH	%8.2f			Chopping throw (arcsec)
M_CHOPPA	%8.2f			Chopping P.A. origin:source/pointing (deg)
M_NODTM	%8.1f			Nodding period (sec)
M_NODTH	%8.2f			Nodding throw (arcsec)
M_NODPA	%8.2f			Nodding P.A. origin:source/pointing (deg)
M_RFX1PP	%d			Corner 1 X for Chop+ Nod+
M_RFY1PP	%d			Corner 1 Y for Chop+ Nod+
M_RFX2PP	%d			Corner 2 X for Chop+ Nod+
M_RFY2PP	%d			Corner 2 Y for Chop+ Nod+
M_RFX1MP	%d			Corner 1 X for Chop- Nod+
M_RFY1MP	%d			Corner 1 Y for Chop- Nod+
M_RFX2MP	%d			Corner 2 X for Chop- Nod+
M_RFY2MP	%d			Corner 2 Y for Chop- Nod+
M_RFX1PM	%d			Corner 1 X for Chop+ Nod-
M_RFY1PM	%d			Corner 1 Y for Chop+ Nod-

[MIRTOS Dictionary 2/2]

Header Key Word	Value Format Type	Unit	Comment
M_RFX2PM	%d		Corner 2 X for Chop+ Nod-
M_RFY2PM	%d		Corner 2 Y for Chop+ Nod-
M_RFX1MM	%d		Corner 1 X for Chop- Nod-
M_RFY1MM	%d		Corner 1 Y for Chop- Nod-
M_RFX2MM	%d		Corner 2 X for Chop- Nod-
M_RFY2MM	%d		Corner 2 Y for Chop- Nod-
M_O-TMP	%4.1f		Optics Temp(K) %%d
M_C-TMP1	%4.1f		CCC 1st stage(K) %%d
M_C-TMP2	%4.1f		CCC 2nd stage(K) %%d
M_A-TMP1	%4.1f		Ambient #1(K) %%d
M_A-TMP2	%4.1f		Ambient #2(K) %%d
M_A-TMP3	%4.1f		Ambient #3(K) %%d
M_W-TMP	%4.1f		CCC Coolant Out (K) %%d
M_W-CUR	%4.1f		CCC Coolant (l/min) %%d
M_CLKFL	%-8s		Clock file name
M_CLKMR	%-8s		Clock pattern marco name %%d
M_CLKMC	%-8s		Coment on clock pattern macro
M_PIXTIM	%9.4G		Clock duration for a pixel (sec)
M_FRTIME	%9.4f		Time to sweep one frame (sec)
M_CBANK	%-8s		Running clock bank when data was taken
M_CEFCT	%c		Clock activity when data taken (T:Conv F:Idle)
M_A-GAIN	%d		Wallace Instruments pre-amp gain
M_A-BWTH	%d		Wallace Instruments pre-amp BW(KHz)
M_JPORT	%2d		Jump port value when data got at %%d
M_REFSUB	%c		Subtraction of reference column T:done
M_ARRANG	%-8.10s		Data sequence FITS/Raw-hardware version
M_BANK	%-8s		Bank name where the data was stored
M_BBPOS	%c		Black Body Position T:In F:Out
M_BBTMP	%4.1f		Temperature of Black Body (K) %%d

6.3.8 IRCS 固有ヘッダー辞書

[IRCS Dictionary 1/2]

Header Key Word	Value Comment	Format
I_TC-SEQ	Telescope controlling sequence	%40s
I_NSQ	Number of the frame in the sequence	%3d
I_NSQMAX	Maximum number of the sequence	%3d
I_ABOFFX	Absolute offset from the center of the pattern (RA)	%8.2f
I_ABOFFY	Absolute offset from the center of the pattern (Dec)	%8.2f
I_RLOFFX	Relative offset from the last frame of the pattern (RA)	%8.2f
I_RLOFFY	Relative offset from the last frame of the pattern(Dec)	%8.2f
I_AG-OBJ	Name of the guide-star	%40s
I_AG-RA	R.A. of the guide-star	%12s
I_AG-DEC	Dec. of the guide-star	%12s
I_AG-EQN	Equinox of the guide-star position	%6.1f
I_AG-X	Position of the guiding probe (X)	%6.2f
I_AG-Y	Position of the guiding probe (Y)	%6.2f
I_AG-R	Position of the guiding probe (R)	%6.2f
I_AG-TH	Position of the guiding probe (theta)	%6.2f
I_TT-OBJ	Name of the tip-tilt guide-star	%40s
I_TT-RA	R.A. of the tip-tilt guide-star	%12s
I_TT-DEC	Dec. of the tip-tilt guide-star	%12s
I_TT-EQN	Equinox of the tip-tilt guide-star position	%6.1f
I_TT-X	Position of the guiding probe (X)	%6.2f
I_TT-Y	Position of the guiding probe (Y)	%6.2f
I_TT-R	Position of the guiding probe (R)	%6.2f
I_TT-TH	Position of the guiding probe (theta)	%6.2f
I_AOMODE	A0 mode	%3s
I_AO-WFS	Wavefront sensor used for A0	%10s
I_AO-GS	Name of the A0 guide star	%40s
I_AO-GSM	Magnitude of the A0 guide star	%3.1f
I_AO-GSB	Band for the magnitude of the A0 guide star	%3s
I_AO-EQN	Equinox of the guide-star position	%6.1f
I_AO-X	Position of the guiding probe (X)	%6.2f
I_AO-Y	Position of the guiding probe (Y)	%6.2f
I_AO-R	Position of the guiding probe (R)	%6.2f
I_AO-TH	Position of the guiding probe (theta)	%6.2f
I_UFNAME	User assigned file name	%40s
I_M-HAT	Status of mechanisms (hatch) HOME/OPEN/CLOSE	%5s
I_M-SW	Status of mechanisms (slit wheel)	%10s

[IRCS Dictionary 2/2]

Header Key Word	Value Comment	Format
I_M-FM1	Status of mechanisms (flip mirror 1) HOME/22mas/60mas	%5s
I_M-FM2	Status of mechanisms (flip mirror 2) HOME/22mas/60mas	%5s
I_M-CFW1	Status of mechanisms (camera filter wheel 1)	%10s
I_M-CFW2	Status of mechanisms (camera filter wheel 2)	%10s
I_M-CFW3	Status of mechanisms (camera filter wheel 2)	%10s
I_M-FS	Status of mechanisms (camera filter wheel 2)	%20s
I_M-SFW	Status of mechanisms (spectrographp filter wheel)	%30s
I_M-ECH	Status of mechanisms (Echelle drive)	%30s
I_M-XD	Status of mechanisms (X-disperser drive)	%30s
I_M-ECHE	Hall sensor value of Echelle drive	%10d
I_M-XDE	Hall sensor value of X-disperser drive	%10d
I_DMIN	MIN DATA VALUE IN FILE	%6d
I_DMAX	MAX DATA VALUE IN FILE	%6d
I_DMEAN	MEAN DATA VALUE IN FILE	%6.2f
I_DIV	Normalization value	%3d
I_NSARRY	Number of Sub Arrays	%3d
I_AR1MIN	x of Sub Arrays	%4d
I_AR2MIN	y of Sub Arrays	%4d
I_AR1RNG	wid of Sub Arrays	%4d
I_AR2RNG	hgt of Sub Arrays	%4d
I_SUBAB	SubAB flag. 0=off, 1=on	%1d
I_CBMODE	CB Mode is ARC_D	%1d
I_SLCNT	Number of Slow Counts	%2d
I_GRCNT	Global Reset Count. 1 cnt = 25 nsec	%4d
I_BGRSTF	Backgroud Reset's flag	%2d
I_BGRSTT	Backgroud Reset's msec	%4d
I_BGRSTC	Backgroud Reset's cnt	%3d
I_GOSIM	G0 simulation flag. 0=off, 1=on	%1d

6.3.9 VTOS 固有ヘッダー辞書

Header Key Word	Value Comment	Format
V_CAMTYP	Camera Type ICCD or HCCD	%6s
V_CAMNUM	Camera Number	%1d
V_OBSMOD	OBSERVATION MODE	%20s
V_DNAME	DATA NAME	%20s
V_FR-P-N	Frame Packet Number	%3d
V_FR-P-T	Frame Packet TOTAL	%3d
V_XSTPOS	X Stage Position (mm)	%10.5f
V_ZSTPOS	Z Stage Position (mm)	%10.5f
V_CAMPOS	Camera Position From Focus (mm)	%10.5f
V_LENSFL	Focal Length of Lens (mm)	%10.5f
V_C-FRFI	Interrace Mode	%20s

6.4 略号表 (1998/09/09)

次ページ参照

Abbreviation	meaning	Category
END	END	Action
MID	MIDdle	Action
STR	STaRt	Action
HUM	HUMidity	Environment
PRS	PReSsure	Environment
TMP	TeMPerature	Environment
WND	WiND	Environment
BIN	BiNning	Image
PRD	Partly ReaD out	Image
AO	Adaptive Optics	Instrument
APT	APerTure	Instrument
DET	DETeCTOR	Instrument
FLT	FiLTer	Instrument
PIX	PIXel	Instrument
PX	PiXel	Instrument
RET	RETarDer	Instrument
SLT	SLiT	Instrument
ANG	ANgLe	Statistics/Unit
AVE	AVErage	Statistics/Unit
CEN	CENter	Statistics/Unit
DIR	DIRection	Statistics/Unit
DISP	DISPersion	Statistics/Unit
FCT	FaCTor	Statistics/Unit
LEN	LENgth	Statistics/Unit
MAX	MAXimum	Statistics/Unit
MED	MEDian	Statistics/Unit
MIN	MINimum	Statistics/Unit
MOD	MODe	Statistics/Unit
PA	Position Angle	Statistics/Unit
RES	RESolution	Statistics/Unit
RNG	RaNGe	Statistics/Unit
SD	Standard Deviation	Statistics/Unit
SPC	SPaCial/SPaCe	Statistics/Unit
SPD	SPeeD	Statistics/Unit
SZ	SiZe	Statistics/Unit
TYP	TYPe	Statistics/Unit
VAL	VALue	Statistics/Unit
WAV	WAVelength	Statistics/Unit
WID	WIDth	Statistics/Unit
ADC	Atmospheric Dispersion Corrector	Telescope
AE	Absolute Encoder	Telescope
AG	AutoGuider	Telescope
AIRM	AIR Mass	Telescope
AZ	AZimuth	Telescope
CAL	CALibration source	Telescope
CS	CaSsEgrain focus	Telescope
DEC	DEClination	Telescope
DOM	DOMe / enclosure	Telescope
EL	ELevation	Telescope
ELBX	ELeCtric terminal BoX	Telescope
FOC	telescope FOCus	Telescope
FV	Field Viewer	Telescope
IE	Incremental Encoder	Telescope
IMR	IMage Rotator	Telescope
INR	INstrumental Rotator	Telescope
M2	2-ndary Mirror	Telescope
M3	Tertiary Mirror	Telescope
NS	NaSmith focus	Telescope
PF	Primary Focus	Telescope
PM	Primary Mirror	Telescope
PMA	Primary Mirror Actuator	Telescope
POS	POSition	Telescope
PRB	PReBe	Telescope
RA	Right Ascension	Telescope
SECZ	SECaNt of Zenith distance	Telescope
TEL	TELescope	Telescope
TIP	TiP/Tilt	Telescope
ZD	Zenith Distance	Telescope
HST	Hawaii Standard Time	Time
JD	Julian Date	Time
LST	Local Siderial Time	Time
MJD	Modified Julian Date	Time
UT	Universal Time	Time

表 19: 略号

6.5 FITS ヘッダーサンプル

現時点ではすばる *FITS* ヘッダールールに反する箇所も見受けられるが、鋭意整備中であり、最新情報を参照願いたい (7.4.4 節参照)。

6.5.1 CIAO(1999/12/10)

● CIAO の Imaging mode

```

1      2      3      4      5      6      7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE  =                               T / DATA IS IN FITS FORMAT
BITPIX  =                               32 / 32 BITS TWOS COMPLEMENT INTEGERS
NAXIS   =                               2 / NUMBER OF AXIS
NAXIS1  =                              1024 / PIXELS ON 1st MOST VARYING AXIS
NAXIS2  =                              1024 / PIXELS ON 2nd MOST VARYING AXIS
OBSERVER= 'Itoh      ' / Observer
PROP-ID = 'o99002   ' / Proposal ID
DATASET = '#        ' / ID of an observation dataset
FRAMEID = 'CIAA00000249' / Image sequential number
EXP-ID  = 'CIAE00000434' / ID of the exposure this data was taken
OBS-MOD = 'Imaging  ' / Observation mode
DATA-TYP= 'OBJECT   ' / Type / Characteristics of this data
DISPAXIS= 1 / Dispersion axis in frame
WCS-ORIG= 'SUBARU Toolkit' / Origin of the WCS value
CRPIX1  = 512 / Reference pixel in X
CRPIX2  = 512 / Reference pixel in Y
CRVAL1  = 283.69570000 / Physical value of the reference pixel X
CRVAL2  = 5.00658333 / Physical value of the reference pixel Y
CDELTA1 = 0.00000000 / Size projected into a detector pixel X
CDELTA2 = 0.00000000 / Size projected into a detector pixel Y
CTYPE1  = 'RA---TAN' / Pixel coordinate system
CTYPE2  = 'DEC--TAN' / Pixel coordinate system
CUNIT1  = 'degree' / Units used in both CRVAL1 and CDELTA1
CUNIT2  = 'degree' / Units used in both CRVAL2 and CDELTA2
PROJ1P  = 0.0 / Projection type of the first axis
PROJ2P  = 0.0 / Projection type of the second axis
LONGPOLE= 180.0 / The North Pole of the standard system
PC001001= 1.00000000 / Pixel coordinate translation matrix
PC001002= 0.00000000 / Pixel coordinate translation matrix
PC002001= 0.00000000 / Pixel coordinate translation matrix
PC002002= 1.00000000 / Pixels coordinate translation matrix
COMMENT
COMMENT
COMMENT
DATE-OBS= '1999-12-06' / Observation start date ('yyyy-mm-dd')
UT       = '18:29:04.817' / HH:MM:SS.S middle UTC at exposure
UT-STR   = '18:29:04.817' / HH:MM:SS.S middle UTC at start
UT-END   = '18:29:07.726' / HH:MM:SS.S middle UTC at end
HST      = '08:29:04.817' / HH:MM:SS.S middle HST at exposure
LST      = '13:07:34.101' / HH:MM:SS.S middle LST at exposure
MJD      = 51518.77020055 / Modified Julian day
TIMESYS  = 'UTC' / Time system used in this header
INSTRUME= 'CIAO' / The name of instrument
OBJECT   = 'dummy' / target Description
RADECSYS= 'FK5' / The equatorial coordinate system
RA       = '18:54:46.968' / HH:MM:SS.SSS RA pointing
DEC      = '+05:00:23.70' / +/-DD:MM:SS.SS DEC pointing
EQUINOX  = 2000.0 / Standard FK5 (years)
RA2000  = '18:54:46.968' / HH:MM:SS.SSS RA (J2000) pointing
DEC2000  = '+05:00:23.70' / +/-DD:MM:SS.SS DEC (J2000) pointing
TELFOCUS= 'Cassegrain' / Focus where a beam is reachable
FOC-POS  = 'Cassegrain' / Focus where the instrument is attached
FOC-VAL  = -0.025 / Encoder value of the focus unit
FILTER01= 'open' / Filter name/ID
FILTER02= 'open' / Filter name/ID
AIRMASS  = 4.11500 / averaged Air Mass
ZD       = 76.14 / Zenith distance at typical time
ZD-STR   = 76.14 / Zenith distance at start
ZD-END   = 76.14 / Zenith distance at end
AZIMUTH  = 89.61928 / Azimuth of telescope pointing
AUTOGUID= 'OFF' / Auto guider on/off
M2-TYPE  = '# ' / 2nd mirror type
M2-TIP   = '# ' / 2nd mirror tip-tilt on-off
INSROT   = -152.886 / Angle of instrument rotator
COMMENT
COMMENT
```

```

COMMENT
DETECTOR= 'Alladin2'          / Name of the detector/CCD
DET-TMP = 0.00 / Detector temperature
GAIN = 1.26 / AD conversion factor
BIN-FCT1= 1 / Binning factor of X axis
BIN-FCT2= 1 / Binning factor of Y axis
DET-RST = 800 / Reset number before exposure
DET-SMPL= 'ARC_D' / Sample method of detector
DET-NSMP= 1 / # of multiple sample in each exposure
DET-VER = 'bigdog99.12' / Array control command script name
DET-TSD = 0.00 / Standard deviation of detector temp.(K)
PRD-MIN1= 1 / Start x pos. of partial read out
PRD-MIN2= 1 / Start y pos. of partial read out
PRD-RNG1= 1024 / x range of partial read out
PRD-RNG2= 1024 / y range of partial read out
EXP1TIME= 1.0000 / Each exposure time (sec)
COADD = 1 / # of coadd
EXPTIME = 1.0000 / Total exposure time (sec)
COMMENT
COMMENT
COMMENT
SLIT = 'none' / Identifier of the entrance slit used
SLT-LEN = 0.000 / Length of the slit used
SLT-WID = 0.000 / Width of the slit used
SLT-PA = 0.0 / Slit position angle
DISPERSR= 'none' / Disperser
WAVELEN = 0.0000 / Wavelength at detector center
WAV-MIN = 0.0000 / Shortest wavelength focused on detector
WAV-MAX = 0.0000 / Longest wavelength focused on detector
SLTC-RA = 283.69570 / RA of slit center (degree)
SLTC-DEC= 5.00658 / DEC of slit center (degree)
SLTCPIX1= 0.0 / Pixel of slit center (AXIS1)
SLTCPIX2= 0.0 / Pixel of slit center (AXIS2)
COMMENT
COMMENT
COMMENT
RETPLAT1= 'none' / Identifier of the retarder plate1
RETPLAT2= 'none' / Identifier of the retarder plate2
RET-ANG1= 0.000 / Position angle of retarder1
RET-ANG2= 0.000 / Position angle of retarder2
POLARIZ1= 'none' / Name of the polarizer
POL-ANG = 0.00 / Position angle of polarizer
COMMENT
COMMENT
COMMENT
C_AO = 'Off' / On or off of adaptive optics
C_AO-WFS= 0.00000 / Sigma of deformable mirror
C_AO-TIP= 'unknown' / AO tip-tilt on/off
C_AO-FRE= -99 / Frequency of AO loop (Hz)
COMMENT
COMMENT
COMMENT
C_OMASK = '1.5' / Identifier of occulting mask
C_LYOTST= 'MTK8' / Identifier of Lyot stop
C_LYOANG= 31 / Lyot stop position angle (degree)
C_CAMERA= 'PIM' / Camera mode
C_BNCTMP= 296.68 / Optical bench temperature (K)
C_COLX = 0 / Collimator lens x position (um)
C_COLY = 0 / Collimator lens y position (um)
C_VACUUM= -99.99 / Vacuum inside dewar (torr)
C_SHUTTR= 'unknown' / Shutter above CIAO on/off
C_DETPOS= 0 / Detector stage position (um)
C_WATER1= -99.99 / Water flow rack1 (l/min)
C_WATER2= -99.99 / Water flow rack2 (l/min)
INS-VER = 'ver9908' / Version of the instrument soft/hard
DOM-HUM = 33.0 / Dome humidity (%)
OUT-HUM = 14.5 / Outside humidity (%)
DOM-TMP = 277.95 / Dome temperature (C)
OUT-TMP = 280.85 / Outside temperature (C)
DOM-WND = 0.10 / Dome wind speed (m/sec)
OUT-WND = 4.40 / Outside wind speed (m/sec)
DOM-PRS = 622.90 / Dome pressure (hpa)
OUT-PRS = 622.90 / Outside pressure (hpa)
SEEING = 0.0000 / seeing size (arcsec)
WEATHER = 'Clear' / Weather condition
EXTEND = F / Existence of extension or not
TELESCOP= 'SUBARU' / The name of telescope data obtained
OBSERVAT= 'NAOJ' / Observatory name
OBS-ALOC= 'Observation' / Allocation mode for Instrument
BLANK = 32768.00 / Value used for NULL pixels
BUNIT = 'ADU' / Unit of original pixel values
BZERO = 0.00 / Real = fits-value*BSCALE+BZERO
END

```

● CIAO の Polarimetry mode

```

1      2      3      4      5      6      7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE   =                               T / DATA IS IN FITS FORMAT
BITPIX   =                               32 / 32 BITS TWOS COMPLEMENT INTEGERS
NAXIS     =                               2 / NUMBER OF AXIS
NAXIS1    =                              1024 / PIXELS ON 1st MOST VARYING AXIS
NAXIS2    =                              1024 / PIXELS ON 2nd MOST VARYING AXIS
OBSERVER= 'Itoh      ' / Observer
PROP-ID   = 'o99002   ' / Proposal ID
DATASET   = '#'       / ID of an observation dataset
FRAMEID   = 'CIAA00000249' / Image sequential number
EXP-ID    = 'CIAE00000434' / ID of the exposure this data was taken
OBS-MOD   = 'Imaging  ' / Observation mode
DATA-TYP= 'OBJECT    ' / Type / Characteristics of this data
DISPAXIS=                               1 / Dispersion axis in frame
WCS-ORIG= 'SUBARU Toolkit' / Origin of the WCS value
CRPIX1    =                               512 / Reference pixel in X
CRPIX2    =                               512 / Reference pixel in Y
CRVAL1    =          283.69570000 / Physical value of the reference pixel X
CRVAL2    =           5.00658333 / Physical value of the reference pixel Y
CDELT1    =           0.00000000 / Size projected into a detector pixel X
CDELT2    =           0.00000000 / Size projected into a detector pixel Y
CTYPE1    = 'RA---TAN' / Pixel coordinate system
CTYPE2    = 'DEC--TAN' / Pixel coordinate system
CUNIT1    = 'degree   ' / Units used in both CRVAL1 and CDELT1
CUNIT2    = 'degree   ' / Units used in both CRVAL2 and CDELT2
PROJ1     =           0.0 / Projection type of the first axis
PROJ2     =           0.0 / Projection type of the second axis
LONGPOLE=          180.0 / The North Pole of the standard system
PC001001=          1.00000000 / Pixel coordinate translation matrix
PC001002=          0.00000000 / Pixel coordinate translation matrix
PC002001=          0.00000000 / Pixel coordinate translation matrix
PC002002=          1.00000000 / Pixels coordinate translation matrix
COMMENT
COMMENT
COMMENT
DATE-OBS= '1999-12-06' / Observation start date ('yyyy-mm-dd')
UT       = '18:29:04.817' / HH:MM:SS.S middle UTC at exposure
UT-STR   = '18:29:04.817' / HH:MM:SS.S middle UTC at start
UT-END   = '18:29:07.726' / HH:MM:SS.S middle UTC at end
HST      = '08:29:04.817' / HH:MM:SS.S middle HST at exposure
LST      = '13:07:34.101' / HH:MM:SS.S middle LST at exposure
MJD      =          51518.77020055 / Modified Julian day
TIMESYS  = 'UTC       ' / Time system used in this header
INSTRUME= 'CIAO      ' / The name of instrument
OBJECT   = 'dummy     ' / target Description
RADECSYS= 'FK5       ' / The equatorial coordinate system
RA       = '18:54:46.968' / HH:MM:SS.SSS RA pointing
DEC      = '+05:00:23.70' / +/-DD:MM:SS.SS DEC pointing
EQUINOX  =          2000.0 / Standard FK5 (years)
RA2000   = '18:54:46.968' / HH:MM:SS.SSS RA (J2000) pointing
DEC2000  = '+05:00:23.70' / +/-DD:MM:SS.SS DEC (J2000) pointing
TELFOCUS= 'Cassegrain' / Focus where a beam is reachable
FOC-POS  = 'Cassegrain' / Focus where the instrument is attached
FOC-VAL  =          -0.025 / Encoder value of the focus unit
FILTER01= 'open      ' / Filter name/ID
FILTER02= 'open      ' / Filter name/ID
AIRMASS  =          4.11500 / averaged Air Mass
ZD       =          76.14 / Zenith distance at typical time
ZD-STR   =          76.14 / Zenith distance at start
ZD-END   =          76.14 / Zenith distance at end
AZIMUTH  =          89.61928 / Azimuth of telescope pointing
AUTOGUID= 'OFF       ' / Auto guider on/off
M2-TYPE  = '#'       / 2nd mirror type
M2-TIP   = '#'       / 2nd mirror tip-tilt on-off
INSROT   =          -152.886 / Angle of instrument rotator
COMMENT
COMMENT
COMMENT
DETECTOR= 'Alladin2' / Name of the detector/CCD
DET-TMP  =          0.00 / Detector temperature
GAIN     =          1.26 / AD conversion factor
BIN-FCT1 =          1 / Binning factor of X axis
BIN-FCT2 =          1 / Binning factor of Y axis
DET-RST  =          800 / Reset number before exposure
DET-SMPL= 'ARC_D    ' / Sample method of detector
DET-NSMP=          1 / # of multiple sample in each exposure
DET-VER  = 'bigdog99.12' / Array control command script name
DET-TSD  =          0.00 / Standard deviation of detector temp.(K)
PRD-MIN1=          1 / Start x pos. of partialy read out
PRD-MIN2=          1 / Start y pos. of partialy read out

```

```

PRD-RNG1=          1024 / x range of partialy read out
PRD-RNG2=          1024 / y range of partialy read out
EXP1TIME=          1.0000 / Each exposure time (sec)
COADD =             1 / # of coadd
EXPTIME =           1.0000 / Total exposure time (sec)
COMMENT
COMMENT
SLIT = 'none' , / Identifier of the entrance slit used
SLT-LEN =          0.000 / Length of the slit used
SLT-WID =          0.000 / Width of the slit used
SLT-PA =           0.0 / Slit position angle
DISPERSR= 'none' , / Disperser
WAVELEN =          0.0000 / Wavelength at detector center
WAV-MIN =          0.0000 / Shortest wavelength focused on detector
WAV-MAX =          0.0000 / Longest wavelength focused on detector
SLTC-RA =          283.69570 / RA of slit center (degree)
SLTC-DEC=          5.00658 / DEC of slit center (degree)
SLTCPIX1=          0.0 / Pixel of slit center (AXIS1)
SLTCPIX2=          0.0 / Pixel of slit center (AXIS2)
COMMENT
COMMENT
COMMENT
RETPLAT1= 'none' , / Identifier of the retarder plate1
RETPLAT2= 'none' , / Identifier of the retarder plate2
RET-ANG1=          0.000 / Position angle of retarder1
RET-ANG2=          0.000 / Position angle of retarder2
POLARIZ1= 'none' , / Name of the polarizer
POL-ANG =          0.00 / Position angle of polarizer
COMMENT
COMMENT
COMMENT
C_AO = 'Off' , / On or off of adaptive optics
C_AO-WFS=          0.00000 / Sigma of deformable mirror
C_AO-TIP= 'unknown' , / AO tip-tilt on/off
C_AO-FRE=          -99 / Frequency of AO loop (Hz)
COMMENT
COMMENT
C_OMASK = '1.5' , / Identifier of occulting mask
C_LYOTST= 'MTK8' , / Identifier of Lyot stop
C_LYOANG=          31 / Lyot stop position angle (degree)
C_CAMERA= 'PIM' , / Camera mode
C_BNCTMP=          296.68 / Optical bench temperature (K)
C_COLX =           0 / Collimator lens x position (um)
C_COLY =           0 / Collimator lens y position (um)
C_VACUUM=          -99.99 / Vacuum inside dewar (torr)
C_SHUTTR= 'unknown' , / Shutter above CIAO on/off
C_DETPOS=          0 / Detector stage position (um)
C_WATER1=          -99.99 / Water flow rack1 (l/min)
C_WATER2=          -99.99 / Water flow rack2 (l/min)
INS-VER = 'ver9908' , / Version of the instrument soft/hard
DOM-HUM =          33.0 / Dome humidity (%)
OUT-HUM =          14.5 / Outside humidity (%)
DOM-TMP =          277.95 / Dome temperature (C)
OUT-TMP =          280.85 / Outside temperature (C)
DOM-WND =          0.10 / Dome wind speed (m/sec)
OUT-WND =          4.40 / Outside wind speed (m/sec)
DOM-PRS =          622.90 / Dome pressure (hpa)
OUT-PRS =          622.90 / Outside pressure (hpa)
SEEING =           0.0000 / seeing size (arcsec)
WEATHER = 'Clear' , / Weather condition
EXTEND =           F / Existence of extension or not
TELESCOP= 'SUBARU' , / The name of telescope data obtained
OBSERVAT= 'NAOJ' , / Observatory name
OBS-ALOC= 'Observation' , / Allocation mode for Instrument
BLANK =           32768.00 / Value used for NULL pixels
BUNIT = 'ADU' , / Unit of original pixel values
BZERO =           0.00 / Real = fits-value*BSCALE+BZERO
END

```

● CIAO の SpectroPolarimetry mode

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE =          T / DATA IS IN FITS FORMAT
BITPIX =          32 / 32 BITS TWOS COMPLEMENT INTEGERS
NAXIS =           2 / NUMBER OF AXIS
NAXIS1 =          1024 / PIXELS ON 1st MOST VARYING AXIS
NAXIS2 =          1024 / PIXELS ON 2nd MOST VARYING AXIS
OBSERVER= 'Itoh' , / Observer

```

```

PROP-ID = 'o99002' , / Proposal ID
DATASET = '# ' , / ID of an observation dataset
FRAMEID = 'CIAA00000249' , / Image sequential number
EXP-ID = 'CIAE00000434' , / ID of the exposure this data was taken
OBS-MOD = 'Imaging' , / Observation mode
DATA-TYP= 'OBJECT' , / Type / Characteristics of this data
DISPAxis= 1 / Dispersion axis in frame
WCS-ORIG= 'SUBARU Toolkit' , / Origin of the WCS value
CRPIX1 = 512 / Reference pixel in X
CRPIX2 = 512 / Reference pixel in Y
CRVAL1 = 283.69570000 / Physical value of the reference pixel X
CRVAL2 = 5.00658333 / Physical value of the reference pixel Y
CDELT1 = 0.00000000 / Size projected into a detector pixel X
CDELT2 = 0.00000000 / Size projected into a detector pixel Y
CTYPE1 = 'RA---TAN' , / Pixel coordinate system
CTYPE2 = 'DEC--TAN' , / Pixel coordinate system
CUNIT1 = 'degree' , / Units used in both CRVAL1 and CDELT1
CUNIT2 = 'degree' , / Units used in both CRVAL2 and CDELT2
PROJP1 = 0.0 / Projection type of the first axis
PROJP2 = 0.0 / Projection type of the second axis
LONGPOLE= 180.0 / The North Pole of the standard system
PC001001= 1.00000000 / Pixel coordinate translation matrix
PC001002= 0.00000000 / Pixel coordinate translation matrix
PC002001= 0.00000000 / Pixel coordinate translation matrix
PC002002= 1.00000000 / Pixels coordinate translation matrix
COMMENT
COMMENT
COMMENT
DATE-OBS= '1999-12-06' , / Observation start date ('yyyy-mm-dd')
UT = '18:29:04.817' , / HH:MM:SS.S middle UTC at exposure
UT-STR = '18:29:04.817' , / HH:MM:SS.S middle UTC at start
UT-END = '18:29:07.726' , / HH:MM:SS.S middle UTC at end
HST = '08:29:04.817' , / HH:MM:SS.S middle HST at exposure
LST = '13:07:34.101' , / HH:MM:SS.S middle LST at exposure
MJD = 51518.77020055 / Modified Julian day
TIMESYS = 'UTC' , / Time system used in this header
INSTRUME= 'CIAO' , / The name of instrument
OBJECT = 'dummy' , / target Description
RADECSYS= 'FK5' , / The equatorial coordinate system
RA = '18:54:46.968' , / HH:MM:SS.SSS RA pointing
DEC = '+05:00:23.70' , / +/-DD:MM:SS.SS DEC pointing
EQUINOX = 2000.0 / Standard FK5 (years)
RA2000 = '18:54:46.968' , / HH:MM:SS.SSS RA (J2000) pointing
DEC2000 = '+05:00:23.70' , / +/-DD:MM:SS.SS DEC (J2000) pointing
TELFOCUS= 'Cassegrain' , / Focus where a beam is reachable
FOC-POS = 'Cassegrain' , / Focus where the instrument is attached
FOC-VAL = -0.025 / Encoder value of the focus unit
FILTER01= 'open' , / Filter name/ID
FILTER02= 'open' , / Filter name/ID
AIRMASS = 4.11500 / averaged Air Mass
ZD = 76.14 / Zenith distance at typical time
ZD-STR = 76.14 / Zenith distance at start
ZD-END = 76.14 / Zenith distance at end
AZIMUTH = 89.61928 / Azimuth of telescope pointing
AUTOGUID= 'OFF' , / Auto guider on/off
M2-TYPE = '# ' , / 2nd mirror type
M2-TIP = '# ' , / 2nd mirror tip-tilt on-off
INSROT = -152.886 / Angle of instrument rotator
COMMENT
COMMENT
COMMENT
DETECTOR= 'Alladin2' , / Name of the detector/CCD
DET-TMP = 0.00 / Detector temperature
GAIN = 1.26 / AD conversion factor
BIN-FCT1= 1 / Binning factor of X axis
BIN-FCT2= 1 / Binning factor of Y axis
DET-RST = 800 / Reset number before exposure
DET-SMPL= 'ARC_D' , / Sample method of detector
DET-NSMP= 1 / # of multiple sample in each exposure
DET-VER = 'bigdog99.12' , / Array control command script name
DET-TSD = 0.00 / Standard deviation of detector temp.(K)
PRD-MIN1= 1 / Start x pos. of partial read out
PRD-MIN2= 1 / Start y pos. of partial read out
PRD-RNG1= 1024 / x range of partial read out
PRD-RNG2= 1024 / y range of partial read out
EXP1TIME= 1.0000 / Each exposure time (sec)
COADD = 1 / # of coadd
EXPTIME = 1.0000 / Total exposure time (sec)
COMMENT
COMMENT
COMMENT
SLIT = 'none' , / Identifier of the entrance slit used
SLT-LEN = 0.000 / Length of the slit used
SLT-WID = 0.000 / Width of the slit used

```

```

SLT-PA = 0.0 / Slit position angle
DISPERSR= 'none' , / Disperser
WAVELEN = 0.0000 / Wavelength at detector center
WAV-MIN = 0.0000 / Shortest wavelength focused on detector
WAV-MAX = 0.0000 / Longest wavelength focused on detector
SLTC-RA = 283.69570 / RA of slit center (degree)
SLTC-DEC= 5.00658 / DEC of slit center (degree)
SLTCPIX1= 0.0 / Pixel of slit center (AXIS1)
SLTCPIX2= 0.0 / Pixel of slit center (AXIS2)
COMMENT
COMMENT
COMMENT
RETPLAT1= 'none' , / Identifier of the retarder plate1
RETPLAT2= 'none' , / Identifier of the retarder plate2
RET-ANG1= 0.000 / Position angle of retarder1
RET-ANG2= 0.000 / Position angle of retarder2
POLARIZ1= 'none' , / Name of the polarizer
POL-ANG = 0.00 / Position angle of polarizer
COMMENT
COMMENT
COMMENT
C_AO = 'Off' , / On or off of adaptive optics
C_AO-WFS= 0.00000 / Sigma of deformable mirror
C_AO-TIP= 'unknown' , / AO tip-tilt on/off
C_AO-FRE= -99 / Frequency of AO loop (Hz)
COMMENT
COMMENT
COMMENT
C_OMASK = '1.5' , / Identifier of occulting mask
C_LYOTST= 'MTK8' , / Identifier of Lyot stop
C_LYOANG= 31 / Lyot stop position angle (degree)
C_CAMERA= 'PIM' , / Camera mode
C_BNCTMP= 296.68 / Optical bench temperature (K)
C_COLX = 0 / Collimator lens x position (um)
C_COLY = 0 / Collimator lens y position (um)
C_VACUUM= -99.99 / Vacuum inside dewar (torr)
C_SHUTTR= 'unknown' , / Shutter above CIAO on/off
C_DETPOS= 0 / Detector stage position (um)
C_WATER1= -99.99 / Water flow rack1 (l/min)
C_WATER2= -99.99 / Water flow rack2 (l/min)
INS-VER = 'ver9908' , / Version of the instrument soft/hard
DOM-HUM = 33.0 / Dome humidity (%)
OUT-HUM = 14.5 / Outside humidity (%)
DOM-TMP = 277.95 / Dome temperature (C)
OUT-TMP = 280.85 / Outside temperature (C)
DOM-WND = 0.10 / Dome wind speed (m/sec)
OUT-WND = 4.40 / Outside wind speed (m/sec)
DOM-PRS = 622.90 / Dome pressure (hpa)
OUT-PRS = 622.90 / Outside pressure (hpa)
SEEING = 0.0000 / seeing size (arcsec)
WEATHER = 'Clear' , / Weather condition
EXTEND = F / Existence of extension or not
TELESCOP= 'SUBARU' , / The name of telescope data obtained
OBSERVAT= 'NAOJ' , / Observatory name
OBS-ALOC= 'Observation' , / Allocation mode for Instrument
BLANK = 32768.00 / Value used for NULL pixels
BUNIT = 'ADU' , / Unit of original pixel values
BZERO = 0.00 / Real = fits-value*BSCALE+BZERO
END

```

● CIAO の Spectroscopy mode

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / DATA IS IN FITS FORMAT
BITPIX = 32 / 32 BITS TWOS COMPLEMENT INTEGERS
NAXIS = 2 / NUMBER OF AXIS
NAXIS1 = 1024 / PIXELS ON 1st MOST VARYING AXIS
NAXIS2 = 1024 / PIXELS ON 2nd MOST VARYING AXIS
OBSERVER= 'Itoh' , / Observer
PROP-ID = 'o99002' , / Proposal ID
DATASET = '#' , / ID of an observation dataset
FRAMEID = 'CIAA00000249' , / Image sequential number
EXP-ID = 'CIAE00000434' , / ID of the exposure this data was taken
OBS-MOD = 'Imaging' , / Observation mode
DATA-TYP= 'OBJECT' , / Type / Characteristics of this data
DISPAXIS= 1 / Dispersion axis in frame
WCS-ORIG= 'SUBARU Toolkit' , / Origin of the WCS value
CRPIX1 = 512 / Reference pixel in X
CRPIX2 = 512 / Reference pixel in Y
CRVAL1 = 283.69570000 / Physical value of the reference pixel X

```

```

CRVAL2 = 5.00658333 / Physical value of the reference pixel Y
CDEL1 = 0.00000000 / Size projected into a detector pixel X
CDEL2 = 0.00000000 / Size projected into a detector pixel Y
CTYPE1 = 'RA---TAN' / Pixel coordinate system
CTYPE2 = 'DEC--TAN' / Pixel coordinate system
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDEL1
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDEL2
PROJP1 = 0.0 / Projection type of the first axis
PROJP2 = 0.0 / Projection type of the second axis
LONGPOLE = 180.0 / The North Pole of the standard system
PC001001 = 1.00000000 / Pixel coordinate translation matrix
PC001002 = 0.00000000 / Pixel coordinate translation matrix
PC002001 = 0.00000000 / Pixel coordinate translation matrix
PC002002 = 1.00000000 / Pixels coordinate translation matrix
COMMENT
COMMENT
COMMENT
DATE-OBS = '1999-12-06' / Observation start date ('yyyy-mm-dd')
UT = '18:29:04.817' / HH:MM:SS.S middle UTC at exposure
UT-STR = '18:29:04.817' / HH:MM:SS.S middle UTC at start
UT-END = '18:29:07.726' / HH:MM:SS.S middle UTC at end
HST = '08:29:04.817' / HH:MM:SS.S middle HST at exposure
LST = '13:07:34.101' / HH:MM:SS.S middle LST at exposure
MJD = 51518.77020055 / Modified Julian day
TIMESYS = 'UTC' / Time system used in this header
INSTRUME = 'CIAO' / The name of instrument
OBJECT = 'dummy' / target Description
RADECSYS = 'FK5' / The equatorial coordinate system
RA = '18:54:46.968' / HH:MM:SS.SSS RA pointing
DEC = '+05:00:23.70' / +/-DD:MM:SS.SS DEC pointing
EQUINOX = 2000.0 / Standard FK5 (years)
RA2000 = '18:54:46.968' / HH:MM:SS.SSS RA (J2000) pointing
DEC2000 = '+05:00:23.70' / +/-DD:MM:SS.SS DEC (J2000) pointing
TELCUS = 'Cassegrain' / Focus where a beam is reachable
FOC-POS = 'Cassegrain' / Focus where the instrument is attached
FOC-VAL = -0.025 / Encoder value of the focus unit
FILTER01 = 'open' / Filter name/ID
FILTER02 = 'open' / Filter name/ID
AIRMASS = 4.11500 / averaged Air Mass
ZD = 76.14 / Zenith distance at typical time
ZD-STR = 76.14 / Zenith distance at start
ZD-END = 76.14 / Zenith distance at end
AZIMUTH = 89.61928 / Azimuth of telescope pointing
AUTOGUID = 'OFF' / Auto guider on/off
M2-TYPE = '#' / 2nd mirror type
M2-TIP = '#' / 2nd mirror tip-tilt on-off
INSROT = -152.886 / Angle of instrument rotator
COMMENT
COMMENT
COMMENT
DETECTOR = 'Alladin2' / Name of the detector/CCD
DET-TMP = 0.00 / Detector temperature
GAIN = 1.26 / AD conversion factor
BIN-FCT1 = 1 / Binning factor of X axis
BIN-FCT2 = 1 / Binning factor of Y axis
DET-RST = 800 / Reset number before exposure
DET-SMPL = 'ARC_D' / Sample method of detector
DET-NSMP = 1 / # of multiple sample in each exposure
DET-VER = 'bigdog99.12' / Array control command script name
DET-TSD = 0.00 / Standard deviation of detector temp.(K)
PRD-MIN1 = 1 / Start x pos. of partial read out
PRD-MIN2 = 1 / Start y pos. of partial read out
PRD-RNG1 = 1024 / x range of partial read out
PRD-RNG2 = 1024 / y range of partial read out
EXP1TIME = 1.0000 / Each exposure time (sec)
COADD = 1 / # of coadd
EXPTIME = 1.0000 / Total exposure time (sec)
COMMENT
COMMENT
COMMENT
SLIT = 'none' / Identifier of the entrance slit used
SLT-LEN = 0.000 / Length of the slit used
SLT-WID = 0.000 / Width of the slit used
SLT-PA = 0.0 / Slit position angle
DISPERSR = 'none' / Disperser
WAVELEN = 0.0000 / Wavelength at detector center
WAV-MIN = 0.0000 / Shortest wavelength focused on detector
WAV-MAX = 0.0000 / Longest wavelength focused on detector
SLTC-RA = 283.69570 / RA of slit center (degree)
SLTC-DEC = 5.00658 / DEC of slit center (degree)
SLTCPIX1 = 0.0 / Pixel of slit center (AXIS1)
SLTCPIX2 = 0.0 / Pixel of slit center (AXIS2)
COMMENT
COMMENT

```

```

COMMENT
RETPLAT1= 'none      ' / Identifier of the retarder plate1
RETPLAT2= 'none      ' / Identifier of the retarder plate2
RET-ANG1=          0.000 / Position angle of retarder1
RET-ANG2=          0.000 / Position angle of retarder2
POLARIZ1= 'none      ' / Name of the polarizer
POL-ANG =          0.00 / Position angle of polarizer
COMMENT
COMMENT
COMMENT
C_AO = 'Off      ' / On or off of adaptive optics
C_AO-WFS=          0.00000 / Sigma of deformable mirror
C_AO-TIP= 'unknown ' / AO tip-tilt on/off
C_AO-FRE=          -99 / Frequency of AO loop (Hz)
COMMENT
COMMENT
COMMENT
C_OMASK = '1.5      ' / Identifier of occulting mask
C_LYOTST= 'MTK8     ' / Identifier of Lyot stop
C_LYOANG=          31 / Lyot stop position angle (degree)
C_CAMERA= 'PIM      ' / Camera mode
C_BNCTMP=          296.68 / Optical bench temperature (K)
C_COLX =          0 / Collimator lens x position (um)
C_COLY =          0 / Collimator lens y position (um)
C_VACUUM=          -99.99 / Vacuum inside dewar (torr)
C_SHUTTR= 'unknown ' / Shutter above CIAO on/off
C_DETPOS=          0 / Detector stage position (um)
C_WATER1=          -99.99 / Water flow rack1 (l/min)
C_WATER2=          -99.99 / Water flow rack2 (l/min)
INS-VER = 'ver9908 ' / Version of the instrument soft/hard
DOM-HUM =          33.0 / Dome humidity (%)
OUT-HUM =          14.5 / Outside humidity (%)
DOM-TMP =          277.95 / Dome temperature (C)
OUT-TMP =          280.85 / Outside temperature (C)
DOM-WND =          0.10 / Dome wind speed (m/sec)
OUT-WND =          4.40 / Outside wind speed (m/sec)
DOM-PRS =          622.90 / Dome pressure (hpa)
OUT-PRS =          622.90 / Outside pressure (hpa)
SEEING =          0.0000 / seeing size (arcsec)
WEATHER = 'Clear    ' / Weather condition
EXTEND =          F / Existence of extension or not
TELESCOP= 'SUBARU   ' / The name of telescope data obtained
OBSERVAT= 'NAOJ     ' / Observatory name
OBS-ALOC= 'Observation ' / Allocation mode for Instrument
BLANK =          32768.00 / Value used for NULL pixels
BUNIT = 'ADU       ' / Unit of original pixel values
BZERO =          0.00 / Real = fits-value*BSCALE+BZERO
END

```

6.5.2 COMICS(1998/08/19)

● COMICS の Imaging mode

```

1      2      3      4      5      6      7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE =          T / Standard FITS format
BITPIX =          32 / # of bits storing pix values
NAXIS =          4 / # of axis in frame %1d
NAXIS1 =          240 / # of pixels/row %5d
NAXIS2 =          336 / # of rows %5d
NAXIS3 =          1 / # of detectors %5d
NAXIS4 =          100 / # of frames %5d
EXTEND =          F / ASCII Table for Z-frame description %c
COMMENT ++++++ ???
DATASET = 'DSET-COMICS-123456' / Dataset Identification Number %20s
FRAMEID = 'COM1234567890123' / FITS File sequential number %16s
EXP-ID = 'COME123456789012' / ID of the exposure this data was takenA %16s
OBS-ALOC= ' ' / Allocation Mode for Instrument %12s
COMMENT ++++++ Observatory/Instrument
OBSERVER= 'Ktz,Ymst,Myt,Okmt ' / Name of observers %64s
PROP-ID = 'P1999-0709-1 ' / Proposal ID %20s
OBSERVAT= 'NAOJ ' / Observatory %30s
TELESCOP= 'Subaru ' / Telescope name %30s
INSTRUME= 'COMICS ' / Name of instrument %20s
INS-VER = '1.0.0 assembled 990701 ' / Version of the instrument %30s
DETECTOR= 'Si:As IBC 320x240 x6 ' / Name of the detector/CCD %10s
DET-ID =          1 / ID of the detector used for this data %d
COMMENT ++++++ Fixed Parameters in COMICS data (img)
DETPXSZ1=          0.0500 / Detector pixel size in axis1 (mm) %.4f

```

```

DETPXSZ2=          0.0500 / Detector pixel size in axis2 (mm)          %.4f
CDEL1T1 =          0.00003611 / X Scale projected on detector(#/pix)    %13.8f
CDEL1T2 =          0.00003611 / Y scale projected on detector(#/pix)    %13.8f
CTYPE1 = 'RA---TAN'          / Pixel coordinate system                  %16s
CTYPE2 = 'DEC--TAN'          / Pixel coordinate system                  %16s
CUNIT1 = 'degree'           / Units used in both CRVAL1 and CDEL1T1      %10s
CUNIT2 = 'degree'           / Units used in both CRVAL2 and CDEL1T2      %10s
CRPIX1 =          120.0 / Reference pixel in X (pixel)                  %-6.1f
CRPIX2 =          160.0 / Reference pixel in Y (pixel)                  %-6.1f
PROJP1 =          0.0 / Projection type of the first axis                %5.1f
PROJP2 =          0.0 / Projection type of the second axis                %5.1f
PC001001=          1.00000000 / Pixel Coordinate translation matrix      %12.8f
PC001002=          0.00000000 / Pixel Coordinate translation matrix      %12.8f
PC002001=          0.00000000 / Pixel Coordinate translation matrix      %12.8f
PC002002=          1.00000000 / Pixel Coordinate translation matrix      %12.8f
BSCALE =          1.0 / Real=fits-value*BSCALE+BZERO                    %.1f
BZERO =          0.0 / Real=fits-value*BSCALE+BZERO                    %.1f
BUNIT = 'ADU'              / Unit of original pixel values              %30s
BLANK =          32768 / Value used for NULL pixels                      %d
COMMENT ++++++ Date
TIMESYS = 'UTC'            / Time System used in the header. UTC fix.    %8s
DATE-OBS= '1999-07-09'     / yyyy-mm-dd UTC obs start date    %10s
UT = '09:12:00.0'          / HH:MM:SS.S UTC at typical time(=start) %10s
HST = '23:12:00.0'          / HH:MM:SS.S HST at typical time(=start) %10s
LST = '12:34:56.789'       / HH:MM:SS.S LST at typical time(=start) %12s
MJD =          12345.67890123 / Modified Julian Day at typ time(=start) %14.8f
COMMENT ++++++ Object
DATA-TYP= 'OBJECT'          / Type / Characteristics of this data    %15s
RADECSYS= 'FK5'            / The equatorial coordinate system        %8s
OBJECT = 'HR 4796'          / Target Description                      %30s
EQUINOX =          2000.0 / Standard FK5 year                      %6.1f
RA = '12:36:01.270'         / HH:MM:SS.SSS RA (J2000) pointing         %12s
RA2000 = '12:36:01.270'     / HH:MM:SS.SSS RA (J2000) pointing         %12s
DEC = '-39:52:09.40'        / +/-DD:MM:SS.SS DEC (J2000) pointing      %12s
DEC2000 = '-39:52:09.40'    / +/-DD:MM:SS.SS DEC (J2000) pointing      %12s
AZIMUTH =          12.34000 / Azimuth of telescope pointing (degree)   %9.5f
ALTITUDE =          12.34000 / Altitude of telescope pointing(degree) %8.5f
CRVAL1 =          189.00529167 / Physical value of the reference pixel X %13.8f
CRVAL2 =          -39.86927778 / Physical value of the reference pixel Y %13.8f
AIRMASS =          1.23456 / Averaged Air Mass                      %9.5f
ZD =          77.66000 / Zenith Distance at typical time                %8.5f
SECZ =          1.234 / SEC(Zenith Distance) at typical time            %6.3f
LONGPOLE=          180.0 / The North Pole of standard system (deg)      %6.1f
COMMENT ++++++ Subaru Parameters
FOC-POS = 'Cassegrain'      / Focus where the instrument is attached    %12s
TELFOCUS= 'Cassegrain'      / Focus where a beam is reachable          %30s
FOC-LEN =          100000.000 / Focal length of the telescope (mm)        %3.3f
FOC-VAL =          2.531 / Encoder value of the focus unit (mm)    %10.3f
INSROT =          12.345 / Instrument Rotator angle (deg)          %-8.3f
AUTOGUID= 'off'            / Auto Guider on/off                      %8s
M2-TYPE = 'IR'              / Type of the Secondary Mirror (Opt/IR)     %8s
M2-TIP = 'on'              / 2nd Mirror tip-tilt on/off              %8s
COMMENT ++++++ COMICS Parameters OPTICS
OBS-MOD = 'spectroscopy'    / Observation Mode                        %20s
FILTER01= 'Through'         / Filter name/ID (pre-opt filter-1)        %30s
FILTER02= 'Nwide'           / Filter name/ID (pre-opt filter-2)        %30s
FILTER03= '12um'            / Filter name/ID (img-opt filter)          %30s
FILTER04= 'N-obj'           / Lens name/ID (img-opt)                  %30s
DISPERSR= 'N-mid grt'       / Identifier of the disperser used          %10s
SLIT = '0.33arcsec'         / Identifier of the entrance slit used      %10s
SLT-LEN =          39.600 / Length of the slit used (arcsec)          %7.3f
SLT-PA =          0.0 / Slit Position Angle (degree)          %5.1f
SLT-WID =          0.3300 / Width of the slit used                %6.3f
SLTCPIX1=          120.0 / Slit center projected on detector(pix)    %6.1f
SLTCPIX2=          160.0 / Slit center projected on detector(pix)    %6.1f
COMMENT ++++++ COMICS Parameters DETECTOR
EXPTIME =          0.080 / Total integration time per frame(sec)    %7.3f
DET-TMP =          6.01 / Detector temperature (K)                %6.2f
GAIN =          330.90 / AD conversion factor (electron/ADU)        %5.2f
PRD-MIN1=          1 / Start X pos. of partially read out (pix)      %d
PRD-MIN2=          1 / Start Y pos. of partially read out (pix)      %d
PRD-RNG1=          320 / X Range of partially read out (pix)         %d
PRD-RNG2=          240 / Y Range of partially read out (pix)         %d
BIN-FCT1=          1 / Binning factor of X axis (pixel)            %2d
BIN-FCT2=          1 / Binning factor of Y axis (pixel)            %2d
COMMENT ++++++ Condition at the observation
WEATHER = 'rainstorm'       / Weather condition                      %30s
SEEING =          0.45 / Long integ PSF FWHM (arcsec)              %.2f
DOM-WND =          4.61 / Wind speed in the dome (m/s)            %5.2f
OUT-WND =          7.79 / Wind speed outside (m/s)                %5.2f
DOM-TMP =          273.51 / Temperature measured in the dome (K)    %6.2f
OUT-TMP =          273.72 / Temperature measured outside dome (K)   %6.2f
DOM-HUM =          90.1 / Humidity measured in the dome            %5.1f
OUT-HUM =          101.1 / Humidity measured outside the dome       %5.1f

```

```

DOM-PRS =          670.00 / Atmospheric pressure in the Dome (hpa)    %7.2f
OUT-PRS =          670.00 / Atmospheric pressure outside dome (hPa)  %7.2f
COMMENT -----
COMMENT Subaru Device Dependent Header Block for COMICS
COMMENT -----
COMMENT 'Q_' provisionally means COMICS header
COMMENT -----
COMMENT ++++++ Type of this data
Q_DTYPE = 'slitview' / type of this file spec/img/slitview          %10s
Q_OBSID =          12345678 / Observation ID of COMICS                %8d
COMMENT ++++++ Pre-Optics
Q_WINDOW= 'Ge10um' / Entrance Window                                %10s
Q_M1MOTA=          224 / Pulse count of 1st mir. para to bench        %8d
Q_M1MOTB=          339 / Pulse count of 1st mir. vert to bench        %8d
COMMENT ++++++ Slit Viewer/Imager
Q_SLTVEW= 'on' / Slit Viewer on/off                                  %8s
Q_SPFILE= 'COMA00000001' / File name of spectroscopy                %20s
Q_SVWMIN=          11650.0000 / Observed Wavelength of S Viewer min(nm) %10.4f
Q_SVWMAX=          12490.0000 / Observed Wavelength of S Viewer max(nm) %10.4f
COMMENT ++++++ Temperature
Q_DETP1=           4.95000 / Temperature of the detector spec-1 (K)   %10.5f
Q_DETP2=           4.85000 / Temperature of the detector spec-2 (K)   %10.5f
Q_DETP3=           4.95000 / Temperature of the detector spec-3 (K)   %10.5f
Q_DETP4=           4.88000 / Temperature of the detector spec-4 (K)   %10.5f
Q_DETP5=           4.95000 / Temperature of the detector spec-5 (K)   %10.5f
Q_DETP6=           6.95000 / Temperature of the detector img (K)      %10.5f
Q_CFTP1 =           4.22 / Temp. of the cooled finger spec (K)        %6.2f
Q_CFTP2 =           3.99 / Temp. of the cooled finger img (K)         %6.2f
Q_OPTP1=           30.00 / Temp. of the optics spec-A (K)             %6.2f
Q_OPTP2=           30.00 / Temp. of the optics spec-B (K)             %6.2f
Q_OPTP3=           30.00 / Temp. of the optics spec-C (K)             %6.2f
Q_OPTP4=           30.00 / Temp. of the optics img-A (K)              %6.2f
Q_OPTP5=           30.00 / Temp. of the optics img-A (K)              %6.2f
Q_OPTP6=           30.00 / Temp. of the optics img-A (K)              %6.2f
Q_COHP1=           3.99 / Temp. of the cooler head spec (K)           %6.2f
Q_COHP2=           3.89 / Temp. of the cooler head img (K)            %6.2f
Q_SHDP1=           67.99 / Temp. of the shield A (K)                  %6.2f
Q_SHDP2=           67.99 / Temp. of the shield B (K)                  %6.2f
Q_ABTP1=           300.14 / Temperature of Ambient thermometer (K)    %6.2f
Q_ABTP2=           350.32 / Temperature of Ambient thermometer (K)    %6.2f
Q_ABTP3=           280.41 / Temperature of Ambient thermometer (K)    %6.2f
COMMENT ++++++ Detector Drive
Q_CLKVER= 'Q_CLK0001-990701' / Clock version                        %30s
Q_CLKFL = 'Q_031_022_039_001_010' / Clock macro file name          %30s
Q_CLKMCC= 'This is preliminary clk' / Coment on clock pattern macro  %30s
Q_CLKNM = 'GETRAW' / Clock pattern name                             %30s
Q_CLKCLC= 'Not coadded' / Coment on each clock pattern              %30s
Q_PIXTIM=           5.00 / Clock duration for a pixel (microsec)      %6.2f
Q_FRRATE=          40.0000 / Detector Framerate (Hz)                 %8.4f
Q_READTM=          0.02500000 / Time for reading out 1 exp (sec)      %12.8f
Q_NDRATE=           100 / N.D. rate of the detector (1/243)           %3d
Q_NDEFF =           0.41142300 / efficiency of the integ by using N.D. %10.8f
COMMENT ++++++ Chopping and Nodding
Q_CHOP = 'on' / Chopping on/off                                      %8s
Q_CPWTP = 'on' / Tip-tilt with chopping on/off                       %8s
Q_CPBMS1= 'origin' / Chopping beam at the 1st exp.                  %16s
Q_CPFREQ=           2.5000 / Chopping Frequency (Hz)                 %8.4f
Q_CPTIME=           0.200000 / Chopping period per 1 beam (sec)       %10.6f
Q_CPEXP =           8 / Number of exp of 1 chopping beam             %d
Q_CPEXAD=           1 / Number of coadded exp.                       %d
Q_CPFRA1=           7 / Number of frame of 1 chopping beam           %d
Q_CPNUM =           120 / Number of chopping in this file            %d
Q_INT1BM=          21.000000 / Integration time per 1 position (sec)   %6f
Q_CPTH1W=           90.0000 / Chopping throw (arcsec)                 %10.4f
Q_CPPA =           0.0000 / Chopping P.A. (deg)                     %8.4f
Q_ND1TME=           10.00 / Nodding period (sec)                     %2f
Q_NDOFRA=           20.0000 / Nodding offset R.A. (arcsec)           %10.4f
Q_NDOFDE=           -10.8 / Nodding offset Dec (arcsec)               %8.4f
Q_NDBEM = 'main' / Nodding Beam main/offset                         %12s
Q_NDCOM = 'Normal 2beam nodding' / Comment about Nodding             %30s
END

```

● COMICS の Spectroscopy mode

```

1      2      3      4      5      6      7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE =          T / Standard FITS format
BITPIX =          32 / # of bits storing pix values
NAXIS =           4 / # of axis in frame                                %1d
NAXIS1 =          336 / # of pixels/row                                %5d

```

```

NAXIS2 = 240 / # of rows %5d
NAXIS3 = 5 / # of detectors %5d
NAXIS4 = 10 / # of frames %5d
EXTEND = F / ASCII Table for Z-frame description %c
COMMENT ++++++ ???
DATASET = 'DSET-COMICS-123456' / Dataset Identification Number %20s
FRAMEID = 'COM1234567890123' / FITS File sequential number %16s
EXP-ID = 'COME123456789012' / ID of the exposure this data was takenA %16s
OBS-ALOC = ' ' / Allocation Mode for Instrument %12s
COMMENT ++++++ Observatory/Instrument
OBSERVER= 'Ktz,Ymst,Myt,Okmt' / Name of observers %64s
PROP-ID = 'P1999-0709-1' / Proposal ID %20s
OBSERVAT= 'NAOJ' / Observatory %30s
TELESCOP= 'Subaru' / Telescope name %30s
INSTRUME= 'COMICS' / Name of instrument %20s
INS-VER = '1.0.0 assembled 990701' / Version of the instrument %30s
DETECTOR= 'Si:As IBC 320x240 x6' / Name of the detector/CCD %10s
DET-ID = 1 / ID of the detector used for this data %d
COMMENT ++++++ Fixed Parameters in COMICS data (spec)
DETPXSZ1= 0.0500 / Detector pixel size in axis1 (mm) %.4f
DETPXSZ2= 0.0500 / Detector pixel size in axis2 (mm) %.4f
CDEL11 = 0.00004583 / X Scale projected on detector(#/pix) %13.8f
CDEL12 = 0.00004583 / Y scale projected on detector(#/pix) %13.8f
CTYPE1 = 'RA---TAN' / Pixel coordinate system %16s
CTYPE2 = 'DEC--TAN' / Pixel coordinate system %16s
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDEL11 %10s
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDEL12 %10s
CRPIX1 = 160.0 / Reference pixel in X (pixel) %-6.1f
CRPIX2 = 120.0 / Reference pixel in Y (pixel) %-6.1f
PROJP1 = 0.0 / Projection type of the first axis %5.1f
PROJP2 = 0.0 / Projection type of the second axis %5.1f
PC001001= 1.00000000 / Pixel Coordinate translation matrix %12.8f
PC001002= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002001= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002002= 1.00000000 / Pixel Coordinate translation matrix %12.8f
BSCALE = 1.0 / Real=fits-value*BSCALE+BZERO %.1f
BZERO = 0.0 / Real=fits-value*BSCALE+BZERO %.1f
BUNIT = 'ADU' / Unit of original pixel values %30s
BLANK = 32768 / Value used for NULL pixels %d
COMMENT ++++++ Date
TIMESYS = 'UTC' / Time System used in the header. UTC fix. %8s
DATE-OBS= '1999-07-09' / yyyy-mm-dd UTC obs start date %10s
UT = '09:12:00.0' / HH:MM:SS.S UTC at typical time(=start) %10s
HST = '23:12:00.0' / HH:MM:SS.S HST at typical time(=start) %10s
LST = '12:34:56.789' / HH:MM:SS.S LST at typical time(=start) %12s
MJD = 12345.67890123 / Modified Julian Day at typ time(=start) %14.8f
COMMENT ++++++ Object
DATA-TYP= 'OBJECT' / Type / Characteristics of this data %15s
RADECSYS= 'FK5' / The equatorial coordinate system %8s
OBJECT = 'HR 4796' / Target Description %30s
EQUINOX = 2000.0 / Standard FK5 year %6.1f
RA = '12:36:01.270' / HH:MM:SS.SSS RA (J2000) pointing %12s
RA2000 = '12:36:01.270' / HH:MM:SS.SSS RA (J2000) pointing %12s
DEC = '-39:52:09.40' / +/-DD:MM:SS.SS DEC (J2000) pointing %12s
DEC2000 = '-39:52:09.40' / +/-DD:MM:SS.SS DEC (J2000) pointing %12s
AZIMUTH = 12.34000 / Azimuth of telescope pointing (degree) %9.5f
ALTITUDE= 12.34000 / Altitude of telescope pointing(degree) %8.5f
CRVAL1 = 189.00529167 / Physical value of the reference pixel X %13.8f
CRVAL2 = -39.86927778 / Physical value of the reference pixel Y %13.8f
AIRMASS = 1.23456 / Averaged Air Mass %9.5f
ZD = 77.66000 / Zenith Distance at typical time %8.5f
SECZ = 1.234 / SEC(Zenith Distance) at typical time %6.3f
LONGPOLE= 180.0 / The North Pole of standard system (deg) %6.1f
COMMENT ++++++ Subaru Parameters
FOC-POS = 'Cassegrain' / Focus where the instrument is attached %12s
TELFOCUS= 'Cassegrain' / Focus where a beam is reachable %30s
FOC-LEN = 100000.000 / Focal length of the telescope (mm) %.3f
FOC-VAL = 2.531 / Encoder value of the focus unit (mm) %10.3f
INSROT = 12.345 / Instrument Rotator angle (deg) %-8.3f
AUTOGUID= 'off' / Auto Guider on/off %8s
M2-TYPE = 'IR' / Type of the Secondary Mirror (Opt/IR) %8s
M2-TIP = 'on' / 2nd Mirror tip-tilt on/off %8s
COMMENT ++++++ COMICS Parameters OPTICS
OBS-MOD = 'spectroscopy' / Observation Mode %20s
FILTER01= 'Through' / Filter name/ID (pre-opt filter-1) %30s
FILTER02= 'Nwide' / Filter name/ID (pre-opt filter-2) %30s
FILTER03= '12um' / Filter name/ID (img-opt filter) %30s
FILTER04= 'N-obj' / Lens name/ID (img-opt) %30s
DISPERSR= 'N-mid grt' / Identifier of the disperser used %10s
SLIT = '0.33arcsec' / Identifier of the entrance slit used %10s
SLT-LEN = 39.600 / Length of the slit used (arcsec) %7.3f
SLT-PA = 0.0 / Slit Position Angle (degree) %5.1f
SLT-WID = 0.3300 / Width of the slit used %6.3f
SLTCPIX1= 160.0 / Slit center projected on detector(pix) %6.1f

```

```

SLTCPIX2=          120.0 / Slit center projected on detector(pix)    %6.1f
DISPAXIS=          1 / Dispersion Axis in frame                    %1d
WAV-MIN =         7510.0000 / Shortest wavelen. focused on det (nm) %10.4f
WAV-MAX =         13500.0000 / Longest wavelen. focused on det (nm) %10.4f
WAVELEN =         10505.0000 / Wavelength at center (nm)           %10.4f
COMMENT ++++++ COMICS Parameters DETECTOR
EXPTIME =          0.080 / Total integration time per frame(sec)    %7.3f
DET-TMP =          6.01 / Detector temperature (K)                 %6.2f
GAIN =           330.90 / AD conversion factor (electron/ADU)       %5.2f
PRD-MIN1=          1 / Start X pos. of partial read out (pix)      %d
PRD-MIN2=          1 / Start Y pos. of partial read out (pix)      %d
PRD-RNG1=          320 / X Range of partial read out (pix)         %d
PRD-RNG2=          240 / Y Range of partial read out (pix)         %d
BIN-FCT1=          1 / Binning factor of X axis (pixel)           %2d
BIN-FCT2=          1 / Binning factor of Y axis (pixel)           %2d
COMMENT ++++++ Condition at the observation
WEATHER = 'rainstorm' / Weather condition                          %30s
SEEING =           0.45 / Long integ PSF FWHM (arcsec)             %2f
DOM-WND =          4.61 / Wind speed in the dome (m/s)             %5.2f
OUT-WND =          7.79 / Wind speed outside (m/s)                 %5.2f
DOM-TMP =          273.51 / Temperature measured in the dome (K)   %6.2f
OUT-TMP =          273.72 / Temperature measured outside dome (K) %6.2f
DOM-HUM =          90.1 / Humidity measured in the dome            %5.1f
OUT-HUM =          101.1 / Humidity measured outside the dome      %5.1f
DOM-PRS =          670.00 / Atmospheric pressure in the Dome (hpa) %7.2f
OUT-PRS =          670.00 / Atmospheric pressure outside dome (hPa) %7.2f
COMMENT -----
COMMENT Subaru Device Dependent Header Block for COMICS
COMMENT -----
COMMENT 'Q_' provisionally means COMICS header
COMMENT -----
COMMENT ++++++ Type of this data
Q_DTYPE = 'slitview' / type of this file spec/img/slitview        %10s
Q_OBSID =          12345678 / Observation ID of COMICS              %8d
COMMENT ++++++ Pre-Optics
Q_WINDOW= 'Ge10um' / Entrance Window                              %10s
Q_M1MOTA=          224 / Pulse count of 1st mir. para to bench      %8d
Q_M1MOTB=          339 / Pulse count of 1st mir. vert to bench     %8d
COMMENT ++++++ Slit Viewer/Imager
Q_SLTVEW= 'on' / Slit Viewer on/off                                %8s
Q_SVFILE= 'COMA00000002' / Image file name obtained slit viewer   %12s
Q_SVWMIN=          11650.0000 / Observed Wavelength of S Viewer min(nm) %10.4f
Q_SVWMAX=          12490.0000 / Observed Wavelength of S Viewer max(nm) %10.4f
COMMENT ++++++ Spectrometer
Q_GRTMOT=          330843 / Pulse count of grating motor           %d
Q_GRTANG=          0.123456 / Grating Tilt Angle (deg)             %10.6f
Q_WVMIN1=          7510.0000 / Observed Wavelen of Spec Det-1 min (nm) %10.4f
Q_WVMAX1=          8510.0000 / Observed Wavelen of Spec Det-1 max (nm) %10.4f
Q_WVMIN2=          9010.0000 / Observed Wavelen of Spec Det-2 min (nm) %10.4f
Q_WVMAX2=          9510.0000 / Observed Wavelen of Spec Det-2 max (nm) %10.4f
Q_WVMIN3=          10000.0000 / Observed Wavelen of Spec Det-3 min (nm) %10.4f
Q_WVMAX3=          10900.0000 / Observed Wavelen of Spec Det-3 max (nm) %10.4f
Q_WVMIN4=          11500.0000 / Observed Wavelen of Spec Det-4 min (nm) %10.4f
Q_WVMAX4=          12200.0000 / Observed Wavelen of Spec Det-4 max (nm) %10.4f
Q_WVMIN5=          12800.0000 / Observed Wavelen of Spec Det-5 min (nm) %10.4f
Q_WVMAX5=          13500.0000 / Observed Wavelen of Spec Det-5 max (nm) %10.4f
COMMENT ++++++ Temperature
Q_DETP1=          4.95000 / Temperature of the detector spec-1 (K) %10.5f
Q_DETP2=          4.85000 / Temperature of the detector spec-2 (K) %10.5f
Q_DETP3=          4.95000 / Temperature of the detector spec-3 (K) %10.5f
Q_DETP4=          4.88000 / Temperature of the detector spec-4 (K) %10.5f
Q_DETP5=          4.95000 / Temperature of the detector spec-5 (K) %10.5f
Q_DETP6=          6.95000 / Temperature of the detector img (K)    %10.5f
Q_CFTP1 =          4.22 / Temp. of the cooled finger spec (K)      %6.2f
Q_CFTP2 =          3.99 / Temp. of the cooled finger img (K)      %6.2f
Q_OPTTP1=          30.00 / Temp. of the optics spec-A (K)         %6.2f
Q_OPTTP2=          30.00 / Temp. of the optics spec-B (K)         %6.2f
Q_OPTTP3=          30.00 / Temp. of the optics spec-C (K)         %6.2f
Q_OPTTP4=          30.00 / Temp. of the optics img-A (K)          %6.2f
Q_OPTTP5=          30.00 / Temp. of the optics img-A (K)          %6.2f
Q_OPTTP6=          30.00 / Temp. of the optics img-A (K)          %6.2f
Q_COHTP1=          3.99 / Temp. of the cooler head spec (K)       %6.2f
Q_COHTP2=          3.89 / Temp. of the cooler head img (K)        %6.2f
Q_SHDTP1=          67.99 / Temp. of the shield A (K)              %6.2f
Q_SHDTP2=          67.99 / Temp. of the shield B (K)              %6.2f
Q_ABTP1=          300.14 / Temperature of Ambient thermometer (K) %6.2f
Q_ABTP2=          350.32 / Temperature of Ambient thermometer (K) %6.2f
Q_ABTP3=          280.41 / Temperature of Ambient thermometer (K) %6.2f
COMMENT ++++++ Detector Drive
Q_CLKVER= 'Q_CLK0001-990701' / Clock version                      %30s
Q_CLKFL = 'Q_031_022_039_001_010' / Clock macro file name        %30s
Q_CLKMCC= 'This is preliminary clk' / Coment on clock pattern macro %30s
Q_CLKNM = 'GETRAW' / Clock pattern name                            %30s

```

```

Q_CLKCLC= 'Not coadded' , / Coment on each clock pattern %30s
Q_PIXTIM= 5.00 / Clock duration for a pixel (microsec) %6.2f
Q_FRRATE= 40.0000 / Detector Framerate (Hz) %8.4f
Q_READTM= 0.02500000 / Time for reading out 1 exp (sec) %12.8f
Q_NDRATE= 100 / N.D. rate of the detector (1/243) %3d
Q_NDEFF= 0.41142300 / efficiency of the integ by using N.D. %10.8f
COMMENT ++++++ Chopping and Nodding
Q_CHOP = 'on' , / Chopping on/off %8s
Q_CPWTP = 'on' , / Tip-tilt with chopping on/off %8s
Q_CPBMS= 'origin' , / Chopping beam at the 1st exp. %16s
Q_CPFREQ= 2.5000 / Chopping Frequency (Hz) %8.4f
Q_CPTIME= 0.200000 / Chopping period per 1 beam (sec) %10.6f
Q_CPEXP = 8 / Number of exp of 1 chopping beam %d
Q_CPEXAD= 1 / Number of coadded exp. %d
Q_CPFRA= 7 / Number of frame of 1 chopping beam %d
Q_CPNUM = 120 / Number of chopping in this file %d
Q_INT1BM= 21.000000 / Integration time per 1 position (sec) %6.2f
Q_CPTHRW= 90.0000 / Chopping throw (arcsec) %10.4f
Q_CPPA = 0.0000 / Chopping P.A. (deg) %8.4f
Q_NDIME= 10.00 / Nodding period (sec) %6.2f
Q_NDOFRA= 20.0000 / Nodding offset R.A. (arcsec) %10.4f
Q_NDOFDE= -10.8 / Nodding offset Dec (arcsec) %8.4f
Q_NDBEM = 'main' , / Nodding Beam main/offset %12s
Q_NDCOM = 'Normal 2beam nodding' , / Comment about Nodding %30s
END

```

6.5.3 FOCAS(1998/09/08)

● FOCAS の Imaging mode

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / Standard FITS format
BITPIX = 16 / # of bits storing pix value
NAXIS = 2 / # of axes in frame
NAXIS1 = 4096 / # of pixels/row
NAXIS2 = 2048 / # of rows (also # of scan lines)
EXTEND = T / Extension FITS format
OBSERVER= 'Y.Yadoumaru, K.Aoki, T.Ozawa, night-staff and WG' / Name of observer
PROP-ID = 'P19970025-0001' / Proposal ID
INSTRUME= 'FOCAS' / Name of instrument
FRAMEID = 'FSCA000023471234' / Image sequential number
EXP-ID = 'FSCE000011741234' / ID of the exposure this data was taken
OBS-MOD = 'Imaging' / Observation Mode
DATA-TYP= 'OBJECT' / Type / Characteristics of this data
OBSERVAT= 'NAOJ' / Observatory
TELESCOP= 'SUBARU' / Telescope name
TIMESYS = 'UTC' / Time System used in the header. UTC fix.
RADECSYS= 'FK5' / The equatorial coordinate system
OBS-ALOC= 'OBSEVING' / Allocation mode for Instrument
DATASET = 'FOCAS-12345' / ID of an observation dataset
WCS-ORIG= 'SUBARU toolkit' / Origin of the WCS value
CRPIX1 = +2048.0 / Reference pixel in X
CRPIX2 = +1024.0 / Reference pixel in Y
CRVAL1 = +0.275108E+03 / Physical value of the reference pixel X
CRVAL2 = -0.161769E+02 / Physical value of the reference pixel Y
CDELT1 = +0.277778E-04 / Size projected into a detector pixel X
CDELT2 = +0.277778E-04 / Size projected into a detector pixel Y
CTYPE1 = 'RA---TAN' / Pixel coordinate system
CTYPE2 = 'DEC--TAN' / Pixel coordinate system
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDELT1
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDELT2
LONGPOLE= 180.00000 / The North Pole of the standard system
PC001001= +0.100000E+01 / Pixel Coordinate translation matrix
PC001002= +0.000000E+00 / Pixel Coordinate translation matrix
PC002001= +0.100000E+01 / Pixel Coordinate translation matrix
PC002002= +0.000000E+00 / Pixel Coordinate translation matrix
COMMENT
C2PIX1 = +2048.0 / Reference pixel in X
C2PIX2 = +1024.0 / Reference pixel in Y
C2VAL1 = +0.275108E+03 / Physical value of ref pix X for WCS
C2VAL2 = -0.161769E+02 / Physical value of ref pix Y for WCS
C2ELT1 = +0.277778E-04 / Size projected into a detector pixel X
C2ELT2 = +0.277778E-04 / Size projected into a detector pixel Y
C2YPE1 = 'RA---TAN' / Pixel coordinate system
C2YPE2 = 'DEC--TAN' / Pixel coordinate system
C2NIT1 = 'degree' / Units used in both C2VAL1 and C2ELT1
C2NIT2 = 'degree' / Units used in both C2VAL2 and C2ELT2
BSCALE = 1.0 / Real=fits_value*BSCALE+BZERO

```

```

BZERO      =      32768.0 / Real=fits_value*BSCALE+BZERO
BUNIT      = 'ADU      ' / Unit of original pixel values
BLANK      =     -32768 / Value used for NULL pixels
DATE-OBS= '1998-05-06' / Observation start date (yyyy-mm-dd)
UT         = '12:34:56.78' / HH:MM:SS.SS typical UTC at exposure
UT-STR     = '12:34:56.78' / HH:MM:SS.SS UTC at exposure start
UT-END     = '13:04:56.78' / HH:MM:SS.SS UTC at exposure end
HST        = '02:34:56.78' / HH:MM:SS.SS typical HST at exposure
HST-STR    = '02:34:56.78' / HH:MM:SS.SS HST at exposure start
HST-END    = '03:04:56.78' / HH:MM:SS.SS HST at exposure end
LST        = '23:53:10.67' / HH:MM:SS.SS typical LST at exposure
LST-STR    = '23:53:10.67' / HH:MM:SS.SS LST at exposure start
LST-END    = '24:23:20.63' / HH:MM:SS.SS LST at exposure end
MJD        =      50396.52420000 / Modified Julian Day at typical time
MJD-STR    =      50396.52420000 / Modified Julian Day at exposure start
MJD-END    =      50396.54500000 / Modified Julian Day at exposure end
EXPTIME    =      1800.00 / Total integration time (sec)
OBJECT     = 'M17      ' / Target Description
RA         = '18:20:26.010' / RA of telescope pointing (HH:MM:SS.SSS)
RA2000    = '18:20:26.010' / RA (J2000) pointing (HH:MM:SS.SSS)
DEC        = '-16:12:07.1' / DEC of telescope pointing (+/-DD:MM:SS.SS)
DEC2000    = '-16:12:07.1' / DEC (J2000) pointing (+/-DD:MM:SS.SS)
EQUINOX    =      2000.0 / Standard FK5 (years)
AZIMUTH    =     -16.625000 / Azimuth angle of telescope pointing (degree), S
ALTITUDE=      36.47000 / Altitude angle of telescope pointing (degree)
TELCAS= 'CASSEGRAIN' / Focus where a beam is reachable
FOC-POS    = 'CASSEGRAIN' / Focus where the instrument is attached
FOC-VAL    =      +2.513 / Encoder value of the focus unit
F-RATIO    =      12.2 / F-ratio of each telescope-focus.
ADC-TYPE= 'RED      ' / ADC name if used
ADC        =      +21.123 / ADC PA during exposure (degree)
ADC-STR    =      +19.059 / ADC PA at exposure start (degree)
ADC-END    =      +25.897 / ADC PA at exposure end (degree)
FILTER01= 'NONE     ' / Filter name/ID
FILTER02= 'NONE     ' / Filter name/ID
FILTER03= 'NONE     ' / Filter name/ID
FLT-A01    =      5.00 / Inclination of n-th Filter (degree)
FLT-A02    =      5.00 / Inclination of n-th Filter (degree)
FLT-A03    =      5.00 / Inclination of n-th Filter (degree)
AIRMASS    =      1.24 / Averaged Air Mass
AIRM-STR=      1.21 / Air Mass at exposure start
AIRM-END=      1.28 / Air Mass at exposure end
ZD         =      36.47 / Zenith Distance at typical time (degree)
ZD-STR     =      34.28 / Zenith Distance at exposure start (degree)
ZD-END     =      38.63 / Zenith Distance at exposure end (degree)
SECZ       =      1.243 / SEC(Zenith Distance) at typical time
SECZ-STR   =      1.210 / SEC(ZD) at exposure start
SECZ-END   =      1.280 / SEC(ZD) at exposure end
DAQ-VER    = 'DAQ-1.0.3' / Version of the DAQ-soft
INS-VER    = 'FCS-1.2-1.0' / Version of the instrument/control-soft
DETECTOR= 'MIT_001 ' / Name of the detector/CCD
DET-ID     =      1 / ID of the detector used for this data
DET-A01    =      0.000 / Relative angle of the nn-th detector (degree)
DET-P101=     -103.5 / Relative X-Position of nn-th detector (nm)
DET-P201=      12.5 / Relative Y-Position of nn-th detector (nm)
DET-TMP    =     132.50 / Detector temperature (K)
DET-TMED=     132.50 / Median of the detector temperature (K)
DET-TMIN=     132.40 / Minimum temperature of the detector (K)
DET-TMAX=     132.55 / Maximum temperature of the detector (K)
GAIN       =      1.26 / AD conversion factor (electron/ADU)
EFP-MIN1=      10 / Start X position of effective data region
EFP-MIN2=      10 / Start Y position of effective data region
EFP-RNG1=     4046 / X range of effective data region
EFP-RNG2=     2028 / Y range of effective data region
PRD-MIN1=      1 / Start X position of partially read out
PRD-MIN2=      1 / Start Y position of partially read out
PRD-RNG1=     4096 / X range of the partially read out
PRD-RNG2=     2048 / Y range of the partially read out
BIN-FCT1=      1 / Binning factor of X axis
BIN-FCT2=      1 / Binning factor of Y axis
WEATHER    = 'CLEAR   ' / Weather condition (selected by observer)
SEEING     =      0.45 / FWHM of star size at telescope focus (arcsec)
DOM-WND    =      4.61 / Wind speed in the dome (m/sec)
OUT-WND    =      7.79 / Wind speed outside the dome (m/sec)
DOM-TMP    =     273.53 / Temperature in the dome (K)
OUT-TMP    =     273.72 / Temperature outside the dome (K)
DOM-HUM    =      45.00 / Humidity in the dome (%)
OUT-HUM    =      58.00 / Humidity outside the dome (%)
SLIT       = 'LONGSLIT' / Identifier of the entrance slit used
COMMENT --- Subaru Device Dependent Header Block for FOCAS ---
F_TMP-A    =     275.33 / Temperature of MOS unit (K)
F_TMP-B    =     272.45 / Temperature of lens unit (K)
F_TMP-C1=     272.15 / Temperature of collimator beam unit-1 (K)
F_TMP-C2=     272.20 / Temperature of collimator beam unit-2 (K)

```

```

F_TMP-C3=      272.10 / Temperature of collimator beam unit-3 (K)
F_TMP-D =      273.29 / Temperature of Camera lens unit (K)
F_TMP-E1=      275.29 / Temperature of VME-1 (K)
F_TMP-E2=      275.30 / Temperature of VME-2 (K)
F_TMP-F1=      275.31 / Temperature of driver-unit A-1 (K)
F_TMP-F2=      275.28 / Temperature of driver-unit A-2 (K)
F_TMP-G1=      275.29 / Temperature of driver-unit B-1 (K)
F_TMP-G2=      275.27 / Temperature of driver-unit B-2 (K)
F_TMP-H1=      275.29 / Temperature of driver-unit C-1 (K)
F_TMP-H2=      275.27 / Temperature of driver-unit C-2 (K)
F_TMP-I1=      275.35 / Temperature of driver-unit D-1 (K)
F_TMP-I2=      275.38 / Temperature of driver-unit D-2 (K)
F_TMP-J1=      275.25 / Temperature of driver-unit E-1 (K)
F_TMP-J2=      275.22 / Temperature of driver-unit E-2 (K)
F_DEWERY=      27.00 / X-position of dewer stage (micron meter)
F_DEWERY=      10.00 / Y-position of dewer stage (micron meter)
F_DEWERY=      152.94 / Z-position of dewer stage (micron meter)
F_HOLANG=      -5.2 / angle of mask holder (degree)
F_MSK-ID= 'MSK300151' / ID of Mask (for all mode)
F_CAD-ID= 'CAD005235' / ID of CAD data for mask cutting
F_CADREF= 'FSCA00002345' / ID/name of image/catalog data for mask design
F_SLT-NO=      3 / total # of slit on mask
F_POSANG=      0.00 / PA of cross-dispersion axis (degree)
END

```

● FOCAS の ImagingPolarimetry mode

```

1      2      3      4      5      6      7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE =          T / Standard FITS format
BITPIX =          16 / # of bits storing pix value
NAXIS =           2 / # of axes in frame
NAXIS1 =          4096 / # of pixels/row
NAXIS2 =          2048 / # of rows (also # of scan lines)
EXTEND =          T / Extension FITS format
OBSERVER= 'Y.Yadoumaru, K.Aoki, T.Ozawa, night-staff and WG' / Name of observer
PROP-ID = 'P19970025-0001' / Proposal ID
INSTRUME= 'FOCAS' / Name of instrument
FRAMEID = 'FSCA000023471234' / Image sequential number
EXP-ID = 'FSCE000011741234' / ID of the exposure this data was taken
OBS-MOD = 'Imaging-Polarimetry' / Observation Mode
DATA-TYP= 'OBJECT' / Type / Characteristics of this data
OBSERVAT= 'NAOJ' / Observatory
TELESCOP= 'SUBARU' / Telescope name
TIMESYS = 'UTC' / Time System used in the header. UTC fix.
RADECSYS= 'FK5' / The equatorial coordinate system
OBS-ALOC= 'OBSEVING' / Allocation mode for Instrument
DATASET = 'FOCAS-12345' / ID of an observation dataset
WCS-ORIG= 'SUBARU toolkit' / Origin of the WCS value
CRPIX1 = +2048.0 / Reference pixel in X
CRPIX2 = +1024.0 / Reference pixel in Y
CRVAL1 = +0.275108E+03 / Physical value of the reference pixel X
CRVAL2 = -0.161769E+02 / Physical value of the reference pixel Y
CDELT1 = +0.277778E-04 / Size projected into a detector pixel X
CDELT2 = +0.277778E-04 / Size projected into a detector pixel Y
CTYPE1 = 'RA---TAN' / Pixel coordinate system
CTYPE2 = 'DEC--TAN' / Pixel coordinate system
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDELT1
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDELT2
LONGPOLE= 180.00000 / The North Pole of the standard system
COMMENT
C2PIX1 = +2048.0 / Reference pixel in X
C2PIX2 = +1024.0 / Reference pixel in Y
C2VAL1 = +0.275108E+03 / Physical value of ref pix X for WCS
C2VAL2 = -0.161769E+02 / Physical value of ref pix Y for WCS
C2ELT1 = +0.277778E-04 / Size projected into a detector pixel X
C2ELT2 = +0.277778E-04 / Size projected into a detector pixel Y
C2YPE1 = 'RA---TAN' / Pixel coordinate system
C2YPE2 = 'DEC--TAN' / Pixel coordinate system
C2NIT1 = 'degree' / Units used in both C2VAL1 and C2ELT1
C2NIT2 = 'degree' / Units used in both C2VAL2 and C2ELT2
C3PIX1 = +2048.0 / Reference pixel in X for Ordinary light
C3PIX2 = +1124.0 / Reference pixel in Y for Ordinary light
C3VAL1 = +0.275108E+03 / Physical value of ref pix X for Ordinary light
C3VAL2 = -0.161769E+02 / Physical value of ref. pix Y for Ordinary light
C3ELT1 = +0.277778E-04 / Size projected into a detector X for Ordinary
C3ELT2 = +0.277778E-04 / Size projected into a detector Y for Ordinary
C3YPE1 = 'RA---TAN' / Pixel coordinate system for Ordinary light
C3YPE2 = 'DEC--TAN' / Pixel coordinate system for Ordinary light
C3NIT1 = 'degree' / Units in both C3VAL1 and C3ELT1 for Ordinary
C3NIT2 = 'degree' / Units in both C3VAL2 and C3ELT2 for Ordinary

```

```

C4PIX1 = +2048.0 / Reference pixel in X for Extraordinary light
C4PIX2 = +924.0 / Reference pixel in Y for Extraordinary light
C4VAL2 = -0.161769E+02 / Physical value of ref. pix Y for Extraordinary
C4ELT1 = +0.277778E-04 / Size projected into a detector X for E-light
C4ELT2 = +0.277778E-04 / Size projected into a detector Y for E-light
C4YPE1 = 'RA---TAN' / Pixel coordinate system for Extraordinary light
C4YPE2 = 'DEC--TAN' / Pixel coordinate system for Extraordinary light
C4NIT1 = 'degree' / Units in both C4VAL1 and C4ELT1 for E-light
C4NIT2 = 'degree' / Units in both C4VAL2 and C4ELT2 for E-light
BSCALE = 1.0 / Real=fits_value*BSCALE+BZERO
BZERO = 32768.0 / Real=fits_value*BSCALE+BZERO
BUNIT = 'ADU' / Unit of original pixel values
BLANK = -32768 / Value used for NULL pixels
DATE-OBS= '1998-05-06' / Observation start date (yyyy-mm-dd)
UT = '12:34:56.78' / HH:MM:SS.SS typical UTC at exposure
UT-STR = '12:34:56.78' / HH:MM:SS.SS UTC at exposure start
UT-END = '13:04:56.78' / HH:MM:SS.SS UTC at exposure end
HST = '02:34:56.78' / HH:MM:SS.SS typical HST at exposure
HST-STR = '02:34:56.78' / HH:MM:SS.SS HST at exposure start
HST-END = '03:04:56.78' / HH:MM:SS.SS HST at exposure end
LST = '23:53:10.67' / HH:MM:SS.SS typical LST at exposure
LST-STR = '23:53:10.67' / HH:MM:SS.SS LST at exposure start
LST-END = '24:23:20.63' / HH:MM:SS.SS LST at exposure end
MJD = 50396.52420000 / Modified Julian Day at typical time
MJD-STR = 50396.52420000 / Modified Julian Day at exposure start
MJD-END = 50396.54500000 / Modified Julian Day at exposure end
EXPTIME = 1800.00 / Total integration time (sec)
OBJECT = 'M17' / Target Description
RA = '18:20:26.010' / RA of telescope pointing (HH:MM:SS.SSS)
RA2000 = '18:20:26.010' / RA (J2000) pointing (HH:MM:SS.SSS)
DEC = '-16:12:07.1' / DEC of telescope pointing (+/-DD:MM:SS.SS)
DEC2000 = '-16:12:07.1' / DEC (J2000) pointing (+/-DD:MM:SS.SS)
EQUINOX = 2000.0 / Standard FK5 (years)
AZIMUTH = -16.625000 / Azimuth angle of telescope pointing (degree), S
ALTITUDE= 36.47000 / Altitude angle of telescope pointing (degree)
TELFOCAS= 'CASSEGRAIN' / Focus where a beam is reachable
FOC-POS = 'CASSEGRAIN' / Focus where the instrument is attached
FOC-VAL = +2.513 / Encoder value of the focus unit
F-RATIO = 12.2 / F-ratio of each telescope-focus.
ADC-TYPE= 'RED' / ADC name if used
ADC = +21.123 / ADC PA during exposure (degree)
ADC-STR = +19.059 / ADC PA at exposure start (degree)
ADC-END = +25.897 / ADC PA at exposure end (degree)
WAVELEN = 600.00 / Typical wavelength on detector (nm)
RETPLAT1= '1/2' / Identifier of the Retarder Plate
RET-ANG = 45.0000 / Position Angle of the Retarder Plate
FILTER01= 'NONE' / Filter name/ID
FILTER02= 'NONE' / Filter name/ID
FILTER03= 'NONE' / Filter name/ID
FLT-A01 = 5.00 / Inclination of n-th Filter (degree)
FLT-A02 = 5.00 / Inclination of n-th Filter (degree)
FLT-A03 = 5.00 / Inclination of n-th Filter (degree)
AIRMASS = 1.24 / Averaged Air Mass
AIRM-STR= 1.21 / Air Mass at exposure start
AIRM-END= 1.28 / Air Mass at exposure end
ZD = 36.47 / Zenith Distance at typical time (degree)
ZD-STR = 34.28 / Zenith Distance at exposure start (degree)
ZD-END = 38.63 / Zenith Distance at exposure end (degree)
SECZ = 1.243 / SEC(Zenith Distance) at typical time
SECZ-STR= 1.210 / SEC(ZD) at exposure start
SECZ-END= 1.280 / SEC(ZD) at exposure end
DAQ-VER = 'DAQ-1.0.3' / Version of the DAQ-soft
INS-VER = 'FCS-1.2-1.0' / Version of the instrument/control-soft
DETECTOR= 'MIT_001' / Name of the detector/CCD
DET-ID = 1 / ID of the detector used for this data
DET-A01 = 0.000 / Relative angle of the nn-th detector (degree)
DET-P101= -103.5 / Relative X-Position of nn-th detector (nm)
DET-P201= 12.5 / Relative Y-Position of nn-th detector (nm)
DET-TMP = 132.50 / Detector temperature (K)
DET-TMED= 132.50 / Median of the detector temperature (K)
DET-TMIN= 132.40 / Minimum temperature of the detector (K)
DET-TMAX= 132.55 / Maximum temperature of the detector (K)
GAIN = 1.26 / AD conversion factor (electron/ADU)
EFP-MIN1= 10 / Start X position of effective data region
EFP-MIN2= 10 / Start Y position of effective data region
EFP-RNG1= 4046 / X range of effective data region
EFP-RNG2= 2028 / Y range of effective data region
PRD-MIN1= 1 / Start X position of partially read out
PRD-MIN2= 1 / Start Y position of partially read out
PRD-RNG1= 4096 / X range of the partially read out
PRD-RNG2= 2048 / Y range of the partially read out
BIN-FCT1= 1 / Binning factor of X axis
BIN-FCT2= 1 / Binning factor of Y axis
WEATHER = 'CLEAR' / Weather condition (selected by observer)

```

```

SEEING = 0.45 / FWHM of star size at telescope focus (arcsec)
DOM-WND = 4.61 / Wind speed in the dome (m/sec)
OUT-WND = 7.79 / Wind speed outside the dome (m/sec)
DOM-TMP = 273.53 / Temperature in the dome (K)
OUT-TMP = 273.72 / Temperature outside the dome (K)
DOM-HUM = 45.00 / Humidity in the dome (%)
OUT-HUM = 58.00 / Humidity outside the dome (%)
SLIT = 'LONGSLIT' / Identifier of the entrance slit used
COMMENT --- Subaru Device Dependent Header Block for FOCAS ---
F_TMP-A = 275.33 / Temperature of MOS unit (K)
F_TMP-B = 272.45 / Temperature of lens unit (K)
F_TMP-C1= 272.15 / Temperature of collimator beam unit-1 (K)
F_TMP-C2= 272.20 / Temperature of collimator beam unit-2 (K)
F_TMP-C3= 272.10 / Temperature of collimator beam unit-3 (K)
F_TMP-D = 273.29 / Temperature of Camera lens unit (K)
F_TMP-E1= 275.29 / Temperature of VME-1 (K)
F_TMP-E2= 275.30 / Temperature of VME-2 (K)
F_TMP-F1= 275.31 / Temperature of driver-unit A-1 (K)
F_TMP-F2= 275.28 / Temperature of driver-unit A-2 (K)
F_TMP-G1= 275.29 / Temperature of driver-unit B-1 (K)
F_TMP-G2= 275.27 / Temperature of driver-unit B-2 (K)
F_TMP-H1= 275.29 / Temperature of driver-unit C-1 (K)
F_TMP-H2= 275.27 / Temperature of driver-unit C-2 (K)
F_TMP-I1= 275.35 / Temperature of driver-unit D-1 (K)
F_TMP-I2= 275.38 / Temperature of driver-unit D-2 (K)
F_TMP-J1= 275.25 / Temperature of driver-unit E-1 (K)
F_TMP-J2= 275.22 / Temperature of driver-unit E-2 (K)
F_DEWERX= 27.00 / X-position of dewer stage (micron meter)
F_DEWERY= 10.00 / Y-position of dewer stage (micron meter)
F_DEWERZ= 152.94 / Z-position of dewer stage (micron meter)
F_HOLANG= -5.2 / angle of mask holder (degree)
F_MSK-ID= 'MSK300151' / ID of Mask (for all mode)
F_CAD-ID= 'CAD005235' / ID of CAD data for mask cutting
F_CADREF= 'FSCA00002345' / ID/name of image/catalog data for mask design
F_SLT-NO= 3 / total # of slit on mask
F_POSANG= 0.00 / PA of cross-dispersion axis (degree)
END

```

● FOCAS の Spectroscopy mode

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / Standard FITS format
BITPIX = 16 / # of bits storing pix value
NAXIS = 2 / # of axes in frame
NAXIS1 = 4096 / # of pixels/row
NAXIS2 = 2048 / # of rows (also # of scan lines)
EXTEND = T / Extension FITS format
OBSERVER= 'Y.Yadoumaru, K.Aoki, T.Ozawa, night-staff and WG' / Name of observer
PROP-ID = 'P19970025-0001' / Proposal ID
INSTRUME= 'FOCAS' / Name of instrument
FRAMEID = 'FSCA000023471234' / Image sequential number
EXP-ID = 'FSCE000011741234' / ID of the exposure this data was taken
OBS-MOD = 'Spectroscopy' / Observation Mode
DATA-TYP= 'OBJECT' / Type / Characteristics of this data
OBSERVAT= 'NAOJ' / Observatory
TELESCOP= 'SUBARU' / Telescope name
TIMESYS = 'UTC' / Time System used in the header. UTC fix.
RADECSYS= 'FK5' / The equatorial coordinate system
OBS-ALOC= 'OBSEVING' / Allocation mode for Instrument
DATASET = 'FOCAS-12345' / ID of an observation dataset
DISPAXIS= 1 / Dispersion axis in frame
WCS-ORIG= 'SUBARU toolkit' / Origin of the WCS value
CRPIX1 = +2048.0 / Reference pixel in X
CRPIX2 = +1024.0 / Reference pixel in Y
CRVAL1 = +0.275108E+03 / Physical value of the reference pixel X
CRVAL2 = -0.161769E+02 / Physical value of the reference pixel Y
CDEL1 = +0.277778E-04 / Size projected into a detector pixel X
CDEL2 = +0.277778E-04 / Size projected into a detector pixel Y
CTYPE1 = 'RA---TAN' / Pixel coordinate system
CTYPE2 = 'DEC--TAN' / Pixel coordinate system
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDEL1
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDEL2
LONGPOLE= 180.00000 / The North Pole of the standard system
COMMENT
C2PIX1 = +2048.0 / Reference pixel in X
C2PIX2 = +1024.0 / Reference pixel in Y
C2VAL1 = +0.275108E+03 / Physical value of ref pix X for WCS
C2VAL2 = -0.161769E+02 / Physical value of ref pix Y for WCS
C2ELT1 = +0.277778E-04 / Size projected into a detector pixel X
C2ELT2 = +0.277778E-04 / Size projected into a detector pixel Y

```

```

C2YPE1 = 'RA---TAN'           / Pixel coordinate system
C2YPE2 = 'DEC--TAN'           / Pixel coordinate system
C2NIT1 = 'degree'             / Units used in both C2VAL1 and C2ELT1
C2NIT2 = 'degree'             / Units used in both C2VAL2 and C2ELT2
BSCALE = 1.0                  / Real=fits_value*BSCALE+BZERO
BZERO   = 32768.0             / Real=fits_value*BSCALE+BZERO
BUNIT   = 'ADU'                / Unit of original pixel values
BLANK   = -32768               / Value used for NULL pixels
DATE-OBS= '1998-05-06'        / Observation start date (yyyy-mm-dd)
UT      = '12:34:56.78'        / HH:MM:SS.SS typical UTC at exposure
UT-STR  = '12:34:56.78'        / HH:MM:SS.SS UTC at exposure start
UT-END  = '13:04:56.78'        / HH:MM:SS.SS UTC at exposure end
HST     = '02:34:56.78'        / HH:MM:SS.SS typical HST at exposure
HST-STR = '02:34:56.78'        / HH:MM:SS.SS HST at exposure start
HST-END = '03:04:56.78'        / HH:MM:SS.SS HST at exposure end
LST     = '23:53:10.67'        / HH:MM:SS.SS typical LST at exposure
LST-STR = '23:53:10.67'        / HH:MM:SS.SS LST at exposure start
LST-END = '24:23:20.63'        / HH:MM:SS.SS LST at exposure end
MJD     = 50396.52420000       / Modified Julian Day at typical time
MJD-STR = 50396.52420000       / Modified Julian Day at exposure start
MJD-END = 50396.54500000       / Modified Julian Day at exposure end
EXPTIME = 1800.00              / Total integration time (sec)
OBJECT  = 'M17'                / Target Description
RA      = '18:20:26.010'       / RA of telescope pointing (HH:MM:SS.SSS)
RA2000  = '18:20:26.010'       / RA (J2000) pointing (HH:MM:SS.SSS)
DEC     = '-16:12:07.1'        / DEC of telescope pointing (+/-DD:MM:SS.SS)
DEC2000 = '-16:12:07.1'        / DEC (J2000) pointing (+/-DD:MM:SS.SS)
EQUINOX = 2000.0               / Standard FK5 (years)
AZIMUTH = -16.625000           / Azimuth angle of telescope pointing (degree), S
ALTITUDE= 36.47000             / Altitude angle of telescope pointing (degree)
TELFOCAS= 'CASSEGRAIN'         / Focus where a beam is reachable
FOC-POS  = 'CASSEGRAIN'         / Focus where the instrument is attached
FOC-VAL  = +2.513              / Encoder value of the focus unit
F-RATIO  = 12.2                / F-ratio of each telescope-focus.
ADC-TYPE= 'RED'                / ADC name if used
ADC      = +21.123             / ADC PA during exposure (degree)
ADC-STR  = +19.059             / ADC PA at exposure start (degree)
ADC-END  = +25.897             / ADC PA at exposure end (degree)
WAVELEN  = 600.00              / Typical wavelength on detector (nm)
WAV-MIN  = 468.93              / Shortest wavelength focused on detector (nm)
WAV-MAX  = 731.07              / Longest wavelength focused on detector (nm)
FILTER01= 'NONE'               / Filter name/ID
FILTER02= 'NONE'               / Filter name/ID
FILTER03= 'NONE'               / Filter name/ID
FLT-A01  = 5.00                / Inclination of n-th Filter (degree)
FLT-A02  = 5.00                / Inclination of n-th Filter (degree)
FLT-A03  = 5.00                / Inclination of n-th Filter (degree)
AIRMASS  = 1.24                / Averaged Air Mass
AIRM-STR = 1.21                / Air Mass at exposure start
AIRM-END = 1.28                / Air Mass at exposure end
ZD       = 36.47               / Zenith Distance at typical time (degree)
ZD-STR   = 34.28               / Zenith Distance at exposure start (degree)
ZD-END   = 38.63               / Zenith Distance at exposure end (degree)
SECZ     = 1.243               / SEC(Zenith Distance) at typical time
SECZ-STR = 1.210               / SEC(ZD) at exposure start
SECZ-END = 1.280               / SEC(ZD) at exposure end
DAQ-VER  = 'DAQ-1.0.3'         / Version of the DAQ-soft
INS-VER  = 'FCS-1.2-1.0'       / Version of the instrument/control-soft
DETECTOR= 'MIT_001'           / Name of the detector/CCD
DET-ID   = 1                   / ID of the detector used for this data
DET-A01  = 0.000               / Relative angle of the nn-th detector (degree)
DET-P101 = -103.5              / Relative X-Position of nn-th detector (nm)
DET-P201 = 12.5                / Relative Y-Position of nn-th detector (nm)
DET-TMP  = 132.50              / Detector temperature (K)
DET-TMED = 132.50              / Median of the detector temperature (K)
DET-TMIN = 132.40              / Minimum temperature of the detector (K)
DET-TMAX = 132.55              / Maximum temperature of the detector (K)
GAIN     = 1.26                / AD conversion factor (electron/ADU)
EFP-MIN1 = 10                  / Start X position of effective data region
EFP-MIN2 = 10                  / Start Y position of effective data region
EFP-RNG1 = 4046                 / X range of effective data region
EFP-RNG2 = 2028                 / Y range of effective data region
PRD-MIN1 = 1                   / Start X position of partially read out
PRD-MIN2 = 1                   / Start Y position of partially read out
PRD-RNG1 = 4096                 / X range of the partially read out
PRD-RNG2 = 2048                 / Y range of the partially read out
BIN-FCT1 = 1                   / Binning factor of X axis
BIN-FCT2 = 1                   / Binning factor of Y axis
WEATHER  = 'CLEAR'             / Weather condition (selected by observer)
SEEING   = 0.45                / FWHM of star size at telescope focus (arcsec)
DOM-WND  = 4.61                / Wind speed in the dome (m/sec)
OUT-WND  = 7.79                / Wind speed outside the dome (m/sec)
DOM-TMP  = 273.53              / Temperature in the dome (K)
OUT-TMP  = 273.72              / Temperature outside the dome (K)

```

```

DOM-HUM = 45.00 / Humidity in the dome (%)
OUT-HUM = 58.00 / Humidity outside the dome (%)
DISPERSR= 'HG600' / Identifier of the disperser used
SLIT = 'LONGSLIT' / Identifier of the entrance slit used
COMMENT --- Subaru Device Dependent Header Block for FOCAS ---
F_TMP-A = 275.33 / Temperature of MOS unit (K)
F_TMP-B = 272.45 / Temperature of lens unit (K)
F_TMP-C1= 272.15 / Temperature of collimator beam unit-1 (K)
F_TMP-C2= 272.20 / Temperature of collimator beam unit-2 (K)
F_TMP-C3= 272.10 / Temperature of collimator beam unit-3 (K)
F_TMP-D = 273.29 / Temperature of Camera lens unit (K)
F_TMP-E1= 275.29 / Temperature of VME-1 (K)
F_TMP-E2= 275.30 / Temperature of VME-2 (K)
F_TMP-F1= 275.31 / Temperature of driver-unit A-1 (K)
F_TMP-F2= 275.28 / Temperature of driver-unit A-2 (K)
F_TMP-G1= 275.29 / Temperature of driver-unit B-1 (K)
F_TMP-G2= 275.27 / Temperature of driver-unit B-2 (K)
F_TMP-H1= 275.29 / Temperature of driver-unit C-1 (K)
F_TMP-H2= 275.27 / Temperature of driver-unit C-2 (K)
F_TMP-I1= 275.35 / Temperature of driver-unit D-1 (K)
F_TMP-I2= 275.38 / Temperature of driver-unit D-2 (K)
F_TMP-J1= 275.25 / Temperature of driver-unit E-1 (K)
F_TMP-J2= 275.22 / Temperature of driver-unit E-2 (K)
F_DEWERX= 27.00 / X-position of dewer stage (micron meter)
F_DEWERY= 10.00 / Y-position of dewer stage (micron meter)
F_DEWERZ= 152.94 / Z-position of dewer stage (micron meter)
F_HOLANG= -5.2 / angle of mask holder (degree)
F_MSK-ID= 'MSK300151' / ID of Mask (for all mode)
F_CAD-ID= 'CAD005235' / ID of CAD data for mask cutting
F_CADREF= 'FSCA00002345' / ID/name of image/catalog data for mask design
F_DISPERS= 0.546 / Dispersion of grism (nm / pixel)
F_SLT-NO= 3 / total # of slit on mask
F_POSANG= 0.00 / PA of cross-dispersion axis (degree)
END

```

● FOCAS の SpectroPolarimetry mode

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / Standard FITS format
BITPIX = 16 / # of bits storing pix value
NAXIS = 2 / # of axes in frame
NAXIS1 = 4096 / # of pixels/row
NAXIS2 = 2048 / # of rows (also # of scan lines)
EXTEND = T / Extension FITS format
OBSERVER= 'Y.Yadoumaru, K.Aoki, T.Ozawa, night-staff and WG' / Name of observer
PROP-ID = 'P19970025-0001' / Proposal ID
INSTRUME= 'FOCAS' / Name of instrument
FRAMEID = 'FSCA000023471234' / Image sequential number
EXP-ID = 'FSCE000011741234' / ID of the exposure this data was taken
OBS-MOD = 'Spectro-Polarimetry' / Observation Mode
DATA-TYP= 'OBJECT' / Type / Characteristics of this data
OBSERVAT= 'NAOJ' / Observatory
TELESCOP= 'SUBARU' / Telescope name
TIMESYS = 'UTC' / Time System used in the header. UTC fix.
RADECSYS= 'FK5' / The equatorial coordinate system
OBS-ALOC= 'OBSEVING' / Allocation mode for Instrument
DATASET = 'FOCAS-12345' / ID of an observation dataset
DISPAXIS= 1 / Dispersion axis in frame
WCS-ORIG= 'SUBARU toolkit' / Origin of the WCS value
CRPIX1 = +2048.0 / Reference pixel in X
CRPIX2 = +1024.0 / Reference pixel in Y
CRVAL1 = +0.275108E+03 / Physical value of the reference pixel X
CRVAL2 = -0.161769E+02 / Physical value of the reference pixel Y
CDELT1 = +0.277778E-04 / Size projected into a detector pixel X
CDELT2 = +0.277778E-04 / Size projected into a detector pixel Y
CTYPE1 = 'RA---TAN' / Pixel coordinate system
CTYPE2 = 'DEC--TAN' / Pixel coordinate system
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDELT1
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDELT2
LONGPOLE= 180.00000 / The North Pole of the standard system
COMMENT
C2PIX1 = +2048.0 / Reference pixel in X
C2PIX2 = +1024.0 / Reference pixel in Y
C2VAL1 = +0.275108E+03 / Physical value of ref pix X for WCS
C2VAL2 = -0.161769E+02 / Physical value of ref pix Y for WCS
C2ELT1 = +0.277778E-04 / Size projected into a detector pixel X
C2ELT2 = +0.277778E-04 / Size projected into a detector pixel Y
C2YPE1 = 'RA---TAN' / Pixel coordinate system
C2YPE2 = 'DEC--TAN' / Pixel coordinate system
C2NIT1 = 'degree' / Units used in both C2VAL1 and C2ELT1

```

```

C2NIT2 = 'degree' , / Units used in both C2VAL2 and C2ELT2
C3PIX1 = +2048.0 / Reference pixel in X for Ordinary light
C3PIX2 = +1124.0 / Reference pixel in Y for Ordinary light
C3VAL1 = +0.275108E+03 / Physical value of ref pix X for Ordinary light
C3VAL2 = -0.161769E+02 / Physical value of ref. pix Y for Ordinary light
C3ELT1 = +0.277778E-04 / Size projected into a detector X for Ordinary
C3ELT2 = +0.277778E-04 / Size projected into a detector Y for Ordinary
C3YPE1 = 'RA---TAN' / Pixel coordinate system for Ordinary light
C3YPE2 = 'DEC--TAN' / Pixel coordinate system for Ordinary light
C3NIT1 = 'degree' , / Units in both C3VAL1 and C3ELT1 for Ordinary
C3NIT2 = 'degree' , / Units in both C3VAL2 and C3ELT2 for Ordinary
C4PIX1 = +2048.0 / Reference pixel in X for Extraordinary light
C4PIX2 = +924.0 / Reference pixel in Y for Extraordinary light
C4VAL2 = -0.161769E+02 / Physical value of ref. pix Y for Extraordinary
C4ELT1 = +0.277778E-04 / Size projected into a detector X for E-light
C4ELT2 = +0.277778E-04 / Size projected into a detector Y for E-light
C4YPE1 = 'RA---TAN' / Pixel coordinate system for Extraordinary light
C4YPE2 = 'DEC--TAN' / Pixel coordinate system for Extraordinary light
C4NIT1 = 'degree' , / Units in both C4VAL1 and C4ELT1 for E-light
C4NIT2 = 'degree' , / Units in both C4VAL2 and C4ELT2 for E-light
BSCALE = 1.0 / Real=fits_value*BSCALE+BZERO
BZERO = 32768.0 / Real=fits_value*BSCALE+BZERO
BUNIT = 'ADU' , / Unit of original pixel values
BLANK = -32768 / Value used for NULL pixels
DATE-OBS= '1998-05-06' / Observation start date (yyyy-mm-dd)
UT = '12:34:56.78' / HH:MM:SS.SS typical UTC at exposure
UT-STR = '12:34:56.78' / HH:MM:SS.SS UTC at exposure start
UT-END = '13:04:56.78' / HH:MM:SS.SS UTC at exposure end
HST = '02:34:56.78' / HH:MM:SS.SS typical HST at exposure
HST-STR = '02:34:56.78' / HH:MM:SS.SS HST at exposure start
HST-END = '03:04:56.78' / HH:MM:SS.SS HST at exposure end
LST = '23:53:10.67' / HH:MM:SS.SS typical LST at exposure
LST-STR = '23:53:10.67' / HH:MM:SS.SS LST at exposure start
LST-END = '24:23:20.63' / HH:MM:SS.SS LST at exposure end
MJD = 50396.52420000 / Modified Julian Day at typical time
MJD-STR = 50396.52420000 / Modified Julian Day at exposure start
MJD-END = 50396.54500000 / Modified Julian Day at exposure end
EXPTIME = 1800.00 / Total integration time (sec)
OBJECT = 'M17' , / Target Description
RA = '18:20:26.010' / RA of telescope pointing (HH:MM:SS.SSS)
RA2000 = '18:20:26.010' / RA (J2000) pointing (HH:MM:SS.SSS)
DEC = '-16:12:07.1' / DEC of telescope pointing (+/-DD:MM:SS.SS)
DEC2000 = '-16:12:07.1' / DEC (J2000) pointing (+/-DD:MM:SS.SS)
EQUINOX = 2000.0 / Standard FK5 (years)
AZIMUTH = -16.625000 / Azimuth angle of telescope pointing (degree), S
ALTITUDE= 36.47000 / Altitude angle of telescope pointing (degree)
TELFOCAS= 'CASSEGRAIN' / Focus where a beam is reachable
FOC-POS = 'CASSEGRAIN' / Focus where the instrument is attached
FOC-VAL = +2.513 / Encoder value of the focus unit
F-RATIO = 12.2 / F-ratio of each telescope-focus.
ADC-TYPE= 'RED' , / ADC name if used
ADC = +21.123 / ADC PA during exposure (degree)
ADC-STR = +19.059 / ADC PA at exposure start (degree)
ADC-END = +25.897 / ADC PA at exposure end (degree)
WAVELEN = 600.00 / Typical wavelength on detector (nm)
WAV-MIN = 468.93 / Shortest wavelength focused on detector (nm)
WAV-MAX = 731.07 / Longest wavelength focused on detector (nm)
RETPLAT1= '1/2' , / Identifier of the Retarder Plate
RET-ANG = 45.0000 / Position Angle of the Retarder Plate
FILTER01= 'NONE' , / Filter name/ID
FILTER02= 'NONE' , / Filter name/ID
FILTER03= 'NONE' , / Filter name/ID
FLT-A01 = 5.00 / Inclination of n-th Filter (degree)
FLT-A02 = 5.00 / Inclination of n-th Filter (degree)
FLT-A03 = 5.00 / Inclination of n-th Filter (degree)
AIRMAS = 1.24 / Averaged Air Mass
AIRM-STR = 1.21 / Air Mass at exposure start
AIRM-END = 1.28 / Air Mass at exposure end
ZD = 36.47 / Zenith Distance at typical time (degree)
ZD-STR = 34.28 / Zenith Distance at exposure start (degree)
ZD-END = 38.63 / Zenith Distance at exposure end (degree)
SECZ = 1.243 / SEC(Zenith Distance) at typical time
SECZ-STR = 1.210 / SEC(ZD) at exposure start
SECZ-END = 1.280 / SEC(ZD) at exposure end
DAQ-VER = 'DAQ-1.0.3' / Version of the DAQ-soft
INS-VER = 'FCS-1.2-1.0' / Version of the instrument/control-soft
DETECTOR= 'MIT_001' , / Name of the detector/CCD
DET-ID = 1 / ID of the detector used for this data
DET-A01 = 0.000 / Relative angle of the nn-th detector (degree)
DET-P101 = -103.5 / Relative X-Position of nn-th detector (nm)
DET-P201 = 12.5 / Relative Y-Position of nn-th detector (nm)
DET-TMP = 132.50 / Detector temperature (K)
DET-TMED = 132.50 / Median of the detector temperature (K)
DET-TMIN = 132.40 / Minimum temperature of the detector (K)

```

```

DET-TMAX=          132.55 / Maximun temperature of the detector (K)
GAIN      =          1.26 / AD conversion factor (electron/ADU)
EFP-MIN1=          10 / Start X position of effective data region
EFP-MIN2=          10 / Start Y position of effective data region
EFP-RNG1=          4046 / X range of effective data region
EFP-RNG2=          2028 / Y range of effective data region
PRD-MIN1=          1 / Start X position of partialy read out
PRD-MIN2=          1 / Start Y position of partialy read out
PRD-RNG1=          4096 / X range of the partialy read out
PRD-RNG2=          2048 / Y range of the partialy read out
BIN-FCT1=          1 / Binning factor of X axis
BIN-FCT2=          1 / Binning factor of Y axis
WEATHER = 'CLEAR' , / Weather condition (selected by observer)
SEEING  =          0.45 / FWHM of star size at telescope focus (arcsec)
DOM-WND =          4.61 / Wind speed in the dome (m/sec)
OUT-WND =          7.79 / Wind speed outside the dome (m/sec)
DOM-TMP =          273.53 / Temperature in the dome (K)
OUT-TMP =          273.72 / Temperature outside the dome (K)
DOM-HUM =          45.00 / Humidity in the dome (%)
OUT-HUM =          58.00 / Humidity outside the dome (%)
DISPERSR= 'HG600' , / Identifier of the disperser used
SLIT     = 'LONGSLIT' / Identifier of the entrance slit used
COMMENT --- Subaru Device Dependent Header Block for FOCAS ---
F_TMP-A =          275.33 / Temperature of MOS unit (K)
F_TMP-B =          272.45 / Temperature of lens unit (K)
F_TMP-C1=          272.15 / Temperature of collimator beam unit-1 (K)
F_TMP-C2=          272.20 / Temperature of collimator beam unit-2 (K)
F_TMP-C3=          272.10 / Temperature of collimator beam unit-3 (K)
F_TMP-D =          273.29 / Temperature of Camera lens unit (K)
F_TMP-E1=          275.29 / Temperature of VME-1 (K)
F_TMP-E2=          275.30 / Temperature of VME-2 (K)
F_TMP-F1=          275.31 / Temperature of driver-unit A-1 (K)
F_TMP-F2=          275.28 / Temperature of diver-unit A-2 (K)
F_TMP-G1=          275.29 / Temperature of drive-unit B-1 (K)
F_TMP-G2=          275.27 / Temperature of driver-unit B-2 (K)
F_TMP-H1=          275.29 / Temperature of driver-unit C-1 (K)
F_TMP-H2=          275.27 / Temperature of drive-unit C-2 (K)
F_TMP-I1=          275.35 / Temperature of driver-unit D-1 (K)
F_TMP-I2=          275.38 / Temperature of driver-unit D-2 (K)
F_TMP-J1=          275.25 / Temperature of driver-unit E-1 (K)
F_TMP-J2=          275.22 / Temperature of driver-unit E-2 (K)
F_DEWERX=          27.00 / X-position of dewer stage (micron meter)
F_DEWERY=          10.00 / Y-position of dewer stage (micron meter)
F_DEWERZ=          152.94 / Z-position of dewer stage (micron meter)
F_HOLANG=          -5.2 / angle of mask holder (degree)
F_MSK-ID= 'MSK300151' / ID of Mask (for all mode)
F_CAD-ID= 'CAD005235' / ID of CAD data for mask cutting
F_CADREF= 'FSCA00002345' / ID/name of image/catalog data for mask design
F_DISPERS=          0.546 / Dispersion of grism (nm / pixel)
F_SLT-NO=          3 / total # of slit on mask
F_POSANG=          0.00 / PA of cross-dispersion axis (degree)
END

```

● FOCAS の ASCII Table Extension sample header とデータ (Imaging and Spectroscopy mode)

```

1      2      3      4      5      6      7
123456789012345678901234567890123456789012345678901234567890123456789
-----
XTENSION= 'TABLE' , / Table extension
BITPIX =          8 / # of bits storing pix value
NAXIS =          2 / simple 2-D matrix
NAXIS1 =          107 / # of characters per row
NAXIS2 =          3 / # of rows
PCOUNT =          0 / No "random" parameters
GCOUNT =          1 / Only one group
TFIELDS =          11 / # of fields in one row
EXTNAME = ' ' , / Name of this table
TTYPE1 = 'SLT-ID' , / Slit ID of mask design in CAD data
TBCOL1 =          1 / start column of this field (= 1)
TFORM1 = 'I4' , / integer
TTYPE2 = 'SLTCPIX1' , / X-position of slit center
TBCOL2 =          6 / start column of this field (= 6)
TFORM2 = 'F7.2' , / float
TUNIT2 = 'pixel' , / unit of 2nd column
TTYPE3 = 'SLTCPIX2' , / Y-position of slit center
TBCOL3 =          14 / start column of this field (= 14)
TFORM3 = 'F7.2' , / float
TUNIT3 = 'pixel' , / unit of 3rd column
TTYPE4 = 'SLTC-RA' , / RA of slit center
TBCOL4 =          22 / start column of this field (= 22)

```



```

TTYPE9  = 'SLTC-DEC'      / DEC of slit center
TBCOL9  =                67 / start column of this field (= 67)
TFORM9  = 'A12'          / character (format is +/-DD:MM:SS.SS)
TTYPE10 = 'SLT-LEN'      / Slit length (Semi-major-axis for ELLIPSE)
TBCOL10 =                80 / start column of this field (= 80)
TFORM10 = 'F5.1'         / float
TUNIT10 = 'arcsec'       / unit of 10th column
TTYPE11 = 'SLT-WID'      / Slit width (Semi-minor-axis for ELLIPSE)
TBCOL11 =                86 / start column of this field (= 86)
TFORM11 = 'F5.1'         / float
TUNIT11 = 'arcsec'       / unit of 11th column
TTYPE12 = 'SLT-PA'       / Position angle of slit
TBCOL12 =                92 / start column of this field (= 92)
TFORM12 = 'F5.1'         / float
TUNIT12 = 'degree'       / unit of 12th column
TTYPE13 = 'SLT-SHP'      / Shape of slit
TBCOL13 =                98 / start column of this field (= 98)
TFORM13 = 'A9'           / character (eclipse, rectangle)
TTYPE14 = 'SLT-OPEN'     / Cutting shape is open or not, open is T(true)
TBCOL14 =                108 / start column of this field (= 108)
TFORM14 = 'A1'           / logical (T or F)
TTYPE15 = 'OBJECT'       / Name of observed
TBCOL15 =                110 / start column of this field (= 110)
TFORM15 = 'A30'          / character
TNULL15 =                / null data for this column
END

1      2      3      4      5      6      7      8      9      0      1      2
12345678901234567890123456789012345678901234567890123456789012345678901234567890
-----
1 102.10 110.79 102.10 10.99 102.10 210.49 12:35:39.940 +42:05:30.8213.8 0.2 0.0 RECTANGLE T
52 1053.05 2090.23 1053.05 1990.43 1053.05 2189.93 12:35:44.555 +42:08:09.5620.0 0.2 0.0 RECTANGLE T FOCAS123545+4208
1893 3179.93 3565.33 3179.93 3465.53 3179.93 3665.03 12:35:59.109 +42:11:12.7418.0 0.2 0.0 RECTANGLE T

```

6.5.4 HDS(1998/08/19)

```

1      2      3      4      5      6      7      8      9
1234567890123456789012345678901234567890123456789012345678901234567890
-----
SIMPLE  =                T / Standard FITS format
BITPIX  =                16 / Number of bits for each pixel
NAXIS   =                2 / Number of axes in frame
NAXIS1  =                4096 / Number of pixels per row
NAXIS2  =                2048 / Number of rows
EXTEND  =                T / There is a standard extension 1 (ASCII table)
BSCALE  =                1.00000 / Real = (fits pixel value)*BSCALE+BZERO
BZERO   =                1355.00000 / Real = (fits pixel value)*BSCALE+BZERO
BUNIT   = 'ADU'          / Unit of original pixel value
BLANK   =                0 / Value used for NULL pixels
DISPAXIS=                1 / Main dispersion axis in frame
CTYPE1  = 'RA---TAN'     / Pixel coordinate system
CTYPE2  = 'DEC--TAN'     / Pixel coordinate system
CUNIT1  = 'degree'       / Units used in both CRVAL1 and CDELT1
CUNIT2  = 'degree'       / Units used in both CRVAL2 and CDELT2
CRPIX1  =                2048.0 / Reference pixel in axis1
CRVAL1  =                190.00000 / Physical value of the reference pixel
CDELT1  =                0.000200 / Size projected into a detector pixel in axis1
CRPIX2  =                1024.0 / Reference pixel in axis2
CRVAL2  =                45.00000 / Physical value of the reference pixel
CDELT2  =                0.000200 / Size projected into a detector pixel in axis2
PROJP1  =                0.0 /
PROJP2  =                0.0 /
LONGPOLE=                180.0 / The North Pole of the standard system
PC001001=                1.00000000 / Pixel Coordinate translation matrix
PC001002=                0.00000000 / Pixel Coordinate translation matrix
PC002001=                0.00000000 / Pixel Coordinate translation matrix
PC002002=                1.00000000 / Pixel Coordinate translation matrix
BIN-FCT1=                1 / Binning factor in axis1
BIN-FCT2=                1 / Binning factor in axis2
N2XIS   =                2 / Number of axes for the slit projection
N2XIS1  =                4096 / Number of pixels per row for slit spectroscopy
N2XIS2  =                2048 / Number of scan lines for slit projection
C2YPE1  = 'WAVELENGTH'   / (nm)
C2PIX1  =                2048.0 / Reference pixel in X
C2VAL1  =                344.53 / Physical value of ref pix X for WCS
C2ELT1  =                0.00117 / Size projected into a detector pixel X
C2NIT1  = 'nm'           / for C2VAL1 and C2ELT1
C2YPE2  = 'DEC--TAN'     /
C2PIX2  =                1024.0 / Reference pixel in Y
C2VAL2  =                45.00000 / Physical value of ref pix Y for WCS
C2ELT2  =                0.000200 / Size projected into a detector pixel Y
C2NIT2  = 'degree'       / for C2VAL2 and C2ELT2

```

```

P20JP1 = 0.0 / f5.1
P20JP2 = 0.0 / f5.1
P2001001= 1.00000000 / f12.8
P2001002= 0.00000000 / f12.8
P2002001= 0.00000000 / f12.8
P2002002= 1.00000000 / f12.8
PRD-MIN1= 1 / Start X position of partialy read out i4
PRD-MIN2= 1 / Start Y position of partialy read out i4
PRD-RNG1= 4096 / X range of the partialy read out i4
PRD-RNG2= 2048 / Y range of the partialy read out i4
EFP-MIN1= 1 / i4
EFP-RNG1= 4096 / i4
EFP-MIN2= 1 / i4
EFP-RNG2= 2048 / i4
OBJECT = 'Q1245+4542' / Target Description a30
DATA-TYP= 'OBJECT' / a15
RA = '12:45:42.700' / RA of the tracked pos. on the slit guide pos. a12
DEC = '+45:42:30.00' / Dec of the tracked pos. on the slit guide pos. a12
RADECSYS= 'FK5' /
EQUINOX = 2000.0 / f6.1
RA2000 = '12:45:42.700' / a12
DEC2000 = '+45:42:30.00' / a12
PROP-ID = 'P1999-A135.HIZUMIUR' / a20
OBSERVER= 'H.Izumiura, S.Kawanomoto, W.Aoki' / a30
OBS-MOD = 'MULTIPLE-ORDER' / SINGLE-ORDER, MULTIPLE-ORDER a30
DATE-OBS= '2000-03-14' / Date of observation a10
EXPTIME = 1800.0 / Exposure time in second f8.1
UT = '08:22:22.2' / Universal Time a10
UT-STR = '08:22:22.2' / a10
UT-END = '10:44:44.4' / a10
HST = '22:22:22.2' / Hawaii Standard Time a10
HST-STR = '22:22:22.2' / a10
HST-END = '00:44:44.4' / a10
LST = '11:11:11.1' / Local SideReal Time a10
LST-STR = '11:11:11.1' / a10
LST-END = '13:33:50.0' / a10
TIMESYS = 'UTC' / Time System
MJD = 51617.3488681 / Modified Julian Day f14.8
MJD-STR = 51617.3488681 / f14.8
MJD-END = 51617.4477361 / f14.8
SECZ = 1.138 / f6.3
SECZ-STR= 1.130 / f6.3
SECZ-END= 1.147 / f6.3
AIRMASS = 1.1388 / f6.4
AIRM-STR= 1.1300 / f6.4
AIRM-END= 1.1472 / f6.4
ALTITUDE= 61.4510 / Altitude of the telescope pointing (degree) f9.5
ALT-STR = 62.2461 / f9.5
ALT-END = 60.6553 / f9.5
AZIMUTH = 78.1000 / Azimuth of the telescope pointing (degree) f9.5
AZ-STR = 75.0000 / 0:North, 90:East f9.5
AZ-END = 80.0000 / f9.5
OBSERVAT= 'NAOJ' /
TELESCOP= 'SUBARU' /
OBS-ALOC= ' ' /
TELFOCUS= 'NASMYTH-OPT' /
FOC-POS = 'NASMYTH-OPT' / Focus a12
FOC-VAL = 1234.567 / Focus position of the telescope f10.3
FOC-LEN = 104207.0 / Focal length of the telescope (mm) f8.1
F-RATIO = 12.71 / F-ratio of incident beam f5.2
INSTRUME= 'HDS' /
FRAMEID = 'HDS00001001' / Frame ID number issued by OBS a16
EXP-ID = 'HDS00000501' / Exposure ID number locally defined a16
DISPERSR= 'echelle' / Identifier of the disperser used
WAVELEN = 344.53 / Center wavelength of the center order (nm) f7.2
WAV-MAX = 298.71 / Maximum wavelength recorded (nm) f7.2
WAV-MIN = 390.02 / Minimum wavelength recorded (nm) f7.2
FILTER01= 'CN603' / Filter wheel No.1 a10
FILTER02= 'R60' / Filter wheel No.2 a10
SLIT = 'SHORT' / Identifier of the entrance slit used (SHORT/LONG)
SLT-WID = 0.200 / Slit width (mm) f6.3
SLT-LEN = 3.500 / Slit length (mm) f6.3
SLT-PA = 60.25 / Slit position angle (degree) f6.2
SLTCPIX1= 2056.04 / Slit center position in axis1 at WAVELEN f7.2
SLTCPIX2= 1028.70 / Slit center position in axis2 at WAVELEN f7.2
SLT-PSTR= 56.2 / Slit position angle at start (degree) f6.2
SLT-PEND= 64.3 / Slit position angle at end (degree) f6.2
SLT-OBJP= -0.05 / Object position on the slit (arcsec) f6.2
DET-ID = 1 / ID number of the CCD in the detector unit i1
DETECTOR= 'SITE' / Detector used to take this frame a10
DETPXSZ1= 0.0150 / pixel size in axis1 (mm) f6.4
DETPXSZ2= 0.0150 / pixel size in axis2 (mm) f6.4
DET-A01 = -8.003 / Rotation angle of the 1st detector (degree) f7.3
DET-A02 = -7.998 / Rotation angle of the 2nd detector (degree) f7.3

```

```

GAIN = 2.00 / Readout gain f5.2
DET-TMP = 158.2 / Nominal detector temperature (Kelvin) f6.2
DET-TAVE= 158.2 / Average detector temperature (Kelvin) f6.2
DET-TMAX= 159.2 / Maximum detector temperature (Kelvin) f6.2
DET-TMIN= 157.2 / Minimum detector temperature (Kelvin) f6.2
DET-TSD = 0.07 / Detector temperature fluctuation (Kelvin) f5.3
WEATHER = 'CLEAR ' / Weather condition a10
SEEING = 0.57 / FWHM of the star observed with Slit Viewer (arcsec) f6.3
NAS-TAVE= 286.25 / Average Nasmyth encl. temp. (Kelvin) f6.2
NAS-TMIN= 287.07 / Minimum Nasmyth encl. temp. (Kelvin) f6.2
NAS-TMAX= 285.64 / Maximum Nasmyth encl. temp. (Kelvin) f6.2
NAS-TSD = 0.25 / Fluctuation of Nasmyth encl. temp. (Kelvin) f5.3
DOM-WND = 4.2 / Wind speed inside dome (m/s) f4.1
DOM-TMP = 276.2 / Atmospheric temperature inside dome (Kelvin) f6.2
DOM-HUM = 3.0 / Humidity inside dome (hPa) f5.1
OUT-WND = 5.3 / Wind speed outside dome (m/s) f4.1
OUT-TMP = 277.1 / Atmospheric temperature outside dome (Kelvin) f6.2
OUT-HUM = 3.0 / Humidity outside dome (hPa) f5.1
DOM-PRS = 654.0 / Nominal atmospheric pressure (hPa) f6.1
DOM-PSTR= 653.8 / Pressure at start (hPa) f6.1
DOM-PEND= 654.2 / Pressure at end (hPa) f6.1
IMR-TYPE= 'BLUE ' / Image Rotator (BLUE, RED, NONE) a8
IMGROT = 153.22 / IMR position during exposure (degree) f7.2
IMR-STR = 153.22 / IMR position angle at start (degree) f7.2
IMR-END = 162.91 / IMR position angle at end (degree) f7.2
ADC-TYPE= 'BLUE ' / Atm. Disp. Compensator (BLUE,RED,NONE) a8
ADC = 348.99 / ADC position during exposure (degree)
ADC-STR = 348.99 / ADC position angle at start (degree) f7.2
ADC-END = 361.23 / ADC position angle at end (degree) f7.2
DAQ-VER = '1.0.0 ' / Data Aquisition System a10
INS-VER = 'HDS-1.00/HDS-1.00' / hardware/software version a20
COMMENT
COMMENT Sample header for HDS revised on 7 July 1998 by W. Aoki
COMMENT Sample header for HDS revised on 6 May 1998 by W. Aoki
COMMENT Sample header for HDS written on 27 November 1997
COMMENT by H.Izumiura, S. Kawanomoto, W. Aoki.
COMMENT
COMMENT -----
COMMENT HH HH DDDDDD SSSSSS
COMMENT HH HH DD DDD SSS S
COMMENT HHHHHH DD DD SSSS
COMMENT HH HH DD DDD S SSS
COMMENT HH HH DDDDDD SSSSSS
COMMENT -----
COMMENT Keywords specific to HDS
COMMENT
COMMENT /Calibration Lamp Unit
H_INPOWR= 10.3 / Input power for the flat lamp (Volt) f6.2
COMMENT /Image Slicer
H_IMSLCR= 'OFF ' / Image slicer (ON, OFF) a8
H_ISTYPE= 'FMOS ' / Type of the image slicer a10
COMMENT /SLIT
H_S-MSK1= 1.499 / Upper mask position from the center (mm) f6.3
H_S-MSK2= -1.505 / Lower mask position from the center (mm) f6.3
H_S-INCL= 31.50 / Slit inclination angle wrt the horizontal plane f7.2
COMMENT /Detector
H_D-UNIT= '1 ' / ID number of the detector unit i1
H_D-OTHR= 'YES ' / Use of the other CCD in this mosaic a10
COMMENT /SHUTTERS
H_SHUTTR= 'OPEN ' / Entrance shutter (OPEN, CLOSE) a10
H_HARTMN= 'ALL-OPEN' / Hartmann shutter (U-OPEN,L-OPEN,ALL-OPEN,ALL-CLOSE) a10
COMMENT /COLLIMATOR MIRROR
H_COLLIM= 'BLUE ' / Collimator (BLUE, RED) a10
H_CLPSTN= -10.00 / Collimator position (mm) f6.2
H_CLFOCL= 3396.51 / Collimator focal length (mm) f10.5
H_CLOFFA= 5.00 / Collimator offset angle (degree) f10.5
COMMENT /ECHELLE GRATING
H_ECHELL= 'RED ' / Echelle (BLUE, RED, NIR) a10
H_ECONST= 31.60 / Ruling pitch (grooves/mm) f7.3
H_EBLAZE= 70.30 / Blaze Angle (degree) f7.3
H_EEPSRN= 6.00 / Offset Angle of the Incident Beam (degree) f7.3
H_EGAMMA= 0.00 / (degree) f7.3
H_EROTAN= 53.13743 / Echelle Rotation Angle (degree) f10.5
COMMENT /CROSS DISPERSER GRATING
H_CROSSD= 'BLUE ' / Cross Disperser (BLUE, RED, MIRROR, NIR) a10
H_CCONST= 400.0 / Ruling pitch (grooves/mm) f7.3
H_CBLAZE= 4.76 / Blaze Angle (degree) f7.3
H_CEPSRN= 0.00 / Offset Angle at Blaze Wavelengths (degree) f7.3
H_CGAMMA= 45.00 / (degree) f7.3
H_CTABAN= 127.4367 / Rotation angle of the turn table (degree) f10.5
H_CROTAN= 34.1244 / Cross Disperser Rotation Angle (degree) f10.5
COMMENT /CAMERA
H_CMRFL = 770.85 / Camera focal length (mm) f10.5
COMMENT /Detector Focusinig Unit

```

```

H_FOCUS = -1.244 / Focusing unit position (mm) f10.5
H_PITCH = 0.0001 / Focusing unit pitching angle (degree) f9.5
H_YAWING= 0.0001 / Focusing unit yawing angle (degree) f9.5
H_F-DRV1= -1.234 / Focusing driver1 position (mm) f9.5
H_F-DRV2= -1.220 / Focusing driver2 position (mm) f9.5
H_F-DRV3= -1.195 / Focusing driver3 position (mm) f9.5
H_DETROT= -8.000 / Rotation angle of the detector unit (degree) f9.5
COMMENT /Nasmyth Enclosure Temperature at n-th position
H_ET1AVE= +13.25 / Average (Kelvin) f6.2
H_ET1MIN= +14.07 / Minimum (Kelvin) f6.2
H_ET1MAX= +12.64 / Maximum (Kelvin) f6.2
H_ET1DEV= 0.25 / Standard Deviation (Kelvin) f5.3
COMMENT /Subaru Adaptive Optics
H_AO-TYP= 'Tip-Tilt' / Type of correction a20
H_AO-ORD= 0 / Maximum order included i3
H_AO-OBJ= 'Nearby bright star' / star used for wavefront correction a20
H_AO-RA = '12:45:40.000' / a20
H_AO-DEC= '+45:42:20.00' / a20
COMMENT /Zero-th order light monitor of the echelle a20
H_ZAXIS1= 'Along Slit' / a20
H_ZAXIS2= 'Cross Slit' / a20
H_ZA1POS= 254.3 / peak position in axis1 (pixel) f7.2
H_ZA2POS= 232.9 / peak position in axis2 (pixel) f7.2
H_ZWID1 = 3.25 / Width in axis1 of the stellar image (pixel) f7.2
H_ZWID2 = 5.43 / Width in axis2 of the stellar image (pixel) f7.2
H_ZDELT = 0.0240 / Pixel size (mm) f6.4
H_ZSCALE= 0.0100 / physical length on the slit plane projected f8.5
COMMENT into one pixel (mm/pixel) f6.2
H_ZTMP = 200.0 / Detector temperature (Kelvin) a10
COMMENT /Super Resolution Mode
H_SUPER = 'NONE' / Super Resolution Mode (POS1, POS2, NONE) a10
COMMENT /Auto Guider (offset guider)
H_AG-OBJ= 'Tycho1245+4542' / a20
H_AG-ORA= '12:45:42.000' / RA of the guide object a20
H_AG-ODE= '+45:42:26.00' / Dec of the guide object a20
H_AG-RA = '12:45:42.800' / RA of the tracked pos. on the slit guide pos. a20
H_AG-DEC= '+45:42:31.00' / Dec of the tracked pos. on the slit guide pos. a20
H_AG-EQN= 2000.0 / f6.1
COMMENT
COMMENT
END

XTENSION= 'TABLE' , / Talbe extension
BITPIX = 8 / 8-bits per "pixel"
NAXIS = 2 / simple 2-D matrix
NAXIS1 = 72 / No. of characters per row
NAXIS2 = 45 / The number of rows (= )
PCOUNT = 0 / No "random" parameters
GCOUNT = 1 / Only one group
TFIELDS = 12 / There are 12 fields per row
TTYPE1 = 'ORDER' , / Order number
TBCOL1 = 1 / starting column
TFORM1 = 'I3' , / Data format
TTYPE2 = 'X-MIN' , / X-position of the blue-end of the order (pixel)
TBCOL2 = 5 /
TFORM2 = 'I4' , /
TUNIT2 = 'PIXEL' , /
TTYPE3 = 'Y-MIN' , / Y-position of the blue-end of the order (pixel)
TBCOL3 = 10 /
TFORM3 = 'I4' , /
TUNIT3 = 'PIXEL' , /
TTYPE4 = 'WL-MIN' , / Blue-end wavelength of the order (nm)
TBCOL4 = 15 /
TFORM4 = 'F8.3' , /
TUNIT4 = 'nanometer' , /
TTYPE5 = 'X-CEN' , / X-position of the center of the order (pixel)
TBCOL5 = 24 /
TFORM5 = 'I4' , /
TUNIT5 = 'PIXEL' , /
TTYPE6 = 'Y-CEN' , / Y-position of the center of the order (pixel)
TBCOL6 = 29 /
TFORM6 = 'I4' , /
TUNIT6 = 'PIXEL' , /
TTYPE7 = 'WL-CEN' , / Center wavelength of the order (nm)
TBCOL7 = 34 /
TFORM7 = 'F8.3' , /
TUNIT7 = 'nanometer' , /
TTYPE8 = 'X-MAX' , / X-position of the red-end of the order (pixel)
TBCOL8 = 43 /
TFORM8 = 'I4' , /
TUNIT8 = 'PIXEL' , /
TTYPE9 = 'Y-MAX' , / Y-position of the blue-end of the order (pixel)
TBCOL9 = 48 /
TFORM9 = 'I4' , /

```

197	1	5	298.714	2048	52	300.812	4096	98	302.910	0.000	0.003
196	1	39	300.238	2048	86	302.347	4096	133	304.456	0.000	0.003
195	1	73	301.778	2048	120	303.897	4096	167	306.017	0.000	0.003
194	1	108	303.333	2048	155	305.464	4096	202	307.595	0.000	0.003
193	1	143	304.905	2048	190	307.047	4096	238	309.188	0.000	0.003
192	1	178	306.493	2048	226	308.646	4096	274	310.799	0.000	0.003
191	1	214	308.098	2048	262	310.262	4096	310	312.426	0.000	0.003
190	1	250	309.719	2048	298	311.895	4096	346	314.070	0.000	0.003
189	1	286	311.358	2048	335	313.545	4096	383	315.732	0.000	0.003
188	1	323	313.014	2048	372	315.213	4096	421	317.411	0.000	0.003
187	1	360	314.688	2048	409	316.898	4096	458	319.109	0.000	0.003
186	1	398	316.380	2048	447	318.602	4096	496	320.824	0.000	0.003
185	1	436	318.090	2048	485	320.324	4096	535	322.559	0.000	0.003
184	1	474	319.819	2048	524	322.065	4096	574	324.312	0.000	0.003
183	1	513	321.566	2048	563	323.825	4096	613	326.084	0.000	0.003
182	1	552	323.333	2048	603	325.604	4096	653	327.875	0.000	0.003
181	1	592	325.120	2048	643	327.403	4096	693	329.687	0.000	0.003
180	1	632	326.926	2048	683	329.222	4096	734	331.519	0.000	0.003
179	1	673	328.752	2048	724	331.061	4096	775	333.371	0.000	0.003
178	1	714	330.599	2048	765	332.921	4096	817	335.243	0.000	0.003
177	1	755	332.467	2048	807	334.802	4096	859	337.137	0.000	0.003
176	1	797	334.356	2048	849	336.705	4096	902	339.053	0.000	0.003
175	1	840	336.267	2048	892	338.629	4096	945	340.991	0.000	0.003
174	1	883	338.199	2048	935	340.575	4096	988	342.950	0.000	0.003
173	1	926	340.154	2048	979	342.543	4096	1032	344.933	0.000	0.003
172	1	970	342.132	2048	1024	344.535	4096	1077	346.938	0.000	0.003
171	1	1015	344.133	2048	1068	346.550	4096	1122	348.967	0.000	0.003
170	1	1060	346.157	2048	1114	348.588	4096	1168	351.020	0.000	0.003
169	1	1105	348.205	2048	1159	350.651	4096	1214	353.097	0.000	0.004
168	1	1151	350.278	2048	1206	352.738	4096	1261	355.198	0.000	0.004
167	1	1198	352.375	2048	1253	354.850	4096	1308	357.325	0.000	0.004
166	1	1245	354.498	2048	1300	356.988	4096	1356	359.478	0.000	0.004
165	1	1293	356.646	2048	1348	359.152	4096	1404	361.657	0.000	0.004
164	1	1341	358.821	2048	1397	361.341	4096	1453	363.862	0.000	0.004
163	1	1390	361.022	2048	1446	363.558	4096	1503	366.094	0.000	0.004
162											

EXP-ID	= 'OHSAA00002347'	/ ID of the exposure this data was taken	%16s	
OBS-MOD	= 'imaging'	/ Observation Mode	%30s	
DATA-TYP	= 'OBJECT'	/ grism/prism の有無で判断 (prism の場合 slitless-spectroscopy) Type / Characteristics of this data	%10s	
RA	= '18:20:26.010'	/ HH:MM:SS.SSS RA pointing	%12s	
DEC	= '-16:12:07.06'	/ RA2000 と同じ +/-DD:MM:SS.SS DEC pointing	%12s	
EQUINOX	= 2000.0	/ DEC2000 と同じ Standard FK5 (years)	%6.1f	固定
RADECSYS	= 'FK5'	/ The equatorial coordinate system	%8s	固定
RA2000	= '18:20:26.010'	/ HH:MM:SS.SSS RA (J2000) pointing	%12s	toolkit
DEC2000	= '-16:12:07.06'	/ +/-DD:MM:SS.SS DEC (J2000) pointing	%12s	toolkit
CRPIX1	= 512.0	/ Reference pixel in X	%6.1f	固定
CRPIX2	= 512.0	/ Reference pixel in Y	%6.1f	固定
CRVAL1	= 275.10837500	/ Physical value of the reference pixel X	%13.8f	toolkit
CRVAL2	= -16.17306000	/ Physical value of the reference pixel Y	%13.8f	toolkit
CDEL1	= 0.00003194	/ Size projected into a detector pixel X	%13.8f	固定
CDEL2	= 0.00003194	/ Size projected into a detector pixel Y	%13.8f	固定
CTYPE1	= 'RA--TAN'	/ Pixel coordinate system	%16s	固定
CTYPE2	= 'DEC--TAN'	/ Pixel coordinate system	%16s	固定
CUNIT1	= 'degree'	/ Units used in both CRVAL1 and CDEL1	%10s	固定
CUNIT2	= 'degree'	/ Units used in both CRVAL2 and CDEL2	%10s	固定
PROJP1	= 0.0	/ Projection Type of the first axis 良く分からんが固定	%5.1f	
PROJP2	= 0.0	/ Projection Type of the second axis 良く分からんが固定	%5.1f	
LONGPOLE	= 180.0	/ The North Pole of the standard system 良く分からんが固定	%6.1f	
PC001001	= 1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
PC001002	= 0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
PC002001	= 0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
PC002002	= 1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
C2PIX1	= 512.0	/ Reference pixel in X	%6.1f	固定
C2PIX2	= 512.0	/ Reference pixel in Y	%6.1f	固定
C2VAL1	= 275.10837500	/ Physical value of the reference pixel Y	%13.8f	toolkit
C2VAL2	= 2120.00000000	/ Physical value of the reference pixel X filter によって変更	%13.8f	
C2ELT1	= 0.00003194	/ Size projected into a detector pixel Y	%13.8f	固定
C2ELT2	= 22.00000000	/ Size projected into a detector pixel X filter によって変更	%13.8f	
C2YPE1	= 'DEC--TAN'	/ Pixel coordinate system	%16s	固定
C2YPE2	= 'WAVELENGTH'	/ Pixel coordinate system	%16s	固定
C2NIT1	= 'degree'	/ Units used in both CRVAL2 and CDEL2	%10s	固定
C2NIT2	= 'nm'	/ Units used in both CRVAL1 and CDEL1	%10s	固定
P2001001	= 1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2001002	= 0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2002001	= 0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2002002	= 1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
SLIT	= 'NONE'	/ Identifier of the entrance slit used 'NONE' if Prism Sp slit-x,slit-y の値で判断 (NONE/Longslit/Pinhole)	%10s	
SLT-LEN	= 120.000	/ Length of the slit used 0.000 if Prism Sp	%7.3f	slit-y 値
SLT-WID	= 120.000	/ Width of the slit used 0.000 if Prism Sp	%6.3f	slit-x 値
SLT-PA	= 0.0	/ Slit Position Angle 0.0 if Prism Sp InR/ImR の値が必要?	%5.1f	
SLTC-RA	= 275.10837500	/ RA of slit center (degree)	%12.8f	toolkit
SLTC-DEC	= -16.17306000	/ DEC of slit center (degree)	%12.8f	toolkit
SLTCPIX1	= 512.0	/ Slit center projected on detector (pixel)	%7.1f	固定
SLTCPIX2	= 512.0	/ Slit center projected on detector (pixel)	%7.1f	固定
DISPERSR	= 'NONE'	/ Name of disperser used prism 使用時は Prism	%15s	
WAVELEN	= 2120.00000	/ Wavelength at detector center (nm) filter によって変更	%10.5f	
WAV-MIN	= 1950.00000	/ Shortest wavelength focused on detector (nm) filter によって変更	%10.5f	
WAV-MAX	= 2290.00000	/ Longest wavelength focused on detector (nm) filter によって変更	%10.5f	
DATE-OBS	= '1997-08-22'	/ Observation start date (yyyy-mm-dd)	%10s	toolkit
UT	= '12:34:56.7'	/ HH:MM:SS.S typical UTC at exposure	%10s	toolkit
UT-STR	= '12:34:56.7'	/ HH:MM:SS.S UTC at start	%10s	toolkit
UT-END	= '13:04:56.7'	/ HH:MM:SS.S UT at end	%10s	toolkit
HST	= '02:34:56.7'	/ HH:MM:SS.S Typical HST at exposure 露出開始時の時間+露出時間の半分	%10s	
LST	= '23:53:10.6'	/ HH:MM:SS.S Typical LST at exposure	%20s	toolkit
MJD	= 5.03965242E+04	/ Modified Julian Day at typical time	%20.8f	toolkit
TIMESYS	= 'UTC'	/ Time system used in this header	%3s	固定

CTYPE1	=	'RA--TAN'	/ Pixel coordinate system	%16s	固定
CTYPE2	=	'DEC--TAN'	/ Pixel coordinate system	%16s	固定
CUNIT1	=	'degree'	/ Units used in both CRVAL1 and CDELT1	%10s	固定
CUNIT2	=	'degree'	/ Units used in both CRVAL2 and CDELT2	%10s	固定
PROJP1	=	0.0	/ Projection Type of the first axis 良く分からんが固定	%5.1f	
PROJP2	=	0.0	/ Projection Type of the second axis 良く分からんが固定	%5.1f	
LONGPOLE	=	180.0	/ The North Pole of the standard system 良く分からんが固定	%6.1f	
PC001001	=	1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
PC001002	=	0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
PC002001	=	0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
PC002002	=	1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
C2PIX1	=	512.0	/ Reference pixel in X	%6.1f	固定
C2PIX2	=	512.0	/ Reference pixel in Y	%6.1f	固定
C2VAL1	=	1425.72191000	/ Physical value of the reference pixel X grism によって変更	%13.8f	
C2VAL2	=	-16.17306000	/ Physical value of the reference pixel Y	%13.8f	toolkit
C2ELT1	=	0.72880318	/ Size projected into a detector pixel X grism によって変更	%13.8f	
C2ELT2	=	0.00003194	/ Size projected into a detector pixel Y	%13.8f	固定
C2YPE1	=	'WAVELENGTH'	/ Pixel coordinate system	%16s	固定
C2YPE2	=	'DEC--TAN'	/ Pixel coordinate system	%16s	固定
C2NIT1	=	'nm'	/ Units used in both CRVAL1 and CDELT1	%10s	固定
C2NIT2	=	'degree'	/ Units used in both CRVAL2 and CDELT2	%10s	固定
P2001001	=	1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2001002	=	0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2002001	=	0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2002002	=	1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
SLIT	=	'Longslit'	/ Identifier of the entrance slit used 'NONE' if Prism Sp slit-x,slit-y の値で判断 (NONE/Longslit/Pinhole)	%10s	
SLT-LEN	=	120.000	/ Length of the slit used 0.000 if Prism Sp	%7.3f	slit-y 値
SLT-WID	=	0.500	/ Width of the slit used 0.000 if Prism Sp	%6.3f	slit-x 値
SLT-PA	=	0.0	/ Slit Position Angle 0.0 if Prism Sp InR/ImR の値が必要?	%5.1f	
SLTC-RA	=	275.10799000	/ RA of slit center (degree)	%12.8f	toolkit
SLTC-DEC	=	-16.20307900	/ DEC of slit center (degree)	%12.8f	toolkit
SLTCPIX1	=	524.0	/ Slit center projected on detector (pixel)	%7.1f	固定
SLTCPIX2	=	547.0	/ Slit center projected on detector (pixel)	%7.1f	固定
DISPERSR	=	'JH-Grism'	/ Name of disperser used zJ-Grism/JH-Grism/wK-Grism	%15s	
WAVELEN	=	1425.72191	/ Wavelength at detector center (nm) grism によって変更	%10.5f	
WAV-MIN	=	1067.82460	/ Shortest wavelength focused on detector (nm) grism によって変更	%10.5f	
WAV-MAX	=	1814.05960	/ Longest wavelength focused on detector (nm) grism によって変更	%10.5f	
DATE-OBS	=	'1997-08-22'	/ Observation start date (yyyy-mm-dd)	%10s	toolkit
UT	=	'12:34:56.7'	/ HH:MM:SS.S typical UTC at exposure	%10s	toolkit
UT-STR	=	'12:34:56.7'	/ HH:MM:SS.S UTC at start	%10s	toolkit
UT-END	=	'13:04:56.7'	/ HH:MM:SS.S UT at end	%10s	toolkit
HST	=	'02:34:56.7'	/ HH:MM:SS.S Typical HST at exposure 露出開始時の時間+露出時間の半分	%10s	
LST	=	'23:53:10.6'	/ HH:MM:SS.S Typical LST at exposure	%20s	toolkit
MJD	=	5.03965242E+04	/ Modified Julian Day at typical time	%20.8f	toolkit
TIMESYS	=	'UTC'	/ Time system used in this header	%3s	固定
EXPTIME	=	20.0	/ Total integration time (sec)	%8.1f	露出時間
OBJECT	=	'M17'	/ Target Description	%30s	コメント
AZIMUTH	=	-16.6	/ Azimuth angle of telescope pointing	%5.1f	toolkit
ALTITUDE	=	36.4	/ Altitude angle of telescope pointing	%5.1f	toolkit
FOC-POS	=	'NASMYTH-IR'	/ Focus where the instrument is attached Messia 立ち上げ時設定	%12s	
FOC-VAL	=	2.531	/ Encoder value of the focus unit	%10.3f	toolkit
M2-TYPE	=	'IR'	/ Type of Secondary mirror Opt/IR(chop)	%8s	
M2-TIP	=	'Off'	/ Secondary Mirror Tip-Tilt Switch (On/Off)	%3s	
FILTER01	=	'NONE'	/ Filter name/ID z/J/H/K'/K/H+K'/N204/NONE	%10s	
FILTER02	=	'JH-Grism'	/ Filter name/ID H2(1-0)/H2(2-1)/K-cont/Prism/zJ-Grism/JH-Grism/wK-Grism/NONE	%10s	
AIRMASS	=	1.24352	/ Averaged Air Mass	%9.5f	toolkit
ZD	=	36.47	/ Zenith Distance at typical time	%5.2f	toolkit
DAQ-VER	=	1.00	/ Version of the instrument control soft Messia Version	%10s	
INS-VER	=	1.00	/ Version of the instrument Control Board	%10s	
DETECTOR	=	'HAWAII'	/ Name of the detector	%10s	固定
DET-TMP	=	77.0	/ Detector temperature Detector 温度	%5.1f	

		grism によって変更		
C2ELT2 =	0.00003194	/ Size projected into a detector pixel Y	%13.8f	固定
C2YPE1 =	'WAVELENGTH'	/ Pixel coordinate system	%16s	固定
C2YPE2 =	'DEC--TAN'	/ Pixel coordinate system	%16s	固定
C2NIT1 =	'nm'	/ Units used in both CRVAL1 and CDELTA1	%10s	固定
C2NIT2 =	'degree'	/ Units used in both CRVAL2 and CDELTA2	%10s	固定
P2001001=	1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2001002=	0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2002001=	0.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
P2002002=	1.00000000	/ Pixel Coordinate translation matrix	%12.8f	固定
SLIT =	'Longslit'	/ Identifier of the entrance slit used 'NONE' if Prism Sp slit-x, slit-y の値で判断 (NONE/Longslit/Pinhole)	%10s	
SLT-LEN =	120.000	/ Length of the slit used 0.000 if Prism Sp	%7.3f	slit-y 値
SLT-WID =	0.500	/ Width of the slit used 0.000 if Prism Sp	%6.3f	slit-x 値
SLT-PA =	0.0	/ Slit Position Angle 0.0 if Prism Sp ImR の値が必要?	%5.1f	
SLTC-RA =	275.10799000	/ RA of slit center (degree)	%12.8f	toolkit
SLTC-DEC=	-16.20307900	/ DEC of slit center (degree)	%12.8f	toolkit
SLTCPIX1=	524.0	/ Slit center projected on detector (pixel)	%7.1f	固定
SLTCPIX2=	547.0	/ Slit center projected on detector (pixel)	%7.1f	固定
DISPERSR=	'JH-Grism'	/ Name of disperser used zJ-Grism/JH-Grism	%15s	
WAVELEN =	1425.72191	/ Wavelength at detector center (nm) grism によって変更	%10.5f	
WAV-MIN =	1067.82460	/ Shortest wavelength focused on detector (nm) grism によって変更	%10.5f	
WAV-MAX =	1814.05960	/ Longest wavelength focused on detector (nm) grism によって変更	%10.5f	
DATE-OBS=	'1997-08-22'	/ Observation start date (yyyy-mm-dd)	%10s	toolkit
UT =	'12:34:56.7'	/ HH:MM:SS.S typical UTC at exposure	%10s	toolkit
UT-STR =	'12:34:56.7'	/ HH:MM:SS.S UTC at start	%10s	toolkit
UT-END =	'13:04:56.7'	/ HH:MM:SS.S UT at end	%10s	toolkit
HST =	'02:34:56.7'	/ HH:MM:SS.S Typical HST at exposure 露出開始時の時間+露出時間の半分	%10s	
LST =	'23:53:10.6'	/ HH:MM:SS.S Typical LST at exposure	%20s	toolkit
MJD =	5.03965242E+04	/ Modified Julian Day at typical time	%20.8f	toolkit
TIMESYS =	'UTC'	/ Time system used in this header	%3s	固定
EXPTIME =	20.0	/ Total integration time (sec)	%8.1f	露出時間
OBJECT =	'M17'	/ Target Description	%30s	コメント
AZIMUTH =	-16.6	/ Azimuth angle of telescope pointing	%5.1f	toolkit
ALTITUDE=	36.4	/ Altitude angle of telescope pointing	%5.1f	toolkit
FOC-POS =	'NASMYTH-IR'	/ Focus where the instrument is attached Messia 立ち上げ時設定	%12s	
FOC-VAL =	2.531	/ Encoder value of the focus unit	%10.3f	toolkit
M2-TYPE =	'IR'	/ Type of Secondary mirror Opt/IR(chop)	%8s	
M2-TIP =	'Off'	/ Secondary Mirror Tip-Tilt Switch (On/Off)	%3s	
FILTER01=	'NONE'	/ Filter name/ID z/J/H/K'/K/H+K'/N204/NONE	%10s	
FILTER02=	'JH-Grism'	/ Filter name/ID H2(1-0)/H2(2-1)/K-cont/Prism/zJ-Grism/JH-Grism/wK-Grism/NONE	%10s	
AIRMASS =	1.24352	/ Averaged Air Mass	%9.5f	toolkit
ZD =	36.47	/ Zenith Distance at typical time	%5.2f	toolkit
DAQ-VER =	1.00	/ Version of the instrument control soft Messia Version	%10s	
INS-VER =	1.00	/ Version of the instrument Control Board	%10s	
DETECTOR=	'HAWAII'	/ Name of the detector	%10s	固定
DET-TMP =	77.0	/ Detector temperature Detector 温度	%5.1f	
GAIN =	4.60	/ AD conversion factor	%5.2f	固定
DET-NSMP=	12	/ The number of multi-sampling	%2d	1 - 12
PRD-MIN1=	449	/ Start X position of partial read out	%4d	固定
PRD-MIN2=	449	/ Start position Y of partial readout	%4d	固定
PRD-RNG1=	64	/ X Range of the partial read out	%4d	固定
PRD-RNG2=	64	/ Y range of the partial readout	%4d	固定
BIN-FCT1=	1	/ Binning factor of X axis	%2d	固定
BIN-FCT2=	1	/ Binning factor of Y axis	%2d	固定
NAS-TAVE=	273.00	/ Average Value of Nasmyth Enclosure ナスミス温度	%6.2f	
O_MSK =	'JH'	/ MASK Name of OH Suppression Messia 立ち上げ時設定 (O_MSK?)	%30s	
O_SLT =	'1x30'	/ OHS slit 1x30/0.5x30/30x30/Blank/Mirror/Pinhole/Test (O_SLT?)	%30s	
O_SLTLEN=	30.000	/ OHS slit length (arcsec) OHS slit によって変更 (O_SLTLEN?)	%7.3f	
O_SLTWID=	1.000	/ OHS slit width (arcsec) OHS slit によって変更 (O_SLTWID?)	%7.3f	
O_FOCVAL=	108.240	/ OHS FOCUS Value Camera 位置 (O_FOCVAL?)	%7.3f	

```

INSTRUME= 'OHS' , / Name of Instrument %10s
Messia 立ち上げ時設定
TELESCOP= 'SUBARU' , / Telescope Name %6s 固定
OBSERVAT= 'NAOJ' , / Observatory Name %4s 固定
BLANK = 32768.00 / Value used for NULL pixels %8.2f 固定
BSCALE = 1.00 / Real = fits-value*BSCALE+BZERO %12.2f 固定
BUNIT = 'ADU' , / Unit of original pixel values %3s 固定
BZERO = 0.00 / Real = fits-value*BSCALE+BZERO %12.2f 固定
EXTEND = F / The existence of extension or not (T or F) %1s 固定
END

```

6.5.6 Suprime-Cam (1998/08/19)

	1	2	3	4	5	6	7	8	9
1234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890									
SIMPLE =			T	/ file does conform to FITS standard				L1	
BITPIX =			16	/ number of bits per data pixel				I3	
NAXIS =			2	/ number of data axes				I1	
NAXIS1 =			2048	/ length of data axis 1				I5	
NAXIS2 =			4096	/ length of data axis 2				I5	
EXTEND =			T	/ FITS dataset may contain extensions				L1	
BZERO =			32768.0	/ offset data range to that of unsigned short				F6.1	
BSCALE =			1.0	/ default scaling factor				F6.1	
BUNIT = 'ADU'				/ Unit of original pixel value				A3	
BLANK =			-32768	/ Value used for NULL pixels				I6	
DATE-OBS= '1999-04-01'				/ Observation start date (yyyy-mm-dd)				A10	
UT = '09:15:04.5'				/ HH:MM:SS.S typical UTC at the exposure (middle)				A10	
UT-STR = '09:12:34.5'				/ HH:MM:SS.S UTC at the start exposure time				A10	
UT-END = '09:17:34.5'				/ HH:MM:SS.S UTC at the end of the exposure				A10	
HST = '23:15:04.5'				/ HH:MM:SS.S Typical HST at exposure				A10	
HST-STR = '23:12:34.5'				/ HH:MM:SS.S HST at the beginning of exp.				A10	
HST-END = '23:17:34.5'				/ HH:MM:SS.S HST at the end of exposure				A10	
LST = '11:33:21.345'				/ HH:MM:SS.SSS Typical LST at exposure				A12	
LST-STR = '11:30:50.912'				/ HH:MM:SS.SSS LST at the beginning of exposure				A12	
LST-END = '11:35:51.723'				/ HH:MM:SS.SSS LST at the end of exposure				A12	
MJD =			51635.385469	/ [d] Mod. Julian Date at typical time				F12.6	
TIMESYS = 'UTC'				/ Time System used in the header				A3	
MJD-STR =			51635.383733	/ [d] Mod. Julian Date at the start of exposure				F12.6	
MJD-END =			51635.387205	/ [d] Mod. Julian Date at the end of exposure				F12.6	
ZD-STR =			10.050	/ [degree] Zenith Distance at exposure start time				F6.3	
ZD-END =			9.740	/ [degree] Zenith Distance at exposure end time				F6.3	
SECZ-STR =			1.017	/ SEC(Zenith Distance) at exposure start time				F6.3	
SECZ-END =			1.015	/ SEC(Zenith Distance) at exposure end time				F6.3	
AIRMASS =			1.0160	/ Average airmass during exposure				F6.4	
AZIMUTH =			319.320	/ [degree] Azimuth of tel-pointing. 0:S->90:W				F7.3	
ALTITUDE =			79.880	/ [degree] Altitude ang. of telescope pointing				F7.3	
PROP-ID = 'P19990025-0001'				/ Proposal ID				A20	
OBSERVER= 'Shimasaku, Yagi, Hamabe'				/ Names of the Observers				A64	
FRAMEID = 'SUPA00000001'				/ Image sequential number				A16	
EXP-ID = 'SUPE00000001'				/ ID of exposure (shot) this data were taken				A16	
OBS-MOD = 'Imaging'				/ Observation Mode				A20	
DATA-TYP = 'OBJECT'				/ Characteristics of this data				A10	
OBJECT = 'artificial sky'				/ Identification of object observed				A30	
RA = '12:00:00.000'				/ Right ascension of telescope pointing (J2000)				A12	
DEC = '+12:00:00.00'				/ Declination of telescope pointing (J2000)				A12	
RADECSYS = 'FK5'				/ The equatorial coordinate system				A8	
EQUINOX =			2000.0	/ [y] Equinox				F6.1	
CTYPE1 = 'RA---TAN'				/ Pixel coordinate system in axis 1				A8	
CRPIX1 =			1.0	/ Reference pixel coordinate system in axis 1				F8.1	
CRVAL1 =			180.1802512	/ [degree] Physical value of the reference pixel				F11.7	
CDEL1 =			-5.55555556E-05	/ [degree] Pixel size in axis 1				E15.8	
CUNIT1 = 'degree'				/ Unit used in both CRVAL1 and CDEL1				A10	
CTYPE2 = 'DEC--TAN'				/ Pixel coordinate system in axis 2				A8	
CRPIX2 =			1.0	/ Reference pixel coordinate system in axis 2				F8.1	
CRVAL2 =			12.0006534	/ [degree] Physical value of the reference pixel				F10.7	
CDEL2 =			5.55555556E-05	/ [degree] Pixel size in axis 2				E15.8	
CUNIT2 = 'degree'				/ Unit used in both CRVAL2 and CDEL2				A10	
LONGPOLE =			180.0	/ The native system of the N.P. in the std. sys.				F6.1	
PC001001 =			1.00000000	/ Pixel coordinate translation matrix				F12.8	
PC001002 =			0.00000000	/ Pixel coordinate translation matrix				F12.8	
PC002001 =			0.00000000	/ Pixel coordinate translation matrix				F12.8	
PC002002 =			1.00000000	/ Pixel coordinate translation matrix				F12.8	
PROJP1 =			0.0	/ Projection type of the axis 1				F5.1	
PROJP2 =			0.0	/ Projection type of the axis 2				F5.1	
WCS-ORIG = 'ROUGH estimation'				/ Origin/quality of the WCS values				A20	
OBSERVAT = 'NAOJ'				/ Observatory				A4	
TELESCOP = 'Subaru'				/ Telescope name				A6	
FOC-POS = 'PRIME'				/ Position of the instrument focus unit				A8	
FOC-VAL =			1234.567	/ [mm] Encoder value of the focus unit				F10.3	

```

FILTER01= 'SDSS-R1' / Filter name/ID A30
EXPTIME = 300.0 / [sec] Total integration time F7.1
INSTRUME= 'SuprimeCam' / Name of instrument A15
DETECTOR= 'Hektro_CCD_XY1230Z' / Name of the detector/CCD A40
DET-ID = 1 / ID of the detector used for this data I2
DET-A01 = 0.000 / [degree] Relative angle of the nn-th detector F7.3
DET-P101= 126.880 / [mm] Relative X-position of the nn-th detector F7.3
DET-P201= 62.440 / [mm] Relative Y-position of the nn-th detector F7.3
DET-TMP = 153.25 / [Kelvin] Detector temperature F6.2
DET-TMED= 153.24 / [Kelvin] Median of the detector temperature F6.2
DET-TMIN= 153.11 / [Kelvin] Minimum of the detector temperature F6.2
DET-TMAX= 153.37 / [Kelvin] Maximum of the detector temperature F6.2
GAIN = 3.456 / AD conversion factor (electron/ADU) F6.3
EFP-MIN1= 21 / Start position of effective frame in axis-1 I5
EFP-RNG1= 2008 / Range of effective frame in axis-1 I5
EFP-MIN2= 21 / Start position of effective frame in axis-2 I5
EFP-RNG2= 4056 / Range of effective frame in axis-2 I5
PRD-MIN1= 6 / Start X position of partially read out I5
PRD-RNG1= 2048 / X range of the partially readout I5
PRD-MIN2= 6 / Start Y position of partially read out I5
PRD-RNG2= 4096 / Y range of the partially readout I5
BIN-FCT1= 1 / Binning factor of axis 1 I2
BIN-FCT2= 1 / Binning factor of axis 2 I2
DET-VER = 'V.1.0.0' / Version of the detector control command A30
INS-VER = 'SC1.000/MS1.201' / Version of the instrument (hard/soft) A30
WEATHER = 'Clear' / Weather condition A50
SEEING = 0.60 / [arcsec] FWHM of the star at telescope focus F5.2
ADC-TYPE= 'RED' / ADC name if it is used. (BLUE, RED, NONE) A30
ADC-STR = 12.345 / [degree] ADC pos. ang. at the start of exposure F7.3
ADC-END = 23.456 / [degree] ADC pos. ang. at the end of exposure F7.3
INR-STR = 23.456 / [degree] Inst. rotator angle at start F8.3
INR-END = 34.567 / [degree] Inst. rotator angle at end F8.3
DOM-WND = 0.10 / [m/s] Wind speed in the dome/enclosure F5.2
OUT-WND = 1.30 / [m/s] Wind speed outside dome/enclosure F5.2
DOM-TMP = 274.23 / [Kelvin] Atm. temp. in the dome/enclosure F6.2
OUT-TMP = 274.37 / [Kelvin] Atm. temp. outside the dome/encl. F6.2
DOM-HUM = 32.3 / [%] Humidity in the dome F5.1
OUT-HUM = 27.9 / [%] Humidity outside the dome/encl. F5.1
DOM-PRS = 1013.12 / [hPa] Atm. pressure in the dome F7.2
OUT-PRS = 1013.12 / [hPa] Atm. press. outside the dome/encl. F7.2
COMMENT -----
COMMENT ----- PARAMETERS FOR SUPRIME_CAM -----
COMMENT -----
S_UFNAME= 'test_field_1' / User assigned file name A40
S_FRMPOS= '0101' / Frame position (IIJJ) A4
S_BCTAVE= 5319.300 / [ADU] Average count outside effective data F9.3
S_BCTSD = 12.300 / [ADU] S.D. of the count outside the eff. data F9.3
S_AG-OBJ= 'HD12345' / Name of the guide-star A40
S_AG-RA = '12:34:56.789' / R.A. of the guide-star A12
S_AG-DEC= '+12:34:56.78' / Dec. of the guide-star A12
S_AG-EQN= 2000.0 / [y] Equinox of the guide-star position F6.1
S_AG-X = 12.34 / [mm] Position of the guiding probe (X) F7.2
S_AG-Y = 12.34 / [mm] Position of the guiding probe (Y) F7.2
S_AG-R = 34.56 / [mm] Position of the guiding probe (R) F7.2
S_AG-TH = 12.34 / [degree] Position of the guiding probe (theta) F7.2
S_ETMED = 275.59 / [Kelvin] Averaged temp. in Camera enclosure F6.2
S_ETMAX = 275.81 / [Kelvin] Maximum temp. in Camera enclosure F6.2
S_ETMIN = 275.41 / [Kelvin] Minimum temp. in Camera enclosure F6.2
END

```

6.5.7 MIRTOS (1998/09/03)

● MIRTOS の MIR mode および ASCII Table Extension

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / Standard FITS format
BITPIX = 32 / Number of bits storing pix values
NAXIS = 3 / Number of axis in frame
NAXIS1 = 336 / Number of pixels/row
NAXIS2 = 240 / Number of rows
NAXIS3 = 10 / Number of frames
EXTEND = T / ASCII Table for Z-frame description
COMMENT Sample Primary header for MIRTOS written by Tomono on 1998/9/2
COMMENT Updated: string format %-30s => %-8.30s, M_BEAM, M_OBSID
OBSERVER= 'D.Tomono, Y.Doi, T.Nishimura' / Name of observers
PROP-ID = 'P1998-0430-1' / Proposal ID
DATASET = 'Used for DASH' / What is this? Ref. George
INSTRUME= 'MIRTOS' / Name of instrument

```

```

INS-VER = '1.1 980701' / Version of the instrument
FRAMEID = 'MIRA000000001' / FITS File sequential number
EXP-ID = 'MIRM000000001'
OBS-MOD = 'imaging' / Observation Mode
DATA-TYP= 'object' / object/flat/pupil/pupil_flat/dark
OBSERVAT= 'NAOJ'
TELESCOP= 'Subaru'
CRPIX1 = 160.0 / Reference pixel in X (pixel)
CRPIX2 = 120.0 / Reference pixel in Y (pixel)
CRVAL1 = 189.00529167 / Physical value of the reference pixel X
CRVAL2 = -39.86927778 / Physical value of the reference pixel Y
CDELT1 = 0.0000186328 / X Scale projected on detector(#/pix)
CDELT2 = 0.0000186328 / Y scale projected on detector(#/pix)
CTYPE1 = 'RA--TAN' / Pixel coordinate system
CTYPE2 = 'DEC--TAN' / Pixel coordinate system
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDELT1
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDELT2
TIMESYS = 'UTC' / Time System used in the header. UTC fix.
RADECSYS= 'FK5' / The equatorial coordinate system
PROJP1 = 0.0 / Projection type of the first axis
PROJP2 = 0.0 / Projection type of the second axis
LONGPOLE= 180.00000 / The North Pole of standard system (deg)
PC001001= 1.00000000 / Pixel Coordinate translation matrix
PC001002= 0.00000000 / Pixel Coordinate translation matrix
PC002001= 0.00000000 / Pixel Coordinate translation matrix
PC002002= 1.00000000 / Pixel Coordinate translation matrix
BSCALE = 1 / Real=fits-value*BSCALE+BZERO
BZERO = 0 / Real=fits-value*BSCALE+BZERO
BUNIT = 'ADU' / Unit of original pixel values
BLANK = 32768 / Value used for NULL pixels
DATE-OBS= '1998-04-30' / yyyy-mm-dd UTC obs start date
UT = '09:12:00.0' / HH:MM:SS.S UTC at typical time(=start)
HST = '23:12:00.0' / HH:MM:SS.S HST at typical time(=start)
LST = '12:34:56.7' / HH:MM:SS.S LST at typical time(=start)
MJD = 12345.67890000 / Modified Julian Day at typical time(=start)
EXPTIME = 0.0800 / Total integration time per frame(sec)
OBJECT = 'HR 4796' / Target Description
RA = '12:36:01.270' / HH:MM:SS.SSS RA (J2000) pointing
RA2000 = '12:36:01.270' / HH:MM:SS.SSS RA (J2000) pointing
DEC = '-39:52:09.40' / +/-DD:MM:SS.SS DEC (J2000) pointing
DEC2000 = '-39:52:09.40' / +/-DD:MM:SS.SS DEC (J2000) pointing
EQUINOX = 2000.0
AZIMUTH = 12.34000 / Azimuth of telescope pointing (degree)
ALTITUDE= 12.34000 / Altitude of telescope pointing(degree)
FOC-POS = 'CASSEGRAIN' / Focus where the instrument is attached
FOC-LEN = 100000.000 / Focal length of the telescope (mm)
FOC-VAL = 2.531 / Encoder value of the focus unit (mm)
M2-TYPE = 'IR' / Type of the secondary mirror (Opt/IR)
M2-TIP = 'off' / Tip/Tilt of the Secondary Mirror (on/off)
APERTURE= '21x16' / Field stop ID
INR-STR = 12.345 / Instrument Rotator angle at Start (deg)
INR-END = 12.345 / Instrument Rotator angle at End (deg)
AIRMASS = 4.67918 / Averaged Air Mass
ZD = 77.660 / Zenith Distance at typical time
SECZ = 4.679 / SEC(Zenith Distance) at typical time
M_WINDOW= 'ZnSe' / MIRTOS dewar entrance window
M_M1MOT1= 224 / Beam Stearing Mirror Direction (count)
M_M1MOT2= 339 / Beam Stearing Mirror Direction (count)
M_M2MOT1= 224 / Beam Splitter Direction (count)
M_M2MOT2= 339 / Beam Splitter Direction (count)
FILTER01= 'Through' / Filter name/ID
FILTER02= 'Q' / Filter name/ID
FILTER03= '30mm-phi' / Lyot Stop name/ID
DETECTOR= 'Ratheon Si:As IBC 320x240' / Name of the detector/CCD
DET-ID = 1 / ID of the detector used for this data
DETPXSZ1= 0.050 / Detector pixel size in axis1 (mm)
DETPXSZ2= 0.050 / Detector pixel size in axis2 (mm)
DET-A00 = 0.100 / Relative angle of nn-th detector (deg)
DET-TMP = 6.01 / Detector temperature (K)
GAIN = 330.90 / AD conversion factor (electron/ADU)
PRD-MIN1= 1 / Start X pos. of partially read out (pix)
PRD-MIN2= 1 / Start Y pos. of partially read out (pix)
PRD-RNG1= 320 / X Range of partially read out (pix)
PRD-RNG2= 240 / Y Range of partially read out (pix)
BIN-FCT1= 1 / Binning factor of X axis (pixel)
BIN-FCT2= 1 / Binning factor of Y axis (pixel)
COMMENT === Beam: U(chop+,nod+) u(-,+ ) D(+,-) d(-,-) X(other) C(Cont)
M_BEAM = 1 / Number of Beam Description Keywords M_BEAMn
M_BEAM1 = 'UUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUUU'
COMMENT === Beams are also described in Ascii table extension
WEATHER = 'Sunny' / Weather condition
SEEING = 0.45 / Long integ PSF FWHM (arcsec)
DOM-WND = 4.61 / Wind speed in the dome (m/s)
OUT-WND = 7.79 / Wind speed outside (m/s)

```

```

DOM-TMP =          273.5 / Temperature measured in the dome (K)
OUT-TMP =          273.7 / Temperature measured outside dome (K)
DOM-HUM =          0.050 / Humidity measured in the dome
OUT-HUM =          0.060 / Humidity measured outside the dome
DOM-PRS =          670.00 / Atmospheric pressure in the Dome (hpa)
OUT-PRS =          670.00 / Atmospheric pressure outside dome (hPa)
COMMENT
COMMENT (: Subaru Device Dependent Header for MIRTOS :)
COMMENT
COMMENT === ID
M_CHID = 'MIR' , / ID of camera channel of MIRTOS
M_OBSID = '19980430-0001' / ID of set of chop/nod observation
M_TWID = '19980430-0010' / ID of two-wavelength simultaneous file
M_FLATID= 'NA' , / ID of the most recent flat field file
M_DARKID= 'NA' , / ID of the most recent dark exposure file
M_DET01 =          12.30000 / Rel X pos of NIR from MIR on sky (pixel)
M_DET02 =          45.60000 / Rel Y pos of NIR from MIR on sky (pixel)
COMMENT === Chopping and Nodding
M_CHOPTH=          0.20 / Chopping period (sec)
M_CHOPTH=          90.00 / Chopping throw (arcsec)
M_CHOPPA=          0.00 / Chopping P.A. origin:source/pointing (deg)
M_NODTM =          10.0 / Nodding period (sec)
M_NODTH =          90.00 / Nodding throw (arcsec)
M_NODPA =          90.00 / Nodding P.A. origin:source/pointing (deg)
COMMENT === M_RF are Reference Square Corners in Pix, -1:NA 0:No ref in image
M_RFX1PP=          -1 / Corner 1 X for Chop+ Nod+
M_RFY1PP=          -1 / Corner 1 Y for Chop+ Nod+
M_RFX2PP=          -1 / Corner 2 X for Chop+ Nod+
M_RFY2PP=          -1 / Corner 2 Y for Chop+ Nod+
M_RFX1MP=          -1 / Corner 1 X for Chop- Nod+
M_RFY1MP=          -1 / Corner 1 Y for Chop- Nod+
M_RFX2MP=          -1 / Corner 2 X for Chop- Nod+
M_RFY2MP=          -1 / Corner 2 Y for Chop- Nod+
M_RFX1PM=          -1 / Corner 1 X for Chop+ Nod-
M_RFY1PM=          -1 / Corner 1 Y for Chop+ Nod-
M_RFX2PM=          -1 / Corner 2 X for Chop+ Nod-
M_RFY2PM=          -1 / Corner 2 Y for Chop+ Nod-
M_RFX1MM=          -1 / Corner 1 X for Chop- Nod-
M_RFY1MM=          -1 / Corner 1 Y for Chop- Nod-
M_RFX2MM=          -1 / Corner 2 X for Chop- Nod-
M_RFY2MM=          -1 / Corner 2 Y for Chop- Nod-
COMMENT === Temperature
M_O-TMP =          35.6 / Temperature of Optics (K)
M_A-TMP1=          300.1 / Temperature of Ambient thermometer (K)
M_A-TMP2=          350.3 / Temperature of Ambient thermometer (K)
M_A-TMP3=          280.4 / Temperature of Ambient thermometer (K)
M_A-TMP4=          300.1 / Temperature of Ambient thermometer (K)
COMMENT === Clock
M_CLKFL = '/common/clock/980828/twsaa2_mir' / Clock file name
M_CLKMR = 'chop02nod10_1' / Clock pattern marco name
M_CLKMC = 'This is only preliminary' / Coment on clock pattern macro
M_PIXTIM=          5.0 / Clock duration for a pixel (us)
M_FRTIME=          32.3 / Time to sweep one frame (ms)
COMMENT === FMC
M_JPORT =          0 / Jump port value at the time of getting data
M_REFSUB=          T / Subtraction of reference column T:done
M_ARRANG= 'Raw980828' / Data sequence FITS/Raw-hardware version
M_BANK = 'A' , / Bank name where the data was stored
COMMENT == BlackBody
M_BBPOS =          F / Black Body Position T:In F:Out
M_BBTMP =          270.0 / Temperature of Black Body (K)
END

XTENSION= 'TABLE' , / ASCII Table extension
BITPIX =          8 / Number of bits storing pix values
NAXIS =          2 / Number of axis in frame
NAXIS1 =          17 / Number of characotors in a row
NAXIS2 =          10 / Number of rows = number of frames
PCOUNT =          0 / No random parameters
GCOUNT =          1 / Only one group
TFIELDS =          4 / Number of fields in a row
EXTNAME = 'Frames' , / Name

TTYPE1 = 'Chop' , / Chop beam: +/-
TBCOL1 =          1 / start column of this field
TFORM1 = 'A1' , / 1 charactor

TTYPE2 = 'Nod' , / Nod beam: +/-
TBCOL2 =          2 / start column of this field
TFORM2 = 'A1' , / 1 charactor

TTYPE3 = 'NumReads' / Number of read outs for a pixel
TBCOL3 =          3 / start column of this field
TFORM3 = 'I6' , / 6 digit integer

```

```

TUNIT3 = 'Samples '          / unti: ADC Samplings for a pixel

TTYPE4 = 'WaitTime'          / Wait time for secondary stabilization
TBCOL4 = = '          '      9 / start column of this field
TFORM4 = 'F10.4 '           / 9 digit floating down to ius + space
TUNIT4 = 'ms '              / units: milli-second

TTYPE5 = 'NDRate '          / Integration Duty Cycle x/243 only MIR
TBCOL5 = = '          '     19 / start column of this field
TFORM5 = 'I4 '              / 3 digit integer + space
TUNIT5 = 'rows '            / units: milli-second

TTYPE6 = 'CentroiX'          / Centroid X Position of Refernce Source
TBCOL6 = = '          '     23 / start column of this field
TFORM6 = 'F7.1 '           / 6 digit floating down to .1 pix + space
TUNIT6 = 'pix '             / units: pix -1:NA

TTYPE7 = 'CentroiY'          / Centroid Y Position of Refernce Source
TBCOL7 = = '          '     30 / start column of this field
TFORM7 = 'F7.1 '           / 6 digit floating down to .1 pix + space
TUNIT7 = 'pix '             / units: pix -1:NA

TTYPE8 = 'PeakX '           / Peak X Position of Refernce Source
TBCOL8 = = '          '     37 / start column of this field
TFORM8 = 'F7.1 '           / 6 digit floating down to .1 pix + space
TUNIT8 = 'pix '             / units: pix -1:NA

TTYPE9 = 'PeakY '           / Peak Y Position of Refernce Source
TBCOL9 = = '          '     44 / start column of this field
TFORM9 = 'F7.1 '           / 6 digit floating down to .1 pix + space
TUNIT9 = 'pix '             / units: pix -1:NA

COMMENT Sample ASCII Extension header for MIRTOS written by Tomono on 1998/9/2
COMMENT Storage of Centeroid/peak position needs to be thought again
END

```

● MIRTOS の NIR mode および ASCII Table Extension

```

1      2      3      4      5      6      7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / Standard FITS format
BITPIX = 32 / Number of bits storing pix values
NAXIS = 3 / Number of axis in frame
NAXIS1 = 256 / Number of pixels/row
NAXIS2 = 256 / Number of rows
NAXIS3 = 10 / Number of frames
EXTEND = T / ASCII Table for Z-frame description
COMMENT Sample Primary header for MIRTOS written by Tomono on 1998/9/2
COMMENT Updated: string format %-30s => %-8.30s, M_BEAM, M_OBSID
OBSERVER= 'D.Tomono, Y.Doi, T.Nishimura' / Name of observers
PROP-ID = 'P1998-0430-1' / Proposal ID
DATASET = 'Used for DASH' / What is this? Ref. George
INSTRUME= 'MIRTOS ' / Name of instrument
INS-VER = '1.1 980701' / Version of the instrument
FRAMEID = 'MIRA000000002' / FITS File sequential number
EXP-ID = 'MIRN000000001'
OBS-MOD = 'imaging ' / Observation Mode
DATA-TYP= 'object ' / object/flat/pupil/pupil_flat/dark
OBSERVAT= 'NAOJ '
TELESCOP= 'Subaru '
CRPIX1 = 128.0 / Reference pixel in X (pixel)
CRPIX2 = 128.0 / Reference pixel in Y (pixel)
CRVAL1 = 189.00529167 / Physical value of the reference pixel X
CRVAL2 = -39.86927778 / Physical value of the reference pixel Y
CDEL1 = 0.0000076860 / X Scale projected on detector(#/pix)
CDEL2 = 0.0000076860 / Y scale projected on detector(#/pix)
CTYPE1 = 'RA--TAN ' / Pixel coordinate system
CTYPE2 = 'DEC--TAN' / Pixel coordinate system
CUNIT1 = 'degree ' / Units used in both CRVAL1 and CDEL1
CUNIT2 = 'degree ' / Units used in both CRVAL2 and CDEL2
TIMESYS = 'UTC ' / Time System used in the header. UTC fix.
RADECSYS= 'FK5 ' / The equatorial coordinate system
PROJ1 = 0.0 / Projection type of the first axis
PROJ2 = 0.0 / Projection type of the second axis
LONGPOLE= 180.00000 / The North Pole of standard system (deg)
PC001001= 1.00000000 / Pixel Coordinate translation matrix
PC001002= 0.00000000 / Pixel Coordinate translation matrix
PC002001= 0.00000000 / Pixel Coordinate translation matrix
PC002002= 1.00000000 / Pixel Coordinate translation matrix
BSCALE = 1 / Real=fits-value*BSCALE+BZERO
BZERO = 0 / Real=fits-value*BSCALE+BZERO

```



```

M_RFX1MP=-1 / Corner 1 X for Chop- Nod+
M_RFY1MP=-1 / Corner 1 Y for Chop- Nod+
M_RFX2MP=-1 / Corner 2 X for Chop- Nod+
M_RFY2MP=-1 / Corner 2 Y for Chop- Nod+
M_RFX1PM=-1 / Corner 1 X for Chop+ Nod-
M_RFY1PM=-1 / Corner 1 Y for Chop+ Nod-
M_RFX2PM=-1 / Corner 2 X for Chop+ Nod-
M_RFY2PM=-1 / Corner 2 Y for Chop+ Nod-
M_RFX1MM=-1 / Corner 1 X for Chop- Nod-
M_RFY1MM=-1 / Corner 1 Y for Chop- Nod-
M_RFX2MM=-1 / Corner 2 X for Chop- Nod-
M_RFY2MM=-1 / Corner 2 Y for Chop- Nod-
COMMENT === Temperature
M_O-TMP = 56.7 / Temperature of Optics (K)
M_A-TMP1= 300.1 / Temperature of Ambient thermometer (K)
M_A-TMP2= 350.3 / Temperature of Ambient thermometer (K)
M_A-TMP3= 280.4 / Temperature of Ambient thermometer (K)
M_A-TMP4= 300.1 / Temperature of Ambient thermometer (K)
COMMENT === Clock
M_CLKFL = '/common/clock/980828/twsaa2_mir' / Clock file name
M_CLKMR = 'chop02nod10_1' / Clock pattern marco name
M_CLKMC = 'This is only preliminary' / Coment on clock pattern macro
M_PIXTIM= 6.1 / Clock duration for a pixel (us)
M_FRTIME= 32.3 / Time to sweep one frame (ms)
COMMENT === FMC
M_JPORT = 0 / Jump port value at the time of getting data
M_ARRANG= 'Raw980828' / Data sequence FITS/Raw-hardware version
M_BANK = 'A' / Bank name where the data was stored
COMMENT == BlackBody
M_BBPOS = F / Black Body Position T:In F:Out
M_BBTMP = 270.0 / Temperature of Black Body (K)
END

XTENSION= 'TABLE' / ASCII Table extension
BITPIX = 8 / Number of bits storing pix values
NAXIS = 2 / Number of axis in frame
NAXIS1 = 17 / Number of characotors in a row
NAXIS2 = 10 / Number of rows = number of frames
PCOUNT = 0 / No random parameters
GCOUNT = 1 / Only one group
TFIELDS = 4 / Number of fields in a row
EXTNAME = 'Frames' / Name

TTYPE1 = 'Chop' / Chop beam: +/-
TBCOL1 = 1 / start column of this field
TFORM1 = 'A1' / 1 charactor

TTYPE2 = 'Nod' / Nod beam: +/-
TBCOL2 = 2 / start column of this field
TFORM2 = 'A1' / 1 charactor

TTYPE3 = 'NumReads' / Number of read outs for a pixel
TBCOL3 = 3 / start column of this field
TFORM3 = 'I6' / 6 digit integer
TUNIT3 = 'Samples' / untis: ADC Samplings for a pixel

TTYPE4 = 'WaitTime' / Wait time for secondary stabilization
TBCOL4 = 9 / start column of this field
TFORM4 = 'F10.4' / 9 digit floating down to ius + space
TUNIT4 = 'ms' / units: milli-second

TTYPE5 = 'MIR_ND' / Integration Duty Cycle x/243 only MIR
TBCOL5 = 19 / start column of this field
TFORM5 = 'I4' / 3 digit integer + space
TUNIT5 = 'rows' / units: milli-second

TTYPE6 = 'CentroiX' / Centroid X Position of Refernce Source
TBCOL6 = 23 / start column of this field
TFORM6 = 'F7.1' / 6 digit floating down to .1 pix + space
TUNIT6 = 'pix' / units: pix -1:NA

TTYPE7 = 'CentroiY' / Centroid Y Position of Refernce Source
TBCOL7 = 30 / start column of this field
TFORM7 = 'F7.1' / 6 digit floating down to .1 pix + space
TUNIT7 = 'pix' / units: pix -1:NA

TTYPE8 = 'PeakX' / Peak X Position of Refernce Source
TBCOL8 = 37 / start column of this field
TFORM8 = 'F7.1' / 6 digit floating down to .1 pix + space
TUNIT8 = 'pix' / units: pix -1:NA

TTYPE9 = 'PeakY' / Peak Y Position of Refernce Source
TBCOL9 = 44 / start column of this field
TFORM9 = 'F7.1' / 6 digit floating down to .1 pix + space

```

```
TUNIT9 = 'pix' , / units: pix -1:NA

COMMENT Sample ASCII Extension header for MIRTOS written by Tomono on 1998/9/2
COMMENT Storage of Centeroid/peak position needs to be thought again
END
```

6.5.8 IRCS (1999/03/02)

● IRCS の Imaging mode

	1	2	3	4	5	6	7	8	9
12345678901234567890123456789012345678901234567890123456789012345678									
SIMPLE =			T	/ SIMPLE must be 'T' for confirming FITS					%1s
BITPIX =		16	/	# of bits storing pix values					%2d
NAXIS =		2	/	# of axes in frame					%1d
NAXIS1 =		1024	/	# of pixels/row					%5d
NAXIS2 =		1024	/	# of rows (also # of scan lines)					%5d
DISPAXIS=		2	/	# of axis describing dispersion direction					%1s
OBSERVER=	'Kobayashi et al.'			/ Name of observer					%30s
PROP-ID =	'o99003'			/ Proposal ID					%20s
FRAME-ID=	'IRCA00002347'			/ Image sequential number					%16s
EXP-ID =	'IRCA00002347'			/ ID of the exposure this data was taken					%16s
OBS-MOD =	'IMAGING'			/ Observation Mode					%30s
DET-ID =		1	/	ID of the detector (1 : CAMERA, 2 : SPECTROGRAPH)					%2d
DETECTOR=	'Aladdin SN-####'			/ Name of the detector/CCD					%10s
DATASET =	'????????'			/ ID of an observation dataset					%20s
DATA-TYP=	'OBJECT'			/ Type / Characteristics of this data					%10s
WCS-ORIG=	'????????'			/ Origin of WCS value					%20s
RA =	'18:20:26.010'			/ HH:MM:SS.SSS RA pointing					%12s
DEC =	'-16:12:07.06'			/ +/-DD:MM:SS.SS DEC pointing					%12s
EQUINOX =		2000.0	/	Standard FK5 (years)					%6.1f
RADECSYS=	'FK5'			/ The equatorial coordinate system					%8s
RA2000 =	'18:20:26.010'			/ HH:MM:SS.SSS RA (J2000) pointing					%12s
DEC2000 =	'-16:12:07.06'			/ +/-DD:MM:SS.SS DEC (J2000) pointing					%12s
FILTER01=	'K-prime'			/ Filter name/ID					%30s
FILTER02=	'NONE'			/ Filter name/ID					%30s
FILTER03=	'PK50'			/ Filter name/ID					%30s
CTYPE1 =	'RA---TAN'			/ Pixel coordinate system					%16s
CTYPE2 =	'DEC--TAN'			/ Pixel coordinate system					%16s
CUNIT1 =	'degree'			/ Units used in both CRVAL1 and CDELT1					%10s
CUNIT2 =	'degree'			/ Units used in both CRVAL2 and CDELT2					%10s
CRPIX1 =		512.0	/	Reference pixel in X					%6.1f
CRPIX2 =		512.0	/	Reference pixel in Y					%6.1f
CRVAL1 =		275.10837500	/	Physical value of the reference pixel X					%13.8f
CRVAL2 =		-16.17306000	/	Physical value of the reference pixel Y					%13.8f
CDELT1 =		0.00003194	/	Size projected into a detector pixel X					%13.8f
CDELT2 =		0.00003194	/	Size projected into a detector pixel Y					%13.8f
PROJP1 =		0.0	/	Projection Type of the first axis					%5.1f
PROJP2 =		0.0	/	Projection Type of the second axis					%5.1f
LONGPOLE=		180.0	/	The North Pole of the standard system					%6.1f
PC001001=		1.00000000	/	Pixel Coordinate translation matrix					%12.8f
PC001002=		0.00000000	/	Pixel Coordinate translation matrix					%12.8f
PC002001=		0.00000000	/	Pixel Coordinate translation matrix					%12.8f
PC002002=		1.00000000	/	Pixel Coordinate translation matrix					%12.8f
DATE-OBS=	'1997-08-22'			/ Observation start date (yyyy-mm-dd)					%10s
UT =	'12:34:56.7'			/ HH:MM:SS.S typical UTC at exposure					%10s
UT-STR =	'12:34:56.7'			/ HH:MM:SS.S UTC at start					%10s
UT-END =	'13:04:56.7'			/ HH:MM:SS.S UT at end					%10s
HST =	'02:34:56.7'			/ HH:MM:SS.S Typical HST at exposure					%10s
LST =	'23:53:10.6'			/ HH:MM:SS.S Typical LST at exposure					%20s
MJD =		5.03965242E+04	/	Modified Julian Day at typical time					%20.8f
TIMESYS=	'UTC'			/ Time system used in this header					(%3s)
EXPTIME =		20.0	/	Total integration time (sec)					%8.1f
DET-NSMP=		8	/	Number of multi-sample (e.g., non-destructive reads)					%3d
COADDS =		10	/	Number of Coadds					%4d
OBJECT =	'M17'			/ Target Description					%30s
AZIMUTH =		-16.6	/	Azimuth angle of telescope pointing					%5.1f
ALTITUDE=		36.4	/	Altitude angle of telescope pointing					%5.1f
FOC-POS =	'CASSEGRAIN'			/ Focus where the instrument is attached					%12s
FOC-VAL =		2.531	/	Encoder value of the focus unit					%10.3f
AIRMASS =		1.24352	/	Averaged Air Mass					%9.5f
ZD =		36.47	/	Zenith Distance at typical time					%5.2f
DAQ-VER =		1.00	/	Version of the instrument control soft					%6.2f
INS-VER =		1.00	/	Version of the instrument					%6.2f
DET-TMP =		30.0	/	Detector temperature					%5.1f
GAIN =		10.00	/	AD conversion factor					%5.2f
BIN-FCT1=		1	/	Binning factor of X axis					%2d
BIN-FCT2=		1	/	Binning factor of Y axis					%2d
CS-TAVE =		273.00	/	Average Value of Cassegrain Enclosure (Container)					%6.2f

```

TELCUS= 'CASSEGRAIN' / %10s
OBS-ALOC= 'Observation' / Observation or Standby %12s
INSTRUME= 'IRCS' / Name of Instrument %20s
TELESCOP= 'SUBARU' / Telescope Name (%6s)
OBSERVAT= 'NAOJ' / Observatory Name (%4s)
BLANK = 32768 / Value used for NULL pixels (%d)
BSCALE = 1.00 / Real = fits-value*BSCALE+BZERO (%12.2f)
BUNIT = 'ADU' / Unit of original pixel values (%3s)
BZERO = 0.00 / Real = fits-value*BSCALE+BZERO (%12.2f)
EXTEND = F / The existence of extension or not (T or F) (%1s)
COMMENT
COMMENT *****
COMMENT ***** TENTATIVELY CLASSIFIED AS IRCS PROPER ITEMS *****
COMMENT *****
COMMENT % Telescope control
COMMENT
I_TC-SEQ= 'dithering1' / Telescope controlling sequence %40s
I_NSQ = 2 / Number of the frame in the sequence %3d
I_NSQMAX= 13 / Maximum number of the sequence %3d
I_ABOFFX= -20.00 / Absolute offset from the center of the pattern (RA) %8.2f
I_ABOFFY= 20.00 / Absolute offset from the center of the pattern (Dec) %8.2f
I_RLOFFX= 10.00 / Relative offset from the last frame of the pattern (RA) %8.2f
I_RLOFFY= -10.00 / Relative offset from the last frame of the pattern (Dec) %8.2f
COMMENT
COMMENT
COMMENT % case {AG}
COMMENT
COMMENT
I_AG-OBJ= 'HD12345' / Name of the guide-star %40s
I_AG-RA = '12:34:56.70' / R.A. of the guide-star %12s
I_AG-DEC= '+12:34:56.7' / Dec. of the guide-star %12s
I_AG-EQN= 2000.0 / Equinox of the guide-star position %6.1f
I_AG-X = 12.34 / Position of the guiding probe (X) %6.2f
I_AG-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_AG-R = 34.56 / Position of the guiding probe (R) %6.2f
I_AG-TH = 12.34 / Position of the guiding probe (theta) %6.2f
COMMENT
COMMENT % case {T-T}
COMMENT
I_TT-OBJ= 'HD12345' / Name of the tip-tilt guide-star %40s
I_TT-RA = '12:34:56.70' / R.A. of the tip-tilt guide-star %12s
I_TT-DEC= '+12:34:56.7' / Dec. of the tip-tilt guide-star %12s
I_TT-EQN= 2000.0 / Equinox of the tip-tilt guide-star position %6.1f
I_TT-X = 12.34 / Position of the guiding probe (X) %6.2f
I_TT-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_TT-R = 34.56 / Position of the guiding probe (R) %6.2f
I_TT-TH = 12.34 / Position of the guiding probe (theta) %6.2f
COMMENT
COMMENT % case {AO}
COMMENT
I_AOMODE= 'ON' / AO mode %3s
I_AO-WFS= 'AO-WFS' / Wavefront sensor used for AO %10s
I_AO-GS = 'HD12345' / Name of the AO guide star %40s
I_AO-GSM= 15.0 / Magnitude of the AO guide star %3.1f
I_AO-GSB= 'R' / Band for the magnitude of the AO guide star %3s
I_AO-EQN= 2000.0 / Equinox of the guide-star position %6.1f
I_AO-X = 12.34 / Position of the guiding probe (X) %6.2f
I_AO-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_AO-R = 34.56 / Position of the guiding probe (R) %6.2f
I_AO-TH = 12.34 / Position of the guiding probe (theta) %6.2f
COMMENT
COMMENT *****
COMMENT ***** IRCS PROPER ITEMS *****
COMMENT *****
COMMENT
I_UFNAME= 'test_field_1' / User assigned file name %40s
COMMENT
COMMENT % for mechanisms
COMMENT
I_M-HAT = 'OPEN' / Status of mechanisms (hatch) HOME/OPEN/CLOSE %30s
I_M-SW = 'Mirror' / Status of mechanisms (slit wheel) %30s
I_M-FM1 = '60mas' / Status of mechanisms (flip mirror 1) HOME/22mas/60mas %30s
I_M-FM2 = '60mas' / Status of mechanisms (flip mirror 2) HOME/22mas/60mas %30s
I_M-CFW1= 'OPEN' / Status of mechanisms (camera filter wheel 1) %30s
I_M-CFW2= 'K' / Status of mechanisms (camera filter wheel 2) %30s
I_M-CFW3= 'PK50' / Status of mechanisms (camera filter wheel 2) %30s

```

```

I_M-FS = '22mas/K' , / Status of mechanisms (camera filter wheel 2) %30s
I_M-SFW = 'Kwide' , / Status of mechanisms (spectrograph filter wheel) %30s
I_M-ECH = 'K*' , / Status of mechanisms (Echelle drive) %30s
I_M-XD = 'K' , / Status of mechanisms (X-disperser drive) %30s
I_M-ECHE= 3560 / Hall sensor value of Echelle drive %10d
I_M-XDE = 2231 / Hall sensor value of X-disperser drive %10d
COMMENT
COMMENT
COMMENT % for detector
COMMENT
COMMENT
I_DMIN = -376 / MIN DATA VALUE IN FILE %6d
I_DMAX = 2429 / MAX DATA VALUE IN FILE %6d
I_DMEAN = 0.00 / MEAN DATA VALUE IN FILE %6.2f
I_DIV = 1 / Normalization value %3d
I_NSARRY= 1 / Number of Sub Arrays %3d
I_AR1MIN= 0 / x of Sub Arrays %4d
I_AR2MIN= 0 / y of Sub Arrays %4d
I_AR1RNG= 512 / wid of Sub Arrays %4d
I_AR2RNG= 512 / hgt of Sub Arrays %4d
I_SUBAB = 0 / SubAB flag. 0=off, 1=on %1d
I_CBMODE= 2 / CB Mode is ARC_D %1d
I_SLCNT = 4 / Number of Slow Counts %2d
I_GRCNT = 800 / Global Reset Count. 1 cnt = 25 nsec %4d
I_BGRSTF='1,1000,40' / Background Reset's flag %30s
I_BGRSTT= 1000 / Background Reset's msec %4d
I_BGRSTC= 40 / Background Reset's cnt %3d
I_GOSIM = 0 / GO simulation flag. 0=off, 1=on %1d
END

```

● IRCS の Grism Spectroscopy モード

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / SIMPLE must be 'T' for confirming FITS %1s
BITPIX = 16 / # of bits storing pix values %2d
NAXIS = 2 / # of axes in frame %1d
NAXIS1 = 1024 / # of pixels/row %5d
NAXIS2 = 1024 / # of rows (also # of scan lines) %5d
DISPAxis= 2 / # of axis describing dispersion direction %1s
OBSERVER='Kobayashi et al.' / Name of observer %30s
PROP-ID = 'o99003' / Proposal ID %20s
FRAMEID = 'IRCA00002347' / Image sequential number %16s
EXP-ID = 'IRCA00002347' / ID of the exposure this data was taken %16s
OBS-MOD = 'GRISM' / Observation Mode %30s
DET-ID = 1 / ID of the detector (1 : CAMERA, 2 : SPECTROGRAPH) %2d
DETECTOR='Aladdin SN-####' / Name of the detector/CCD %10s
DATASET = '?????????' / ID of an observation dataset %20s
DATA-TYP='OBJECT' / Type / Characteristics of this data %10s
WCS-ORIG='?????????' / Origin of WCS value %20s
RA = '18:20:26.010' / HH:MM:SS.SSS RA pointing %12s
DEC = '-16:12:07.06' / +/-DD:MM:SS.SS DEC pointing %12s
EQUINOX = 2000.0 / Standard FK5 (years) %6.1f
RADECSYS='FK5' / The equatorial coordinate system %8s
RA2000 = '18:20:26.010' / HH:MM:SS.SSS RA (J2000) pointing %12s
DEC2000 = '-16:12:07.06' / +/-DD:MM:SS.SS DEC (J2000) pointing %12s
FILTER01='Kwide' / Filter name/ID %30s
FILTER02='60mas_midJHK' / Filter/Grism name/ID %30s
FILTER03='PK50' / Filter name/ID %30s
CTYPE1 = 'LINEAR' / Pixel coordinate system %16s
CTYPE2 = 'RA---TAN' / Pixel coordinate system %16s
CUNIT1 = 'microns' / Units used in both CRVAL1 and CDELT1 %10s
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDELT2 %10s
CRPIX1 = 512.0 / Reference pixel in X %6.1f
CRPIX2 = 512.0 / Reference pixel in Y %6.1f
CRVAL1 = 275.10837500 / Physical value of the reference pixel X %13.8f
CRVAL2 = 2.12350000 / Physical value of the reference pixel Y %13.8f
CDELT1 = 8.32653965E-4 / Size projected into a detector pixel X %13.8f
CDELT2 = 0.00003194 / Size projected into a detector pixel Y %13.8f
PROJP1 = 0.0 / Projection Type of the first axis %5.1f
PROJP2 = 0.0 / Projection Type of the second axis %5.1f
LONGPOLE= 180.0 / The North Pole of the standard system %6.1f
PC001001= 1.00000000 / Pixel Coordinate translation matrix %12.8f
PC001002= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002001= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002002= 1.00000000 / Pixel Coordinate translation matrix %12.8f
C2YPE1 = 'RA---TAN' / Pixel coordinate system %16s
C2YPE2 = 'DEC--TAN' / Pixel coordinate system %16s
C2NIT1 = 'degree' / Units used in both CRVAL1 and CDELT1 %10s
C2NIT2 = 'degree' / Units used in both CRVAL2 and CDELT2 %10s
C2PIX1 = 512.0 / Reference pixel in X %6.1f

```

```

C2PIX2 = 512.0 / Reference pixel in Y %6.1f
C2VAL1 = 275.10837500 / Physical value of the reference pixel X %13.8f
C2VAL2 = -16.17306000 / Physical value of the reference pixel Y %13.8f
C2ELT1 = 0.00003194 / Size projected into a detector pixel X %13.8f
C2ELT2 = 0.00003194 / Size projected into a detector pixel Y %13.8f
P20JP2 = 0.0 / Projection Type of the second axis %5.1f
P2001001= 1.00000000 / Pixel Coordinate translation matrix %12.8f
P2001002= 0.00000000 / Pixel Coordinate translation matrix %12.8f
P2002001= 0.00000000 / Pixel Coordinate translation matrix %12.8f
P2002002= 1.00000000 / Pixel Coordinate translation matrix %12.8f
SLIT = '0.3-0.9' / Identifier of the entrance slit %10s
SLT-LEN = 30.000 / Length of the slit used %7.3f
SLT-WID = 0.3 / Width of the slit used (arcsec) %6.3f
SLT-PA = 90.0 / Slit Position Angle %5.1f
SLTC-RA = 275.10837500 / RA of slit center (degree) %12.8f
SLTC-DEC= -16.17306000 / DEC of slit center (degree) %12.8f
SLTPIX1= 512.0 / Slit center projected on detector (pixel) %7.1f
SLTPIX2= 512.0 / Slit center projected on detector (pixel) %7.1f
DISPERSR= 'GRISM' / Name of disperser used %15s
DATE-OBS= '1997-08-22' / Observation start date (yyyy-mm-dd) %10s
UT = '12:34:56.7' / HH:MM:SS.S typical UTC at exposure %10s
UT-STR = '12:34:56.7' / HH:MM:SS.S UTC at start %10s
UT-END = '13:04:56.7' / HH:MM:SS.S UT at end %10s
HST = '02:34:56.7' / HH:MM:SS.S Typical HST at exposure %10s
LST = '23:53:10.6' / HH:MM:SS.S Typical LST at exposure %20s
MJD = 5.03965242E+04 / Modified Julian Day at typical time %20.8f
TIMESYS = 'UTC' / Time system used in this header (%3s)
EXPTIME = 20.0 / Total integration time (sec) %3.1f
DET-NSMP= 8 / Number of multi-sample (e.g., non-destructive reads) %3d
COADDS = 10 / Number of Coadds %4d
OBJECT = 'M17' / Target Description %30s
AZIMUTH = -16.6 / Azimuth angle of telescope pointing %5.1f
ALTITUDE= 36.4 / Altitude angle of telescope pointing %5.1f
FOC-POS = 'CASSEGRAIN' / Focus where the instrument is attached %12s
FOC-VAL = 2.531 / Encoder value of the focus unit %10.3f
AIRMASS = 1.24352 / Averaged Air Mass %9.5f
ZD = 36.47 / Zenith Distance at typical time %5.2f
DAQ-VER = 1.00 / Version of the instrument control soft %6.2f
INS-VER = 1.00 / Version of the instrument %6.2f
DET-TMP = 30.0 / Detector temperature %5.1f
GAIN = 10.00 / AD conversion factor %5.2f
BIN-FCT1= 1 / Binning factor of X axis %2d
BIN-FCT2= 1 / Binning factor of Y axis %2d
CS-TAVE = 273.00 / Average Value of Cassegrain Enclosure (Container) %6.2f
TELCOCUS= 'CASSEGRAIN' / %10s
OBS-ALOC= 'Observation' / Observation or Standby %12s
INSTRUME= 'IRCS' / Name of Instrument %20s
TELESCOP= 'SUBARU' / Telescope Name (%6s)
OBSERVAT= 'NAOJ' / Observatory Name (%4s)
BLANK = 32768 / Value used for NULL pixels %d
BSCALE = 1.00 / Real = fits-value*BSCALE+BZERO (%12.2f)
BUNIT = 'ADU' / Unit of original pixel values (%3s)
BZERO = 0.00 / Real = fits-value*BSCALE+BZERO (%12.2f)
EXTEND = F / The existence of extension or not (T or F) (%1s)
COMMENT
COMMENT
COMMENT ***** TENTATIVELY CLASSIFIED AS IRCS PROPER ITEMS *****
COMMENT *****
COMMENT
COMMENT % Telescope control
COMMENT
I_TC-SEQ= 'dithering1' / Telescope controlling sequence %40s
I_NSQ = 2 / Number of the frame in the sequence %3d
I_NSQMAX= 13 / Maximum number of the sequence %3d
I_ABOFFX= -20.00 / Absolute offset from the center of the pattern (RA) %8.2f
I_ABOFFY= 20.00 / Absolute offset from the center of the pattern (Dec) %8.2f
I_RLOFFX= 10.00 / Relative offset from the last frame of the pattern (RA) %8.2f
I_RLOFFY= -10.00 / Relative offset from the last frame of the pattern (Dec) %8.2f
COMMENT
COMMENT
COMMENT
COMMENT % case {AG}
COMMENT
COMMENT
COMMENT
I_AG-OBJ= 'HD12345' / Name of the guide-star %40s
I_AG-RA = '12:34:56.70' / R.A. of the guide-star %12s
I_AG-DEC= '+12:34:56.7' / Dec. of the guide-star %12s
I_AG-EQN= 2000.0 / Equinox of the guide-star position %6.1f
I_AG-X = 12.34 / Position of the guiding probe (X) %6.2f
I_AG-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_AG-R = 34.56 / Position of the guiding probe (R) %6.2f
I_AG-TH = 12.34 / Position of the guiding probe (theta) %6.2f

```

```

COMMENT
COMMENT % case {T-T}
COMMENT
I_TT-OBJ= 'HD12345 ' / Name of the tip-tilt guide-star %40s
I_TT-RA = '12:34:56.70' / R.A. of the tip-tilt guide-star %12s
I_TT-DEC= '+12:34:56.7' / Dec. of the tip-tilt guide-star %12s
I_TT-EQN= 2000.0 / Equinox of the tip-tilt guide-star position %6.1f
I_TT-X = 12.34 / Position of the guiding probe (X) %6.2f
I_TT-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_TT-R = 34.56 / Position of the guiding probe (R) %6.2f
I_TT-TH = 12.34 / Position of the guiding probe (theta) %6.2f
COMMENT
COMMENT % case {AO}
COMMENT
I_AOMODE= 'ON ' / AO mode %3s
I_AO-WFS= 'AO-WFS ' / Wavefront sensor used for AO %10s
I_AO-GS = 'HD12345 ' / Name of the AO guide star %40s
I_AO-GSM= 15.0 / Magnitude of the AO guide star %3.1f
I_AO-GSB= 'R ' / Band for the magnitude of the AO guide star %3s
I_AO-EQN= 2000.0 / Equinox of the guide-star position %6.1f
I_AO-X = 12.34 / Position of the guiding probe (X) %6.2f
I_AO-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_AO-R = 34.56 / Position of the guiding probe (R) %6.2f
I_AO-TH = 12.34 / Position of the guiding probe (theta) %6.2f
COMMENT
COMMENT *****
COMMENT ***** IRCS PROPER ITEMS *****
COMMENT *****
COMMENT
I_UFNAME= 'test_field_1' / User assigned file name %40s
COMMENT
COMMENT % for mechanisms
COMMENT
COMMENT
I_M-HAT = 'OPEN ' / Status of mechanisms (hatch) HOME/OPEN/CLOSE %30s
I_M-SW = 'Mirror ' / Status of mechanisms (slit wheel) %30s
I_M-FM1 = '60mas ' / Status of mechanisms (flip mirror 1) HOME/22mas/60mas %30s
I_M-FM2 = '60mas ' / Status of mechanisms (flip mirror 2) HOME/22mas/60mas %30s
I_M-CFW1= 'OPEN ' / Status of mechanisms (camera filter wheel 1) %30s
I_M-CFW2= 'K' ' / Status of mechanisms (camera filter wheel 2) %30s
I_M-CFW3= 'PK50 ' / Status of mechanisms (camera filter wheel 2) %30s
I_M-FS = '22mas/K' ' / Status of mechanisms (camera filter wheel 2) %30s
I_M-SFW = 'Kwide ' / Status of mechanisms (spectrographp filter wheel) %30s
I_M-ECH = 'K* ' / Status of mechanisms (Echelle drive) %30s
I_M-XD = 'K ' / Status of mechanisms (X-disperser drive) %30s
I_M-ECHE= 3560 / Hall sensor value of Echelle drive %10d
I_M-XDE = 2231 / Hall sensor value of X-disperser drive %10d
COMMENT
COMMENT
COMMENT % for detector
COMMENT
COMMENT
I_DMIN = -376 / MIN DATA VALUE IN FILE %6d
I_DMAX = 2429 / MAX DATA VALUE IN FILE %6d
I_DMEAN = 0.00 / MEAN DATA VALUE IN FILE %6.2f
I_DIV = 1 / Normalization value %3d
I_NSARRY= 1 / Number of Sub Arrays %3d
I_AR1MIN= 0 / x of Sub Arrays %4d
I_AR2MIN= 0 / y of Sub Arrays %4d
I_AR1RNG= 512 / wid of Sub Arrays %4d
I_AR2RNG= 512 / hgt of Sub Arrays %4d
I_SUBAB = 0 / SubAB flag. 0=off, 1=on %1d
I_CBMODE= 2 / CB Mode is ARC_D %1d
I_SLCNT = 4 / Number of Slow Counts %2d
I_GRCNT = 800 / Global Reset Count. 1 cnt = 25 nsec %4d
I_BGRSTF= '1,1000,40' / Backgroud Reset's flag %30s
I_BGRSTT= 1000 / Backgroud Reset's msec %4d
I_BGRSTC= 40 / Backgroud Reset's cnt %3d
I_GOSIM = 0 / GO simulation flag. 0=off, 1=on %1d
END

```

● IRCS の Echelle モード

	1	2	3	4	5	6	7	8	9
1234567890123456789012345678901234567890123456789012345678901234567890123456789012345678									
SIMPLE =			T						%1s
BITPIX =			16						%2d
NAXIS =			2						%1d

```

NAXIS1 = 1024 / # of pixels/row %5d
NAXIS2 = 1024 / # of rows (also # of scan lines) %5d
DISPAXIS= 2 / # of axis describing dispersion direction %1s
OBSERVER= 'Kobayashi et al.' / Name of observer %30s
PROP-ID = 'o99003' / Proposal ID %20s
FRAMEID = 'IRCA00002347' / Image sequential number %16s
EXP-ID = 'IRCA00002347' / ID of the exposure this data was taken %16s
OBS-MOD = 'ECHELLE' / Observation Mode %30s
DET-ID = 2 / ID of the detector (1 : CAMERA, 2 : SPECTROGRAPH) %2d
DETECTOR= 'Aladdin SN-####' / Name of the detector/CCD %10s
DATASET = '?????????' / ID of an observation dataset %20s
DATA-TYP= 'OBJECT' / Type / Characteristics of this data %10s
WCS-ORIG= '?????????' / Origin of WCS value %20s
RA = '18:20:26.010' / HH:MM:SS.SSS RA pointing %12s
DEC = '-16:12:07.06' / +/-DD:MM:SS.SS DEC pointing %12s
EQUINOX = 2000.0 / Standard FK5 (years) %6.1f
RADECSYS= 'FK5' / The equatorial coordinate system %8s
RA2000 = '18:20:26.010' / HH:MM:SS.SSS RA (J2000) pointing %12s
DEC2000 = '-16:12:07.06' / +/-DD:MM:SS.SS DEC (J2000) pointing %12s
FILTER01= 'Kwide' / Filter name/ID %30s
CTYPE1 = 'LINEAR' / Pixel coordinate system %16s
CTYPE2 = 'RA---TAN' / Pixel coordinate system %16s
CUNIT1 = 'microns' / Units used in both CRVAL1 and CDELT1 %10s
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDELT2 %10s
CRPIX1 = 512.0 / Reference pixel in X %6.1f
CRPIX2 = 512.0 / Reference pixel in Y %6.1f
CRVAL1 = 275.10837500 / Physical value of the reference pixel X %13.8f
CRVAL2 = 2.12350000 / Physical value of the reference pixel Y %13.8f
CDELT1 = 8.32653965E-4 / Size projected into a detector pixel X %13.8f
CDELT2 = 0.00003194 / Size projected into a detector pixel Y %13.8f
PROJP1 = 0.0 / Projection Type of the first axis %5.1f
PROJP2 = 0.0 / Projection Type of the second axis %5.1f
LONGPOLE= 180.0 / The North Pole of the standard system %6.1f
PC001001= 1.00000000 / Pixel Coordinate translation matrix %12.8f
PC001002= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002001= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002002= 1.00000000 / Pixel Coordinate translation matrix %12.8f
C2YPE1 = 'RA---TAN' / Pixel coordinate system %16s
C2YPE2 = 'DEC--TAN' / Pixel coordinate system %16s
C2NIT1 = 'degree' / Units used in both CRVAL1 and CDELT1 %10s
C2NIT2 = 'degree' / Units used in both CRVAL2 and CDELT2 %10s
C2PIX1 = 512.0 / Reference pixel in X %6.1f
C2PIX2 = 512.0 / Reference pixel in Y %6.1f
C2VAL1 = 275.10837500 / Physical value of the reference pixel X %13.8f
C2VAL2 = -16.17306000 / Physical value of the reference pixel Y %13.8f
C2ELT1 = 0.00003194 / Size projected into a detector pixel X %13.8f
C2ELT2 = 0.00003194 / Size projected into a detector pixel Y %13.8f
P20JP2 = 0.0 / Projection Type of the second axis %5.1f
P2001001= 1.00000000 / Pixel Coordinate translation matrix %12.8f
P2001002= 0.00000000 / Pixel Coordinate translation matrix %12.8f
P2002001= 0.00000000 / Pixel Coordinate translation matrix %12.8f
P2002002= 1.00000000 / Pixel Coordinate translation matrix %12.8f
SLIT = '0.30x10.5' / Identifier of the entrance slit %10s
SLT-LEN = 10.500 / Length of the slit used %7.3f
SLT-WID = 0.300 / Width of the slit used (arcsec) %6.3f
SLT-PA = 90.0 / Slit Position Angle %5.1f
SLTC-RA = 275.10837500 / RA of slit center (degree) %12.8f
SLTC-DEC= -16.17306000 / DEC of slit center (degree) %12.8f
SLTCPIX1= 512.0 / Slit center projected on detector (pixel) %7.1f
SLTCPIX2= 512.0 / Slit center projected on detector (pixel) %7.1f
DISPERSR= 'ECHELLE' / Name of disperser used %15s
DATE-OBS= '1997-08-22' / Observation start date (yyyy-mm-dd) %10s
UT = '12:34:56.7' / HH:MM:SS.S typical UTC at exposure %10s
UT-STR = '12:34:56.7' / HH:MM:SS.S UTC at start %10s
UT-END = '13:04:56.7' / HH:MM:SS.S UT at end %10s
HST = '02:34:56.7' / HH:MM:SS.S Typical HST at exposure %10s
LST = '23:53:10.6' / HH:MM:SS.S Typical LST at exposure %20s
MJD = 5.03965242E+04 / Modified Julian Day at typical time %20.8f
TIMESYS = 'UTC' / Time system used in this header (%3s)
EXPTIME = 20.0 / Total integration time (sec) %3.1f
DET-NSMP= 8 / Number of multi-sample (e.g., non-destructive reads) %3d
COADDS = 10 / Number of Coadds %4d
OBJECT = 'M17' / Target Description %30s
AZIMUTH = -16.6 / Azimuth angle of telescope pointing %5.1f
ALTITUDE= 36.4 / Altitude angle of telescope pointing %5.1f
FOC-POS = 'CASSEGRAIN' / Focus where the instrument is attached %12s
FOC-VAL = 2.531 / Encoder value of the focus unit %10.3f
AIRMASS = 1.24352 / Averaged Air Mass %9.5f
ZD = 36.47 / Zenith Distance at typical time %5.2f
DAQ-VER = 1.00 / Version of the instrument control soft %6.2f
INS-VER = 1.00 / Version of the instrument %6.2f
DET-TMP = 30.0 / Detector temperature %5.1f
GAIN = 10.00 / AD conversion factor %5.2f
BIN-FCT1= 1 / Binning factor of X axis %2d

```

```

BIN-FCT2=          1 / Binning factor of Y axis                      %2d
CS-TAVE =          273.00 / Average Value of Cassegrain Enclosure (Container) %6.2f
TELFOCUS= 'CASSEGRAIN' /                                         %10s
OBS-ALOC= 'Observation' / Observation or Standby                  %12s
INSTRUME= 'IRCS'       / Name of Instrument                      %20s
TELESCOP= 'SUBARU'     / Telescope Name                          (%6s)
OBSERVAT= 'NAOJ'       / Observatory Name                        (%4s)
BLANK    =          32768 / Value used for NULL pixels            %d
BSCALE   =          1.00 / Real = fits-value*BSCALE+BZERO        (%12.2f)
BUNIT    = 'ADU'       / Unit of original pixel values           (%3s)
BZERO    =          0.00 / Real = fits-value*BSCALE+BZERO        (%12.2f)
EXTEND   =          F   / The existence of extension or not (T or F) (%1s)
COMMENT
COMMENT
COMMENT *****
COMMENT ***** TENTATIVELY CLASSIFIED AS IRCS PROPER ITEMS *****
COMMENT *****
COMMENT
COMMENT % Telescope control
COMMENT
I_TC-SEQ= 'dithering1' / Telescope controlling sequence          %40s
I_NSQ    =          2   / Number of the frame in the sequence      %3d
I_NSQMAX=          13   / Maximum number of the sequence          %3d
I_ABOFFX= -20.00 / Absolute offset from the center of the pattern (RA) %8.2f
I_ABOFFY=  20.00 / Absolute offset from the center of the pattern (Dec) %8.2f
I_RLOFFX=  10.00 / Relative offset from the last frame of the pattern (RA) %8.2f
I_RLOFFY= -10.00 / Relative offset from the last frame of the pattern (Dec) %8.2f
COMMENT
COMMENT
COMMENT
COMMENT % case {AG}
COMMENT
COMMENT
COMMENT
I_AG-OBJ= 'HD12345' / Name of the guide-star                      %40s
I_AG-RA  = '12:34:56.70' / R.A. of the guide-star                %12s
I_AG-DEC = '12:34:56.7' / Dec. of the guide-star                %12s
I_AG-EQN= 2000.0 / Equinox of the guide-star position            %6.1f
I_AG-X   = 12.34 / Position of the guiding probe (X)             %6.2f
I_AG-Y   = 12.34 / Position of the guiding probe (Y)             %6.2f
I_AG-R   = 34.56 / Position of the guiding probe (R)             %6.2f
I_AG-TH  = 12.34 / Position of the guiding probe (theta)         %6.2f
COMMENT
COMMENT % case {T-T}
COMMENT
I_TT-OBJ= 'HD12345' / Name of the tip-tilt guide-star            %40s
I_TT-RA  = '12:34:56.70' / R.A. of the tip-tilt guide-star        %12s
I_TT-DEC = '12:34:56.7' / Dec. of the tip-tilt guide-star        %12s
I_TT-EQN= 2000.0 / Equinox of the tip-tilt guide-star position    %6.1f
I_TT-X   = 12.34 / Position of the guiding probe (X)             %6.2f
I_TT-Y   = 12.34 / Position of the guiding probe (Y)             %6.2f
I_TT-R   = 34.56 / Position of the guiding probe (R)             %6.2f
I_TT-TH  = 12.34 / Position of the guiding probe (theta)         %6.2f
COMMENT
COMMENT % case {AO}
COMMENT
I_AOMODE= 'ON' / AO mode                                          %3s
I_AO-WFS = 'AO-WFS' / Wavefront sensor used for AO                %10s
I_AO-GS  = 'HD12345' / Name of the AO guide star                  %40s
I_AO-GSM = 15.0 / Magnitude of the AO guide star                  %3.1f
I_AO-GSB = 'R' / Band for the magnitude of the AO guide star      %3s
I_AO-EQN= 2000.0 / Equinox of the guide-star position            %6.1f
I_AO-X   = 12.34 / Position of the guiding probe (X)             %6.2f
I_AO-Y   = 12.34 / Position of the guiding probe (Y)             %6.2f
I_AO-R   = 34.56 / Position of the guiding probe (R)             %6.2f
I_AO-TH  = 12.34 / Position of the guiding probe (theta)         %6.2f
COMMENT
COMMENT
COMMENT *****
COMMENT ***** IRCS PROPER ITEMS *****
COMMENT *****
COMMENT
COMMENT
I_UFNAME= 'test_field_1' / User assigned file name                %40s
COMMENT
COMMENT % for mechanisms
COMMENT
COMMENT
I_M-HAT = 'OPEN' / Status of mechanisms (hatch) HOME/OPEN/CLOSE %30s
I_M-SW  = 'Mirror' / Status of mechanisms (slit wheel)           %30s
I_M-FM1 = '60mas' / Status of mechanisms (flip mirror 1) HOME/22mas/60mas %30s
I_M-FM2 = '60mas' / Status of mechanisms (flip mirror 2) HOME/22mas/60mas %30s
I_M-CFW1= 'OPEN' / Status of mechanisms (camera filter wheel 1) %30s

```



```

SLT-PA = 90.0 / Slit Position Angle %5.1f
SLTC-RA = 275.10837500 / RA of slit center (degree) %12.8f
SLTC-DEC= -16.17306000 / DEC of slit center (degree) %12.8f
SLTCPIX1= 512.0 / Slit center projected on detector (pixel) %7.1f
SLTCPIX2= 512.0 / Slit center projected on detector (pixel) %7.1f
DISPERSR= 'ECHELLE' / Name of disperser used %15s
DATE-OBS= '1997-08-22' / Observation start date (yyyy-mm-dd) %10s
UT = '12:34:56.7' / HH:MM:SS.S typical UTC at exposure %10s
UT-STR = '12:34:56.7' / HH:MM:SS.S UTC at start %10s
UT-END = '13:04:56.7' / HH:MM:SS.S UT at end %10s
HST = '02:34:56.7' / HH:MM:SS.S Typical HST at exposure %10s
LST = '23:53:10.6' / HH:MM:SS.S Typical LST at exposure %20s
MJD = 5.03965242E+04 / Modified Julian Day at typical time %20.8f
TIMESYS = 'UTC' / Time system used in this header (%3s)
EXPTIME = 20.0 / Total integration time (sec) %8.1f
DET-NSMP= 8 / Number of multi-sample (e.g., non-destructive reads) %3d
COADDS = 10 / Number of Coadds %4d
OBJECT = 'M17' / Target Description %30s
AZIMUTH = -16.6 / Azimuth angle of telescope pointing %5.1f
ALTITUDE= 36.4 / Altitude angle of telescope pointing %5.1f
FOC-POS = 'CASSEGRAIN' / Focus where the instrument is attached %12s
FOC-VAL = 2.531 / Encoder value of the focus unit %10.3f
AIRMASS = 1.24352 / Averaged Air Mass %9.5f
ZD = 36.47 / Zenith Distance at typical time %5.2f
DAQ-VER = 1.00 / Version of the instrument control soft %6.2f
INS-VER = 1.00 / Version of the instrument %6.2f
DET-TMP = 30.0 / Detector temperature %5.1f
GAIN = 10.00 / AD conversion factor %5.2f
BIN-FCT1= 1 / Binning factor of X axis %2d
BIN-FCT2= 1 / Binning factor of Y axis %2d
CS-TAVE = 273.00 / Average Value of Cassegrain Enclosure (Container) %6.2f
TELFOCUS= 'CASSEGRAIN' / %10s
OBS-ALOC= 'Observation' / Observation or Standby %12s
INSTRUME= 'IRCS' / Name of Instrument %20s
TELESCOP= 'SUBARU' / Telescope Name (%6s)
OBSERVAT= 'NAOJ' / Observatory Name (%4s)
BLANK = 32768 / Value used for NULL pixels %d
BSCALE = 1.00 / Real = fits-value*BSCALE+BZERO (%12.2f)
BUNIT = 'ADU' / Unit of original pixel values (%3s)
BZERO = 0.00 / Real = fits-value*BSCALE+BZERO (%12.2f)
EXTEND = F / The existence of extension or not (T or F) (%1s)
COMMENT
COMMENT
COMMENT *****
COMMENT ***** TENTATIVELY CLASSIFIED AS IRCS PROPER ITEMS *****
COMMENT *****
COMMENT
COMMENT % Telescope control
COMMENT
I_TC-SEQ= 'dithering1' / Telescope controlling sequence %40s
I_NSQ = 2 / Number of the frame in the sequence %3d
I_NSQMAX= 13 / Maximum number of the sequence %3d
I_ABOFFX= -20.00 / Absolute offset from the center of the pattern (RA) %8.2f
I_ABOFFY= 20.00 / Absolute offset from the center of the pattern (Dec) %8.2f
I_RLOFFX= 10.00 / Relative offset from the last frame of the pattern (RA) %8.2f
I_RLOFFY= -10.00 / Relative offset from the last frame of the pattern (Dec) %8.2f
COMMENT
COMMENT
COMMENT
COMMENT % case {AG}
COMMENT
COMMENT
COMMENT
I_AG-OBJ= 'HD12345' / Name of the guide-star %40s
I_AG-RA = '12:34:56.70' / R.A. of the guide-star %12s
I_AG-DEC= '+12:34:56.7' / Dec. of the guide-star %12s
I_AG-EQN= 2000.0 / Equinox of the guide-star position %6.1f
I_AG-X = 12.34 / Position of the guiding probe (X) %6.2f
I_AG-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_AG-R = 34.56 / Position of the guiding probe (R) %6.2f
I_AG-TH = 12.34 / Position of the guiding probe (theta) %6.2f
COMMENT
COMMENT % case {T-T}
COMMENT
I_TT-OBJ= 'HD12345' / Name of the tip-tilt guide-star %40s
I_TT-RA = '12:34:56.70' / R.A. of the tip-tilt guide-star %12s
I_TT-DEC= '+12:34:56.7' / Dec. of the tip-tilt guide-star %12s
I_TT-EQN= 2000.0 / Equinox of the tip-tilt guide-star position %6.1f
I_TT-X = 12.34 / Position of the guiding probe (X) %6.2f
I_TT-Y = 12.34 / Position of the guiding probe (Y) %6.2f
I_TT-R = 34.56 / Position of the guiding probe (R) %6.2f
I_TT-TH = 12.34 / Position of the guiding probe (theta) %6.2f
COMMENT
COMMENT % case {A0}

```



```

CDEL1 = -0.00047247 / 計算式 %13.8f
CDEL2 = 0.00047257 / 計算式 %13.8f
CUNIT1 = 'degree' / →固定 %6s
CUNIT2 = 'degree' / →固定 %6s
BIN-FCT1= 1 / V-LAN 画像ヘッダ %2d
BIN-FCT2= 1 / V-LAN 画像ヘッダ %2d
PRD-MIN1= 1 / V-LAN 画像ヘッダより、読出開始X位置 (%d) %4d
PRD-MIN2= 1 / V-LAN 画像ヘッダより、読出開始Y位置 (%d) %4d
PRD-RNG1= 100 / V-LAN 画像ヘッダより、読出X範囲 (%d) %4d
PRD-RNG2= 100 / V-LAN 画像ヘッダより、読出Y範囲 (%d) %4d
RA = '02:46:02.379' / Status : FITS.SBR.RA %12s
DEC = '+41:30:35.69' / Status : FITS.SBR.DEC %12s
EQUINOX = 1998.7 / Status : FITS.SBR.EQUINOX %6.1f
RA2000 = '02:46:02.379' / Status : FITS.SBR.RA %12s
DEC2000 = '+41:30:35.69' / Status : FITS.SBR.DEC %12s
RADECSYS= 'FK5' / 固定
PC001001= 1.0 / ツールキットのロジックを使用 %13.8f
PC001002= 0.0 / ツールキットのロジックを使用 %13.8f
PC002001= 0.0 / ツールキットのロジックを使用 %13.8f
PC002002= 1.0 / ツールキットのロジックを使用 %13.8f
LONGPOLE= 180.0 / 固定 %5.1f
WCS-ORIG= 'SUBARU Toolkit' / 固定
ALTITUDE= 23.4567 / Status : FITS.SBR.ALTITUDE %8.5f
AZIMUTH = 187.6543 / Status : FITS.SBR.AZIMUTH %9.5f
TIMESYS = 'UTC' / 固定
DATE-OBS= '1998-12-31' / ツールキット関数の UTC-Date %10s
UT = '00:00:00.000' / ツールキット関数の UTC %12s
MJD = 40587.00000000 / ツールキット関数の MJD %15.8f
HST = '00:00:00.000' / プログラム内獲得 %12s
LST = '00:00:00.000' / ツールキット関数の LST %12s
EXPTIME = 10.000 / V-LAN 画像ヘッダ %8.3f
AIRMASS = 1.00000 / Status : FITS.SBR.AIRMASS %8.5f
ZD = 56.700 / Status : FITS.SBR.ZA %6.3f
DOM-PRS = 600.00 / Status : FITS.SBR.DOM-PRS(%7.2f)hpa %7.2f
OBSERVER= 'George' / Status : FITS.VGW.OBSERVER %30s
PROP-ID = 'o98001' / FITS.VGW.PROP-ID %6s
OBSERVAT= 'NAOJ' / 固定
TELESCOP= 'Subaru' / Status : FITS.SBR.TELESCOP
TELFOCUS= 'CASSEGRAIN' / Status : FITS.SBR.TELFOCUS %12s
FOC-POS = 'CASSEGRAIN' / V-LAN 画像ヘッダ %12s
FOC-VAL = 1.000 / Status : FITS.SBR.FOC-VAL %7.3f
M2-POS1 = 1.000 / Status : ??????(%8.3f)mm %8.3f
M2-POS2 = 1.000 / Status : ??????(%8.3f)mm %8.3f
M2-ANG1 = 30.000 / Status : TSCL.TX(%8.5f)arcmin %8.5f
M2-ANG2 = 30.000 / Status : TSCL.TY(%8.5f)arcmin %8.5f
AG-PRB1 = -123.45678 / Status : TSCV.AGr Probe-r(%10.5f)mm %10.5f
AG-PRB2 = -100.45678 / Status : TSCV.AGTheta Probe-Theta(%10.5f)deg %10.5f
INSROT = +123.456 / Status : FITS.SBR.INSROT(%+8.3f)degree %8.3f
ADC-TYPE= 'RED' / Status : FITS.SBR.ADC-TYPE(%30s) %30s
ADC = 130.123 / Status : FITS.SBR.ADC(%7.3f) %7.3f
FRAMEID = 'CACA00000001' / OBS からのコマンド %12s
EXP-ID = 'CACA00000001' / FRAMEID と同様の値 %12s
OBS-ALOC= 'Observation' / Status : FITS.VGW.OBS-ALOC %12s
OBS-MOD = 'IMAGING' / 固定 %7s
INSTRUME= 'CAC' / Cassegrain Alignment Camera %3s
OBJECT = 'First Light Target' / Object Name %20s
DATA-TYP= 'OBJECT' / 画像により OBJECT/DARK/FLAT/SKY/BIAS %6s
DATASET = 'CACD00000001' / %6s
DETECTOR= 'SI003A-1B' / %30s
GAIN = 1.00 / %5.2f
DET-TMP = 131.0 / Status : FITS.VGW.DET-TMP-AG %6.1f
FILTER01= 'None' / None, ND0.5, ND1.0, ND1.5, ND2.0, ND3.0 %6s
FILTER02= 'U' / None, U, B, V, R, I %4s
EXTEND = F / 固定
END

```

6.5.10 VTOS (1999/03/02)

```

1 2 3 4 5 6 7
123456789012345678901234567890123456789012345678901234567890123456789
-----
SIMPLE = T / Standard FITS format
BITPIX = 32 / Number of bits storing pix values %2d
NAXIS = 3 / Number of axis in frame %1d
NAXIS1 = 336 / Number of pixels/row %3d
NAXIS2 = 240 / Number of rows %3d
NAXIS3 = 1000 / Number of frames %4d
EXTEND = T / ASCII Table for Z-frame description
OBSERVER= 'N.Baba' / Name of observers %30s
PROP-ID = 'o98001' / Proposal ID %6s

```

```

DATASET = 'Used for DASH' / What is this? Ref. George %16s
INSTRUME= 'VTOS' / Name of instrument %4s
INS-VER = '1.1 980701' / Version of the instrument %16s
FRAMEID = 'VTOS000000001' / FITS File sequential number %12s
EXP-ID = 'VTOS000000001' / Exposure ID %12s
OBS-MOD = 'imaging' / Observation Mode %8s
DATA-TYP= 'object' / object/flat/pupil/pupil_flat/dark %10s
OBSERVAT= 'NAOJ' / %s
TELESCOP= 'Subaru' / %s
CRPIX1 = 328.5 / Reference pixel in X (pixel) %5.1f
CRPIX2 = 246.5 / Reference pixel in Y (pixel) %5.1f
CRVAL1 = 189.00529167 / Physical value of the reference pixel X %12.8f
CRVAL2 = -39.86927778 / Physical value of the reference pixel Y %12.8f
CDEL1 = 0.0000000000 / X Scale projected on detector(#/pix) %14.10f
CDEL2 = 0.0000000000 / Y scale projected on detector(#/pix) %14.10f
CTYPE1 = 'RA--TAN' / Pixel coordinate system %7s
CTYPE2 = 'DEC--TAN' / Pixel coordinate system %8s
CUNIT1 = 'degree' / Units used in both CRVAL1 and CDEL1 %6s
CUNIT2 = 'degree' / Units used in both CRVAL2 and CDEL2 %6s
TIMESYS = 'UTC' / Time System used in the header. UTC fix. %s
RADECSYS= 'FK5' / The equatorial coordinate system %s
LONGPOLE= 180.00000 / The North Pole of standard system (deg) %10.5f
PC001001= 1.00000000 / Pixel Coordinate translation matrix %12.8f
PC001002= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002001= 0.00000000 / Pixel Coordinate translation matrix %12.8f
PC002002= 1.00000000 / Pixel Coordinate translation matrix %12.8f
BSCALE = 1 / Real=fits-value*BSCALE+BZERO %d
BZERO = 0 / Real=fits-value*BSCALE+BZERO %d
BUNIT = 'ADU' / Unit of original pixel values %s
BLANK = 32768 / Value used for NULL pixels %d
DATE-OBS= '1998-04-30' / yyyy-mm-dd UTC obs start date %10s
UT = '09:12:00.0' / HH:MM:SS.S UTC at typical time(=start) %10s
HST = '23:12:00.0' / HH:MM:SS.S HST at typical time(=start) %10s
LST = '12:34:56.7' / HH:MM:SS.S LST at typical time(=start) %10s
MJD = 12345.67890000 / Modified Julian Day at typical time(=start) %14.8f
EXPTIME = 0.0185 / Total integration time per frame(sec) %6.4f
OBJECT = 'HR 4796' / Target Description %30s
RA = '12:36:01.270' / HH:MM:SS.SSS RA (J2000) pointing %12s
RA2000 = '12:36:01.270' / HH:MM:SS.SSS RA (J2000) pointing %12s
DEC = '-39:52:09.40' / +/-DD:MM:SS.SS DEC (J2000) pointing %12s
DEC2000 = '-39:52:09.40' / +/-DD:MM:SS.SS DEC (J2000) pointing %12s
EQUINOX = 2000.0 / %6.1f
AZIMUTH = 12.34000 / Azimuth of telescope pointing (degree) %11.5f
ALTITUDE= 12.34000 / Altitude of telescope pointing(degree) %11.5f
FOC-POS = 'CASSEGRAIN' / Focus where the instrument is attached %10s
FOC-LEN = 100000.000 / Focal length of the telescope (mm) %10.3f
FOC-VAL = 2.531 / Encoder value of the focus unit (mm) %6.3f
M2-TYPE = 'OPT' / Type of the secondary mirror (Opt/IR) %3s
M2-TIP = 'off' / Tip/Tilt of the Secondary Mirror (on/off) %3s
INR-STR = 12.345 / Instrument Rotator angle at Start (deg) %8.3f
INR-END = 12.345 / Instrument Rotator angle at End (deg) %8.3f
AIRMASS = 4.67918 / Averaged Air Mass %8.5f
ZD = 77.660 / Zenith Distance at typical time %6.3f
SECZ = 4.679 / SEC(Zenith Distance) at typical time %6.3f
FILTER01= 'NONE' / Filter name/ID %16s
DETECTOR= '????' / Name of the detector/CCD %16s
DET-ID = 1 / ID of the detector used for this data %1d
DETPXSZ1= 0.012 / Detector pixel size in axis1 (mm) %5.3f
DETPXSZ2= 0.012 / Detector pixel size in axis2 (mm) %5.3f
DET-TMP = 273.00 / Detector temperature (K) %6.2f
GAIN = 1.0 / AD conversion factor (electron/ADU) %4.1f
PRD-MIN1= 1 / Start X pos. of partial read out (pix) %3d
PRD-MIN2= 1 / Start Y pos. of partial read out (pix) %3d
PRD-RNG1= 656 / X Range of partial read out (pix) %3d
PRD-RNG2= 492 / Y Range of partial read out (pix) %3d
BIN-FCT1= 1 / Binning factor of X axis (pixel) %2d
BIN-FCT2= 1 / Binning factor of Y axis (pixel) %2d
WEATHER = 'Sunny' / Weather condition %10s
SEEING = 0.58 / Long integ PSF FWHM (arcsec) %4.2f
DOM-WND = 4.61 / Wind speed in the dome (m/s) %6.2f
OUT-WND = 7.79 / Wind speed outside (m/s) %6.2f
DOM-TMP = 273.5 / Temperature measured in the dome (K) %5.1f
OUT-TMP = 273.7 / Temperature measured outside dome (K) %5.1f
DOM-HUM = 0.050 / Humidity measured in the dome %7.3f
OUT-HUM = 0.060 / Humidity measured outside the dome %7.3f
DOM-PRS = 670.00 / Atmospheric pressure in the Dome (hpa) %7.2f
OUT-PRS = 670.00 / Atmospheric pressure outside dome (hPa) %7.2f
V_CAMTYP= 'ICCD' / Camera Type ICCD or HCCD %6s
V_CAMNUM= 1 / Camera Number %1d
V_OBSMOD= 'PHASE DIVERSITY' / OBSERVATION MODE %20s
V_DNAME = 'TEST' / DATA NAME %20s
V_FR-P-N= 1 / Frame Packet Number %3d
V_FR-P-T= 3 / Frame Packet TOTAL %3d
V_XSTPOS= 100.00000 / X Stage Position (mm) %10.5f

```

```

V_ZSTPOS=          100.00000 / Z Stage Position (mm)                %10.5f
V_CAMPOS=          200.00000 / Camera Position From Focus (mm)      %10.5f
V_LENSFL=          180.00000 / Focal Length of Lens (mm)           %10.5f
V_C-FRFI= 'FRAME'   / Interrace Mode                               %20s
END

```

6.6 FITS ヘッダ情報の STARS データベースへの登録形式

以下は観測データが山麓に転送され、STARS (すばる望遠鏡データアーカイブシステム) にアーカイビングされる際に、そのヘッダ情報がデータベースにどのような形式で登録されるかを示したものである。

[FITS フォーマットと STARS データベース内フォーマットの対応表]

(1999 年 2 月 14 日版)

この対応表のねらいは、すばる FITS 辞書のフォーマットと、STARS データベース内のフォーマットの違いを明確にし、桁数でどのような値をデフォルト、もしくは OBS との通信エラー時などにキーワード値としてほうり込んでおくべきかを明示することにある。FITS 辞書の場合と違い、STARS のフォーマットはなるべくデータベースの容量を削減すべく、このような方式を取らざるを得ないのが現状である。

本表は、FITS 辞書の項目からキーワード名 (KeyWord)、カテゴリ (Category)、重要度 (Importance)、フォートラン型フォーマット (FormatF) を抽出し、さらに各観測装置ごとのフォーマットを装置名の下に書き記したものである。

なお、この表は「WEB 版すばる FITS 辞書」のページ (7.4.4 節参照) から参照できる。

(注: 紙面の都合でオリジナル版から一部のカラム名を略してある。Importance → Importanc, SupCam → SupCa, COMICS → COMIC, MIRTOS → MIRTO である。また一部隣接する内容間に空白が取れず見にくい部分のあることをお断りしておく。)

[FITS フォーマットと STARS データベース内フォーマット対応表 (1/4)]

KeyWord	Category	Importanc	FormatF	SupCa	FOCAS	HDS	IRCS	OHS	COMIC	CIAO	MIRTO	VTOS	CAC
ADC	Telescope	Optional	F20.3	-	A80	A80	-	-	-	-	-	-	A80
ADC-END	Telescope	Optional	F20.3	F7.3	-	F7.2	-	-	-	-	-	-	-
ADC-STR	Telescope	Optional	F20.3	F7.3	-	F7.2	-	-	-	-	-	-	-
ADC-TYPE	Telescope	Optional	A20	A80	-	A80	-	-	-	-	-	-	A80
AG-PRB1	Telescope	Optional	F20.3	-	-	-	-	-	-	-	-	-	F10.5
AG-PRB2	Telescope	Optional	F20.3	-	-	-	-	-	-	-	-	-	F10.5
AIRM-END	Time	Optional	F20.3	F6.4	F5.2	F6.4	-	-	-	-	-	-	-
AIRM-STR	Time	Optional	F20.3	F6.4	F5.2	F6.4	-	-	-	-	-	-	-
AIRMASS	Time	Common	F20.3	F6.4	F5.2	F6.4	F9.5	F9.5	F9.5	F9.5	F9.5	F8.5	F8.5
ALT-END	Telescope	Optional	F20.5	-	-	F9.5	-	-	-	-	-	-	-
ALT-STR	Telescope	Optional	F20.5	-	-	F9.5	-	-	-	-	-	-	-
ALTITUDE	Telescope	Optional	F20.5	F7.3	F8.5	F9.5	F5.1	F5.1	F8.5	-	F9.5	F11.5	F8.5
A0-FREQ	Telescope	Optional	I20	-	-	-	-	-	-	I3	-	-	-
A0-TIP	Telescope	Optional	A8	-	-	-	-	-	-	A80	-	-	-
A0-WFS	Telescope	Optional	F20.5	-	-	-	-	-	-	F9.5	-	-	-
APERTURE	Spectroscopy	Optional	A30	-	-	-	-	-	-	-	A80	-	-
APT-SIZE	Spectroscopy	Optional	F20.3	-	-	-	-	-	-	-	-	-	-
APTC-DEC	Spectroscopy	Optional	F20.5	-	-	-	-	-	-	-	-	-	-
APTC-RA	Spectroscopy	Optional	F20.5	-	-	-	-	-	-	-	-	-	-
APTCPIX1	Spectroscopy	Optional	F20.1	-	-	-	-	-	-	-	-	-	-
APTCPIX2	Spectroscopy	Optional	F20.1	-	-	-	-	-	-	-	-	-	-
AUTOGUID	Instrument	Optional	A8	-	-	-	-	-	A80	A80	-	-	-
AZ-END	Telescope	Optional	F20.5	-	-	F9.5	-	-	-	-	-	-	-

[FITS フォーマットと STARS データベース内フォーマット対応表 (2/4)]

KeyWord	Category	Importanc	FormatF	SupCa	FOCAS	HDS	IRCS	OHS	COMIC	CIAO	MIRTO	VTOS	CAC
AZ-STR	Telescope	Optional	F20.5	-	-	F9.5	-	-	-	-	-	-	-
AZIMUTH	Telescope	Optional	F20.5	F7.3	F10.5	F9.5	F5.1	F5.1	F9.5	F9.5	F10.5	F11.5	F9.5
BIN-FCT1	Instrument	Common	I20	I2	I4	I2	I2	I2	I2	I2	I2	I2	I2
BIN-FCT2	Instrument	Common	I20	I2	I4	I2	I2	I2	I2	I2	I2	I2	I2
BITPIX	FITS	Common	I20	-	-	-	-	-	-	-	-	-	-
BLANK	File	Common	I20	-	-	-	-	-	-	-	-	-	-
BSCALE	File	Common	F20.8	-	-	-	-	-	-	-	-	-	-
BUNIT	File	Common	A10	-	-	-	-	-	-	-	-	-	-
BZERO	File	Common	F20.8	-	-	-	-	-	-	-	-	-	-
C2ELT1	WCS	Optional	F20.8	-F13.10	F13.8	-	F13.8	-	-	-	-	-	-
C2ELT2	WCS	Optional	F20.8	-F13.10	F13.8	-	F13.8	-	-	-	-	-	-
C2NIT1	WCS	Optional	A8	-	A80	A80	-	A80	-	-	-	-	-
C2NIT2	WCS	Optional	A8	-	A80	A80	-	A80	-	-	-	-	-
C2PIX1	WCS	Optional	F20.1	-	F7.1	F6.1	-	F6.1	-	-	-	-	-
C2PIX2	WCS	Optional	F20.1	-	F7.1	F6.1	-	F6.1	-	-	-	-	-
C2VAL1	WCS	Optional	F20.8	-	F9.3	F13.8	-	F13.8	-	-	-	-	-
C2VAL2	WCS	Optional	F20.8	-	F9.4	F13.8	-	F13.8	-	-	-	-	-
C2YPE1	WCS	Optional	A8	-	A80	A80	-	A80	-	-	-	-	-
C2YPE2	WCS	Optional	A8	-	A80	A80	-	A80	-	-	-	-	-
CDEL1	File	Common	F20.8F16.13F13.10	F13.8	F13.8	F13.8	F13.8	F13.8	F13.8	F13.8F12.10F14.10	F13.8	-	-
CDEL2	File	Common	F20.8F16.13F13.10	F13.8	F13.8	F13.8	F13.8	F13.8	F13.8	F13.8F12.10F14.10	F13.8	-	-
COADD	Instrument	Optional	I20	-	-	-	I4	-	-	I2	-	-	-
COMMENT	Comment	Optional	A79	-	-	-	-	-	-	-	-	-	-
CRPIX1	File	Common	F20.1	F8.1	F7.1	F6.1	F6.1	F6.1	F6.1	F6.1	F6.1	F5.1	F5.1
CRPIX2	File	Common	F20.1	F8.1	F7.1	F6.1	F6.1	F6.1	F6.1	F6.1	F6.1	F5.1	F5.1
CRVAL1	File	Common	F20.8	F11.7	F9.3	F13.8	F13.8	F13.8	F13.8	F13.8	F13.8	F12.8	F10.6
CRVAL2	File	Common	F20.8	F11.7	F9.4	F13.8	F13.8	F13.8	F13.8	F13.8	F13.8	F12.8	F10.6
CTYPE1	File	Common	A10	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
CTYPE2	File	Common	A10	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
CUNIT1	File	Common	A10	A80	A80	A80	A80	A80	A80	A80	A80	A80	-
CUNIT2	File	Common	A10	A80	A80	A80	A80	A80	A80	A80	A80	A80	-
DATA-TYP	Object	Common	A30	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
DATASET	Object	Object	A20	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
DATE-OBS	Time	Common	A10	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
DEC	Object	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
DEC2000	Object	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
DET-Ann	Instrument	Optional	F20.3	F7.3	F6.3	F7.3	-	-	-	-	F6.3	-	-
DET-ID	Instrument	Optional	I20	I2	I1	I1	-	-	I1	-	I1	I1	-
DET-NSMP	Instrument	Optional	I20	-	-	-	-	I2	-	I2	-	-	-
DET-P1nn	Instrument	Optional	F20.3	F7.3	F6.1	F10.5	-	-	-	-	-	-	-
DET-P2nn	Instrument	Optional	F20.3	-	-	-	-	-	-	-	-	-	-
DET-RST	Instrument	Optional	I20	-	-	-	-	-	-	I2	-	-	-
DET-SMPL	Instrument	Optional	A20	-	-	-	-	-	-	A80	-	-	-
DET-TAVE	Instrument	Optional	F20.2	-	-	F6.2	-	-	-	-	-	-	-
DET-TMAX	Instrument	Optional	F20.2	F6.2	F6.2	F6.2	-	-	-	-	-	-	-
DET-TMED	Instrument	Optional	F20.2	F6.2	F6.2	-	-	-	-	-	-	-	-
DET-TMIN	Instrument	Optional	F20.2	F6.2	F6.2	F6.2	-	-	-	-	-	-	-
DET-TMP	Instrument	Common	F20.2	F6.2	F6.2	F6.2	F5.1	F5.1	F6.2	F5.1	F5.2	F6.2	F6.1
DET-TSD	Instrument	Optional	F20.2	-	-	F5.3	-	-	-	F6.2	-	-	-
DETECTOR	Instrument	Common	A20	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
DETPXSZ1	Instrument	Optional	F20.4	-	-	F6.4	-	-	F6.4	-	F5.3	F5.3	-
DETPXSZ2	Instrument	Optional	F20.4	-	-	F6.4	-	-	F6.4	-	F5.3	F5.3	-
DISPAXIS	Spectroscopy	Spectroscopy	I20	-	I1	-	I1	I1	I1	I1	-	-	-
DISPERSR	Spectroscopy	Spectroscopy	A20	-	A80	A80	A80	A80	A80	-	-	-	-
DOM-HUM	Environment	Optional	F20.1	F5.1	F6.2	F5.1	-	-	F5.1	F5.1	F7.3	F7.3	-
DOM-PEND	Environment	Optional	F20.2	-	-	F6.1	-	-	-	-	-	-	-
DOM-PRS	Environment	Optional	F20.2	F7.2	-	F6.1	-	-	F7.2	F7.2	F7.2	F7.2	F7.2
DOM-PSTR	Environment	Optional	F20.2	-	-	F6.1	-	-	-	-	-	-	-
DOM-TMP	Environment	Optional	F20.2	F6.2	F6.2	F6.2	-	-	F6.2	F6.2	F6.2	F5.1	-
DOM-WND	Environment	Optional	F20.2	F5.2	F5.2	F4.1	-	-	F5.2	F5.2	F7.2	F6.2	-
EFP-MIN1	Instrument	Optional	I20	I5	I5	I5	-	-	-	-	-	-	-
EFP-MIN2	Instrument	Optional	I20	I5	I5	I5	-	-	-	-	-	-	-
EFP-RNG1	Instrument	Optional	I20	I5	I5	I5	-	-	-	-	-	-	-

[FITS フォーマットと STARS データベース内フォーマット対応表 (3/4)]

KeyWord	Category	Importanc	FormatF	SupCa	FOCAS	HDS	IRCS	OHS	COMIC	CIAO	MIRTO	VTOS	CAC
EFP-RNG2	Instrument	Optional	I20	I5	I5	I5	-	-	-	-	-	-	-
END	FITS	Common	-	-	-	-	-	-	-	-	-	-	-
EQUINOX	Object	Common	F20.1	F6.1	F6.1	F6.1	F6.1	F6.1	F6.1	F6.1	F6.1	F6.1	F6.1
EXP-ID	Instrument	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	-
EXP1TIME	Time	Optional	F20.3	-	-	-	-	-	-	F8.1	-	-	-
EXPTIME	Time	Common	F20.2	F7.1	F8.2	F8.1	F8.1	F8.1	F7.3	F7.1	F9.4	F6.4	F8.3
EXTEND	FITS	Common	BOOLEAN	-	-	-	-	-	-	-	-	-	-
FILTERnn	Instrument	Optional	A30	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
FLT-Ann	Instrument	Optional	F20.2	-	F5.2	-	-	-	-	-	-	-	-
FOC-LEN	Origin	Optional	F20.3	-	-	F8.1	-	-	F10.3	-	F10.3	F10.3	-
FOC-POS	Origin	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
FOC-VAL	Origin	Common	F20.3	F10.3	F6.3	F10.3	F10.3	F10.3	F10.3	F10.3	F6.3	F6.3	F7.3
FRAMEID	Instrument	Common	A12	A16	A16	A16	A16	A16	A16	A16	A16	A16	A16
GAIN	Instrument	Common	F20.3	F6.3	F6.2	F5.2	F5.2	F5.2	F5.2	F5.2	F6.2	F4.1	F5.2
HISTORY	Comment	Optional	A60	-	-	-	-	-	-	-	-	-	-
HST	Time	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
HST-END	Time	Optional	A12	A80	A80	A80	-	-	-	-	-	-	-
HST-STR	Time	Optional	A12	A80	A80	A80	-	-	-	-	-	-	-
IMGROT	Telescope	Optional	F20.3	-	-	A80	-	-	-	-	-	-	-
IMR-END	Telescope	Optional	F20.3	-	-	F7.2	-	-	-	-	-	-	-
IMR-STR	Telescope	Optional	F20.3	-	-	F7.2	-	-	-	-	-	-	-
IMR-TYPE	Telescope	Optional	A20	-	-	A80	-	-	-	-	-	-	-
INR-END	Telescope	Optional	F20.3	F8.3	-	-	-	-	-	-	F8.3	F8.3	-
INR-STR	Telescope	Optional	F20.3	F8.3	-	-	-	-	-	-	F8.3	F8.3	-
INS-VER	Instrument	Optional	A30	A80	A80	A80	A80	A80	A80	A80	A80	A80	-
INSROT	Telescope	Optional	F20.3	-	-	-	-	-	F8.3	F7.3	-	-	F8.3
INSTRUME	Instrument	Common	A20	-	-	-	-	-	-	-	-	-	-
LONGPOLE	WCS	Imaging	F20.1	F6.1	F9.5	F6.1	F6.1	F6.1	F6.1	F6.1	F9.5	F10.5	F5.1
LST	Time	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
LST-END	Time	Optional	A12	A80	A80	A80	-	-	-	-	-	-	-
LST-STR	Time	Optional	A12	A80	A80	A80	-	-	-	-	-	-	-
M2-ANG1	Telescope	Optional	F20.3	-	-	-	-	-	-	-	-	-	F8.5
M2-ANG2	Telescope	Optional	F20.3	-	-	-	-	-	-	-	-	-	F8.5
M2-POS1	Telescope	Optional	F20.3	-	-	-	-	-	-	-	-	-	F8.3
M2-POS2	Telescope	Optional	F20.3	-	-	-	-	-	-	-	-	-	F8.3
M2-TIP	Telescope	Optional	A8	-	-	-	-	A80	A80	A80	A80	A80	-
M2-TYPE	Telescope	Optional	A8	-	-	-	-	A80	A80	-	A80	A80	-
MJD	Time	Common	F20.8	F12.6	F14.8	F15.8	F20.8	F20.8	F14.8	F20.8	F14.8	F14.8	F15.8
MJD-END	Time	Optional	F20.8	F12.6	F14.8	F15.8	-	-	-	-	-	-	-
MJD-STR	Time	Optional	F20.8	F12.6	F14.8	F15.8	-	-	-	-	-	-	-
N2XIS	WCS	Optional	I20	-	-	I1	-	-	-	-	-	-	-
N2XIS1	WCS	Optional	I20	-	-	I5	-	-	-	-	-	-	-
N2XIS2	WCS	Optional	I20	-	-	I5	-	-	-	-	-	-	-
NAS-TAVE	Environment	Optional	F20.2	-	-	F6.2	-	F6.2	-	-	-	-	-
NAS-TMAX	Environment	Optional	F20.2	-	-	F6.2	-	-	-	-	-	-	-
NAS-TMIN	Environment	Optional	F20.2	-	-	F6.2	-	-	-	-	-	-	-
NAS-TSD	Environment	Optional	F20.1	-	-	F5.3	-	-	-	-	-	-	-
NAXIS	FITS	Common	I20	I1	I1	I1	I1	I1	I1	I1	I1	I1	I2
NAXIS1	FITS	Common	I20	I5	I4	I5	I5	I5	I5	I5	I3	I3	I4
NAXIS2	FITS	Common	I20	I5	I4	I5	I5	I5	I5	I5	I3	I3	I4
NAXIS3	FITS	Optional	I20	-	-	-	-	-	I4	-	I3	I3	-
OBJECT	Object	Common	A30	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
OBS-ALOC	Telescope	Common	A12	A80	A80	A80	A80	A80	A80	-	-	-	A80
OBS-MOD	Instrument	Common	A30	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
OBSERVAT	Origin	Common	A20	-	-	-	-	-	-	-	-	-	-
OBSERVER	Origin	Common	A50	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
OUT-HUM	Environment	Optional	F20.1	F5.1	F6.2	F5.1	-	-	F5.1	F5.1	F7.3	F7.3	-
OUT-PRS	Environment	Optional	F20.2	F7.2	-	-	-	-	F7.2	F7.2	F7.2	F7.2	-
OUT-TMP	Environment	Optional	F20.2	F6.2	F6.2	F6.2	-	-	F6.2	F6.2	F6.2	F5.1	-
OUT-WND	Environment	Optional	F20.2	F5.2	F5.2	F4.1	-	-	F5.2	F5.2	F7.2	F6.2	-
P20JP1	WCS	Optional	F20.1	-	-	F5.1	-	-	-	-	-	-	-
P20JP2	WCS	Optional	F20.1	-	-	F5.1	-	-	-	-	-	-	-
P2iiiijj	WCS	Optional	F20.8	-	-	F12.8	-	F12.8	-	-	-	-	-

[FITS フォーマットと STARS データベース内フォーマット対応表 (4/4)]

KeyWord	Category	Importanc	FormatF	SupCa	FOCAS	HDS	IRCS	OHS	COMIC	CIAO	MIRTO	VTOS	CAC
PCiiiijj	WCS	Imaging	F20.8	F12.8	F9.6	F12.8	F12.8	F12.8	F12.8	F12.8	F12.8	F12.8	F13.8
POL-ANGn	Polarimetry	Optional	F20.2	-	-	-	-	-	-	F6.2	-	-	-
POLARIZn	Polarimetry	Polarimetry	A30	-	-	-	-	-	-	A80	-	-	-
PRD-MIN1	Instrument	Optional	I20	I5	I4	I4	I4	I4	I3	I5	I4	I3	I4
PRD-MIN2	Instrument	Optional	I20	I5	I4	I4	I4	I4	I3	I5	I4	I3	I4
RRD-RNG1	Instrument	Optional	I20	I5	I4	I4	I4	I4	I3	I5	I4	I3	I4
PRD-RNG2	Instrument	Optional	I20	I5	I4	I4	I4	I4	I3	I5	I4	I3	I4
PROJP1	WCS	Optional	F20.1	F5.1	-	F5.1	F5.1	F5.1	F5.1	F5.1	F5.1	-	-
PROJP2	WCS	Optional	F20.1	F5.1	-	F5.1	F5.1	F5.1	F5.1	F5.1	F5.1	-	-
PROP-ID	Origin	Common	A8	A8	A8	A8	A8	A8	A8	A8	A8	A8	A8
RA	Object	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
RA2000	Object	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
RADECSYS	Object	Common	A8	-	-	-	-	-	-	-	-	-	-
RET-ANGn	Polarimetry	Polarimetry	F20.2	-	F8.4	-	-	-	-	F6.2	-	-	-
RETPLATn	Polarimetry	Polarimetry	A30	-	A80	-	-	-	-	A80	-	-	-
SECZ	Time	Optional	F20.3	F6.3	F6.3	F6.4	-	-	F6.3	-	F6.3	F6.3	-
SECZ-END	Time	Optional	F20.3	F6.3	F6.3	F6.4	-	-	-	-	-	-	-
SECZ-STR	Time	Optional	F20.3	F6.3	F6.3	F6.4	-	-	-	-	-	-	-
SEEING	Environment	Optional	F20.2	F5.2	F5.2	-	-	-	F5.2	F4.2	F5.2	F4.2	-
SIMPLE	FITS	Common	BOOLEAN	-	-	-	-	-	-	-	-	-	-
SLIT	Spectroscopy	Spectroscopy	A20	-	A80	A80	A80	A80	A80	A80	-	-	-
SLT-LEN	Spectroscopy	Spectroscopy	F20.3	-	-	F6.3	F7.3	F7.3	F7.3	F7.3	-	-	-
SLT-OBJP	Spectroscopy	Optional	F20.3	-	-	F6.2	-	-	-	-	-	-	-
SLT-PA	Spectroscopy	Spectroscopy	F20.1	-	-	F6.2	F5.1	F5.1	F5.1	F5.1	-	-	-
SLT-PEND	Spectroscopy	Optional	F20.1	-	-	F6.2	-	-	-	-	-	-	-
SLT-PSTR	Spectroscopy	Optional	F20.1	-	-	F6.2	-	-	-	-	-	-	-
SLT-WID	Spectroscopy	Spectroscopy	F20.3	-	-	F6.3	F6.3	F6.3	F6.3	F6.3	-	-	-
SLTC-DEC	Spectroscopy	Optional	F20.5	-	-	-	F12.8	F12.8	-	F9.5	-	-	-
SLTC-RA	Spectroscopy	Optional	F20.5	-	-	-	F12.8	F12.8	-	F9.5	-	-	-
SLTCPIX1	Spectroscopy	Spectroscopy	F20.1	-	-	F7.2	F7.1	F7.1	F6.1	F6.1	-	-	-
SLTCPIX2	Spectroscopy	Spectroscopy	F20.1	-	-	F7.2	F7.1	F7.1	F6.1	F6.1	-	-	-
SV-PRB	Telescope	Optional	F20.3	-	-	-	-	-	-	-	-	-	-
TELESCOP	Origin	Common	A30	-	-	-	-	-	-	-	-	-	-
TELFOCUS	Telescope	Common	A30	A80	A80	A80	A80	A80	A80	-	-	-	A80
TIMESYS	Time	Common	A8	-	-	-	-	-	-	-	-	-	-
TRAN-END	Environment	Optional	F20.3	-	-	-	-	-	-	-	-	-	-
TRAN-STR	Environment	Optional	F20.3	-	-	-	-	-	-	-	-	-	-
TRANSP	Environment	Optional	F20.3	-	-	-	-	-	-	-	-	-	-
UT	Time	Common	A12	A80	A80	A80	A80	A80	A80	A80	A80	A80	A80
UT-END	Time	Optional	A12	A80	A80	A80	A80	A80	-	A80	-	-	-
UT-STR	Time	Optional	A12	A80	A80	A80	A80	A80	-	A80	-	-	-
UT1-UTC	Time	Optional	F20.5	-	-	-	-	-	-	-	-	-	-
WAV-MAX	Spectroscopy	Spectroscopy	F20.4	-	F6.2	F7.2	F10.5	F10.5	F10.4	F6.2	-	-	-
WAV-MIN	Spectroscopy	Spectroscopy	F20.4	-	F6.2	F7.2	F10.5	F10.5	F10.4	F6.2	-	-	-
WAVELEN	Spectroscopy	Spectroscopy	F20.4	-	F6.2	F7.2	F10.5	F10.5	F10.4	F6.2	-	-	-
WCS-ORIG	WCS	Imaging	A20	A80	-	-	-	A80	-	-	-	-	-
WEATHER	Environment	Optional	A30	A80	A80	-	-	-	A80	A80	A80	A80	-
ZD	Time	Optional	F20.5	F6.3	F5.2	-	F5.2	F5.2	F8.5	F5.2	F6.3	F6.3	F6.3
ZD-END	Time	Optional	F20.5	F6.3	F5.2	-	-	-	-	F5.2	-	-	-
ZD-STR	Time	Optional	F20.5	F6.3	F5.2	-	-	-	-	F5.2	-	-	-